

ECMA/TC38-TG3/2015/026 (Rev. 1 – 15 April 2017)

### Annex B2 - Product environmental attributes Desktop/All-in-One Computers

The declaration may be published only when all rows and/or fields marked with \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lenovo	Logo				
Company name *	npany name * Lenovo					
Contact information *	Lenovo Global Environmental Affairs		Lenovo			
e-mail address	Alvin L Carter		LEIIOVO			
	alcarter@lenovo.com					
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment.html					
Additional information	The latest version of this document can be found at:					
	http://www.lenovo.com/ecodeclaration					

The company declares (based on product specification or test results based obtained from sample testing), that the produc conforms to the statements given in this declaration.						
Type of product *	Desktop					
Commercial name *	IdeaCentre 5 AMD					
Model number *	90Q2, 90Q3					
Issue date *	2020/07/03					
Intended market *	🔀 Global 📃 Europe 📃 Asia, Pacific & Japan 📃 Americas 📃 Other					
Additional information						

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

#### About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template: P4.1 – P4.3 Consumable materials P9.1 TEC and Print speed P10.2 - P10.3 Chemical emissions from printing products P11.1 - P11.3 Consumable materials for printing products.

Model nu	umber *	90Q2, 90Q3 Logo	lon		
Issue da	te *	2020/07/03	Len		Тм
Product	t environ	mental attributes - Legal requirements	Require	men	t met
Item			Yes	No	n.a.
P1		ous substances and preparations			
P1.1*		do comply with current European RoHS Directive. (See legal reference and NOTE B1)	$\bowtie$		
P1.2*		s do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value.	$\square$		
P1.3*	hydrobro trichloro	a do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), pmofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- ethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum ration values.			
P1.4*		do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated (PCT) in preparations (see legal reference).	$\boxtimes$		
P1.5*		s do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).	•		
P1.6*	(see lega	h direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm²/week al reference). nt: Max limit in legal reference when tested according to EN1811:2011-5.			
P1.7*	REACH	Article 33 information about substances in articles is available at (add URL or mail contact): ww.lenovo.com/us/en/Lenovo-REACH-SVHC-Disclosure	$\square$		
P2	Batterie	S			
P2.1*		oduct contains a battery or an accumulator, the battery/accumulator is labeled with the disposal Information on proper disposal is provided in user manual. (See legal reference)	$\boxtimes$		
P2.2*	Batteries referenc	s or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal e)	$\boxtimes$		
P2.3*	Batteries	and accumulators are readily removable. (See legal reference)	$\square$		
P3	Conform	nity verification & Eco design (ErP)			
P3.1*	The proc	Juct is CE-marked to show conformance with applicable legal requirements (see legal reference). laration of Conformity can be requested at: https://www.lenovo.com/us/en/compliance/eu-doc	$\boxtimes$		
P3.2*		Juct complies with the Eco design requirements for energy-related products, al reference).	$\boxtimes$		
	· ·	d information is;	$\square$		
P5	Product	packaging			
P5.1*	Packagi	ng and packaging components do not contain more than 0,01% lead, mercury, cadmium an ent chromium by weight of these together.	d 🖂		
P5.2*	The pac	kaging materials are marked with abbreviations and numbers indicating the nature of the material(s e legal reference).	;)		
P5.3*	The proc (see lega	luct packaging material is free from ozone depleting substances as specified in the Montreal Protoco al reference).	ol 🔀		
P6		nt: Legal reference has no maximum concentration values. nt information			
P6.1*		on for recyclers/treatment facilities is available (see legal reference).			
10.1	mormati	טוו זטו ובניצטובושינו במנוובות ומטוונובש וש מימוומטוב (שבב ובעמו ובובובווטב).			

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model nu	umber *	90Q2, 90Q3	Logo	Lon		
Issue dat	te *	2020/07/03		Len	ovc	Этн
Product	environ	mental attributes - Market requirements (See General NOTE GN I	below)			
		onmental conscious design		Require		met
Item		tory to fill in. Additional information regarding each item may be found under P14.		Yes	No	n.a.
P7.1*		Disassembly, recycling t have to be treated separately are easily separable				
P7.2*		aterials in covers/housing have no surface coating.			<u> </u>	╞
P7.3*		arts > 100 g consist of one material or of easily separable materials.			╞	╞
P7.4*	Plastic pa			<u> </u>	╞	
P7.5			<u> </u>	<u> </u>		
P7.6*		arts are free from metal inlays or have inlays that can be removed with commonly a re easily separable. (This requirement does not apply to safety/regulatory labels).			╞	╞┼┥
F7.0						
P7.7*	Product Upgradin	ig can be done e.g. with processor, memory, cards or drives				
P7.8*		ig can be done using commonly available tools			╞	╞
P7.9		Ints are available after end of production for: 5 years				╞
P7.10		s available after end of production for: 5 years				╞
F7.10		and substance requirements				
P7.11*		cover/housing material type (e.g. plastics, metal, aluminum):				
		type: ABS Material type: Materia	Il type:			
P7.12		n materials of external electrical cables are PVC free.	<u></u>		$\boxtimes$	
P7.13	Insulation	n materials of internal electrical cables are PVC free.		<u> </u>		Ē
P7.14	weight (1 polyvinyl	plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) br 1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine ir n 25% post-consumer recycled content.	e retardants, an	d 🗖		
P7.15	Printed c	ircuit boards, PCBs (without components) are low halogen: all PCBs > 25 g 🔀 d in IEC 61249-2-21. (See 1NOTE B2)	are low haloge	n 🔀		
P7.16	Flame re Marking:	tarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:				$\boxtimes$
P7.17		nemical specifications of flame retardants in printed circuit boards > 25 g (without co PA (additive), TBBPA (reactive) (See NOTE B3), Other: , CAS #: <b>79-94</b>				
		nemical specifications of flame retardants in printed circuit boards (without compone g ISO 1043-4:	ents) > 25 g			
P7.18	concentra 1. Chemi 2. Chemi	ame retarded plastic parts > 25 g contain the following flame retardant substance ations above 0,1%: ical name: , CAS #: (See NOTE B4) ical name: , CAS #: " ical name: , CAS #: "	s/preparations i	n		
		nemical specifications of flame retardants in plastic parts > 25 g according ISO 1043				
P7.19	assigned	parts > 25 g, flame retardant substances/preparations above 0,1% are used which the following Risk phrases; and Hazard statements:				
P7.20*		cce(s) for these classifications is/are found at (add URL(s)): , (S sumer recycled plastic material content is used in the product (See Note B6):	ee note B5)			
	a) Of t a pe or	t least one of the two alternatives below shall be answered; otal plastic parts' weight > 25 g, the postconsumer recycled plastic material content ercentage of total plastic by weight) is <b>38.2%</b> .	t (calculated as			

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model number *	90Q2, 90Q3	Logo	
Issue date *	2020/07/03		LEIIOVO

Product environmental attributes - Market requirements (continued)

Item

Requirement met Yes No n.a.

P7.21*       Biobased plastic material content is used in the product (See NOTE B7):       Image: Second Se	Material and sub	stance requirements	(continued)			
P7.22*       Light sources are free from mercury, i.e. less than 0,1 mg/lamp. If mercury is used specify. Number of lamps: and maximum mercury content per lamp: mg       Image: mg         P8       Batteries         P8.1*       Battery chemical composition:       Image: mg         P9       Energy consumptions (See NOTE B8)       Image: mg         Powr level at       Powr level at       Powr level at         Powr level at       Powr level at       Powr level at         Powr level at       Powr level at       Powr level at         Powr level at       Powr level at       Powr level at         Powr level at       Powr level at       Powr level at         Powr level at       Powr level at       Powr level at         Powr level at       Powr level at       Powr level at         Powr level at       Powr level at       Powr level at         Powr level at       Powr level at       Powr level at         Powr level at       Powr level at       Powr level at         Powr level at       Powr level at       Powr level at         Powr level at       Powr level at       Powr level at         Powr level at       Powr level at       Powr level at         Powr level at       Powr level at       Powr level at         Powr level at </td <td></td> <td></td> <td></td> <td>IOTE B7):</td> <td></td> <td><math>\square</math></td>				IOTE B7):		$\square$
If mercury is used specify: Number of lamps:     and maximum mercury content per lamp:     mg     mg     mg       P8     Battery chemical composition:     Image: State Sta						<u> </u>
P8       Batteries         P9.1       Battery chemical composition:       Image: Comparison of the product the following power levels or energy consumptions are reported.         P9.1       For the product the following power levels or energy consumptions are reported.       Reference/Standard for energy mode and the following power level at the foll						
P8.1*       Battery chemical composition:       Image: State of the product the following power levels or energy consumptions are reported:         P9.1       For the product the following power levels or energy consumptions are reported:       Power level at Power level at Power level at Power level at 230 V AC       Reference/Standard for energy mode *         Peak (0n-max)       W       W       W       W       Four level at Power Power level at Power P		specify: Number of la	mps: and maxim	ium mercury content pe	riamp: mg	
P9         Energy consumption (See NOTE B8)         Low           P9.1         For the product the following power level at 100 V AC         Power level at 115 V AC         Power level at 230 V AC         Reference/Standard for energy           Peak (0n-max)         W         W         W         Full load           Category 12         Short Idle State - WOL Enabled         12.55 W         12.74 W         11.32 W         Use for EMERCY STAR V8 registration (Pam)           Short Idle State - WOL Enabled         10.91 W         9.74 W         9.62 W         Use for EMERCY STAR V8 registration (Pam)           Sleep (S3) - WOL Enabled         0.89 W         0.94 W         Use for EMERCY STAR V8 registration (Pam)           Off (S5) - WOL Enabled         0.57 W         0.57 W         Use for EMERCY STAR V8 registration (Pam)           Off (S5) - WOL Disabled         W         W         0.58 W         Use for EMERCY STAR V8 registration (Pam)           Short Idle State - WOL Enabled         23.54 W         23.31 W         23.03 W         Use for EMERCY STAR V8 registration           Short Idle State - WOL Enabled         0.92 W         0.92 W         Use for EMERGY STAR V8 registration           Category D2         Imable         0.92 W         Use for EMERGY STAR V8 registration           Sleep (S3) - WOL Enabled         0.92 W         0.92 W		composition:				
P0.1       For the product the following power levels or energy consumptions are reported:         Energy mode*       Power level at 100 V AC       115 V AC       Power level at 230 V AC       Reference/Standard for energy modes and test method*         Peak (0n-max)       W       W       W       Full load         Category 12       12.74 W       11.32 W       Use for ENERGY STAR V8 registration (P <sub>dim</sub> )         Short Idle State - WOL Enabled       10.91 W       9.74 W       9.62 W       Use for ENERGY STAR V8 registration (P <sub>dim</sub> )         Sleep (S3) - WOL Enabled       0.89 W       0.94 W       Use for ENERGY STAR V8 registration (P <sub>dim</sub> )         Off (S5) - WOL Enabled       0.57 W       0.57 W       Use for ENERGY STAR V8 registration (P <sub>dim</sub> )         Off (S5) - WOL Disabled       W       W       0.58 W       Use for ENERGY STAR V8 registration         Category D2       I       I       I       I       I         Short Idle State - WOL Enabled       23.54 W       23.31 W       23.03 W       Use for ENERGY STAR V8 registration         I.ong Idle State - WOL Enabled       0.92 W       0.92 W       Use for ENERGY STAR V8 registration       I         Steep (S3) - WOL Enabled       0.92 W       0.92 W       Use for ENERGY STAR V8 registration       I         Cift (S5) - WOL Enabled       0.57		•				
Energy mode *         Power level at 100 V AC         Power level at 115 V AC         Power level at 230 V AC         Reference/Standard for energy index modes and less method *           Peak (On-max)         W         W         W         W         W         Full load           Category 12         11.32 W         W         W         W         Full load           Short Idle State - WOL Enabled         12.55 W         12.74 W         11.32 W         Use for ENERGY STAR V8 registration (Pame)           Sleep (S3) - WOL Enabled         0.89 W         9.62 W         Use for ENERGY STAR V8 registration (Pame)           Sleep (S3) - WOL Enabled         0.57 W         0.57 W         Use for ENERGY STAR V8 registration (Pame)           Off (S5) - WOL Disabled         W         W         0.58 W         Use for ENERGY STAR V8 registration (Pame)           Off (S5) - WOL Disabled         W         W         0.57 W         Use for ENERGY STAR V8 registration (Pame)           Off (S5) - WOL Disabled         W         W         0.58 W         Use for ENERGY STAR V8 registration           Category D2         Intel 6 State - WOL Enabled         21.65 W         21.5 W         Use for ENERGY STAR V8 registration           Sleep (S3) - WOL Enabled         0.92 W         0.92 W         0.92 W         Use for ENERGY STAR V8 registration      <			ls or energy consumpt	ions are reported:		
Category 12       Short Idle State - WOL       12.55 W       12.74 W       11.32 W       Use for ENERGY STAR V8 registration (P <sub>rotex</sub> )         Long Idle State - WOL       10.91 W       9.74 W       9.62 W       Use for ENERGY STAR V8 registration (P <sub>rotex</sub> )         Sleep (S3) - WOL Enabled       0.89 W       0.89 W       0.94 W       Use for ENERGY STAR V8 registration (P <sub>rotex</sub> )         Off (S5) - WOL Enabled       0.57 W       0.57 W       0.57 W       Use for ENERGY STAR V8 registration (P <sub>rotex</sub> )         Off (S5) - WOL Disabled       W       W       0.58 W       Use for ENERGY STAR V8 registration (P <sub>rotex</sub> )         Off (S5) - WOL Disabled       W       W       0.57 W       Use for ENERGY STAR V8 registration (P <sub>rotex</sub> )         Off (S5) - WOL Disabled       W       W       0.58 W       Use for ENERGY STAR V8 registration         Category D2       Imabled       23.54 W       23.31 W       23.03 W       Use for ENERGY STAR V8 registration         Long Idle State - WOL       21.65 W       21.65 W       21.5 W       Use for ENERGY STAR V8 registration         Sleep (S3) - WOL Enabled       0.57 W       0.57 W       Use for ENERGY STAR V8 registration         Off (S5) - WOL Enabled       0.57 W       0.57 W       Use for ENERGY STAR V8 registration         Imable distaconcodet from the protex)       0.5	Energy mode *	Power level at	Power level at	Power level at		
Short Idle State - WOL Enabled       12.55 W       12.74 W       11.32 W       Use for ENERGY STAR V8 registration (Purk)         Long Idle State - WOL Enabled       10.91 W       9.74 W       9.62 W       Use for ENERGY STAR V8 registration (Purk)         Sleep (S3) - WOL Enabled       0.89 W       0.89 W       0.94 W       Use for ENERGY STAR V8 registration (Purk)         Off (S5) - WOL Enabled       0.57 W       0.57 W       0.57 W       Use for ENERGY STAR V8 registration (Purk)         Off (S5) - WOL Disabled       W       W       0.58 W       Use for ENERGY STAR V8 registration (Purk)         Off (S5) - WOL Disabled       W       W       0.58 W       Use for ENERGY STAR V8 registration         Category D2             Short Idle State - WOL Enabled       21.65 W       21.65 W       21.5 W       Use for ENERGY STAR V8 registration         Long Idle State - WOL Enabled       0.92 W       0.92 W       0.92 W       Use for ENERGY STAR V8 registration         Off (S5) - WOL Enabled       0.57 W       0.57 W       0.57 W       Use for ENERGY STAR V8 registration         Off (S5) - WOL Enabled       0.92 W       0.92 W       Use for ENERGY STAR V8 registration       Erection Star V8 registration         CEPS No-load       W       W       W       W	Peak (On-max)	W	W	W	Full load	
Enabled       registration (Pow)         Long Idle State - WOL Enabled       10.91 W       9.74 W       9.62 W       Use for ENERGY STAR V8 registration (Pow)         Sleep (S3) - WOL Enabled       0.89 W       0.89 W       0.94 W       Use for ENERGY STAR V8 registration (Pow)         Off (S5) - WOL Enabled       0.57 W       0.57 W       0.57 W       Use for ENERGY STAR V8 registration (Pow)         Off (S5) - WOL Disabled       W       W       0.58 W       Use for ENERGY STAR V8 registration (Pow)         Off (S5) - WOL Disabled       W       W       0.58 W       Use for ENERGY STAR V8 registration         Short Idle State - WOL Enabled       23.54 W       23.31 W       23.03 W       Use for ENERGY STAR V8 registration         Sleep (S3) - WOL Enabled       0.92 W       21.65 W       21.55 W       Use for ENERGY STAR V8 registration         Sleep (S3) - WOL Enabled       0.92 W       0.92 W       0.92 W       Use for ENERGY STAR V8 registration         Off (S5) - WOL Enabled       0.57 W       0.57 W       0.57 W       Use for ENERGY STAR V8 registration         CH (S5) - WOL Enabled       0.57 W       0.57 W       0.57 W       Use for ENERGY STAR V8 registration         CH (S5) - WOL Enabled       0.57 W       0.57 W       0.57 W       Use for ENERGY STAR V8 registration	Category I2					
Enabled       registration (Pson)         Sleep (S3) - WOL Enabled       0.89 W       0.89 W       0.94 W       Use for ENERGY STAR V8 registration (Pson)         Off (S5) - WOL Enabled       0.57 W       0.57 W       0.57 W       Use for ENERGY STAR V8 registration (Pson)         Off (S5) - WOL Disabled       W       W       0.58 W       Use for ENERGY STAR V8 registration (Pson)         Off (S5) - WOL Disabled       W       W       0.58 W       Use for ENERGY STAR V8 registration         Short Idle State - WOL Enabled       23.54 W       23.03 W       Use for ENERGY STAR V8 registration         Long Idle State - WOL Enabled       21.65 W       21.65 W       21.5 W       Use for ENERGY STAR V8 registration         Sleep (S3) - WOL Enabled       0.92 W       0.92 W       0.92 W       Use for ENERGY STAR V8 registration         Off (S5) - WOL Enabled       0.57 W       0.57 W       0.57 W       Use for ENERGY STAR V8 registration         EPS No-load       0.57 W       0.57 W       0.57 W       Use for ENERGY STAR V8 registration         EPS No-load       W       W       W       W       X         PTEC *       W       W       W       X       Y         Annual Energy Consumption       12:46.27 kWh/year       12:42.63 kWh/year       Erec = (8760/10		12.55 W	12.74 W	11.32 W		
Off (S5) - WOL Enabled       0.57 W       0.57 W       0.57 W       Use for ENERGY STAR V8 registration (Pon)         Off (S5) - WOL Disabled       W       W       0.58 W       Use for ENERGY STAR V8 registration (Pon)         Off (S5) - WOL Disabled       W       W       0.58 W       Use for ErP         Category D2       Image: Comparison of the product of the p	Long Idle State - WOL Enabled	10.91 W	9.74 W	9.62 W		
Off (S5) - WOL Disabled       W       W       0.58 W       Use for ErP         Category D2       Image: Construction of the product of the produ	Sleep (S3) - WOL Enabled	0.89 W	0.89 W	0.94 W		
Category D2       Image: Category D2       Image: Category D2         Short Idle State - WOL Enabled       23.54 W       23.31 W       23.03 W       Use for ENERGY STAR V8 registration         Long Idle State - WOL Enabled       21.65 W       21.65 W       21.5 W       Use for ENERGY STAR V8 registration         Sleep (S3) - WOL Enabled       0.92 W       0.92 W       0.92 W       Use for ENERGY STAR V8 registration         Off (S5) - WOL Enabled       0.57 W       0.57 W       0.57 W       Use for ENERGY STAR V8 registration         EPS No-load       W       W       W       W       Image: State S		0.57 W	0.57 W	0.57 W		
Short Idle State - WOL       23.54 W       23.31 W       23.03 W       Use for ENERGY STAR V8 registration         Long Idle State - WOL       21.65 W       21.65 W       21.5 W       Use for ENERGY STAR V8         Biabled       0.92 W       0.92 W       0.92 W       Use for ENERGY STAR V8 registration         Sleep (S3) - WOL Enabled       0.92 W       0.92 W       0.92 W       Use for ENERGY STAR V8         Off (S5) - WOL Enabled       0.57 W       0.57 W       0.57 W       Use for ENERGY STAR V8 registration         EPS No-load       W       W       W       W       Image: State Stat	Off (S5) - WOL Disabled	W	W	0.58 W	Use for ErP	
Enabled       registration         Long Idle State - WOL Enabled       21.65 W       21.65 W       21.5 W       Use for ENERGY STAR V8 registration         Sleep (S3) - WOL Enabled       0.92 W       0.92 W       0.92 W       Use for ENERGY STAR V8 registration         Off (S5) - WOL Enabled       0.57 W       0.57 W       0.57 W       Use for ENERGY STAR V8 registration         EPS No-load (standapower supply / drage plaged in the wall outlet but disconnected from the product)       W       W       W         PTEC * Annual Energy Consumption       12:46.80 kWh/year D:85.2 kWh/year       12:46.27 kWh/year D:84.6 kWh/year       12:42.63 kWh/year D:83.73 kWh/year       Erec = (8760/1000) x (Poir x 0.45 + Paleep x 0.05 + Plong_die x 0.15 + Pshort_Idie x 0.35)         Point: Off Mode(S5) - WOL Enabled; Paleep: Sleep Mode(S3) - WOL Enabled; Paleex       Image: Sleep Mode(S3) - WOL Enabled; Paleex       Image: Sleep Mode(S3) - WOL Enabled; Paleex         Display resolution * : N/A megapixels       Image: Sleep Mode(S3) - WOL Enabled; Paleex       Image: Sleep Mode(S3) - WOL Enabled; Paleex       Image: Sleep Mode(S3) - WOL Enabled; Paleex         P9.2*       Information about the energy save function is provided with the product.       Image: Sleep Mode(S)       Image: Sleep Mode(S)       Image: Sleep Mode(S)	Category D2					
Enabled       registration         Sleep (\$3) - WOL Enabled       0.92 W       0.92 W       0.92 W       Use for ENERGY STAR V8 registration         Off (\$5) - WOL Enabled       0.57 W       0.57 W       0.57 W       Use for ENERGY STAR V8 registration         (Extemal power supply icharger plugged in the wall outlet but disconnected from the product.)       W       W       W         PTEC *       W       W       W       X         Typical Energy Consumption       12:46.27 kWh/year       12:42.63 kWh/year       ErEc = (8760/1000) × (Point × 0.45 + Poing_Jdle × 0.15 + Poing_Jdle × 0.15 + Poing_Jdle × 0.35)       Image: Not State = NOL Enabled         External Power Supply Efficiency Level (International Efficiency Marking Protocol) * : N/A       Image: N/A megapixels       Image: N/A megapixels         Default time to enter energy save mode: 25 minutes       Image: N/A megapixels       Image: N/A megapixels       Image: N/A megapixels       Image: N/A megapixels         P9.2*       Information about the energy save function is provided with the product.       Image: N/A megapixels       Image: N/A megapixels       Image: N/A megapixels       Image: N/A megapixels		23.54 W	23.31 W	23.03 W		
Off (S5) - WOL Enabled       0.57 W       0.57 W       0.57 W       Use for ENERGY STAR V8 registration         EPS No-load       W       W       W       W       W       Image: State of the product of the		21.65 W	21.65 W	21.5 W		
Image: State of the state	Sleep (S3) - WOL Enabled	0.92 W	0.92 W	0.92 W		
(External power supply / charger plugged in the wall outlet but disconnected from the product.)       W       W       W         PTEC *       W       W       W       M         Typical Energy Consumption       I2:46.80 kWh/year       I2:46.27 kWh/year       I2:42.63 kWh/year       ETEC = (8760/1000) x (Poff x 0.45 + Psileep x 0.05 + Plong_Idle x 0.15 + Psileep x 0.15 + Psileep x 0.05 + Plong_Idle x 0.15 + Psileep x 0.15 + Psi	Off (S5) - WOL Enabled	0.57 W	0.57 W	0.57 W		
PTEC * Typical Energy Consumption       W       W       W       W       W       M         ETEC * Annual Energy Consumption       12:46.80 kWh/year D2:85.2 kWh/year       12:46.27 kWh/year D2:84.6 kWh/year       12:42.63 kWh/year D2:83.73 kWh/year       ETEC = (8760/1000) x (Port x 0.45 + Psileep x 0.05 + Plong_Idle x 0.15+ Pshort_Idle x 0.35)         Port: Off Mode(S5) - WOL Enabled; Psileep: Sleep Mode(S3) - WOL Enabled; Psileep: Sleep Mode(S3) - WOL Enabled; Plate: Idle State - WOL Enabled         External Power Supply Efficiency Level (International Efficiency Marking Protocol) * : N/A       Image: Sleep Mode(S3) - WOL Enabled; Plate: Idle State - WOL Enabled         Display resolution * : N/A megapixels       Image: Sleep Mode(S3) - WOL Enabled; Plate: Idle State - WOL Enabled       Image: Sleep Mode(S3) - WOL Enabled; Plate: Idle State - WOL Enabled         P9.2*       Information about the energy save function is provided with the product.       Image: Sleep Mode(S3) - WOL Enabled; Plate: Idle State - WOL Enabled	EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.)	W	W	W		$\square$
Annual Energy Consumption       D2:85.2 kWh/year       D2:84.6 kWh/year       D2:83.73 kWh/year       + P sleep x 0.05 + Plong_Idle x 0.15 + Pshort_Idle x 0.35)         Port: Off Mode(S5) - WOL Enabled; P sleep: Sleep Mode(S3) - WOL Enabled; Pidle: Idle State - WOL Enabled         External Power Supply Efficiency Level (International Efficiency Marking Protocol) * : N/A       Image: Sleep Mode(S3) - WOL Enabled; Pidle: Idle State - WOL Enabled         Display resolution * : N/A megapixels       Image: Sleep Mode(S1) - WOL Enabled       Image: Sleep Mode(S1) - WOL Enabled         P9.2*       Information about the energy save function is provided with the product.       Image: Sleep Mode(S1) - WOL Enabled	PTEC * Typical Energy Consumption					
External Power Supply Efficiency Level (International Efficiency Marking Protocol)*: N/A       Image: State St	ETEC * Annual Energy Consumption				+ Psleep x 0.05 + Plong_Idle x 0.15+	
External Power Supply Efficiency Level (International Efficiency Marking Protocol)*: N/A       Image: State St		Poff: Off Mode(	S5) - WOL Enabled; Pslee	p: Sleep Mode(S3) - WOL	Enabled; Pidle: Idle State - WOL Enabled	1
Default time to enter energy save mode: 25 minutes         P9.2*       Information about the energy save function is provided with the product.						
P9.2* Information about the energy save function is provided with the product.	Display resolution * : N/A meg	apixels				$\square$
	Default time to enter energy sa	ave mode: 25 minutes				Π
	P9.2* Information about	the energy save funct	ion is provided with the	product.		Π
						Ē

NOTE B8 A Guidance document on Energy Efficiency is available;

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see <u>http://www.ecma-international.org/publications/standards/Ecma-370.htm</u>

P10	Emissions						
	Noise emission	n – Declared according to ISO 9296 (See N	OTE B9)				
P10.1	Mode	Mode description	Statistical upp	er limit A-weighted sound powe	er level,	Lwa,c (	B)
	Idle	* HDD:Idle	* 3.6				
	Operation	* HDD: Operating	* 3.7				
	Other mode	Declared A-weighted sound pressure level (dBL,	(A) <b>19.5</b> (operato	r position desktop – idle)			
	Other mode	Declared A-weighted sound pressure level (dBL)	(A) 29.7 (operato	r position desktop – HDD operati	ing)		
	Measured acco	rding to: 🔀 ISO 7779 🔀 ECMA-74					
	Other (only if not covered by ECMA-74)						
Item		, <u> </u>	•		Yes	No	n.a.
nem	Electromagnet	ic emissions			163	NO	n.a.
P10.4		ay meets the requirement for low frequency	electromagnetic field	s of the following voluntary			X
1 10.1	program(s):		election agriculto nota	o of the following voluntary			
P12	Ergonomics fo	r computing products					
P12.1*	The display me	ets the ergonomic requirements of ISO 924	I-307 for visual displa	ay technologies.			X
P12.2*	The physical in	out device meets the requirements of ISO 9	995 and ISO 9241-41	10.			$\overline{\mathbf{X}}$
P13	Packaging and	documentation					
P13.1*			(g): <b>1.07</b>				
			(g): <mark>0.26</mark>				
	· · ·	ing material type(s): weight (	<g):< td=""><td></td><td></td><td></td><td></td></g):<>				
P13.2*		primary packaging is free from PVC.					$\boxtimes$
P13.3*	consumer recov	mary corrugated fiberboard packaging, sp /ered fiber content: <b>30</b> %	•	percentage of minimum post-			
P13.4*	Specify media f	or user and product documentation (tick bo› ☑Paper, ☑Other	:):				
P13.5		mplete this item if paper documentation use ct documentation on paper media is chloring pecify:					
	Totally chlorine	free			$\square$		
	Elemental chlor	ine-free			X		
	Processed chlo	rine-free					
P14	Voluntary prog	Irams					
P14.1		ets the requirements of the following volunt	ary program(s):				
	ENERGY STAF		Date: 2020/2/24	Product category: <b>Desktop</b>			
	Eco-label: Eco-label:	Criteria version: Criteria version:	Date: Date:	Product category: Product category:			
P15		rmation (See NOTE B10)	Dale.	Product category.			
P9		nption of specific configuration may var	: description of the	e tested product configuration	n:		
		makes no representations, guarantees, as				a the	
	information contained in this document. All information provided by supplier in this document is provided based on supplier's						
	knowledge available at the time of completion, and supplier shall have no obligation to update such information. The information					ion	
		approximate and provided for informationa	I purposes only. See	a Lenovo Account Representa	tive for r	nore	
<b>D0</b>	information.	a Overlifted Netebooks & Tablet Overset	Construction of the Construction	ti			
P9	See Energy Star Qualified Notebooks & Tablet Computers for the latest information: http://www.energystar.gov/index.cfm?fuseaction=find_a_product.showProductGroup&pgw_code=CO						
	map.//www.ener	gystar.gov/index.citri?idseaction=lifid_a_pr		ioupapyw_coue=co			

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

## Legal references Europe Annex B2

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1
Regulation (EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7
Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)	P1.3, P5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) No 1272/2008 (CLP Regulation)	P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1

# Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

#### Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	IdeaCentre 5 14ARE05	Logo
Model Number	90Q2, 90Q3	
Issue Date	2020/07/03	Lenovo
Additional information	Energy Star 8.0;	

P7.1.1	Product environmental attributes						
(d)	year of manufacture:				2020		
(e)	Etec value (kWh) per ErP Lot 3 Categor disabled and if the system is tested with				cards (dGfx) are		
(f)	Etec value (kWh) per ErP Lot 3 Categor enable	y and capability adjust	ments applied when <b>a</b>	II discrete graphics	cards (dGfx) are		
	Category A (according to ErP Lot 3)Category B (according to ErP Lot 3)Category C (according to ErP Lot 3)						
	Memory over base [GB]				30		
ents ting	Additional internal storage	(Yes / No)	(Yes / No)	(Yes / No)	Yes (Yes / No)		
capability adjustments applied during testing	Discrete television tuner	(Yes / No)	(Yes / No)	(Yes / No)	No (Yes / No)		
ability a	Discrete Audio Card	(Yes / No)	(Yes / No)	(Yes / No)	No (Yes / No)		
cap app	Discrete graphics Card(s) [number / #]	#: (Yes / No)	#: (Yes / No)	#: (Yes / No)	Yes #: 1 (Yes / No)		
	Category of discrete graphics Card(s)				G5		
Test results	Etec Value (kWh) - dGfx disabled all discrete graphics cards (dGfx) are disabled/ UMA is active for switchable graphics/ product has no graphics cards (dGfx)						
Test n	Etec Value (kWh) - dGfx enabled all discrete graphics cards (dGfx) are enabled				73.52		
(g)	Idle state power demand (Watts);	·	·	·	20.05		
(h)	Sleep mode power demand (Watts);				0.93		
(i)	Sleep mode with WOL enabled power de	emand (Watts) (where	enabled);		0.97		
(j)	Off mode power demand (Watts);				0.55		
(k)	Off mode with WOL enabled power dema	and (Watts) (where en	abled);		0.59		
(I)	Internal power supply efficiency at 10 %,	, 20 %, 50 % and 100 °	% of rated output powe	er (if applicable):			
	PCK012-EL0G : 10% 83.83% 20% 85.34% 50% 87.16% 100% 84.63% Average 85.71%						
	HK360-71PP: 10% 85.63% 20% 86.30% 50% 87.45% 100% 84.36% Average 86.04%						
	FSP260-20TLA: 10% 85.61% 20% 86.	.23% 50% 86.98%	100% 84.26% Aver	age 85.82%			
(m)	External power supply efficiency (if applied	cable)*:					
	Average active efficiency: N/A						
(-)	*internal note: show values for all available external po		hand (applies set 1				
(o)	Minimum number of loading cycles that the batteries can withstand (applies only to notebook computers):						

(p-1)	(p-1) Measurement methodology used to determine information mentioned in points (I) – internal PSU efficiency: Generalized Test Protocol for Calculating the Energy Efficiency of Internal Ac-Dc and Dc-Dc Power Supplies Revision 6.6					
(p-2)	Measurement metho	dology used to determine information mentioned in p N/A	points (m) – external PSU efficiency:			
(p-3)	Measurement methodology used to determine information mentioned in points (o) – loading cycles batteries: N/A					
(p-4)	4) Measurement methodology used to determine information mentioned in maximum, idle, sleep, off mode power as defined in Point P9.1 in the Product IT Eco Declaration:					
		IEC 62623 Ed. 1.0, 2012-10				
(q)	Sequence of steps for	or achieving a stable condition with respect to power	demand:			
	B	ased on user manual/Power on->Wait 5 minutes-	>Stable condition			
(r)	Description of how s	leep and/or off mode was selected or programmed:				
	Bas	ed on user manual/Begin menu -> Power -> Selec	ct sleep or off mode			
(s)	Sequence of events off mode:	required to reach the mode where the equipment au	tomatically changes to sleep and/or			
	Based on user ma	anual/Control Panel->Power Options-> Change So for this plan	ettings-> Restore default settings			
(t)		te condition before the computer automatically re- s not exceed the applicable power demand requirement		20		
(u)	Length of time after	r a period of user inactivity in which the compute ver power demand requirement than sleep mode (in	r automatically reaches a power	NA		
(v)		ore the display sleep mode is set to activate after		10		
(w)	Information on the er	nergy-saving potential of power management functio	nality:			
		Based on user manual				
(x)	User information on	how to enable the power management functionality:				
		Based on user manual				
(z)		measurements: — test voltage in V and frequency in system, — information and documentation on the in- sting:				
		230V, 50Hz, Total Harmonic Distortion	<2 %			
Additio	nal Notebook Batter					
		Battery[ies] not user replaceable	Battery[ies] user replaceable	n/a		
		The battery[ies] in this product cannot be easily replaced by users themselves. <sup>1)</sup>				
Internal/	/built-in Battery					
Externa	External/detachable Battery					
Bios Ba	Bios Backup Battery					
Other:						
Addition	al information					
		asily replaced by users themselves.				
кумулаторн as baterías c	ата[ите] батерия[и] в този п de este producto no pueden s	родукт не може да се замени[ят] лесно от самите потребител er sustituidas fácilmente por los propios usuarios.	и.			
ýměnu bater	rie/baterií v tomto výrobku by	neměli provádět sami uživatelé				

Vymenu baterie/baterii v tomto vyrooku by nemeii provadet sami uzivatele. Brugeren kan ikke uden videre udskifte batteriet/batterierne i dette produkt. Der Akku/die Akkus dieses Produkts kann/können nicht ohne weiteres vom Benutzer selbst ausgetauscht werden. Kasutajad ei saa selle toote akut/akusid ise hõlpsasti asendada. Η μπαταρία[-ες] στο προϊόν αυτό δεν μπορούν να αντικατασταθούν εύκολα από τους ίδιους τους χρήστες La/les batterie(s présente(s) dans ce produit ne peuvent être facilement remplacée(s) par les utilisateurs eux-mêmes. Korisnik ne može lako zamijeniti Bateriju sam u ovom proizvodu.

La batteria/le batteria questo prodotto non può/possono essere facilmente sostituita/e dall'utente. Lietotăji paši nevar nomainīt šā ražojuma akumulatoru(-us). Šio gaminio baterijos [bateriju] pats vartotojas negali lengvai pakeisti. A termék akkumulátorát/akkumulátorait a felhasznáió nem tudja egyedül egyszerűen kicserélni. II-batterija/batteriji f'dan iI-prodott ma tistax/jistgħux tiġi/jiġu sostitwita/i mill-utenti stess.

Batteriet [ene] i dette produktet kan ikke lett erstattes av brukerne selv. De batterij(en) in dit product is (zijn) door de gebruiker niet gemakkelijk vervangbaar. Użytkownik nie może sam w łatwy sposób wymienić baterii w tym produkcie. A ou as baterias deste produto não podem ser facilmente substituídas pelos próprios utilizadores. Bateria (bateriile) din acest produs nu poate (pot) fi uşor înlocuită (înlocuite) de utilizatorii înșiși. Batériu(-ie) v tomto výrobku nemôže vymieňať používateľ. Baterijaterije v tem izdelku uporabniki sami ne morejo zlahka zamenjati. Tämän tuotteen akku [akut] ei[vät] ole helposti käyttäjän vaihdettavissa. Det är inte enkelt för kunden att själv byta ut batteriet/batterierna. Bu üründeki batarya(lar) kullanıcılar tarafından kolaylıkla değiştirilemez.