

ECMA/TC38-TG3/2015/026 (Rev. 1 – 15 April 2017)

Annex B2 - Product environmental attributes Desktop/All-in-One Computers

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lenovo	Logo		
Company name *	Lenovo			
Contact information *	Lenovo Global Environmental Affairs		Lenovo	
e-mail address	Alvin L Carter		LEIIOVO	
	alcarter@lenovo.com			
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment	.html		
Additional information	The latest version of this document can be found at:			
	http://www.lenovo.com/ecodeclaration			

The company declares (The company declares (based on product specification or test results based obtained from sample testing), that the product						
conforms to the statement	conforms to the statements given in this declaration.						
Type of product *	Desktop						
Commercial name *	IdeaCentre Creator 5						
Model number *	90R7, 90R8						
Issue date *	2020/05/21						
Intended market *	🗌 Global 🔀 Europe 🗌 Asia, Pacific & Japan 🔀 Americas 🗌 Other						
Additional information							

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template: P4.1 – P4.3 Consumable materials P9.1 TEC and Print speed P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products.

Model number * Issue date *		90R7, 90R8	ogo	010		
		2020/05/21		_enc		Этн
Produc	t enviror	mental attributes - Legal requirements	F	Require	ment	t met
Item				Yes	No	n.a.
P1	Hazard	ous substances and preparations				
P1.1*	Product	s do comply with current European RoHS Directive. (See legal reference and NOTE B	1)	\square		
P1.2*		s do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value.		\boxtimes		
P1.3*	hydrobr trichloro	s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), omofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachlor ethane, methyl bromide (see legal reference). Comment: Legal reference has no max ration values.		\boxtimes		
P1.4*		s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlor yl (PCT) in preparations (see legal reference).	inated	\boxtimes		
P1.5*	Product	s do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbor intaining at least 48% per mass of chlorine in the SCCP (see legal reference).	atoms in the	\square		
P1.6*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm ² /week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:2011-5.					
P1.7*	REACH	Article 33 information about substances in articles is available at (add URL or mail cor ww.lenovo.com/us/en/Lenovo-REACH-SVHC-Disclosure	itact):	\square		
P2	Batterie	S				
P2.1*		oduct contains a battery or an accumulator, the battery/accumulator is labeled with the Information on proper disposal is provided in user manual. (See legal reference)	disposal	\square		
P2.2*	Batterie referenc	s or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmiur e)	n. (See legal	\boxtimes		
P2.3*	Batterie	s and accumulators are readily removable. (See legal reference)		\square		
P3	Confor	nity verification & Eco design (ErP)				
P3.1*	The pro	duct is CE-marked to show conformance with applicable legal requirements (see legal claration of Conformity can be requested at: https://www.lenovo.com/us/en/compliance		\square		
P3.2*	The pro	duct complies with the Eco design requirements for energy-related products, al reference).		\boxtimes		
		d information is; given in item P15 or added to this document, available at: https://www.lenovo.com/us/en/compliance/eco	declaration	\boxtimes		
P5	Droduc	t packaging				_
P5.1*		ng and packaging components do not contain more than 0,01% lead, mercury, o	cadmium and			
	hexaval	ent chromium by weight of these together.				
P5.2*	used (se	kaging materials are marked with abbreviations and numbers indicating the nature of t e legal reference).	()			
P5.3*	(see leg	duct packaging material is free from ozone depleting substances as specified in the Mor al reference). nt: Legal reference has no maximum concentration values.	treal Protocol			
P6		Int information				
P6.1*		ion for recyclers/treatment facilities is available (see legal reference).				

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model nu	ımber *	90R7, 90R8	Logo	Lon		
Issue dat	te *	2020/05/21		Len	OVC	Рн
Product	environ	mental attributes - Market requirements (See General NOTE GN I	pelow)			
		onmental conscious design		Require		met
Item		tory to fill in. Additional information regarding each item may be found under P14.		Yes	No	n.a.
P7.1*		Disassembly, recycling t have to be treated separately are easily separable				
P7.2*		aterials in covers/housing have no surface coating.			╞┼╴	<u> </u>
P7.3*		arts > 100 g consist of one material or of easily separable materials.			╞	<u> </u>
					<u> </u>	<u> </u>
P7.4*		arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.			Ц_	<u> </u>
P7.5		arts are free from metal inlays or have inlays that can be removed with commonly a	vallable tools.		Ц_	<u>Ц</u>
P7.6*		re easily separable. (This requirement does not apply to safety/regulatory labels).				
D7.7*	Product					
P7.7*		g can be done e.g. with processor, memory, cards or drives			——	_ᆜ
P7.8*		ig can be done using commonly available tools		\bowtie		<u>Ц</u>
P7.9		rts are available after end of production for: 5 years				
P7.10	Service i	s available after end of production for: 5 years				
D7.44*		and substance requirements				
P7.11*		cover/housing material type (e.g. plastics, metal, aluminum): type: ABS Material type: PC Materia	l tupo:			
P7.12		n materials of external electrical cables are PVC free.	i type.		\boxtimes	
P7.13		n materials of internal electrical cables are PVC free.		<u> </u>		╞
P7.14		plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) br	omine and 0 1º	/o 🔀	\square	╞
17.14	weight (1 polyvinyl	1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine ir n 25% post-consumer recycled content.	retardants, an	d 🗖		
P7.15	as define	ircuit boards, PCBs (without components) are low halogen: all \square PCBs > 25 g \bowtie d in IEC 61249-2-21. (See 1NOTE B2)	are low haloge	n 🔀		
P7.16	Marking:			\square		
P7.17		nemical specifications of flame retardants in printed circuit boards > 25 g (without co PA (additive), TBBPA (reactive) (See NOTE B3), Other: , CAS #: 79-94-		\boxtimes		
		nemical specifications of flame retardants in printed circuit boards (without compone g ISO 1043-4:	ents) > 25 g			\square
P7.18	concentra 1. Chemi 2. Chemi	ame retarded plastic parts > 25 g contain the following flame retardant substances ations above 0,1%: ical name: , CAS #: (See NOTE B4) ical name: , CAS #: " ical name: , CAS #: "	s/preparations i			
	<u>Alt. 2: </u> Ch	nemical specifications of flame retardants in plastic parts > 25 g according ISO 1043				
P7.19	•	parts > 25 g, flame retardant substances/preparations above 0,1% are used which the following Risk phrases; and Hazard statements:	have been			
			ee note B5)			
P7.20*	Postcons	sumer recycled plastic material content is used in the product (See Note B6):		\boxtimes		
	a) Of the a performance or	t least one of the two alternatives below shall be answered; otal plastic parts' weight > 25 g, the postconsumer recycled plastic material content ercentage of total plastic by weight) is 13.6% .	(calculated as			

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model number *	90R7, 90R8	Logo	
Issue date *	2020/05/21		LEHOVO

Product environmental attributes - Market requirements (continued) Item Requirement met Yes No n.a.

	Material and su	bstance requirements	(continued)			
P7.21*		material content is used		OTE B7):		Τ
P7.22*		e free from mercury, i.e. d specify: Number of la		um mercury content pe	er lamp: mg	
P8	Batteries					
P8.1*	Battery chemical	composition:				$\overline{\langle}$
P9		ption (See NOTE B8)				
P9.1		he following power leve				
Energy m		Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference/Standard for energy modes and test method *	
Peak (On	-max)	W	W	W	Full load	
<u>Catego</u>	<u>ry D2</u>					
Short Idle Enabled	e State - WOL	29.1 W	28.8 W	29.3 W	Use for ENERGY STAR V8 registration (P _{idle})	
Long Idle Enabled	e State - WOL	26.1 W	26.3 W	27.2 W	Use for ENERGY STAR V8 registration (P _{idle})	
Sleep (S3	3) - WOL Enabled	0.9 W	0.9 W	0.9 W	Use for ENERGY STAR V8 registration (P _{sleep})	
Off (S5) -	WOL Enabled	0.5 W	0.5 W	0.5 W	Use for ENERGY STAR V8 registration (P_{off})	
Off (S5) -	WOL Disabled	W	W	0.63 W	Use for ErP	
EPS No-lo (External power wall outlet but d	oad r supply / charger plugged in th lisconnected from the product.)	W	W	W		\triangleleft
PTEC *	nergy Consumption	W	W	W		\triangleleft
ETEC * Annual Er	nergy Consumption	D2:103.7kWh/year	D2:103.1 kWh/year	D2:105.1 kWh/year	E _{TEC} = (8760/1000) x (P _{off} x 0.45 + P _{sleep} x 0.05 + P _{long_ldle} x 0.15+ P _{short_ldle} x 0.35)]
		Poff: Off Mode(S5) - WOL Enabled; P _{slee}	sieep Mode(S3) - WOL	. Enabled; P _{idle} : Idle State - WOL Enabled	
External F	Power Supply Efficie	ency Level (Internationa				\triangleleft
Display re	esolution * :	megapixels				2
		save mode: 25 minutes				Ť
P9.2*	0,	it the energy save funct	ion is provided with the	product.		╡
P9.3		y class (monitors only):				
P10	Emissions	, sidee (merinere enity).				<u> </u>
		- Declared according to	o ISO 9296 (See NOTE	B9)		
P10.1	Mode	Mode description	(it A-weighted sound power level, L _{WA,c} (B)	1
	Idle	* HDD:Idle			,,,,,,, _	Т
	Operation	* HDD: Operating		* 3.9		Ŧ
	Other mode	Declared A-weighted sour	nd pressure level (dBL)(A)	23 (operator position	on desktop – idle)	<u> </u>
	Other mode	Declared A-weighted sour			on desktop – HDD operating)	
		ding to: 🔀 ISO 7779	ECMA-74			
		Other	(only if not covered by	ECMA-74)		
				/		

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see <u>http://www.ecma-international.org/publications/standards/Ecma-370.htm</u>

Model nu	mber *	90R7, 90R8					Logo				
Issue dat	e *	2020/05/21						Le	eno	VO	тм
Product	environ	mental attribut	es - Market requirer	nents (con	tinued)			Re	quire	ment	met
Item									Yes	No	n.a.
		magnetic emissi									
P10.4	Comput program		the requirement for low	frequency el	ectromagnetic field	Is of the foll	owing volunt	tary	\square		
P12		mics for comput									
P12.1*	The disp	play meets the er	gonomic requirements c	of ISO 9241-3	307 for visual displa	ay technolo	gies.				\boxtimes
P12.2*	The phy	sical input device	meets the requirement	s of ISO 999	5 and ISO 9241-42	10.					
P13	Packag	ing and docume	ntation								
P13.1*	Product	packaging mater	ial type(s): <i>Paper</i> ial type(s): <i>EPE</i> ial type(s): <i>PE</i> weight (weight (kg weight (kg kg): 0.05							
P13.2*			ackaging is free from P								\square
P13.3*	For product primary corrugated fiberboard packaging, specify the contained percentage of minimum post-										
P13.4*		media for user ar ronic, XPaper,	nd product documentatio	on (tick box):							
P13.5	Ùser an		is item if paper documer entation on paper media								
	Totally o	hlorine-free							\bowtie		
	Elemen	al chlorine-free							$\overline{\boxtimes}$		
	Processed chlorine-free						$\overline{\boxtimes}$				
P14	Volunta	ry programs									
P14.1	The pro	duct meets the re	quirements of the follow	ving voluntar	y program(s):						
	ENERG Eco-lab Eco-lab		Criteria version: 8. Criteria version: Criteria version:	0	Date: 2020/2/24 Date: Date:	Product o Product o Product o	0,	sktop			
P15	Additio	nal information	(See NOTE B10)								
P9			^f specific configuration								
	informat knowled	ion contained in t ge available at th d here is approxim	o representations, guara this document. All inform the time of completion, an nate and provided for in	nation provid nd supplier s	ed by supplier in th hall have no obliga	is documer tion to upda	nt is provided ate such info	based o rmation.	n supp The in	olier's format	tion
P9	See Ene	ergy Star Qualifie	d Notebooks & Tablet C v/index.cfm?fuseaction=				code=CO				

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B2

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1
Regulation (EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7
Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)	P1.3, P5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) No 1272/2008 (CLP Regulation)	P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1

Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	IdeaCentre Creator 5 14IMB05	Logo
Model Number	90R7, 90R8	
Issue Date	2020/05/21	Lenovo
Additional information	Energy Star 8.0	

P7.1.1	Product environmental attributes				
(d)	year of manufacture:				2020
(e)	Etec value (kWh) per ErP Lot 3 Categor disabled and if the system is tested with				cards (dGfx) are
(f)	Etec value (kWh) per ErP Lot 3 Categor enable	y and capability adjust	ments applied when a	III discrete graphics o	cards (dGfx) are
		Category A (according to ErP Lot 3)	Category B (according to ErP Lot 3)	Category C (according to ErP Lot 3)	Category D (according to ErP Lot 3)
	Memory over base [GB]				30
ents ting	Additional internal storage	(Yes / No)	(Yes / No)	(Yes / No)	Yes (Yes / No)
capability adjustments applied during testing	Discrete television tuner	(Yes / No)	(Yes / No)	(Yes / No)	No (Yes / No)
ability a	Discrete Audio Card	(Yes / No)	(Yes / No)	(Yes / No)	No (Yes / No)
cap app	Discrete graphics Card(s) [number / #]	#: (Yes / No)	#: (Yes / No)	#: (Yes / No)	Yes #: 1 (Yes / No)
	Category of discrete graphics Card(s)				G6
Test results	Etec Value (kWh) - dGfx disabled all discrete graphics cards (dGfx) are disabled/ UMA is active for switchable graphics/ product has no graphics cards (dGfx)				
Test r	Etec Value (kWh) - dGfx enabled all discrete graphics cards (dGfx) are enabled				105.69
(g)	Idle state power demand (Watts);	•	•		29.33
(h)	Sleep mode power demand (Watts);				0.92
(i)	Sleep mode with WOL enabled power de	emand (Watts) (where	enabled);		0.94
(j)	Off mode power demand (Watts);				0.54
(k)	Off mode with WOL enabled power dema	and (Watts) (where en	abled);		0.52
(I)	Internal power supply efficiency at 10 %,	20 %, 50 % and 100 9	% of rated output pow	er (if applicable):	
	PCK012-EL0G : 10% 83.83% 20% 85	.34% 50% 87.16%	100% 84.63% Ave	rage 85.71%	
	HK360-71PP: 10% 85.63% 20% 86.30	% 50% 87.45% 10	00% 84.36% Averag	e 86.04%	
	FSP260-20TLA: 10% 85.61% 20% 86.	23% 50% 86.98%	100% 84.26% Aver	age 85.82%	
	PCJ007-EL0G: 10% 89.17% 20% 91.3	8% 50% 92.74% 1	100% 89.72% Avera	ge 91.28%	
	PCK014-EL0G: 10% 90.84% 20% 91.1	12% 50% 93.00% ⁻	100% 90.54% Avera	age 91.55%	
(m)	External power supply efficiency (if applied	cable)*:			
	Average active efficiency: N/A *internal note: show values for all available external po				
(0)	Minimum number of loading cycles that t		tand (applies only to n	otebook computers):	N/A

(p-1) Measurement methodology used to determine information mentioned in points (i) – internal PSU efficiency: Generalized Test Protocol for Calculating the Carryg Efficiency of Internal Ac-Dc and Dc-Dc Power Supplies Revision 6.6 (p-2) Measurement methodology used to determine information mentioned in points (o) – loading cycles batteries: N/A (p-3) Measurement methodology used to determine information mentioned in maximum, idle, sieep, off mode power as defined in Point P9.1 in the Product IT Eco Declaration: IEC 62623 Ed. 1.0, 2012-10 (q) Sequence of steps for achieving a stable condition with respect to power demand: Based on user manual/Power on-Walf 5 minutes-Stable condition (r) Description of how sleep and/or off mode was selected or programmed: Based on user manual/Power on-Walf 5 minutes-Stable condition (r) Description of how sleep and/or off mode was selected or programmed: Based on user manual/Control Panel->Power Options-> Change Settings-> Restore default settings for mode: Based on user manual/Segin menu > Power -> Select sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes): (u) 20 (u) Length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirements for sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode, in minutes): (u) 20								
N/A (p-3) Measurement methodology used to determine information mentioned in points (o) – loading cycles batteries: N/A (p-4) Measurement methodology used to determine information mentioned in maximum, idle, sleep, off mode power as defined in Point P9.1 in the Product IT Eco Dedaration: Dece 2623 Ed.1.0, 2012-10 (q) Sequence of steps for achieving a stable condition with respect to power demand: Based on user manual/Power on-Walt 5 minutes->Stable condition (r) Description of how sleep and/or off mode was selected or programmed: Based on user manual/Power on-Walt 5 minutes->Stable condition (r) Description of how sleep and/or off mode was selected or programmed: Based on user manual/Power on-Walt 5 minutes->Stable condition (r) Description of how sleep and/or off mode was selected or programmed: Based on user manual/Power Options-> Change Settings-> Restore default settings for this plan (l) Duration of idle state condition before the computer automatically reaches a power mode that has a lower power demand requirements for sleep mode (in minutes): (v) 20 (u) Length of time before the display sleep mode is set to activate after user indexity (in minutes): (v) 10 (u) Length of time before the display sleep mode (in minutes): (v) 10 (u) Length of time before the display add on user manual (x) User information on how to enable the power management functionality: Based on user manual	(p-1)	Generalized Test Protocol for Calculating the Energy Efficiency of Internal Ac-Dc and Dc-Dc Power Supplies Revision 6.6						
N/A (p-4) Measurement methodology used to determine information mentioned in maximum, idle, sleep, off mode power as defined in Point P9.1 in the Product IT Eco Declaration:	(p-2)	Measurement metho		points (m) – external PSU efficiency:				
power as defined in Point P9.1 in the Product IT Eco Declaration: IEC 62623 Ed. 1.0, 2012-10 (q) Sequence of steps for achieving a stable condition with respect to power demand: Based on user manual/Power on-Wait 5 minutes->Stable condition (r) Description of how sleep and/or off mode was selected or programmed: Based on user manual/Begin menu -> Power -> Select sleep or off mode (s) Sequence of events required to reach the mode where the equipment automatically changes to sleep and/or off mode: Based on user manual/Control Panel->Power Options-> Change Settings-> Restore default settings for this plan (t) Duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode, or another mode that has a lower power demand requirement than sleep mode (in minutes): 20 (u) Length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes): 10 (w) Length of time before the display sleep mode is set to activate after user inactivity (in minutes): 10 (w) Information on how to enable the power management functionality: Based on user manual 20 (x) User information on how to enable the power management functionality: Based on user manual 20 (z) Test parameters for	(p-3)							
Based on user manual/Power on->Wait 5 minutes->Stable condition (r) Description of how sleep and/or off mode was selected or programmed: Based on user manual/Begin menu -> Power -> Select sleep or off mode (s) Sequence of events required to reach the mode where the equipment automatically changes to sleep and/or off mode: Based on user manual/Control Panel->Power Options-> Change Settings-> Restore default settings for this plan (t) Duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes): 20 (u) Length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes): 10 (v) Length of time before the display sleep mode is set to activate after user inactivity (in minutes): 10 (w) Information on the energy-saving potential of power management functionality: Based on user manual 20 (x) User information on how to enable the power management functionality: Based on user manual 20 (z) Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: 230V, 50Hz, Total Harmonic Distortion <2 %	(p-4)		Point P9.1 in the Product IT Eco Declaration:	naximum, idle, sleep, off mode				
Based on user manual/Begin menu -> Power -> Select sleep or off mode (s) Sequence of events required to reach the mode where the equipment automatically changes to sleep and/or off mode: Based on user manual/Control Panel->Power Options-> Change Settings-> Restore default settings for this plan (t) Duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes): 20 (u) Length of time after a period of user inactivity in which the computer automatically reaches a power NA (v) Length of time before the display sleep mode is set to activate after user inactivity (in minutes): 10 (w) Information on the energy-saving potential of power management functionality: Based on user manual 10 (x) User information on how to enable the power management functionality: Based on user manual 11 (x) User information on how to enable the power management functionality: Based on user manual 12 (z) Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: 20V, 50Hz, Total Harmonic Distortion <2 %	(q)							
off mode: Based on user manual/Control Panel->Power Options-> Change Settings-> Restore default settings for this plan (t) Duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes): 20 (u) Length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes): NA (v) Length of time before the display sleep mode is set to activate after user inactivity (in minutes): 10 (w) Information on the energy-saving potential of power management functionality: Based on user manual (x) User information on how to enable the power management functionality: Based on user manual (x) User information on how to enable the power management functionality: Based on user manual (z) Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: 200///////////////////////////////////	(r)							
condition which does not exceed the applicable power demand requirements for sleep mode (in minutes): 20 (u) Length of time after a period of user inactivity in which the computer automatically reaches a power NA (u) Length of time before the display sleep mode is set to activate after user inactivity (in minutes): NA (v) Length of time before the display sleep mode is set to activate after user inactivity (in minutes): 10 (w) Information on the energy-saving potential of power management functionality: Based on user manual (x) User information on how to enable the power management functionality: Based on user manual (x) User information on how to enable the power management functionality: Based on user manual (z) Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: 230V, 50Hz, Total Harmonic Distortion <2 %	(s)	off mode: Based on user manual/Control Panel->Power Options-> Change Settings-> Restore default settings						
mode that has a lower power demand requirement than sleep mode (in minutes): IV4 (v) Length of time before the display sleep mode is set to activate after user inactivity (in minutes): 10 (w) Information on the energy-saving potential of power management functionality: Based on user manual 10 (x) User information on how to enable the power management functionality: Based on user manual 10 (z) Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: 230V, 50Hz, Total Harmonic Distortion <2 %	(t)							
(v) Length of time before the display sleep mode is set to activate after user inactivity (in minutes): 10 (w) Information on the energy-saving potential of power management functionality: Based on user manual 10 (x) User information on how to enable the power management functionality: Based on user manual 10 (z) Test parameters for measurements: test voltage in V and frequency in Hz, total harmonic distortion of the electricity supply system, information and documentation on the instrumentation, set-up and circuits used for electrical testing: 230V, 50Hz, Total Harmonic Distortion <2 %	(u)	(u) Length of time after a period of user inactivity in which the computer automatically reaches a power						
(w) Information on the energy-saving potential of power management functionality: Based on user manual (x) User information on how to enable the power management functionality: Based on user manual (z) Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: 230V, 50Hz, Total Harmonic Distortion <2 %	(v)				10			
Based on user manual (z) Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: 230V, 50Hz, Total Harmonic Distortion <2 %	(w)	Information on the er		nality:				
the electricity supply system, — information and documentation on the instrumentation, set-up and circuits 230V, 50Hz, Total Harmonic Distortion <2 %	(x)	User information on I						
Battery[ies] not user replaceable The battery[ies] in this product cannot be easily replaced by users themselves. 1)Battery[ies] user replaceablen/aInternal/built-in BatteryImage: Image: Image	(z)	the electricity supply	system, — information and documentation on the in sting:	strumentation, set-up and circuits				
The battery[ies] in this product cannot be easily replaced by users themselves. 1) Internal/built-in Battery Image: Constraint of the senseling of the	Additio	nal Notebook Batter	y Information:					
replaced by users themselves. 1) Internal/built-in Battery Internal/built-in Battery Image: Comparison of the set				Battery[ies] user replaceable	n/a			
External/detachable Battery Image: Constraint of the second sec								
Bios Backup Battery	Internal/built-in Battery							
	External/detachable Battery							
Additional information	Bios Ba	Bios Backup Battery						
	Addition	nal information		•	·			
) ne battery[ies] in this product cannot be easily replaced by users themselves.	ne battervlie	es] in this product cannot be e	asily replaced by users themselves.					

Las baterías de este producto no pueden ser sustituidas fácilmente por los propios usuarios.

Výměnu baterie/baterií v tomto výrobku by neměli provádět sami uživatelé. Brugeren kan ikke uden videre udskifte batteriet/batterierne i dette produkt. Der Akku/die Akkus dieses Produkts kann/können nicht ohne weiteres vom Benutzer selbst ausgetauscht werden.

Kasutajad ei saa selle toote akut/akusid ise hõlpsasti asendada. Η μπαταρία[-ες] στο προϊόν αυτό δεν μπορούν να αντικατασταθούν εύκολα από τους ίδιους τους χρήστες La/les batterie(s présente(s) dans ce produit ne peuvent être facilement remplacée(s) par les utilisateurs eux-mêmes.

Korisnik ne može lako zamijeniti Bateriju sam u ovom proizvodu. La batteria/le batterie in questo prodotto non può/possono essere facilmente sostituita/e dall'utente. Lietotāji paši nevar nomainīt šā ražojuma akumulatoru(-us).

šio gaminio baterijos [bateriju] pats vartotojas negali lengvai pakeisti. A termék akkumulátorát/akkumulátorait a felhasználó nem tudja egyedül egyszerűen kicserélni. II-batterija/batteriji f'dan il-prodott ma tistax/jistgħux tiġi/jiġu sostitwita/i mill-utenti stess.

Batteriet [ene] i dette produktet kan ikke lett erstattes av brukerne selv. De batterij(en) in dit product is (zijn) door de gebruiker niet gemakkelijk vervangbaar. Użytkownik nie może sam w łatwy sposób wymienić baterii w tym produkcie.

A ou as baterias deste produto não podem ser facilmente substituídas pelos próprios utilizadores. Bateria (bateriile) din acest produs nu poate (pot) fi ușor înlocuită (înlocuite) de utilizatorii înșiși.

Batériu(-ie) v tomto výrobku nemôže vymieňať používateľ.

Baterij/baterije v tem izdelku uporabniki sami ne morejo zlahka zamenjati. Tämän tuotteen akku [akut] ei[vät] ole helposti käyttäjän vaihdettavissa. Det är inte enkelt för kunden att själv byta ut batteriet/batterierna.

Bu üründeki batarya(lar) kullanıcılar tarafından kolaylıkla değiştirilemez.