

ECMA/TC38-TG3/2015/026 (Rev. 1 - 15 April 2015)

### Annex B2 - Product environmental attributes **Notebooks and Tablets**

The declaration may be published only when all rows and/or fields marked with \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lenovo	Logo				
Company name *	Lenovo					
Contact information * e-mail address	Lenovo Global Environmental Affairs Alvin L Carter alcarter@lenovo.com	Lenovo				
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment.html					
Additional information	The latest version of this document can be found at: http://www.lenovo.com/ecodeclaration					

The company declares (based on product specification or test results based obtained from sample testing), that the produc conforms to the statements given in this declaration.						
Type of product *	NB					
Commercial name *	Lenovo Legion Y740S-15/Legion Y9000X 2020R					
Model number *	81YX, 81YY					
Issue date *	2020.4.20					
Intended market *	🔀 Global 📃 Europe 📃 Asia, Pacific & Japan 📃 Americas 🗌 Other					
Additional information						

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

#### About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template: P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products P11.1 - P11.3 Consumable materials for printing products

Model nu	ımber *	81YX, 81YY Logo			
Issue dat	te *	2020.4.20	Len	ovo	Этн
	environ	mental attributes - Legal requirements	Require		
Item			Yes	No	n.a.
P1		bus substances and preparations			
P1.1*		s do comply with current European RoHS Directive. (See legal reference and NOTE B1)			
P1.2*	Comme	s do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value.			
P1.3*	hydrobro trichloro	s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), omofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1 ethane, methyl bromide (see legal reference). Comment: Legal reference has no maximun ration values.			
P1.4*		s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinate /I (PCT) in preparations (see legal reference).	d 🛛		
P1.5*		ms in the 🛛 🔀			
P1.6*	(see leg	th direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cr al reference). nt: Max limit in legal reference when tested according to EN1811:2011-5.	m²/week 🔀		
P1.7*	REACH	Article 33 information about substances in articles is available at (add URL or mail contact) <a href="http://www.lenovo.com/us/en/Lenovo-REACH-SVHC-Disclosure">www.lenovo.com/us/en/Lenovo-REACH-SVHC-Disclosure</a>	:		
P2	Batterie	S			
P2.1*		oduct contains a battery or an accumulator, the battery/accumulator is labeled with the disp Information on proper disposal is provided in user manual. (See legal reference)	osal 🛛 🔀		
P2.2*	Batteries referenc	s or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (S e)	ee legal 🛛 🔀		
P2.3*	Batteries	s and accumulators are readily removable. (See legal reference)	$\square$		
P3	Conform	nity verification & Eco design (ErP)			
P3.1*	The proc	duct is CE-marked to show conformance with applicable legal requirements (see legal refer claration of Conformity can be requested at: <u>https://www.lenovo.com/us/en/compliance/eu-c</u>			
P3.2*	The proc	duct complies with the Eco design requirements for energy-related products, al reference).	$\boxtimes$		
	· ·	d information is; given in item P15 or added to this document,			
DE	Dreduct	available at: https://www.lenovo.com/us/en/compliance/eco-deci	ลาสแบบ		
P5.1*		t <b>packaging</b> ng and packaging components do not contain more than 0,01% lead, mercury, cadm	ium and 🔽		
	hexavale	ent chromium by weight of these together.			
P5.2*	used (se	kaging materials are marked with abbreviations and numbers indicating the nature of the mater legal reference).			
P5.3*	Protocol	duct packaging material is free from ozone depleting substances as specified in the (see legal reference). nt: Legal reference has no maximum concentration values.	Montreal 🔀		
P6		Int information			
		ion for recyclers/treatment facilities is available (see legal reference).		_	

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model nu	umber *	81YX, 81YY	Logo			
Issue dat	te *	2020.4.20		Len	ovc	Тм
Product	t environ	mental attributes - Market requirements (See General NOTE GN	below)			
		onmental conscious design		Require	ment	met
Item		tory to fill in. Additional information regarding each item may be found under P14.		Yes	No	n.a.
<b>P7</b> P7.1*		Disassembly, recycling thave to be treated separately are easily separable				
P7.2*						<u> </u>
P7.3*		naterials in covers/housing have no surface coating. arts > 100 g consist of one material or of easily separable materials.				<u> </u>
P7.4*		arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.			<u> </u>	<u> </u>
P7.5	•	arts are free from metal inlays or have inlays that can be removed with commonly a	wailable toole		<u> </u>	<u> </u>
					<u> </u>	
P7.6*		re easily separable. (This requirement does not apply to safety/regulatory labels).		$\square$		
P7.7*	Product	Interime ng can be done e.g. with processor, memory, cards or drives				
P7.8*						<u> </u>
		ng can be done using commonly available tools			$\boxtimes$	<u> </u>
P7.9		arts are available after end of production for: 5 years				<u> </u>
P7.10		s available after end of production for: 5 years				
P7.11*		and substance requirements				
P7.11		cover/housing material type (e.g. plastics, metal, aluminum): type: <i>Aluminum 5052</i> Material type: <i>Covestro FR3008</i> Materia	al type: <b>Covestr</b>	o FR3002		
P7.12		n materials of external electrical cables are PVC free.			$\boxtimes$	
P7.13	Insulation	n materials of internal electrical cables are PVC free.				╞
P7.14		plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) b	romine and 0.1	%		
	weight (* polyvinyl	1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) og more than 25% post-consumer recycled content.	e retardants, an	d		
P7.15	Printed of	circuit boards, PCBs (without components) are low halogen: all PCBs > as defined in IEC 61249-2-21. (See 1NOTE B2)	25 g 🗌 are lo	w		
P7.16		tarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:				$\square$
P7.17	TBBF	nemical specifications of flame retardants in printed circuit boards > 25 g (without c PA (additive), TBBPA (reactive) (See NOTE B3), Other: <i>Halogen-free epoxy</i> Frade secret / 35948-25-5		$\boxtimes$		
		nemical specifications of flame retardants in printed circuit boards (without compone g ISO 1043-4:	ents) > 25 g			$\square$
P7.18	concentr 1. Chemi	ame retarded plastic parts > 25 g contain the following flame retardant substance ations above 0,1%: ical name: , CAS #: (See NOTE B4) ical name: , CAS #: "	es/preparations i	n		
		ical name: , CAS #: " nemical specifications of flame retardants in plastic parts > 25 g according ISO 104	3- <u>4</u> ·			
P7.19		parts > 25 g, flame retardant substances/preparations above $0,1\%$ are used which		<u> </u>		
17.15	•	I the following Risk phrases; and Hazard statements:	i nave been			
	0		See note B5)			
P7.20*		sumer recycled plastic material content is used in the product (See Note B6):			$\square$	
		t least one of the two alternatives below shall be answered; Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material of (calculated as a percentage of total plastic by weight) is 0 %. The weight of recycled material is 0 g.	ontent			

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Item P7.21* Ma P7.21* Bid If Y a) or b) P7.22* Lig If r P8 Ba P8.1* Ba P9 En P9.1 Fo Energy mode * Peak (On-max Category - Short Idle Stat Enabled	of total plastic The weight of ght sources are f mercury is used atteries attery chemical c nergy consump or the product the * x) 2 atte - WOL	tributes - Mai stance requiren haterial content i e of the two alter ic parts' weight by weight) is i the biobased p free from mercur specify: Number omposition: Li-p tion (See NOTE	nents (continu s used in the pr rnatives below = > 25 g, the biol %. lastic material is ry, i.e. less thar r of lamps: colymer B8) er levels or ener I at Pow	ed) roduct (See I shall be answ based plastic s g. n 0,1 mg/lam and maxin	NOTE B7): wered; c material co p. mum mercul ptions are rep Powe	ry content p	er lamp: 1	Yes	iremer No	
Item P7.21* Ma P7.21* Bid If Y a) or b) P7.22* Lig If r P8 Ba P8.1* Ba P9 En P9.1 Fo Energy mode * Peak (On-max Category - Short Idle Stat Enabled	aterial and subs iobased plastic m YES; at least one ) Of total plastic of total plastic ) The weight of ght sources are f mercury is used atteries attery chemical c nergy consump or the product the * x) 2 ate - WOL	stance requiren naterial content i e of the two alter ic parts' weight by weight) is f the biobased p ree from mercur specify: Number omposition: <i>Li-p</i> tion (See NOTE e following power Power level 100 V AC 95 W	nents (continu s used in the pr rnatives below = > 25 g, the biol %. lastic material is ry, i.e. less thar r of lamps: colymer B8) er levels or ener l at Pow 2 1'	ed) roduct (See I shall be ansy based plastic s g. n 0,1 mg/lam and maxin and maxin gy consump rer level at 15 V AC	NOTE B7): wered; c material co p. mum mercul vitions are rep Powe 23	ry content po ported: er level at	er lamp: 1	Yes	No	
Item Ma P7.21* Bid If Y a) or b) P7.22* Lig If r P8 Ba P8.1* Ba P9 En P9.1 Fo Energy mode * Peak (On-max Category - Short Idle Stat Enabled	aterial and subs iobased plastic m YES; at least one ) Of total plastic of total plastic ) The weight of ght sources are f mercury is used atteries attery chemical c nergy consump or the product the * x) 2 ate - WOL	stance requiren naterial content i e of the two alter ic parts' weight by weight) is f the biobased p ree from mercur specify: Number omposition: <i>Li-p</i> tion (See NOTE e following power Power level 100 V AC 95 W	nents (continu s used in the pr rnatives below = > 25 g, the biol %. lastic material is ry, i.e. less thar r of lamps: colymer B8) er levels or ener l at Pow 2 1'	ed) roduct (See I shall be ansy based plastic s g. n 0,1 mg/lam and maxin and maxin gy consump rer level at 15 V AC	NOTE B7): wered; c material co p. mum mercul vitions are rep Powe 23	ry content po ported: er level at	er lamp: 1	Yes	No	
MaP7.21*BidIf N a)or b)P7.22*Lig If rP8BaP8.1*BaP9.1FoEnergy mode *Peak (On-maxCategory -Short Idle StateEnabledLong Idle StateEnabled	iobased plastic m YES; at least one ) Of total plastic of total plastic ) The weight of ght sources are f mercury is used atteries attery chemical c nergy consump or the product the * x) 2 ate - WOL	aterial content i e of the two alter ic parts' weight by weight) is f the biobased p ree from mercur specify: Number omposition: <i>Li-p</i> tion (See NOTE following power Power level 100 V AC 95 W	s used in the prinatives below s > 25 g, the biol %. lastic material is ry, i.e. less thar r of lamps: bolymer B8) r levels or ener l at Pow 2 1'	roduct (See I shall be answ based plastic s g. n 0,1 mg/lam and maxin and maxin gy consump rer level at 15 V AC	wered; c material co p. mum mercu vtions are rep Powe 230	ry content po ported: er level at	er lamp: 1	centage mg		
P7.21* Bid If V a) or b) P7.22* Lig If r P8 Ba P8.1* Ba P9 En P9.1 Fo Energy mode * Peak (On-max Category - Short Idle Stat Enabled	iobased plastic m YES; at least one ) Of total plastic of total plastic ) The weight of ght sources are f mercury is used atteries attery chemical c nergy consump or the product the * x) 2 ate - WOL	aterial content i e of the two alter ic parts' weight by weight) is f the biobased p ree from mercur specify: Number omposition: <i>Li-p</i> tion (See NOTE following power Power level 100 V AC 95 W	s used in the prinatives below s > 25 g, the biol %. lastic material is ry, i.e. less thar r of lamps: bolymer B8) r levels or ener l at Pow 2 1'	roduct (See I shall be answ based plastic s g. n 0,1 mg/lam and maxin and maxin gy consump rer level at 15 V AC	wered; c material co p. mum mercu vtions are rep Powe 230	ry content po ported: er level at	er lamp: 1	mg andard for e		
If N a) P7.22* Lig If r P8 Ba P8.1* Ba P9 En P9.1 Fo Energy mode * Peak (On-max Category - Short Idle Stat Enabled	YES; at least one ) Of total plastic of total plastic ) The weight of ght sources are f mercury is used atteries attery chemical c nergy consump or the product the * x) 2 ate - WOL	e of the two alter ic parts' weight) is 5 the biobased p free from mercur specify: Number omposition: <i>Li-p</i> tion (See NOTE e following power Power level 100 V AC 95 W	rnatives below > 25 g, the biol %. lastic material is ry, i.e. less than r of lamps: bolymer B8) er levels or ener l at Pow 1 1	shall be answer based plastic s g. 0,1 mg/lam and maxin and maxin gy consump ver level at 15 V AC	wered; c material co p. mum mercu vtions are rep Powe 230	ry content po ported: er level at	er lamp: 1	mg andard for e		
a) or b) P7.22* Lig If r P8 Ba P8.1* Ba P9 En P9.1 Fo Energy mode * Peak (On-max Category - Short Idle Stat Enabled	<ul> <li>Of total plastic of total plastic of total plastic</li> <li>The weight of ght sources are f mercury is used atteries attery chemical c</li> <li>nergy consumption the product the x</li> <li>x)</li> <li>2</li> <li>ate - WOL</li> </ul>	ic parts' weight by weight) is if the biobased p iree from mercur specify: Number omposition: Li-p tion (See NOTE of following power Power level 100 V AC 95 W	> 25 g, the biol %.          lastic material is ry, i.e. less than r of lamps:         polymer         B8)         er levels or ener l at         Pow         1 at         Pow         1 at	oased plastic s g. n 0,1 mg/lam and maxin and maxin gy consump rer level at 15 V AC	c material co p. mum mercur tions are rep Powe 23	ry content po ported: er level at	er lamp: 1	mg andard for e	energy	
or b) P7.22* Lig If r P8 Ba P8.1* Ba P9 En P9.1 Fo Energy mode * Peak (On-max Category - Short Idle Stat Enabled Long Idle Stat Enabled	of total plastic The weight of ght sources are f mercury is used atteries attery chemical c nergy consump or the product the * x) 2 atte - WOL	the biobased p ree from mercur specify: Number omposition: <i>Li-p</i> tion (See NOTE following power Power level 100 V AC 95 W	%.         lastic material is         ry, i.e. less than         r of lamps:         polymer         B8)         er levels or ener         I at       Pow         I at       Pow         I at       Pow	s g. a 0,1 mg/lam and maxin gy consump rer level at 15 V AC	p. mum mercui tions are rep Powe 23	ry content po ported: er level at	er lamp: 1	mg andard for e	energy	
b) P7.22* Lig Ifr P8 Ba P8.1* Ba P9 En P9.1 Fo Energy mode * Peak (On-max Category - Short Idle Stat Enabled	) The weight of ght sources are f mercury is used atteries attery chemical c nergy consump or the product the * x) 2 ate - WOL	iree from mercul specify: Number omposition: <i>Li-p</i> tion (See NOTE following power Power level 100 V AC 95 W	ry, i.e. less thar r of lamps: <b>bolymer</b> <b>E B8)</b> er levels or ener l at Pow C 1'	and maxin and maxin gy consump /er level at 15 V AC	tions are rep Powe	ported: er level at	Reference/St modes and te	andard for e	energy	
P7.22* Lig If r P8 Ba P8.1* Ba P9 En P9.1 Fo Energy mode * Peak (On-max Category - Short Idle Stat Enabled	ght sources are f mercury is used atteries attery chemical c nergy consump or the product the * x) 2 ate - WOL	iree from mercul specify: Number omposition: <i>Li-p</i> tion (See NOTE following power Power level 100 V AC 95 W	ry, i.e. less thar r of lamps: <b>bolymer</b> <b>E B8)</b> er levels or ener l at Pow C 1'	and maxin and maxin gy consump /er level at 15 V AC	tions are rep Powe	ported: er level at	Reference/St modes and te	andard for e	energy	
P8 Ba P8.1* Ba P9.1 Fo Energy mode * Peak (On-max Category - Short Idle Stat Enabled	mercury is used atteries attery chemical c nergy consump or the product the * x) 2 ate - WOL	specify: Number omposition: <i>Li-p</i> tion (See NOTE e following power Power level 100 V AC 95 W	r of lamps: <b>bolymer</b> <b>E B8)</b> r levels or ener l at Pow C 1 <sup>4</sup>	and maxin gy consump /er level at 15 V AC	tions are rep Powe	ported: er level at	Reference/St modes and te	andard for e	energy	
P8     Ba       P8.1*     Ba       P9     En       P9.1     Fo       Energy mode *       Peak (On-max       Category -       Short Idle State       Enabled	atteries attery chemical c nergy consumptor for the product the * x) 2 ate - WOL	omposition: <i>Li-p</i> tion (See NOTE e following powe Power level 100 V AC 95 W	oolymer B8) r levels or ener l at Pow C 11	gy consump ver level at <b>15</b> V AC	itions are rep Powe 23	ported: er level at	Reference/St modes and te	andard for e	energy	
P9       En         P9.1       Fo         Energy mode *         Peak (On-max         Category -         Short Idle State         Enabled         Long Idle State         Enabled	nergy consumption or the product the * x) 2 ate - WOL	tion (See NOTE of following power Power level 100 V AC 95 W	B8) er levels or ener l at Pow C 1'	ver level at <b>15</b> V AC	Powe 23	er level at	modes and te		energy	
P9.1 Fo Energy mode * Peak (On-max Category - Short Idle Stat Enabled Long Idle Stat Enabled	or the product the * x) 2 ate - WOL	e following powe Power level <b>100</b> V AC <b>95</b> W	r levels or ener	ver level at <b>15</b> V AC	Powe 23	er level at	modes and te		energy	
Energy mode * Peak (On-max Category - Short Idle Sta Enabled Long Idle Stat Enabled	* 2 ate - WOL	Power level 100 V AC 95 W	lat Pow C 1'	ver level at <b>15</b> V AC	Powe 23	er level at	modes and te		energy	
Peak (On-max Category - Short Idle Sta Enabled Long Idle Stat Enabled	x) - <u>2</u> ate - WOL	100 V AC 95 W	<b>1</b> '	15 V AC	23		modes and te		energy	
Category - Short Idle Sta Enabled Long Idle Stat Enabled	• 2 ate - WOL	95 W				0 0 7 10				
Category - Short Idle Sta Enabled Long Idle Stat Enabled	• 2 ate - WOL	8.29 W				W	Full load			
Short Idle Sta Enabled Long Idle Stat Enabled	ate - WOL	8.29 W								
Enabled Long Idle Stat Enabled		8.29 W	1							
Long Idle Stat Enabled	oto - WOI	1	7.71	W	8.15	W	Use for ENE	RGY STAR V	3.0	
Enabled	to - WO!						registration	(Pidle)		
Enabled		4.21 W	4.08	W	4.25	W	Use for ENE	RGY STAR VE	3.0	
							registration			
Sleep (S3) - W	VOL Enabled	0.87 W	0.87	W	1.03	W	Use for ENE registration(	RGY STAR V8	8.0	
Off (S5) - WOI	L Enabled	0.35 W	0.35	W	0.34	W		RGY STAR VE	8.0	
							registration(	Poff)		
Off (S5) - WOI	L Disabled	0.35 W	0.35	W	0.34	W	Use for ErP(	(Poff)		
EPS No-load		0.025 W	0.028	W	0.051	W				
(External power supply	y / charger plugged in the ected from the product.)									
PTEC *	ected from the product.)	W	١	N	W	1				$\boxtimes$
	y Consumption									
ETEC *	v Concumption	28.91	27.27	or	29.04	-		/1000) x (P <sub>off</sub> x		
Annual Energy	y Consumption	kWh/year	kWh/ye	ar	kWh/yea	ſ	+ Psleep X U.3 Pshort_Idle X 0.3	5 + P <sub>long_ldle</sub> x 0 30)	.10+	
		Poff: Off Mode(S	5) - WOL Enable	ed; P <sub>sleep</sub> : Slee	ep Mode(S3)	- WOL Enabl	ed; P <sub>idle</sub> : Idle Sta		d	
External Powe	er Supply Efficien	cy Level (Intern	ational Efficiend	cy Marking P	Protocol) * :	VI				
Display resolut	ition * : 3840*21	160 megapi	ixels							
	o enter energy sa									
P9.2* Inf	formation about	the energy save	function is prov	vided with th	e product.					$\boxtimes$
P9.3 En	nergy efficiency o	class (monitors o	only):							$\square$
	missions						·			
	oise emission –			6 (See NOT						(5)
		Node description	1			al upper lim	it A-weighted so	ound power lev	el, <i>Lw</i> a,c	: (B)
Idl		Idle CBU Operatir			* 2.8					<u> </u>
	peration *	CPU Operatin Declared A-weighte	-	lovel (dP)	* 3.7			term fall )		
Ot		_	a souna pressure	e ievei (aB)	18.6	(operat	or position deskt	op – Idle)		
		<sup>-</sup> <i>p</i> Am								
Ot		eclared A-weighte	a sound pressure	e level (dB)	29.7	(operat	or position deskt	top – operating)		
		<i>p</i> Am								
Me	leasured accordir		79 🔀 ECMA-7	74						
		Other	(only if n	ot covered b	y ECMA-74	)				

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B9 A Guidance document on Acoustic Noise is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

Model nur	nber *	81YX, 81YY					Logo				
lssue date	*	2020.4.20						Le	no	VO	<b>1</b> 94
Product	environr	nental attributes - M	larket requireme	nts (conti	nued)			Ree	quire	ment	me
ltem									Yes	No	n.a
		nagnetic emissions									
P10.4	Compute program	er display meets the req (s):	uirement for low free	quency elec	ctromagnetic field	ts of the foll	owing volunta	ry			$\boxtimes$
P12		nics for computing pro									
P12.1*	The disp	lay meets the ergonomi	c requirements of IS	SO 9241-30	7 for visual displ	ay technolo	gies.			$\boxtimes$	
P12.2*	The phy	ical input device meets	the requirements of	f ISO 9995	and ISO 9241-4	10.				$\boxtimes$	
P13	Packagi	ng and documentation	า								
P13.1*	Product	backaging material type backaging material type backaging material type	(s): gift box wei	ht (kg): ight (kg): veight (kg):	).395kg 0.48kg 0.178kg						
P13.2*	Product	plastic primary packagir	ng is free from PVC.						X		
P13.3*	For proc	uct primary corrugated	l fiberboard packag nt: <b>80</b> %	jing, specif	the contained	percentage	of minimum	post-			
P13.4*		nedia for user and prod onic, 🛛 paper, 🗌 Othe	```	(tick box):							
P13.5	Ùser and	only complete this item product documentation ease specify:			e:					$\square$	
	Totally c	nlorine-free									
	Elemental chlorine-free								Ħ		
	Process	ed chlorine-free							H		
P14	Volunta	y programs							<u> </u>		
P14.1		uct meets the requirem	ents of the following	g voluntary	program(s):						
	Eco-labe	l: Ci	riteria version: <b>8.0</b> riteria version:	[	Date: 2020/3/23 Date:	Product of		2			
P15	Eco-labe	al information (See N	riteria version:		Date:	Product	category:				
P9		consumption of specia	/	an name d	ocorintian of the	a tootod ar	aduat aanfigu	ration			
1.3	NOTE: S informat knowled	upplier makes no repre on contained in this doo ge available at the time here is approximate an	sentations, guarante cument. All information of completion, and s	ees, assuration provided supplier sha	nces or warrantion by supplier in the all have no obligation	es whether his documer ation to upda	express or imp nt is provided I ate such inform	olied, reg based or nation. T	h supp The inf	olier's format	ion
P9	See Ene	rgy Star Qualified Notel w.energystar.gov/index					code=CO				

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

## Legal references Europe Annex B2

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1
Regulation (EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7
Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)	P1.3, P5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) No 1272/2008 (CLP Regulation)	P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1

# Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

#### Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	Lenovo Legion Y740S-15IMH, Lenovo Legion Y9000X 2020R	Logo
Model Number	81YX, 81YY	Lenovo
Issue Date	2020.4.20	
Additional information		

(d)	Year of manufacture:				2020
e)	Etec value (kWh) per ErP Lot 3 Catego disabled and if the system is tested with				cards (dGfx) are
f)	Etec value (kWh) per ErP Lot 3 Categor enable	y and capability adjust	ments applied when a	II discrete graphics o	cards (dGfx) are
		Category A (according to ErP Lot 3)	Category B (according to ErP Lot 3)	Category C (according to ErP Lot 3)	Category D (according to ErP Lot 3)
	Memory over base [GB]	28			
ents sting	Additional internal storage	Yes (Yes / No)	(Yes / No)	(Yes / No)	(Yes / No)
adjustm rring tee	Discrete television tuner	No (Yes / No)	(Yes / No)	(Yes / No)	(Yes / No)
capability adjustments applied during testing	Discrete Audio Card	<mark>No</mark> (Yes / No)	(Yes / No)	(Yes / No)	(Yes / No)
cap	Discrete graphics Card(s) [number / #]	No #: (Yes / No)	#: (Yes / No)	#: (Yes / No)	#: (Yes / No)
	Category of discrete graphics Card(s)				
sults	Etec Value (kWh) - dGfx disabled all discrete graphics cards (dGfx) are disabled/ UMA is active for switchable graphics/ product has no graphics cards (dGfx)	14.59			
Test results	Etec Value (kWh) - dGfx enabled all discrete graphics cards (dGfx) are enabled				
(g)	Idle state power demand (Watts);		L		4.38
(h)	Sleep mode power demand (Watts);				0.88
(i)	Sleep mode with WOL enabled power de	emand (Watts) (where	enabled);		0.88
(j)	Off mode power demand (Watts);				0.44
(k)	Off mode with WOL enabled power dem	and (Watts) (where en	abled);		0.44
(I)	Internal power supply efficiency at 10 %,	20 %, 50 % and 100 %	% of rated output pow	er (if applicable):	
	10% 20% 50%	100% Avera	ige		
(m)	External power supply efficiency (if appli	cable)*:			
	Average active efficiency: 85.56%, 89.0	8%, 86.24%			
	*internal note: show values for all available external po				
(o)	Minimum number of loading cycles that t	he batteries can withs	tand (applies only to n	otebook computers):	800 cycles
(p-1)	Measurement methodology used to dete	rmine information mer	ntioned in points (I) – ii	nternal PSU efficiency:	

	dology used to determine information mentioned in p rogram Requirements for Single Voltage Externa Eligibility Criteria (Version 2.0)		
(p-3) Measurement method	dology used to determine information mentioned in p <i>≥</i> 70% of Cmin	points (o) – loading cycles batteries:	
	dology used to determine information mentioned in r Point P9.1 in the Product IT Eco Declaration: IEC 62623	naximum, idle, sleep, off mode	
(q) Sequence of steps fo	r achieving a stable condition with respect to power Power on -> Wait 5 minutes ->Stable con		
(r) Description of how sl	eep and/or off mode was selected or programmed: Begin menu -> Power -> Select sleep or o	ff mode	
(s) Sequence of events r off mode:	required to reach the mode where the equipment au	tomatically changes to sleep and/or	
	N/A		
condition which does	e condition before the computer automatically re not exceed the applicable power demand requirement	ents for sleep mode (in minutes):	30min
	a period of user inactivity in which the compute ver power demand requirement than sleep mode (in	· ·	NA
(v) Length of time befo	re the display sleep mode is set to activate after	user inactivity (in minutes):	10min
(w) Information on the en	ergy-saving potential of power management function Refer to User Guide	nality:	
(x) User information on h	now to enable the power management functionality: <b>Refer to User Guide</b>		
	neasurements: — test voltage in V and frequency in system, — information and documentation on the in- ting: 30V50HZ-2%-Edition 2.0, 2011-01, Section 4	strumentation, set-up and circuits	
Additional Notebook Batter		L	T
	Battery[ies] <u>not</u> user replaceable	Battery[ies] user replaceable	n/a
	The battery[ies] in this product cannot be easily replaced by users themselves. $^{1\!\mathrm{)}}$		
Internal/built-in Battery	$\square$		
External/detachable Battery			$\square$
Bios Backup Battery			
Other:			
Additional information			
Las baterías de este producto no pueden Výměnu baterie/bateríi v tomto výrobku by Brugeren kan ikke uden videre udskifte ba Der Akku/die Akkus dieses Produkts kann Kasutajad ei saa selle toote akut/akusid is H µmarapía(-sc) στο προϊόν αυτό δεν µποj La/les batterie(s présente(s) dans ce prod Korisnik ne može lako zamijeniti Bateriju s La batteria/le batterie in questo prodotto n Lietotāji paši nevar nomainīt šā ražojuma a Šio gaminio baterijos [bateriju] pats vartote A termék akkumulátorát/akkumulátorait a t Il-batterija/batteriji f'dan il-prodott ma tistaæ Batteriet [ene] i dette produktet kan ikke le De batterij(en) in dit product is (zijn) door Użytkownik nie może sam w łatwy sposób A ou as baterias deste produto nāo poden	<ul> <li>προμνκτ не може да се замени[ят] лесно от самите потребите ser sustituidas fácilmente por los propios usuarios.</li> <li>neměli provádět sami uživatelé.</li> <li>tkeriet/batterierne i dette produkt.</li> <li>/können nicht ohne weiteres vom Benutzer selbst ausgetauscht e hölpsasti asendada.</li> <li>pooúv vα αντικατασταθούν εύκολα από τους ίδιους τους χρήστες uit ne peuvent être facilement remplacée(s) par les utilisateurs e am u ovom proizvodu.</li> <li>on può/possono essere facilmente sostituita/e dall'utente.</li> <li>akumulatoru(-us).</li> <li>bjas negali lengvai pakeisti.</li> <li>felhasználó nem tudja egyedül egyszerűen kicserélni.</li> <li>(/jistghux tiġ/ijġu sostitwita/i mill-utenti stess.</li> <li>tt erstattes av brukerne selv.</li> <li>de gebruiker niet gemakkelijk vervangbaar.</li> <li>wymienić baterii w tym produkcie.</li> <li>n ser facilmente substituídas pelos próprios utilizadores.</li> <li>te (pot) fi uşor înlocuită (înlocuite) de utilizatorii înşişi.</li> <li>eňať používateľ.</li> <li>min ne morejo zlahka zamenjati.</li> <li>posti käyttäjän vaihdettavissa.</li> <li>ut batteriet/batterierna.</li> </ul>	werden.	