

ECMA/TC38-TG3/2015/026 (Rev. 1 – 15 April 2017)

Annex B2 - Product environmental attributes Desktop/All-in-One Computers

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

| Brand * | Lenovo | Logo | | | | | |
|------------------------|---|-------|--------|--|--|--|--|
| Company name * | Lenovo | | | | | | |
| Contact information * | Lenovo Global Environmental Affairs | | Lenovo | | | | |
| e-mail address | Alvin L Carter | | | | | | |
| | alcarter@lenovo.com | | | | | | |
| Internet site * | http://www.lenovo.com/social_responsibility/us/en/environment | .html | | | | | |
| Additional information | The latest version of this document can be found at: | | | | | | |
| | http://www.lenovo.com/ecodeclaration | | | | | | |

| The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the | | | | | |
|--|--|--|--|--|--|
| statements given in this decl | aration. | | | | |
| Type of product * | ct * Personal Computer | | | | |
| Commercial name * | ThinkCentre M80q Tiny | | | | |
| Model number * | 11DN, 11DQ, 11DR, 11DS, 11F6, 11F7, 11F8, 11F9, 11DM | | | | |
| Issue date * | 2020-4-30 | | | | |
| Intended market * | 🛛 Global 🔄 🗌 Europe 🔄 Asia, Pacific & Japan 🔛 Americas 🔛 Other | | | | |
| Additional information | on Energy Star, EPEAT, TCO | | | | |

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template: P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products.

| Model nu | umber * | 11DN, 11DQ, 11DR, 11DS, 11F6, 11F7, 11F8, 11F9, 11DM | | | | | | |
|-----------|------------------------|---|-------------|-------------|------|--|--|--|
| Issue dat | e * | 2020-4-30 | Leno | | Этн | | | |
| Produc | t environ | mental attributes - Legal requirements | Require | ment | met | | | |
| Item | | | Yes | No | n.a. | | | |
| P1 | Hazardo | is substances and preparations | | | | | | |
| P1.1* | Products | do comply with current European RoHS Directive. (See legal reference and NOTE B1) | \square | | | | | |
| P1.2* | | do not contain Asbestos (see legal reference). t: Legal reference has no maximum concentration value. | \boxtimes | | | | | |
| P1.3* | hydrochl | do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), profluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal e). Comment: Legal reference has no maximum concentration values. | | | | | | |
| P1.4* | | do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated terphenyl (PCT) ations (see legal reference). | \boxtimes | | | | | |
| P1.5* | Products | Products do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference). Parts with direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm ² /week (see | | | | | | |
| P1.6* | legal refe | | | | | | | |
| P1.7* | REACH A | t: Max limit in legal reference when tested according to EN1811:2011-5. rticle 33 information about substances in articles is available at (add URL or mail contact): ww.lenovo.com/us/en/Lenovo-REACH-SVHC-Disclosure | | | | | | |
| P2 | Batteries | | | | | | | |
| P2.1* | • | duct contains a battery or an accumulator, the battery/accumulator is labeled with the disposal symbol. on on proper disposal is provided in user manual. (See legal reference) | \boxtimes | | | | | |
| P2.2* | Batteries reference | or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal | \boxtimes | | | | | |
| P2.3* | Batteries | and accumulators are readily removable. (See legal reference) | | \boxtimes | | | | |
| P3 | Conform | ity verification & Eco design (ErP) | | | | | | |
| P3.1* | • | uct is CE-marked to show conformance with applicable legal requirements (see legal reference). aration of Conformity can be requested at: https://www.lenovo.com/us/en/compliance/eu-doc | \boxtimes | | | | | |
| P3.2* | | uct complies with the Eco design requirements for energy-related products, reference). | \boxtimes | | | | | |
| | Required | information is; given in item P15 or added to this document, | \boxtimes | | | | | |
| P5 | Droduct | available at: https://www.lenovo.com/us/en/compliance/eco-declaration | | | | | | |
| P5.1* | Packagin | packaging g and packaging components do not contain more than 0,01% lead, mercury, cadmium and hexavalent p by weight of these together. | | | | | | |
| P5.2* | The pack | n by weight of these together. aging materials are marked with abbreviations and numbers indicating the nature of the material(s) used reference). | \square | | | | | |
| P5.3* | The prod legal refe | uct packaging material is free from ozone depleting substances as specified in the Montreal Protocol (see rence). | | | | | | |
| | | t: Legal reference has no maximum concentration values. | | | | | | |
| P6 | | t information | | | | | | |
| P6.1* | Informati | on for recyclers/treatment facilities is available (see legal reference). | \bowtie | | | | | |

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

| Model number * | | 11DN, 11DQ, 11DR, 11DS, 11F6, 11F7, 11F8, 11F9, 11DM | go | | | | | |
|----------------|---|--|-----------------|-------------|-----------|-------------|--|--|
| Issue date | * | 2020-4-30 | | ene | | Тн | | |
| Product | | mental attributes - Market requirements (See General NOTE GN be onmental conscious design | | quirer | nentı | net | | |
| Item | | ory to fill in. Additional information regarding each item may be found under P14. | | Yes | No | n.a. | | |
| P7 | Design, D | isassembly, recycling | | | | | | |
| P7.1* | Parts that | have to be treated separately are easily separable | | \boxtimes | | | | |
| P7.2* | Plastic ma | aterials in covers/housing have no surface coating. | | \boxtimes | | | | |
| P7.3* | Plastic pa | rts > 100 g consist of one material or of easily separable materials. | | \boxtimes | | | | |
| P7.4* | Plastic pa | rts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. | | \boxtimes | | | | |
| P7.5 | Plastic pa | rts are free from metal inlays or have inlays that can be removed with commonly available too | ols. | \square | \Box | | | |
| P7.6* | Labels are | e easily separable. (This requirement does not apply to safety/regulatory labels). | | \square | | | | |
| | Product lifetime P7.7* Upgrading can be done e.g. with processor, memory, cards or drives | | | | | | | |
| P7.7* | Upgrading | g can be done e.g. with processor, memory, cards or drives | | \boxtimes | | | | |
| P7.8* | Upgrading | g can be done using commonly available tools | | \boxtimes | | | | |
| P7.9 | Spare par | ts are available after end of production for: 5 years | | | | | | |
| P7.10 | Service is available after end of production for: 5 years | | | | | | | |
| | Material | and substance requirements | | | | | | |
| P7.11* | | over/housing material type (e.g. plastics, metal, aluminum): | | | | | | |
| | | | pe: ABS+PC | | | | | |
| P7.12 | | materials of external electrical cables are PVC free. | | Ц. | | Ц. | | |
| P7.13 | | | | | | | | |
| P7.14 | (1000 ppr chloride c | plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0, n) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and po pr 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing r umer recycled content. | lyvinyl | | | | | |
| P7.15 | | rcuit boards, PCBs (without components) are low halogen: all \square PCBs > 25 g \square are low halo n IEC 61249-2-21. (See 1NOTE B2) | ogen as | | \square | | | |
| P7.16 | Flame ret Marking: | arded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: | | | | \boxtimes | | |
| P7.17 | <u>Alt. 1: </u> Che | emical specifications of flame retardants in printed circuit boards > 25 g (without components) |): | | | | | |
| | TBBPA | A (additive), TBBPA (reactive) (See NOTE B3), Other: , CAS #: | | | | \bowtie | | |
| | <u>Alt. 2: </u> Che 1043-4: | emical specifications of flame retardants in printed circuit boards (without components) > 25 g $$ | g according ISO | | | \boxtimes | | |
| P7.18 | concentra | me retarded plastic parts > 25 g contain the following flame retardant substances/preparation ations above 0,1%: ical name: , CAS #: (See NOTE B4) | ns in | | | | | |
| | <u>Alt. 2: </u> Ch | nemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: | : | | | \boxtimes | | |
| P7.19 | In plastic | parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been a | assigned the | | | \boxtimes | | |
| | - | Risk phrases; and Hazard statements: | | | | | | |
| | | | note B5) | | | | | |
| P7.20* | If YES; at I a) Of to | umer recycled plastic material content is used in the product (See Note B6): least one of the two alternatives below shall be answered; otal plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculate sentage of total plastic by weight) is %. | ed as a | | | | | |
| | b) The | weight of recycled material is g. | | | | | | |

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

| Model number * | 11DN, 11DQ, 11DR, 11DS, 11F6, 11F7, 11F8, 11F9, 11DM | Logo | |
|----------------|--|------|----------|
| Issue date * | 2020-4-30 | | Leiiuvu. |

Product environmental attributes - Market requirements (continued) Item

Yes No n.a.

| Material and substa | ince requirements (cor | ntinued) | | |
|---|--------------------------|---------------------------------------|---------------------------------------|---|
| | | n the product (See NOTE | B7): | |
| P7.22* Light sources are fre | e from mercury, i.e. les | ss than 0.1 mg/lamp. | | |
| 0 | ecify: Number of lamp | , 0, 1 | mercury content per lamp | p: mg |
| P8 Batteries | | | | |
| P8.1* Battery chemical cor | nposition: Lithium Io | n/Lithium Manganes | e Dioxide | |
| P9 Energy consumption | n (See NOTE B8) | | | |
| P9.1 For the product the | following power leve | els or energy consump | otions are reported: | |
| Energy mode * | Power level at | Power level at | Power level at | Reference/Standard for energy |
| | 100 V AC | 115 V AC | 230 V AC | modes and test method * |
| Peak (On-max) | 35.57 W | 35.44 W | 36.12 W | Full load |
| Category I1 | | | | |
| Short Idle State - WOL Enabled | 7.74 W | 7.73 W | 7.75 W | Use for ENERGY STAR V8 registration (P _{idle}) |
| Long Idle State - WOL Enabled | 6.65 W | 6.65 W | 6.63 W | Use for ENERGY STAR V8 registration (P _{idle}) |
| Sleep (S3) - WOL Enabled | 1.9 W | 1.9 W | 1.9 W | Use for ENERGY STAR V8 registration (P _{sleep}) |
| Off (S5) - WOL Enabled | 0.4 W | 0.4 W | 0.4 W | Use for ENERGY STAR V8 registration (P _{off}) |
| Off (S5) - WOL Disabled | 0.25 W | 0.25 W | 0.25 W | Use for ErP |
| Category I2 | | | | |
| Short Idle State - WOL Enabled | 11.56 W | 11.53 W | 11.82 W | Use for ENERGY STAR V8 registration |
| Long Idle State - WOL Enabled | 9.69 W | 9.66 W | 9.73 W | Use for ENERGY STAR V8 registration |
| Sleep (S3) - WOL Enabled | 1.6 W | 1.6 W | 1.6 W | Use for ENERGY STAR V8 registration |
| Off (S5) - WOL Enabled | 0.8 W | 0.8 W | 0.8 W | Use for ENERGY STAR V8 registration |
| Off (S5) - WOL Disabled | 0.25 W | 0.25 W | 0.25 W | Use for ErP |
| EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.) | W | 0.120 W | 0.168 W | |
| PTEC * Typical Energy Consumption | W | W | W | |
| ETEC * Annual Energy Consumption | 34.18 46.23 kWh/year | 34.16 46.12 kWh/year | 34.19 46.94 kWh/year | ETEC = (8760/1000) x (Poff x 0.45 + Psleep x 0.05 + Plong_idle x 0.15 + Pshort_idle x 0.35) |
| | | | | Enabled; P _{idle} : Idle State - WOL Enabled |
| External Power Supply Efficiency I | evel (International Eff | iciency Marking Protoco | I) * : VI | |
| Display resolution * : me | gapixels | | | |
| Default time to enter energy save | mode: 25 minutes | | | |
| P9.2* Information about th | ne energy save functio | n is provided with the pr | oduct. | |
| P9.3 Energy efficiency cla | ss (monitors only): | | | |
| | | | | |

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available;

see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available;

see http://www.ecma-international.org/publications/standards/Ecma-370.htm

| P10 | Emissions | | | | | | | | | |
|------------------|---|--|---|--|--------------------------|-----|------|--|--|--|
| | | - Declared according to ISO 9296 (See NOTE B | 9) | | | | | | | |
| P10.1 | Mode | Mode description | | per limit A-weighted sound power | level, L _{WA,d} | (B) | | | | |
| | Idle | * HDD:Idle | * 3.2 | | | | | | | |
| | Operation | * HDD: Operating | * 3.6 | | | | ऩ | | | |
| | Other mode | Declared A-weighted sound pressure level (dB) $L_{p\rm Am}$ | 24.5 (operato | or position desktop – idle - HDD) | | | | | | |
| | Other mode | Declared A-weighted sound pressure level (dB) L_{pAm} | 27 (operator | position desktop – operating - HDD) | | | | | | |
| | Idle | Idle * <i>SSD: Idle</i> * 2.5 | | | | | | | | |
| | Operation | * SSD: Operating | * 3.3 | | | | | | | |
| | Other mode | Declared A-weighted sound pressure level (dB) $L_{p{\rm An}}$ | 16.5 (operator position desktop – idle - SSD) | | | | | | | |
| | Other mode | Declared A-weighted sound pressure level (dB) $L_{p{\rm An}}$ | 24.5 (operato | or position desktop – operating – SSD) | | | | | | |
| | Measured acco | rding to: 🔀 ISO 7779 📃 ECMA-74 | | | | | | | | |
| | | Other (only if not covered by ECMA-74) | | | | | | | | |
| | t environment | al attributes - Market requirements (| continued) | | Require | | | | | |
| Item | | | | | Yes | No | n.a. | | | |
| | Electromagnet | | | | | | | | | |
| P10.4 | Computer displ program(s): | ay meets the requirement for low frequency el | ectromagnetic fields of | the following voluntary | | | | | | |
| P12 | Ergonomics for computing products | | | | | | | | | |
| P12.1* | The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies. | | | | | | | | | |
| P12.2* | The physical in | out device meets the requirements of ISO 9995 | and ISO 9241-410. | | \boxtimes | | | | | |
| P13 | Packaging and | documentation | | | | | | | | |
| P13.1* P13.2* | Product packag Product packag | <pre>ing material type(s): Corrugated Fiberboard ing material type(s): EPE weight (kg): 0.083 ing material type(s): LDPE weight (kg): 0.01 primary packaging is free from PVC.</pre> | | | | | | | | |
| P13.3* | | mary corrugated fiberboard packaging, specify content: 70% % | the contained percenta | age of minimum post-consumer | | | | | | |
| P13.4* | | or user and product documentation (tick box): | | | | | | | | |
| P13.5 | | mplete this item if paper documentation used) ict documentation on paper media is chlorine-fi becify: | ree: | | | | | | | |
| | Totally chlorine | | \boxtimes | | | | | | | |
| | Elemental chlorine-free | | | | | | | | | |
| | Processed chlo | rine-free | | | | | | | | |
| P14 | Voluntary prog | rams | | | | | | | | |
| P14.1 | The product m | eets the requirements of the following voluntar | y program(s): | | | | | | | |
| | ENERGY STAR® Eco-label: TC | | Date: 2020/3 Date: 2020/5 | Product category: Desktop Product category: Desktop | | | | | | |
| | Eco-label: | Criteria version: | Date: | Product category: | | | | | | |
| P15 | | rmation (See NOTE B10) | | | | | | | | |
| Р9 | I1-G5900T/32 | ption of specific configuration may vary; descr GB/M.2&2.5"HDD | iption of the tested pro | oduct configuration: | | | | | | |
| | | 32GB/M.2&2.5"HDD | | | | | | | | |
| P9 | | [•] Qualified Notebooks & Tablet Computers for t ergystar.gov/index.cfm?fuseaction=find_a_r | | Group&pgw_code=CO | | | | | | |

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B2

| Reference | Declaration item |
|---|------------------------|
| Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications. | P1.1 |
| Regulation (EC) 1907/2006(REACH, Annex XVII | P1.2, P1.4, P1.6, P1.7 |
| Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances) | P1.3, P5.3 |
| Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002 | P1.5 |
| Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator. | P2.1, P2.2, P2,3, P8.1 |
| Directive 2006/95/EC (Low Voltage Directive) | P3.1 |
| Directive 2004/108/EC (EMC Directive) | P3.1 |
| Directive 1999/5/EC (R&TTE Directive) | P3.1 |
| Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions | P3.1, P3.2 |
| Regulation (EC) No 1272/2008 (CLP Regulation) | P7.19 |
| Directive 2004/12/EC (Packaging Directive) | P5.1 |
| Decision 97/129/EC (Secondary packaging legislation) | P5.2 |
| Directive 2012/19/EU (WEEE directive) | P6.1 |

Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

| Commercial name | ThinkCentre M80q Tiny | Logo |
|------------------------|--|--------|
| Model Number | 11DN, 11DQ, 11DR, 11DS, 11F6, 11F7, 11F8, 11F9, 11DM | |
| Issue Date | 2020-4-30 | Lenovo |
| Additional information | Energy Star, EPEAT, TCO, | |

| year of manufacture: | | | | 2020 |
|--|--|--|---|---|
| system is tested with switchable graphics | mode with UMA driving t | he display. | | |
| | Category A | Category B | Category C | Category D (according to ErP Lot 3) |
| Memory over base [GB] | | 64 | | 64 |
| Additional internal storage | (Yes / No) | Yes (Yes / No) | (Yes / No) | Yes (Yes / No) |
| Discrete television tuner | (Yes / No) | Yes (Yes / No) | (Yes / No) | Yes (Yes / No) |
| Discrete Audio Card | (Yes / No) | No (Yes / No) | (Yes / No) | No (Yes / No) |
| Discrete graphics Card(s) [number / #] | #: (Yes / No) | No #: (Yes / No) | #: (Yes / No) | No #: (Yes / No) |
| Category of discrete graphics Card(s) | | No | | No |
| Etec Value (kWh) - dGfx disabled all discrete graphics cards (dGfx) are disabled/ UMA is active for switchable graphics/ product has no graphics cards (dGfx) | | 31.05 | | 33.66 |
| Etec Value (kWh) - dGfx enabled all discrete graphics cards (dGfx) are enabled | | | | |
| Idle state power demand (Watts); | | | | 7.54 8.32 |
| Sleep mode power demand (Watts); | | | | 1.87 1.98 |
| Sleep mode with WOL enabled power de | mand (Watts) (where enal | bled); | | 1.87 1.98 |
| Off mode power demand (Watts); | | | | 0.79 0.76 |
| Off mode with WOL enabled power dema | and (Watts) (where enable | ed); | | 0.23 0.23 |
| | Etec value (kWh) per ErP Lot 3 Category a system is tested with switchable graphics Etec value (kWh) per ErP Lot 3 Category a Memory over base [GB] Additional internal storage Discrete television tuner Discrete qraphics Card(s) [number / #] Category of discrete graphics Card(s) Etec Value (kWh) - dGfx disabled all discrete graphics cards (dGfx) are disabled/ UMA is active for switchable graphics/ product has orgenptics cards (dGfx) are enabled all discrete graphics cards (dGfx) are enabled Idle state power demand (Watts); Sleep mode power demand (Watts); Sleep mode with WOL enabled power demand (Watts); | Etec value (kWh) per ErP Lot 3 Category and capability adjustments system is tested with switchable graphics mode with UMA driving to Etec value (kWh) per ErP Lot 3 Category and capability adjustments Category A (according to ErP Lot 3) Memory over base [GB] Additional internal storage (Yes / No) Discrete television tuner (Yes / No) Discrete graphics Card(s) [number / #] #: (Yes / No) Category of discrete graphics Card(s) Etec Value (kWh) - dGfx disabled all discrete graphics cards (dGfx) Product has no graphics cards (dGfx) Etec Value (kWh) - dGfx enabled all discrete graphics cards (dGfx) Etec Value (kWh) - dGfx enabled all discrete graphics cards (dGfx) Etec Value (kWh) - dGfx enabled all discrete graphics cards (dGfx) Etec value (kWh) - dGfx enabled all discrete graphics cards (dGfx) Sleep mode power demand (Watts); Sleep mode with WOL enabled power demand (Watts) (where enalled Off mode power demand (Watts); | Etec value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discressive system is tested with switchable graphics mode with UMA driving the display. Etec value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete free value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete free value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete free value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete value (kWh) and the value value (kWh) - dGfx disabled all discrete graphics cards (diff) are disabled all discrete g | File value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete graphics cards (dGfx) system is tested with switchable graphics mode with UMA driving the display. Etec value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete graphics cards (dGfx) (according to ErP Lot 3) Category B (according to ErP Lot 3) Category C (according to ErP Lot 3) Memory over base [GB] 64 Category C (according to ErP Lot 3) (according to ErP Lot 3) Additional internal storage (Yes / No) Yes / No) (Yes / No) (Yes / No) Discrete television tuner (Yes / No) (Yes / No) (Yes / No) (Yes / No) Discrete graphics Card(s) [number / #] #: (Yes / No) (Yes / No) (Yes / No) Etec Value (kWh) - dGfx disabled and thistoret graphics card(s) No Etec Value (kWh) - dGfx disabled and thistoret graphics card(s) No Etec Value (kWh) - dGfx enabled and thistoret graphics card(s) No Image: Single card (sGfx) Image: Single card (sGfx) Etec Value (kWh) - dGfx enabled and thistoret graphics card(sGfx) Image: Single card (sGfx) Image: Single card (sGfx) Image: Single card (sGfx) Indiscrete graphics card(sGfx) Image: Single card (sGfx) Image: Single card (sGfx) Image: Single card (sGfx) Indiscrete gra |

| (m) | External power supply efficiency (if applicable)*: | | | | | | | |
|------------|--|------------------------------|---|---|---|------------------|-----------------|-----|
| | | tive efficiency E, 91.94% | : | | | | | |
| | A19-065N | I2A, 88.7% | | | | | | |
| | | E, 89.93% 74FS, 88.61% | 6 | | | | | |
| | | 3A, 89.87% | | | | | | |
| | | JB, 90.5% 72, 90.11% | | | | | | |
| | ADP-170 | CB, 91.39% | | | | | | |
| | | | ll available external pow | | | | | |
| (0) | Minimum | number of load | ding cycles that the | e batteries can with | istand (applies only to notel | book computer | rs): | N/A |
| (p-1) | Measurem | ent methodol | ogy used to detern | nine information m N/A | entioned in points (l) – inter | rnal PSU efficie | ency: | |
| (p-2) | Measurem | ent methodol | ogy used to detern | nine information m Erp Lo | entioned in points (m) – ext ot7 | ernal PSU effic | ciency: | |
| (p-3) | Measurem | ent methodol | ogy used to detern | nine information m N/A | entioned in points (o) – load | ding cycles bat | teries: | |
| (p-4) | | | ogy used to detern he Product IT Eco I | | entioned in maximum, idle, | sleep, off mod | le power as | |
| | | | | IEC 62623 Ed. | 1.0, 2012-10 | | | |
| (q) | Sequence | of steps for ac | nieving a stable co | ndition with respec | t to power demand: | | | |
| | Bas | ed on Energ | y Star Compute | r V8I/Power on-> | Wait 5 minutes->Stable | condition(Si | hort idle) | |
| (r) | Description | n of how sleep | and/or off mode v | was selected or pro | grammed: | | | |
| | | | | Based on use | er manual | | | |
| (s) | Sequence | of events requ | ired to reach the n | node where the eq | uipment automatically chan | ges to sleep ar | nd/or off mode: | |
| | | | | Based on use | er manual | | | |
| (t) | | | | | tically reaches sleep mode, for sleep mode (in minutes): | | ndition which | 25 |
| (u) | - | - | | vity in which the c ep mode (in minut | omputer automatically read | ches a power r | node that has a | N/A |
| (v) | Length of t | ime before th | e display sleep mo | ode is set to activat | e after user inactivity (in mi | nutes): | | 10 |
| (w) | Informatio | n on the ener | gy-saving potential | of power manager | nent functionality: | | | |
| | | | | N/A | | | | |
| (x) | User inform | nation on how | to enable the pov | ver management fu | inctionality: | | | |
| | | | | Refer to Us | er Guide | | | |
| (z) | • | supply system | | • | equency in Hz, — total harn on the instrumentation, set- | | | |
| | | | | 230V/5 | 0Hz | | | |
| | Instr. | Instrument | Instrument | Range Used | Make and Model ** | Calibrat | tion Date | |
| | Code | I.D. | Туре | Or *** | | Last | Due | |
| | | A09 | AC Power Source | 1~280VAC;1~55 0HZ;1000VA. | NF;EC1000S; SN:9152124 | 2019-08-29 | 2020-08-28 | |
| | | B64 | | Full range | CASIO; HS-70W; SN:107Q03R | 2019-09-09 | 2020-09-08 | |
| | | B100 | power Meter | 0~600V;0~20A | YOKOGAWA;WT310;SN: C2RD07008V | | 2020-08-28 | |
| | | C18 | Ambient Monitor | -10~60℃ /0~100%RH | Testo;622;SN:39504298/ 305 | 2019-09-11 | 2020-09-10 | |
| Additional | Notebook | Battery Info | ormation: | | | | | |

| | Battery[ies] <u>not</u> user replaceable The battery[ies] in this product cannot be easily replaced by users themselves. ¹⁾ | Battery[ies] user replaceable | n/a |
|-----------------------------|--|-------------------------------|-----------|
| Internal/built-in Battery | | | |
| External/detachable Battery | | | \square |
| Bios Backup Battery | | | \square |
| Other: | | | \square |
| Additional information | | | • |
| | | | |
| | | | |
| | | | |

1) The battery[ies] in this product cannot be easily replaced by users themselves.

Akywynarophara[uris] батерия[и] в този продукт не може да се замени[ят] лесно от самите потребители. Las baterías de este producto no pueden ser sustituidas fácilmente por los propios usuarios.

Výměnu baterie/baterii v tomto výrobku by neměli provádět sami uživatelé. Brugeren kan ikke uden videre udskifte batteriet/batterierne i dette produkt. Der Akku/die Akkus dieses Produkts kann/können nicht ohne weiteres vom Benutzer selbst ausgetauscht werden.

Kasutajad el saa selle toote akut/akusid ise hõlpsasti asendada. Η μπαταρία[-ες] στο προϊόν αυτό δεν μπορούν να αντικατασταθούν εύκολα από τους ίδιους τους χρήστες La/les batterie(s présente(s) dans ce produit ne peuvent être facilement remplacée(s) par les utilisateurs eux-mêmes.

Korisnik ne može lako zamijeniti Bateriju sam u ovom proizvodu.

La batteria/le batterie in questo prodotto non puó/possono essere facilmente sostituita/e dall'utente. Lietotāji paši nevar nomainīt šā ražojuma akumulatoru(-us).

Šio gaminio baterijos [bateriju] pats vartotojas negali lengvai pakeisti. A termék akkumulátorát/akkumulátorait a felhasználó nem tudja egyedül egyszerűen kicserélni. II-batterija/batteriji f'dan il-prodott ma tistax/jistgħux tiġi/jiġu sostitwita/i mill-utenti stess.

Batteriet [ene] i dette produktet kan ikke lett erstattes av brukerne selv. De batterii(en) in dit product is (zijn) door de gebruiker niet gemakkelijk vervangbaar. Użytkownik nie może sam w łatwy sposób wymienić baterii w tym produkcie.

A ou as baterias deste produto não podem ser facilmente substituídas pelos próprios utilizadores. Bateria (bateriile) din acest produs nu poate (pot) fi uşor înlocuită (înlocuite) de utilizatorii înșiși. Batériu(-ie) v tomto výrobku nemôže vymieňať používateľ.

Baterij/baterije v tem izdelku uporabniki sami ne morejo zlahka zamenjati. Tämän tuotteen akku [akut] ei[vät] ole helposti käyttäjän vaihdettavissa. Det är inte enkelt för kunden att själv byta ut batteriet/batterierna.

Bu üründeki batarya(lar) kullanıcılar tarafından kolaylıkla değiştirilemez.