



Ecma/TC38-TG3/2015/026 (Rev. 1 – 15 April 2015)

Annex B2 - Product environmental attributes Notebooks and Tablets

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lenovo	Logo				
Company name *	Lenovo	<u> </u>				
Contact information *	Lenovo Global Environmental Affairs	Lenovo				
e-mail address	Alvin L Carter	LEITOVO				
	alcarter@lenovo.com					
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment	.html				
Additional information	The latest version of this document can be found at:					
	http://www.lenovo.com/ecodeclaration					

The company declares (based on product specification or test results based obtained from sample testing), that the product					
conforms to the statements given in this declaration.					
Type of product * Notebook					
Commercial name *	ThinkPad X1 Carbon 8th Gen				
Model number *	20U9, 20UA				
Issue date *	2020/02				
Intended market *	Global Europe Asia, Pacific & Japan Americas Other				
Additional information					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products.

Model n	umber *	20U9, 20UA						Logo	Lon		
Issue da	ate *	2020/02							Len	OVC	O _{TM}
Produc	t environ	mental attributes	s - Leg	gal requirer	nents				Require	emen	t met
Item									Yes	No	n.a.
P1		ous substances and									
P1.1*	Products	s do comply with curr	rrent Ει	uropean RoH	S Directive.	. (See legal	reference and N	OTE B1)			
P1.2*		Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.									
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.										
P1.4*		s do not contain more yl (PCT) in preparatio				l biphenyl (F	PCB), 0,005% pc	lychlorinated			
P1.5*	Products do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).					the 🔀					
P1.6*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm²/wee (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:2011-5.				ek 🔀						
P1.7*	REACH	Article 33 information	on abou	ut substances	in articles	is available		mail contact):			
P2	Batterie	s									
P2.1*		oduct contains a batte Information on prope									
P2.2*	Batteries referenc	s or accumulators do e)	o not co	ontain more tl	han 0,0005	% of mercur	y or 0,002% of o	cadmium. (See leg	gal 🔀		
P2.3*	Batteries	s and accumulators a	are rea	adily removab	le. (See leg	gal reference	e)				
P3	Conforr	mity verification & E	Eco de	esign (ErP)							
P3.1*		duct is CE-marked to claration of Conformit									
P3.2*		duct complies with th al reference).	he Eco	design requi	rements for	energy-rela	ted products,				
	, -	d information is;	`	given in item available at:				nce/eco-declaratio	on 🖂		

Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium and

The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s) used (see legal reference).

The product packaging material is free from ozone depleting substances as specified in the Montreal Protocol (see legal reference).

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Product packaging

Treatment information

hexavalent chromium by weight of these together.

Comment: Legal reference has no maximum concentration values.

Information for recyclers/treatment facilities is available (see legal reference).

P5 P5.1*

P5.2*

P5.3*

P6

P6.1*

Model number *	20U9, 20UA	Logo	Lanava
Issue date *	2020/02		Lei IOVO.

Product	environmental attributes - Market requirements (See General NOTE GN below)			
	- Environmental conscious design	Require	ment	met
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.
P7	Design Disassembly, recycling			
P7.1*	Parts that have to be treated separately are easily separable	\square	П	
P7.2*	Plastic materials in covers/housing have no surface coating.	X	\Box	
P7.3*	Plastic parts > 100 g consist of one material or of easily separable materials.	X	\Box	
P7.4*	Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.	X	\Box	
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.		Ħ	
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).		Ħ	
	Product lifetime			
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	\boxtimes		
P7.8*	Upgrading can be done using commonly available tools			
P7.9	Spare parts are available after end of production for: 5 years			
P7.10	Service is available after end of production for: 5 years			
	Material and substance requirements			
P7.11*	Product cover/housing material type (e.g. plastics, metal, aluminum):			
D7.40	Material type: PC+CF Material type: PC+GF Material type: Metal			
P7.12	Insulation materials of external electrical cables are PVC free.		$\underline{\underline{X}}$	
P7.13	Insulation materials of internal electrical cables are PVC free.		<u>Ц</u>	
P7.14	External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content.		Ш	
P7.15	Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2)			
P7.16	Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: FR(40)	\boxtimes		
P7.17	Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other: DOPO, CAS #: 35948-25-5			
	Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4:			
P7.18	Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: halogen-free organic phosphorus compound, CAS #: confidential (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: "	\boxtimes		
	Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:		П	\boxtimes
P7.19	In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; <i>confidential</i> and Hazard statements: <i>confidential</i>			
	The source(s) for these classifications is/are found at (add URL(s)): , (See note B5)			
P7.20*	Postconsumer recycled plastic material content is used in the product (See Note B6):	\boxtimes		
	 If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 7.8%. or b) The weight of recycled material is 17.6 g. 			

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Product environmental attributes - Market requirements (continued) Requirement met	Model nur	nber *	20U9, 20	OUA			Logo
Material and substance requirements (continued)	Issue date	*	2020/02				Lenovo.
Material and substance requirements (continued)	Product	environn	nental at	tributes - Market r	equirements (cont	inued)	Requirement me
## Biobased plastic material content is used in the product (See NOTE BT): ## If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts weight > 25 g, the biobased plastic material content (calculated as a percentage of total plastic by weight) is %. ## The weight of the biobased plastic material is g. ## P7.22** Light sources are free from mercury, i.e. less than 0,1 mg/lamp. ## If mercury is used specify. Number of lamps: ## Intercury is used specify. ## Intercury is used specif	Item						Yes No n.a.
If YES; at least one of the two alternatives below shall be answered: a) Of total plastic parts' weight ≥ 25 g, the biobased plastic material content (calculated as a percentage of total plastic by weight) is %. b) The weight of the biobased plastic material is g. b) The weight of the biobased flastic material is g. b) The weight of the biobased flastic material is g. b) The weight of the biobased flastic material is g. b) The weight of the biobased flastic material is g. b) The weight of the biobased flastic material is g. b) The weight of the biobased flastic material is g. b) The weight of the biobased flastic material is g. b) The weight of the biobased flastic material is g. b) The weight of the biobased flastic material is g. b) The weight of the biobased flastic material is g. b) The weight of the biobased							
a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of total plastic by weight) is % or b) The weight of the biobased plastic material is g. P7.22* Light sources are free from mercury, i.e. less than 0,1 mg/lamp. If mercury is used specify. Number of lamps: and maximum mercury content per lamp: mg P8 Batteries P9 Energy consumption (See NOTE 88) P9.1 For the product the following power levels or energy consumptions are reported: Energy mode * Power level at Power level at 100 V AC 115V AC 230 V AC 145V AC 245V AC 2	P7.21*		•			•	
of total plastic by weight) is %. or of b) The weight of the biobased plastic material is g. P7.22* Light sources are free from mercury, i.e. less than 0,1 mg/lamp. If mercury is used specify. Number of lamps: and maximum mercury content per lamp: mg P8 Batteries P8.1* Battery chemical composition: Li-lion P9 Energy consumption (See NOTE B) P9.1 For the product the following power levels or energy consumptions are reported: Energy mode * Power level at 100 ∨ AC 115 ∨ AC 230 ∨							lated as a management
or b) The weight of the biobased plastic material is g. P7.22* Light sources are free from mercury, i.e. less than 0,1 mg/lamp. If mercury is used specify: Number of lamps: and maximum mercury content per lamp: mg P8 Batter of lamps: and maximum mercury content per lamp: mg P8.1* Battery chemical composition: Li-lion P9 Energy consumption (See NOTE B8) P9.1 For the product the following power levels or energy consumptions are reported: Energy mode* Power level at 115 V.A.C. 230 V.A.C. Reference/Standard for energy modes and test method 115 V.A.C. 230 V.A.C. Pull food Peak (On-max) 65 W 65 W 65 W Full food Category -1- Short lide State - WOL Long lide State - WOL Long lide State - WOL Enabled Long lide State - W						material content (calcu	lated as a percentage
PT.22 Light sources are free from mercury, i.e. less than 0,1 mg/lamp. If mercury is used specify. Number of lamps: and maximum mercury content per lamp: mg P8 Satteries P8.1* Battery chemical composition: Li-lon P9 Energy consumption (See NOTE B8) P9.1 For the product the following power levels or energy consumptions are reported: Energy modes Power level at 115 V.AC 230 V.AC Full load Full lo		or	•				
PR Batteries P8.1 Batteries P8.1 Batteries P8.1 Batteries P9.1 For the product the following power levels or energy consumptions are reported: Power level at 100 v AC 115 v AC 230 v AC 23	D7 00*						
P8. 1 Batter y chemical composition: Li-lon P9 Energy consumption (See NOTE B8) P9.1 For the product the following power levels or energy consumptions are reported: Energy mode* Power level at 100 V AC 115 V AC 230 V AC modes and test method 100 V AC 115 V AC 230 V AC modes and test method 100 V AC 115 V AC 230 V AC modes and test method 100 V AC 115 V AC 230 V AC modes and test method 100 V AC 115 V AC 230 V AC modes and test method 100 V AC 115 V AC 230 V AC modes and test method 100 V AC 115 V AC 230 V AC modes and test method 100 V AC 115 V AC 230 V AC modes and test method 100 V AC 115 V AC 230 V AC 23	P1.22"						
P9.1 For the product the following power levels or energy consumptions are reported: Energy mode 100 V AC 115 V AC 230 V AC Reference/Standard for energy modes and test method ** 100 V AC 115 V AC 230 V AC Reference/Standard for energy modes and test method ** Peak (On-max) 65 W 65 W Full load Category -1- Short Idie State - WOL Enabled 1.22 W 1.34 W 1.36 W Use for ENERGY STAR V8.0 registration (Pake) Enabled 1.22 W 1.34 W 1.36 W Use for ENERGY STAR V8.0 registration (Pake) Sleep (S3) - WOL Enabled 1.43 W 1.35 W 1.38 W Use for ENERGY STAR V8.0 registration (Pake) Sleep (S3) - WOL Enabled 0.30 W 0.30 W 0.34 W Use for ENERGY STAR V8.0 registration (Pake) EPS No-load (EPS No-load 0.10 W 0.10 W 0.10 W Use for ENERGY STAR V8.0 registration (Pake) ETEC ** Annual Energy Consumption EXECUTED ** 1.51 KWh/year 18.37 KWh/year 16.79 kWh/year Ersc = (8760/1000) × (Par × 0.25 + Pakes) state > WOL Enabled EXECT = (8760/1000) × (Par × 0.25 + Pakes) state > WOL Enabled EXECT = (8760/1000) × (Par × 0.25 + Pakes) state > WOL Enabled > Pakes (Idie State - WOL Enabled > P	P8		•			iam moreary content po	
P9.1 For the product the following power levels or energy consumptions are reported: Energy mode* Power level at Power level at Power level at 100 VAC 115 VAC 230 V	P8.1*	Battery of	chemical c	omposition: <i>Li-ion</i>			
Power level at 100 V AC 115 V AC 230 V							
100 V AC			product the	e following power level			Deference/Standard for energy
Category -1- Short Idle State - WOL Enabled Long Idle State - WOL Enabled 1.22 W 1.34 W 1.36 W Use for ENERGY STAR V8.0 registration (Palma) Sleep (S3) - WOL Enabled 1.43 W 1.35 W Use for ENERGY STAR V8.0 registration (Palma) Sleep (S3) - WOL Enabled 0.30 W 0.30 W 0.34 W Use for ENERGY STAR V8.0 registration (Palma) EPS No-load (Enternal power supply 1 charger plagged in the (Palmap) 1.00 W Use for ENERGY STAR V8.0 registration (Palmap) FTEC ** Annual Energy Consumption ETEC ** Annual Energy Consumption External Power Supply Efficiency Level (International Efficiency Marking Protocol) *: VI Display resolution *: 8.2944 megapixels Default time to enter energy save mode: 10 minutes P9.2* Information about the energy save function is provided with the product. P9.3* Energy efficiency class (monitors only): P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, Lwac (B) 16 (Depration *: Operating (PDI) ** 2.5 Operation *: Operating (PDI) ** 2.5 Other mode Declared A-weighted sound pressure level (dB) 15 (operator position desktop – operatingCPU) Measured according to: SIGN 7779 SECMA-74	Litergy IIIO	ue					
Short Ide State - WOL Enabled Long Idle State - WOL Enabled 1.22 W 1.34 W 1.36 W Use for ENERGY STAR V8.0 registration (Ptate) Sleep (S3) - WOL Enabled 1.43 W 1.35 W Use for ENERGY STAR V8.0 registration (Ptate) Sleep (S3) - WOL Enabled 1.43 W 1.35 W Use for ENERGY STAR V8.0 registration (Ptate) Off (S5) - WOL Enabled 0.30 W 0.30 W 0.34 W Use for ENERGY STAR V8.0 registration (Ptate) EPS No-load (external power supply / theraper plugged in the product) PTEC ' W W W W Use for ENERGY STAR V8.0 registration (Ptate) Typical Energy Consumption ETEC - W W W W W W Free Consumption External Power Supply Efficiency Level (International Efficiency Marking Protocol) *: VI Display resolution *: 8.2944 megapixels Default time to enter energy save mode: 10 minutes P9.2* Information about the energy save function is provided with the product. P9.3* Energy efficiency class (monitors only): P10 Emissions Noise emission — Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, Lwa.c (B) Operation *Operating (PDU) *2.7 Other mode Declared A-weighted sound pressure level (dB) 15 (operator position desktop – operatingCPU) Measured according to: SO 7779 SECMA-74	Peak (On-	max)		65 W	65 W	65 W	Full load
Short Ide State - WOL Enabled Long Idle State - WOL Enabled 1.22 W 1.34 W 1.36 W Use for ENERGY STAR V8.0 registration (Ptate) Sleep (S3) - WOL Enabled 1.43 W 1.35 W Use for ENERGY STAR V8.0 registration (Ptate) Sleep (S3) - WOL Enabled 1.43 W 1.35 W Use for ENERGY STAR V8.0 registration (Ptate) Off (S5) - WOL Enabled 0.30 W 0.30 W 0.34 W Use for ENERGY STAR V8.0 registration (Ptate) EPS No-load (external power supply / theraper plugged in the product) PTEC ' W W W W Use for ENERGY STAR V8.0 registration (Ptate) Typical Energy Consumption ETEC - W W W W W W Free Consumption External Power Supply Efficiency Level (International Efficiency Marking Protocol) *: VI Display resolution *: 8.2944 megapixels Default time to enter energy save mode: 10 minutes P9.2* Information about the energy save function is provided with the product. P9.3* Energy efficiency class (monitors only): P10 Emissions Noise emission — Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, Lwa.c (B) Operation *Operating (PDU) *2.7 Other mode Declared A-weighted sound pressure level (dB) 15 (operator position desktop – operatingCPU) Measured according to: SO 7779 SECMA-74	Categor	v -1-					
Enabled Long Idle State - WOL Enabled 1.22 W 1.34 W 1.36 W 1.36 W Use for ENERGY STAR V8.0 registration (P _{tothey}) Off (S5) - WOL Enabled 0.30 W 0.30 W 0.34 W Use for ENERGY STAR V8.0 registration (P _{tothey}) EPS No-load (External power supply charger pulgged in the wall outlieb but disconnected from the groduct.) PTEC * Typical Energy Consumption TT.51 kWh/year 18.37 kWh/year 16.79 kWh/year 16.79 kWh/year These y 0.35 + Plong, life x 0.25				4.00.144	5.00 144	4.55.14	
Long Idle State - WOL Enabled 1.22 W 1.34 W 1.36 W 1.36 W 1.38 W		State - W	OL	4.88 W	5.39 W	4.57 W	
Sleep (S3) - WOL Enabled 1.43 W 1.35 W 1.38 W 1.39 W 1.30 Fercips (Archivolopy Consulting Color) 1.4 Palocap X 0.35 + Pang, Ide X 0.10 + Palocap X 0.25 Paloca		04 4 144		4.00.114	4.04104	4.0014	, ,
Sleep (S3) - WOL Enabled 1.43 W 1.35 W 1.38 W Use for ENERGY STAR V8.0 registration (Paleap) Off (S5) - WOL Enabled 0.30 W 0.30 W 0.34 W Use for ENERGY STAR V8.0 registration (Paleap) PES No-load (External power supply / charger plagged in the product.) PTEC ' Annual Energy Consumption ETEC ' Annual Energy Consumption External Power Supply Efficiency Level (International Efficiency Marking Protocol) *: WI Display resolution *: 8.2944 megapixels Default time to enter energy save mode: 10 minutes P9.2 Information about the energy save function is provided with the product. P9.3 Energy efficiency class (monitors only): Noise emission — Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode description (Paleap) Noise emission — Declared A-weighted sound pressure level (dB) L _{p,Am} Other mode Declared A-weighted sound pressure level (dB) L _{p,Am} Other mode Declared A-weighted sound pressure level (dB) L _{p,Am} Measured according to: Signal Signa		State - W	OL	1.22 VV	1.34 VV	1.36 VV	
Post Continue C	Zilazioa						region and (Finis)
Display resolution * : 8.2944 megapixels Default time to enter energy save mode: 10 minutes	Sleep (S3)	- WOL E	nabled	1.43 W	1.35 W	1.38 W	
EPS No-load (External power supply) charger plugged in the word outdoth of demonstration (Psteep) PTEC * W W W Typical Energy Consumption ETEC * Annual Energy Consumption ETEC * Annual Energy Consumption External Power Supply Efficiency Level (International Efficiency Marking Protocol) *: VI							registration (P _{sleep})
EPS No-load (External power supply I charger plugged in the wall oxidio but disconnected from the product) PTEC Typical Energy Consumption T7.51 kWh/year 18.37 kWh/year 16.79 kWh/year ETEC = (8760/1000) x (Poiff x 0.25 Palsey x 0.35 + Phong, jalle x 0.10+ Pashori, jalle x 0.30) Poiff Mode(S5) - WOL Enabled; Palsey: Sleep Mode(S3) - WOL Enabled; Palsey:	Off (S5) - V	NOL Enal	bled	0.30 W	0.30 W	0.34 W	
External power supply / charger plugged in the wall outlib but disconnected from the product. W W W Typical Energy Consumption T7.51 kWh/year 18.37 kWh/year 16.79 kWh/year Erec = (8760/1000) x (Port x 0.25 + Paleep x 0.35 + Plong_late x 0.10+ Pathort_late x 0.30)							registration (Psleep)
PTEC * Typical Energy Consumption TTST kWh/year Typical Energy Consumption TTST kWh/year Typical Energy Consumption TTST kWh/year TYPICA * Annual Energy Consumption TTST kWh/year TYPICA *			plugged in the	0.10 W	0.10 W	0.10 W	
Typical Energy Consumption ETEC * Annual Energy Consumption ### T7.51 kWh/year ###	wall outlet but dis	connected from	the product.)	144	144	100	
ETEC * Annual Energy Consumption 17.51 kWh/year 18.37 kWh/year 16.79 kWh/year 16.79 kWh/year ETEC = (8760/1000) x (Poff x 0.25 + Palsep x 0.35 + Plong_ide x 0.10 + Pahort_Idle x 0.30) Poff: Off Mode(S5) - WOL Enabled; Palsep Mode(S3) - WOL Enabled; Phile: Idle State - WOL Enabled External Power Supply Efficiency Level (International Efficiency Marking Protocol) *: VI Display resolution *: 8.2944 megapixels Default time to enter energy save mode: 10 minutes P9.2* Information about the energy save function is provided with the product. P9.3 Energy efficiency class (monitors only): P10 Emissions Noise emission - Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode description Idle * HDD idle * 2.5 Operation * Operating (HDD) * 2.5 Operation * Operating (HDD) * 2.5 Other mode Declared A-weighted sound pressure level (dB)		erav Cons	umntion	W	W	W	
External Power Supply Efficiency Level (International Efficiency Marking Protocol) *: VI Display resolution *: 8.2944 megapixels Default time to enter energy save mode: 10 minutes P9.2* Information about the energy save function is provided with the product. P9.3 Energy efficiency class (monitors only): P10 Emissions Noise emission – Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, L _{WA,C} (B) Operation * Operating (PPU) * 2.5		orgy conc	шприоп	17.51 kWh/year	18.37 kWh/year	16.79 kWh/year	$E_{TEC} = (8760/1000) \times (P_{off} \times 0.25)$
External Power Supply Efficiency Level (International Efficiency Marking Protocol) *: VI Display resolution *: 8.2944 megapixels Default time to enter energy save mode: 10 minutes P9.2* Information about the energy save function is provided with the product. P9.3 Energy efficiency class (monitors only): P10 Emissions Noise emission – Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, L _{WA,c} (B) Idle *HDD idle *2.5 Operation *Operating (HDD) *2.7 Other mode Declared A-weighted sound pressure level (dB) 15 (operator position desktop – idle) L _{pAm} 15 (operator position desktop – operatingCPU) Measured according to: SISO 7779 ECMA-74	Annual En	ergy Cons	umption				
External Power Supply Efficiency Level (International Efficiency Marking Protocol) *: W Display resolution *: 8.2944 megapixels				Poff: Off Mode(\$5) - W	 OL Enabled: P _{sleen} : Slee	p Mode(S3) - WOL Enable	
Default time to enter energy save mode: 10 minutes P9.2* Information about the energy save function is provided with the product. P9.3 Energy efficiency class (monitors only): P10 Emissions Noise emission – Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, $L_{WA,c}$ (B) Idle * HDD idle * 2.5 Operation * Operating (HDD) * 2.5 Operation * Operating (CPU) * 2.7 Other mode Declared A-weighted sound pressure level (dB) 15 (operator position desktop – idle) L_{pAm} Other mode Declared A-weighted sound pressure level (dB) 15 (operator position desktop – operatingHDD) 18 (operator position desktop – operatingCPU) Measured according to: ISO 7779 ECMA-74	External Po	ower Supp	oly Efficien	, ,		• •	The state of the s
Default time to enter energy save mode: 10 minutes P9.2* Information about the energy save function is provided with the product. P9.3 Energy efficiency class (monitors only): P10 Emissions Noise emission – Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, $L_{WA,c}$ (B) Idle * HDD idle * 2.5 Operation * Operating (HDD) * 2.5 Operation * Operating (CPU) * 2.7 Other mode Declared A-weighted sound pressure level (dB) 15 (operator position desktop – idle) L_{pAm} Other mode Declared A-weighted sound pressure level (dB) 15 (operator position desktop – operatingHDD) 18 (operator position desktop – operatingCPU) Measured according to: ISO 7779 ECMA-74	Display res	solution * :	8.2944 m	negapixels	<u> </u>	·	3840*2160
$ \begin{array}{ c c c c c }\hline P9.3 & Energy efficiency class (monitors only): & & & & & \\\hline P10 & Emissions & & & & \\\hline Noise emission - Declared according to ISO 9296 (See NOTE B9) & & & \\\hline P10.1 & Mode & Mode description & Statistical upper limit A-weighted sound power level, L_{WA,c} (B) & & & & \\\hline Idle & * HDD \ idle & * 2.5 & & & \\\hline Operation & * Operating (HDD) & * 2.5 & & & \\\hline & * Operating (CPU) & * 2.7 & & \\\hline Other \ mode & Declared \ A-weighted \ sound \ pressure \ level \ (dB) & & \\\hline & L_{pAm} & & & \\\hline & Other \ mode & Declared \ A-weighted \ sound \ pressure \ level \ (dB) & & \\\hline & L_{pAm} & & & \\\hline & Measured \ according \ to: & & & \\\hline & ISO \ 7779 & ECMA-74 & & \\\hline \end{array} $	Default time	e to enter	energy sa	ve mode: 10 minutes			
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	P9.2*	Informati	ion about	the energy save functi	on is provided with the	product.	
P10 Emissions Noise emission – Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, $L_{WA,c}$ (B) Idle * HDD idle * 2.5 Operation * Operating (HDD) * 2.7 Other mode Declared A-weighted sound pressure level (dB) L_{pAm} 15 (operator position desktop – idle) Other mode Declared A-weighted sound pressure level (dB) L_{pAm} 15 (operator position desktop – operatingHDD) 18 (operator position desktop – operatingCPU)	P9.3	Energy e	efficiency of	class (monitors only):			
$ \begin{array}{ c c c c c }\hline P10.1 & Mode & Mode description & Statistical upper limit A-weighted sound power level, $L_{WA,c}$ (B)\\\hline Idle & *HDD idle & *2.5\\\hline Operation & *Operating (HDD) & *2.5\\\hline *Operating (CPU) & *2.7\\\hline Other mode & Declared A-weighted sound pressure level (dB) & 15 (operator position desktop – idle)\\\hline Other mode & Declared A-weighted sound pressure level (dB) & 15 (operator position desktop – operating HDD) & 18 (operator position desktop – operating CPU)\\\hline Measured according to: $\sumsymbol{\text{NO}}$ ISO 7779 $\sumsymbol{\text{ECMA-74}}$ ECMA-74$	P10	Emissio	ns				
	D40.4				ISO 9296 (See NOT		(2)
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	P10.1						t A-weighted sound power level, LwA,c (B)
$ \begin{array}{c c} L_{p\text{Am}} \\ \hline \text{Other mode} & \begin{array}{c} \textbf{Declared A-weighted sound pressure level (dB)} \\ L_{p\text{Am}} \\ \hline \end{array} & \begin{array}{c} \textbf{15 (operator position desktop - operatingHDD)} \\ \textbf{18 (operator position desktop - operatingCPU)} \\ \hline \\ \text{Measured according to: } & \begin{array}{c} \square \\ \square $		Operatio	*	Operating (CPU)			
Other mode L_{pAm} Declared A-weighted sound pressure level (dB) L_{pAm} 15 (operator position desktop – operatingHDD) 18 (operator position desktop – operatingCPU) 18 (operator position desktop – operatingCPU)	The state of the s					ion desktop – idle)	
		Other me			d pressure level (dB)	15 (operator positi	on deskton – operatingHDD)
				•			
		Measure	d according	ng to: 🔀 ISO 7779 🔀	ECMA-74		
Other (only if not covered by ECMA-74)				Other	(only if not covered b	y ECMA-74)	

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; $see \ \underline{http://www.ecma-international.org/publications/standards/Ecma-370.htm}$

Model number *	20U9, 20UA	Logo	Lanava
Issue date *	2020/02		LEI IOVO"

Product met	environmental attribute	s - Market requirements (continued)	Requi	emei	nt
Item			Yes	No	n.a.
	Electromagnetic emissio	ns			
P10.4	Computer display meets the program(s): MPR-II(3 pin A	ne requirement for low frequency electromagnetic fields of the following voluntary AC adapter only)			
P12	Ergonomics for computing				
P12.1*	The display meets the ergo	onomic requirements of ISO 9241-307 for visual display technologies.	\boxtimes		
P12.2*	The physical input device r	meets the requirements of ISO 9995 and ISO 9241-410.	\boxtimes		
P13	Packaging and documen				
P13.1*	Product packaging materia	al type(s): Acc Box weight (kg): 0.0632 al type(s): EPE cushion weight (kg): 0.059 al type(s): PE bag(NB) weight (kg): 0.006 al type(s): PE Bag(manual) weight (kg): 0.005			
P13.2*	Product plastic primary page	ckaging is free from PVC.	\boxtimes		
P13.3*	For product primary corrug	gated fiberboard packaging, specify the contained percentage of minimum post-content: $70\ \%$			
P13.4*		d product documentation (tick box): Other			
P13.5		item if paper documentation used) ntation on paper media is chlorine-free:			
	Totally chlorine-free Elemental chlorine-free				
	Processed chlorine-free		Ħ		
P14	Voluntary programs				
P14.1		uirements of the following voluntary program(s):			
	ENERGY STAR® Eco-label: <i>EPEAT</i>	Criteria version: V8.0 Date: 2020/02 Product category: 2 Criteria version: IEEE 1680.1- Date: 2020/02 Product category: Noteb	ook		
	Eco-label: TCO	Criteria version: NoteBook 8.0 Date: 2020/03/25 Product category: Note	book		
	Eco-label: PCGL	Criteria version: V13 Date: 2020/20 Product category: Note	book		
P15	Additional information (S	See NOTE B10)			
P9	Energy consumption of s	specific configuration may vary; description of the tested product configurat	tion:		
	information contained in the knowledge available at the provided here is approximatinformation.	representations, guarantees, assurances or warranties whether express or implie is document. All information provided by supplier in this document is provided base time of completion, and supplier shall have no obligation to update such informatiate and provided for informational purposes only. See a Lenovo Account Representation of the completion of t	ed on su ion. The i	pplier' inform	s ation
P9		Notebooks & Tablet Computers for the latest information: /index.cfm?fuseaction=find a product.showProductGroup&pgw code=CO			
	, , , , , , , , , , , , , , , , , , , ,				

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B2

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1
Regulation (EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7
Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)	P1.3, P5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) No 1272/2008 (CLP Regulation)	P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1

Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	ThinkPad X1 Carbon 8th Gen	Logo	
Model Number	20U9, 20UA		Lenovo
Issue Date	2020/02		renovo.
Additional information			

(d)	year of manufacture:				2020
e)	Etec value (kWh) per ErP Lot 3 Catego disabled and if the system is tested with				cards (dGfx) are
f)	Etec value (kWh) per ErP Lot 3 Categor enable	y and capability adjust	tments applied when a	all discrete graphics	cards (dGfx) are
		Category A (according to ErP Lot 3)	Category B (according to ErP Lot 3)	Category C (according to ErP Lot 3)	Category D (according to ErP Lot 3)
	Memory over base [GB]	12			
ents	Additional internal storage	No (Yes / No)	(Yes / No)	(Yes / No)	(Yes / No)
capability adjustments applied during testing	Discrete television tuner	No (Yes / No)	(Yes / No)	(Yes / No)	(Yes / No)
bility a	Discrete Audio Card	No (Yes / No)	(Yes / No)	(Yes / No)	(Yes / No)
cape	Discrete graphics Card(s) [number / #]	No #: (Yes / No)	#: (Yes / No)	#: (Yes / No)	#: (Yes / No)
	Category of discrete graphics Card(s)				
sults	Etec Value (kWh) - dGfx disabled all discrete graphics cards (dGfx) are disabled/ UMA is active for switchable graphics/ product has no graphics cards (dGfx)	31.8			
Test results	Etec Value (kWh) - dGfx enabled all discrete graphics cards (dGfx) are enabled				
g)	Idle state power demand (Watts);	ı	l .	<u> </u>	1.34
h)	Sleep mode power demand (Watts);				1.33
i)	Sleep mode with WOL enabled power de	emand (Watts) (where	enabled);		1.33
j)	Off mode power demand (Watts);				0.41
k)	Off mode with WOL enabled power dem	and (Watts) (where en	abled);		0.41
I)	Internal power supply efficiency at 10 %,	20 %, 50 % and 100 °	% of rated output pow	er (if applicable):	
	10% 20% 50%	100% Avera	age		
m)	external power supply efficiency (if applied	cable)*:			
	Average active efficiency: 45W: 87,98%	5,88,63%,88,83%; 65W	V: 89,41%,88,62%,88	,96%	
	*internal note: show values for all available external po				
(o)	Minimum number of loading cycles that t	the batteries can withst	tand (applies only to r	notebook computers):	500 cycles
(p-1)	Measurement methodology used to dete	rmine information men	ntioned in points (I) - i	nternal PSU efficiency	:
(p-2)	Measurement methodology used to dete	rmine information men		external PSU efficience	cy:

(p-3)	Measurement methodology used to determine information mentioned in points (o) – loading cycles batteries: EN 61960 measurement methodology							
(p-4)		dology used to determine information mentioned in r Point P9.1 in the Product IT Eco Declaration: EN 62623:2013 measurement methodo						
(q)	Sequence of steps for	or achieving a stable condition with respect to power EN 62623:2013 measurement methodo						
(r)	Description of how sleep and/or off mode was selected or programmed: By selecting sleep and/or off mode thru Windows operating system							
(s)	Sequence of events required to reach the mode where the equipment automatically changes to sleep and/or off mode: **Automatically changes to sleep after 30 minutes**							
(t)	Duration of idle star	te condition before the computer automatically re	eaches sleep mode, or another	10				
()		not exceed the applicable power demand requirement	. , ,					
(u)	•	a period of user inactivity in which the compute ver power demand requirement than sleep mode (in	•	NA				
(v)		re the display sleep mode is set to activate after	,	10				
(w)		nergy-saving potential of power management function on described in User Guide and Power Manager u programs						
(x)		now to enable the power management functionality: on described in User Guide and Power Manager u programs	nder ThinkVantage menu in all					
(z)		neasurements: — test voltage in V and frequency in tem, — information and documentation on the instruction. 230V/50HZ; Total Harmonic Distortion	mentation, set-up and circuits used					
Additio	n Notebook Battery	Information:						
, ta artis		Battery[ies] not user replaceable The battery[ies] in this product cannot be easily replaced by users themselves. 1)	Battery[ies] user replaceable	n/a				
Internal	/built-in Battery							
	Il/detachable Battery							
Bios Backup Battery								
Other:	Other:							
Addition	Additional information							
1)								
he battery[[ies] in this product cannot be	easily replaced by users themselves.						

Акумулаторната[ите] батерия[и] в този продукт не може да се замени[ят] лесно от самите потребители. Las baterías de este producto no pueden ser sustituidas fácilmente por los propios usuarios. Výměnu baterie/baterií v tomto výrobku by neměli provádět sami uživatelé.

Brugeren kan ikke uden videre udskifte batteriet/batterierne i dette produkt. Der Akku/die Akkus dieses Produkts kann/können nicht ohne weiteres vom Benutzer selbst ausgetauscht werden.

Kasutajad ei saa selle toote akut/akusid ise hõlpsasti asendada.

Η μπαταρία[-ες] στο προϊόν αυτό δεν μπορούν να αντικατασταθούν εύκολα από τους ίδιους τους χρήστες La/les batterie(s présente(s) dans ce produit ne peuvent être facilement remplacée(s) par les utilisateurs eux-mêmes. Korisnik ne može lako zamijeniti Bateriju sam u ovom proizvodu.

La batteria/le batterie in questo prodotto non può/possono essere facilmente sostituita/e dall'utente. Lietotāji paši nevar nomainīt šā ražojuma akumulatoru(-us). Šio gaminio baterijos [baterijų] pats vartotojas negali lengvai pakeisti.

A termék akkumulátorát/akkumulátorait a felhasználó nem tudja egyedül egyszerűen kicserélni. Il-batterija/batteriji f'dan il-prodott ma tistax/jistgħux tiġi/jiġu sostitwita/i mill-utenti stess. Batteriet [ene] i dette produktet kan ikke lett erstattes av brukerne selv.

De batterij(en) in dit product is (zijn) door de gebruiker niet gemakkelijk vervangbaar. Użytkownik nie może sam w łatwy sposób wymienić baterii w tym produkcie. A ou as baterias deste produto não podem ser facilmente substituídas pelos próprios utilizadores.

Bateria (bateriile) din acest produs nu poate (pot) fi uşor înlocuită (înlocuite) de utilizatorii înşişi. Batériu(-ie) v tomto výrobku nemôže vymieňať používateľ. Baterij/baterije v tem izdelku uporabniki sami ne morejo zlahka zamenjati.

Tämän tuotteen akku [akut] ei[vät] ole helposti käyttäjän vaihdettavissa. Det är inte enkelt för kunden att själv byta ut batteriet/batterierna. Bu üründeki batarya(lar) kullanıcılar tarafından kolaylıkla değiştirilemez.