



ECMA/TC38-TG3/2015/026 (Rev. 1 – 15 April 2017)

Annex B2 - Product environmental attributes Desktop/All-in-One Computers

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lenovo	Logo	
Company name *	Lenovo	To a second second	
Contact information *	Lenovo Global Environmental Affairs	Lenovo	
e-mail address	Alvin L Carter	LEI IOVO.	
	alcarter@lenovo.com		
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment	.html	
Additional information	The latest version of this document can be found at:		
	http://www.lenovo.com/ecodeclaration		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.				
Type of product *	Workstation			
Commercial name *	ThinkStation P350 Tower			
Model number *	30E3,30E4			
Issue date *	2021/5/13			
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other			
Additional information				

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products

Model nu	mber *	30E3,30E4	Logo	Lon	27/10	
Issue date	e *	2021/5/13		Len	JVC) _
Product	environ	mental attributes - Legal requirements		Require	men	t met
Item				Yes	No	n.a.
P1		ous substances and preparations				
P1.1*	Products	s do comply with current European RoHS Directive. (See legal reference and NOTE	EB1)	\boxtimes		
P1.2*		s do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value.				
P1.3*	hydrobro trichloroe	s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), omofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrach ethane, methyl bromide (see legal reference). Comment: Legal reference has no mation values.				
P1.4*	terpheny	s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polych l (PCT) in preparations (see legal reference).				
P1.5*		edo not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carb ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).	oon atoms in	the 🔀		
P1.6*	(see lega	th direct and prolonged skin contact do not release nickel in concentrations above 0 al reference). nt: Max limit in legal reference when tested according to EN1811:2011-5.	,5 μg/cm²/we	eek 🔀		
P1.7*	REACH	Article 33 information about substances in articles is available at (add URL or mail www.lenovo.com/us/en/Lenovo-REACH-SVHC-Disclosure	contact):			
P2	Batterie					
P2.1*	symbol.	educt contains a battery or an accumulator, the battery/accumulator is labeled with t Information on proper disposal is provided in user manual. (See legal reference)	•			
P2.2*	Batteries reference	s or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadme)	nium. (See le	gal 🔀		
P2.3*	Batteries	and accumulators are readily removable. (See legal reference)		\boxtimes		
P3	Conforn	nity verification & Eco design (ErP)				
P3.1*		duct is CE-marked to show conformance with applicable legal requirements (see leg laration of Conformity can be requested at: https://www.lenovo.com/us/en/comp				
P3.2*	The prod	duct complies with the Eco design requirements for energy-related products, al reference).		\boxtimes		
	, ,	d information is; Sigiven in item P15 or added to this document, Sigiven available at: https://www.lenovo.com/us/en/compliance/ecc	o-declaration			
P5		packaging				
P5.1*	hexavale	ng and packaging components do not contain more than 0,01% lead, mercury ent chromium by weight of these together.	,			
P5.2*		kaging materials are marked with abbreviations and numbers indicating the nature α be legal reference).	of the materia	al(s)		
P5.3*	(see lega	luct packaging material is free from ozone depleting substances as specified in the N al reference). nt: Legal reference has no maximum concentration values.	nontreal Proto	ocol 🔀		
P6		nt information				_
P6.1*		on for recyclers/treatment facilities is available (see legal reference).				

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model nu	ımber *	30E3,30E4	Logo	Lon	21/0			
Issue dat	te *	2021/5/13		Len	enovo			
Product	environ	mental attributes - Market requirements (See General NOTE GN	helow)					
Troduct		onmental conscious design	,	Require	ment	met		
Item		tory to fill in. Additional information regarding each item may be found under P14.		Yes	No	n.a.		
P7		Disassembly, recycling						
P7.1*	Parts tha	t have to be treated separately are easily separable						
P7.2*	Plastic m	aterials in covers/housing have no surface coating.		\boxtimes				
P7.3*	Plastic pa	arts > 100 g consist of one material or of easily separable materials.		\boxtimes				
P7.4*	Plastic pa	arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.						
P7.5	Plastic pa	arts are free from metal inlays or have inlays that can be removed with commonly a	vailable tools.	\boxtimes				
P7.6*	Labels a	re easily separable. (This requirement does not apply to safety/regulatory labels).		\boxtimes				
	Product	lifetime						
P7.7*	Upgradin	g can be done e.g. with processor, memory, cards or drives						
P7.8*	Upgradin	g can be done using commonly available tools		\boxtimes				
P7.9	Spare pa	rts are available after end of production for: 5 years						
P7.10	Service i	s available after end of production for: 5 years						
	Material	and substance requirements						
P7.11*	Material	cover/housing material type (e.g. plastics, metal, aluminum): type: <i>ABS</i> Material type: <i>Steel</i> Materia	ıl type:					
P7.12	Insulation	n materials of external electrical cables are PVC free.			\boxtimes			
P7.13	Insulatio	n materials of internal electrical cables are PVC free.			\boxtimes			
P7.14	weight (* polyvinyl	plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bi 1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine ir n 25% post-consumer recycled content.	retardants, and	l 💆				
P7.15		ircuit boards, PCBs (without components) are low halogen: all ☐ PCBs > 25 g ☒ d in IEC 61249-2-21. (See 1NOTE B2)	are low haloger	n 🔀				
P7.16	Marking:							
P7.17		nemical specifications of flame retardants in printed circuit boards > 25 g (without co A (additive), TBBPA (reactive) (See NOTE B3), Other: , CAS #: 79-94	. ,					
		nemical specifications of flame retardants in printed circuit boards (without compone g ISO 1043-4:	ents) > 25 g					
P7.18	concentr 1. Chemi 2. Chemi	ame retarded plastic parts > 25 g contain the following flame retardant substance ations above 0,1%: cal name: , CAS #: (See NOTE B4) ical name: , CAS #: " ical name: , CAS #: "	s/preparations in					
		nemical specifications of flame retardants in plastic parts > 25 g according ISO 1043						
P7.19		parts > 25 g, flame retardant substances/preparations above 0,1% are used which the following Risk phrases; and Hazard statements:	have been					
		() () ()	ee note B5)					
P7.20*	Postcons	sumer recycled plastic material content is used in the product (See Note B6):						
	a) Of t a pe	t least one of the two alternatives below shall be answered; otal plastic parts' weight > 25 g, the postconsumer recycled plastic material contentercentage of total plastic by weight) is 39.4%. weight of recycled material is 243.2 g.	t (calculated as					

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model number *	30E3,30E4	Logo	Len	01/0	
Issue date *	2021/5/13		Len	UVC	,
Product environn		Requi	remen	t met	
Item			Yes	No	n.a.

	Material and sub	stance requirements	(continued)							
P7.21*			d in the product (See N	IOTE B7):						
	If YES; at least or a) Of total plast total plastic l	ne of the two alternativ tic parts' weight > 25 g	es below shall be answ	rered;	ated as a percentage of					
	or b) The weight of	of the biobased plastic	material is							
P7.22*	Light sources are		less than 0,1 mg/lamp	o. num mercury content po	er lamp: mg					
P8	Batteries	i specily. Number of la	ilips. aliu iliaxili	ium mercury content po	er lamp.					
P8.1*	Battery chemical	composition:								
P9		otion (See NOTE B8)								
P9.1			lowing power levels or energy consumptions are reported:							
Energy mo		Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference/Standard for energy modes and test method *					
Peak (On-I	max)	135.81 W	316.52 W	316.47 W	Full load					
Categor	<u>V</u>									
Short Idle Enabled	State - WOL	43.87 W	43.45 W	43.45 W	Use for ENERGY STAR V8 registration (P _{idle})					
Long Idle : Enabled	State - WOL	41.13 W	40.49 W	40.05 W	Use for ENERGY STAR V8 registration (P _{idle})					
Sleep (S3)	- WOL Enabled	2.36 W	2.36 W	2.36 W	Use for ENERGY STAR V8 registration (P _{sleep})					
Off (S5) - V	VOL Enabled	0.8 W	0.8 W	0.8 W	Use for ENERGY STAR V8 registration (P _{off})					
Off (S5) - V	VOL Disabled	W	W	0.8 W	Use for ErP					
EPS No-loa (External power s wall outlet but disc	ad upply / charger plugged in the connected from the product.)	W	W	W						
PTEC *		24.49 W	24.21 W	24.12 W						
ETEC *	ergy Consumption ergy Consumption	kWh/year	kWh/year	kWh/year	E _{TEC} = (8760/1000) x (P _{off} x 0.45 + P _{sleep} x 0.05 + P _{long_idle} x 0.15+ P _{short idle} x 0.35)					
		P _{off} : Off Mode((S5) - WOL Enabled; Psies	p: Sleep Mode(S3) - WOL	Enabled; P _{idle} : Idle State - WOL Enabled					
External Po	ower Supply Efficie	ncy Level (Internationa	al Efficiency Marking Pr	otocol) *:						
Display res	olution * : n	negapixels								
Default time	e to enter energy s	ave mode: 25 minutes								
P9.2*	Information about	the energy save funct	tion is provided with the	product.						
P9.3	Energy efficiency	class (monitors only):		·						
P10	Emissions	, ,,								
	Noise emission	 Declared according t 	to ISO 9296 (See NOTE	E B9)						
P10.1		Mode description			it A-weighted sound power level, $L_{WA,c}$ (B)					
	Idle	* HDD:Idle		* 3.5						
	Operation	* HDD: Operating		* 4.2						
	ound mode	<u>-</u>	nd pressure level (dBL)(A)	26 (operator position						
	0 11.01 11.0 10		nd pressure level (dBL)(A)	33 (operator position	on desktop – HDD operating)					
	Measured accord	ing to: 🔀 ISO 7779 🛭								
		Other	(only if not covered by	y ECMA-74)						

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

Model num	ber *	30E3,30E4			Logo	Long	1/0	
Issue date	*	2021/5/13				Leno	VO.	
Product e	nvironn	nental attributes	- Market requirements (cor	ntinued)		Require	ment	met
Item			-	•		Yes	No	n.a.
	Electron	nagnetic emissions	3					
	program	(s):	requirement for low frequency el	lectromagnetic fields	s of the following voluntary			
P12		mics for computing						
1	-	•	omic requirements of ISO 9241-	•				\boxtimes
P12.2*	The phys	sical input device me	ets the requirements of ISO 999	95 and ISO 9241-41	0.			\boxtimes
P13		ng and documenta						
	Product Product	packaging material t packaging material t	ype(s): <i>LDPE</i> weight (kg	g): 0.305	g): 1.076			
P13.2*	Product	plastic primary packa	aging is free from PVC.			\boxtimes		\Box
		luct primary corruga er recovered fiber co	ited fiberboard packaging, specintent: 70 %	cify the contained p	percentage of minimum po	st-		
P13.4*		media for user and p ronic, ⊠Paper, ⊡(roduct documentation (tick box): Other	:				
P13.5	Ùser and		em if paper documentation used tion on paper media is chlorine-					
	Element	hlorine-free al chlorine-free						
		ed chlorine-free						
	Volunta	ry programs						
P14.1	The proc	luct meets the requir	ements of the following voluntar	y program(s):				
		Y STAR® el: <i>EPEAT</i> el:	Criteria version: 8.0 Criteria version: 1680.1-2018 Criteria version:	Date: 2020/3/31 Date: 2020/7/21 Date:	Product category: Works Product category: Works Product category:			
		nal information (See						
			ecific configuration may vary;					
	informati knowled provided informati	on contained in this ge available at the tin here is approximate on.	presentations, guarantees, assu document. All information provid me of completion, and supplier s and provided for informational p	led by supplier in thi shall have no obligati purposes only. See	s document is provided bas ion to update such informat a Lenovo Account Represe	sed on supp ion. The inf	olier's formati	on
			otebooks & Tablet Computers fo dex.cfm?fuseaction=find_a_proc					

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B2

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1
Regulation (EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7
Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)	P1.3, P5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) No 1272/2008 (CLP Regulation)	P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1

Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	ThinkStation P350 Tower	Logo
Model Number	30E3,30E4	Lenovo
Issue Date	2021/5/13	Lenovo.
Additional information		

(d)	year of manufacture:				2021
e)	Etec value (kWh) per ErP Lot 3 Categor disabled and if the system is tested with				cards (dGfx) are
f)	Etec value (kWh) per ErP Lot 3 Categorienable	ry and capability adjust	ments applied when a	III discrete graphics of	cards (dGfx) are
		Category A (according to ErP Lot 3)	Category B (according to ErP Lot 3)	Category C (according to ErP Lot 3)	Category D (according to ErP Lot 3)
	Memory over base [GB]				
ents	Additional internal storage	(Yes / No)	(Yes / No)	(Yes / No)	(Yes / No)
capability adjustments applied during testing	Discrete television tuner	(Yes / No)	(Yes / No)	(Yes / No)	(Yes / No)
ability a lied du	Discrete Audio Card	(Yes / No)	(Yes / No)	(Yes / No)	(Yes / No)
cap	Discrete graphics Card(s) [number / #]	#: (Yes / No)	#: (Yes / No)	#: (Yes / No)	#: (Yes / No)
	Category of discrete graphics Card(s)				
esults	Etec Value (kWh) - dGfx disabled all discrete graphics cards (dGfx) are disabled/ UMA is active for switchable graphics/ product has no graphics cards (dGfx)				
Test results	Etec Value (kWh) - dGfx enabled all discrete graphics cards (dGfx) are enabled				
g)	Idle state power demand (Watts);	I			44.08
h)	Sleep mode power demand (Watts);				NA
i)	Sleep mode with WOL enabled power de	emand (Watts) (where	enabled);		2.37
j)	Off mode power demand (Watts);				NA
k)	Off mode with WOL enabled power dem	and (Watts) (where en	abled);		0.8
I)	Internal power supply efficiency at 10 %	, 20 %, 50 % and 100 °	% of rated output pow	er (if applicable):	
	Lowest Efficiency of all Power Supplies:	10% 85.35 20% 92.	57% 50% 93.35 10	00% 89.32 Average	91.57
m)	External power supply efficiency (if appli	icable)*:			
	Average active efficiency:				
0)	*internal note: show values for all available external p Minimum number of loading cycles that		tand (applies only to n	otebook computers):	
p-1)	Measurement methodology used to dete Generalized Test Protocol for Calcu		iciency of Internal A		

	Measurement methodology used to	determine information mentioned in poin N/A	nts (m) – external PSU efficiency:		
)-3)	Measurement methodology used to	determine information mentioned in poin N/A	nts (o) – loading cycles batteries:		
0-4)	Measurement methodology used to power as defined in Point P9.1 in the	determine information mentioned in made Product IT Eco Declaration:	ximum, idle, sleep, off mode		
		IEC 62623 Ed. 1.0, 2012-10			
(q)	Sequence of steps for achieving a s	stable condition with respect to power de	emand:		
	Based on user r	manual/Power on->Wait 5 minutes->S	table condition		
r)	Description of how sleep and/or off	mode was selected or programmed:			
	Based o	on user manual-Set power button beh	naviors		
	Set power button beha	aviors			
		utton does according to your preference e computer or put the computer to slee			
	To change what the power button	n does:			
	1. Go to Control Panel and vie	w by large icons or small icons.			
	Click Power Options → Choose what the power buttons do.				
	3. Change the settings as you p	orefer.			
(S)	Sequence of events required to read	ch the mode where the equipment auton	natically changes to sleep and/or		
(s)	off mode:	ch the mode where the equipment auton Panel->Power Options-> Change Sette for this plan	, , ,		
`	off mode: Based on user manual/Control I Duration of idle state condition be	Panel->Power Options-> Change Settle for this plan	ches sleep mode, or another	25	
(t)	Duration of idle state condition be condition which does not exceed the Length of time after a period of us	Panel->Power Options-> Change Sette for this plan efore the computer automatically reace applicable power demand requirement ser inactivity in which the computer a	ches sleep mode, or another ts for sleep mode (in minutes):	25 NA	
(t) (u) (v)	Duration of idle state condition be condition which does not exceed the Length of time after a period of us mode that has a lower power dem Length of time before the display	Panel->Power Options-> Change Sette for this plan efore the computer automatically read e applicable power demand requirement ser inactivity in which the computer a nand requirement than sleep mode (in m sleep mode is set to activate after use	ches sleep mode, or another ts for sleep mode (in minutes): automatically reaches a power ninutes): er inactivity (in minutes):		
(t) (u) (v)	Duration of idle state condition be condition which does not exceed the Length of time after a period of us mode that has a lower power dem Length of time before the display	Panel->Power Options-> Change Sette for this plan efore the computer automatically read e applicable power demand requirement ser inactivity in which the computer a hand requirement than sleep mode (in m	ches sleep mode, or another ts for sleep mode (in minutes): automatically reaches a power ninutes): er inactivity (in minutes):	NA	
(t) (u) (v) (w)	Duration of idle state condition be condition which does not exceed the Length of time after a period of us mode that has a lower power dem Length of time before the display Information on the energy-saving possible.	Panel->Power Options-> Change Setts for this plan efore the computer automatically read e applicable power demand requirement ser inactivity in which the computer a nand requirement than sleep mode (in m sleep mode is set to activate after use otential of power management functional	ches sleep mode, or another ts for sleep mode (in minutes): automatically reaches a power ninutes): er inactivity (in minutes):	NA	
(s) (t) (u) (v) (w) (x)	Duration of idle state condition be condition which does not exceed the Length of time after a period of us mode that has a lower power dem Length of time before the display Information on the energy-saving possible.	Panel->Power Options-> Change Setts for this plan efore the computer automatically read e applicable power demand requirement ser inactivity in which the computer a nand requirement than sleep mode (in m sleep mode is set to activate after use ottential of power management functional Based on user manual	ches sleep mode, or another ts for sleep mode (in minutes): automatically reaches a power ninutes): er inactivity (in minutes):	NA	
(t) (u) (v) (w)	Duration of idle state condition be condition which does not exceed the Length of time after a period of us mode that has a lower power dem Length of time before the display Information on the energy-saving pour length of time before the display Information on the energy-saving pour length of time before the display Information on the energy-saving pour length of time before the display Information on how to enable the Test parameters for measurements:	Panel->Power Options-> Change Setts for this plan efore the computer automatically read e applicable power demand requirement ser inactivity in which the computer a nand requirement than sleep mode (in m sleep mode is set to activate after use otential of power management functional Based on user manual the power management functionality:	ches sleep mode, or another ts for sleep mode (in minutes): automatically reaches a power ninutes): er inactivity (in minutes): lity: z, — total harmonic distortion of	NA	
(t) (u) (v) (w)	Duration of idle state condition be condition which does not exceed the Length of time after a period of us mode that has a lower power dem Length of time before the display Information on the energy-saving pour length of time before the display Information on the energy-saving pour length of time before the display Information on the energy-saving pour length of time before the display Information on how to enable the electricity supply system, — information of electricity supply system, — information displayed for electrical testing:	Panel->Power Options-> Change Setts for this plan efore the computer automatically read e applicable power demand requirement ser inactivity in which the computer a hand requirement than sleep mode (in m sleep mode is set to activate after use otential of power management functional Based on user manual the power management functionality: Based on user manual	ches sleep mode, or another ts for sleep mode (in minutes): automatically reaches a power ninutes): er inactivity (in minutes): lity: z, — total harmonic distortion of rumentation, set-up and circuits	NA	
(t) (u) (v) (w)	Duration of idle state condition be condition which does not exceed the Length of time after a period of us mode that has a lower power dem Length of time before the display Information on the energy-saving position of the condition which does not exceed the Length of time before the display Information on the energy-saving position on the energy-saving position of the condition on how to enable the lectricity supply system, — information of the electricity	Panel->Power Options-> Change Setts for this plan efore the computer automatically read e applicable power demand requirement ser inactivity in which the computer a nand requirement than sleep mode (in m sleep mode is set to activate after use otential of power management functional Based on user manual the power management functionality: Based on user manual :— test voltage in V and frequency in Ha ormation and documentation on the instru	ches sleep mode, or another ts for sleep mode (in minutes): automatically reaches a power ninutes): er inactivity (in minutes): lity: z, — total harmonic distortion of rumentation, set-up and circuits	NA	
(t) (u) (v) (w)	Duration of idle state condition be condition which does not exceed the Length of time after a period of us mode that has a lower power dem Length of time before the display Information on the energy-saving position of the condition which does not exceed the Length of time before the display Information on the energy-saving position on the energy-saving position of the condition on how to enable the lectricity supply system, — information of the electricity	Panel->Power Options-> Change Setts for this plan efore the computer automatically read e applicable power demand requirement ser inactivity in which the computer a nand requirement than sleep mode (in m sleep mode is set to activate after use otential of power management functional Based on user manual the power management functionality: Based on user manual :— test voltage in V and frequency in Hz: 230V	ches sleep mode, or another ts for sleep mode (in minutes): automatically reaches a power ninutes): er inactivity (in minutes): lity: z, — total harmonic distortion of rumentation, set-up and circuits	NA	
(t) (u) (v) (w)	Duration of idle state condition be condition which does not exceed the Length of time after a period of us mode that has a lower power dem Length of time before the display Information on the energy-saving position of the electricity supply system, — information in the electrical testing: Test very condition of the condition of the electrical testing:	Panel->Power Options-> Change Setts for this plan efore the computer automatically read e applicable power demand requirement ser inactivity in which the computer a mand requirement than sleep mode (in m sleep mode is set to activate after use otential of power management functional Based on user manual the power management functionality: Based on user manual	ches sleep mode, or another ts for sleep mode (in minutes): automatically reaches a power ninutes): er inactivity (in minutes): lity: z, — total harmonic distortion of umentation, set-up and circuits //50Hz m: ≦2%	NA	
(t) (u) (v) (w)	Duration of idle state condition be condition which does not exceed the Length of time after a period of us mode that has a lower power dem Length of time before the display Information on the energy-saving position of the electricity supply system, — information electrical testing: Test very total ham. Instrument Name	Panel->Power Options-> Change Setts for this plan efore the computer automatically read e applicable power demand requirement ser inactivity in which the computer a nand requirement than sleep mode (in m sleep mode is set to activate after use otential of power management functional Based on user manual the power management functionality: Based on user manual :— test voltage in V and frequency in Harden and documentation on the instructional of the electricity supply system monic distortion of the electricity supply system Range Used or ******	ches sleep mode, or another ts for sleep mode (in minutes): automatically reaches a power ninutes): er inactivity (in minutes): lity: z, — total harmonic distortion of rumentation, set-up and circuits //50Hz m: ≦2% Make and Model**	NA	
(t) (u) (v) (w)	Duration of idle state condition be condition which does not exceed the Length of time after a period of us mode that has a lower power dem Length of time before the display Information on the energy-saving position of the condition which does not exceed the Length of time after a period of us mode that has a lower power dem Length of time before the display Information on the energy-saving position of the energy-saving position on the energy-saving position of the energy-saving position of the energy-saving position of the energy-saving position of the energy-saving po	Panel->Power Options-> Change Setts for this plan efore the computer automatically read e applicable power demand requirement ser inactivity in which the computer a nand requirement than sleep mode (in m sleep mode is set to activate after use otential of power management functional Based on user manual the power management functionality: Based on user manual :— test voltage in V and frequency in Hz: 230V monic distortion of the electricity supply system Range Used or ******* 1~300VAC;1~550Hz; 1000VA	ches sleep mode, or another ts for sleep mode (in minutes): automatically reaches a power ninutes): er inactivity (in minutes): lity: z, — total harmonic distortion of rumentation, set-up and circuits //50Hz m: ≦2% Make and Model** NF; EC1000S	NA	
(t) (u) (v) (w)	Duration of idle state condition be condition which does not exceed the Length of time after a period of us mode that has a lower power dem Length of time before the display Information on the energy-saving position of the electricity supply system, — information used for electrical testing: Test very Total ham Instrument Name AC Power Source Power Meter	Panel->Power Options-> Change Setts for this plan efore the computer automatically read e applicable power demand requirement ser inactivity in which the computer a nand requirement than sleep mode (in m sleep mode is set to activate after use otential of power management functional Based on user manual the power management functionality: Based on user manual :— test voltage in V and frequency in Hz ormation and documentation on the instru- coltage in V and frequency in Hz: 230V monic distortion of the electricity supply system Range Used or ****** 1~300VAC;1~550Hz; 1000VA 1~500V;0~20A	ches sleep mode, or another ts for sleep mode (in minutes): automatically reaches a power ninutes): er inactivity (in minutes): lity: z, — total harmonic distortion of rumentation, set-up and circuits //50Hz m: ≦2% Make and Model** NF; EC1000S YOKOGAWA; WT310	NA	

Additional Notebook Battery Information:							
	Battery[ies] not user replaceable	Battery[ies] user replaceable	n/a				
	The battery[ies] in this product cannot be easily replaced by users themselves. 1)						
Internal/built-in Battery							
External/detachable Battery							
Bios Backup Battery							
Other:							
Additional information							

1)
The battery[ies] in this product cannot be easily replaced by users themselves.

Акумулаторната[ите] батерия[и] в този продукт не може да се замени[ят] лесно от самите потребители.

Las baterías de este producto no pueden ser sustituidas fácilmente por los propios usuarios. Výměnu baterie/baterií v tomto výrobku by neměli provádět sami uživatelé.

Brugeren kan ikke uden videre udskifte batteriet/batterierne i dette produkt.

Der Akku/die Akkus dieses Produkts kann/können nicht ohne weiteres vom Benutzer selbst ausgetauscht werden. Kasutajad ei saa selle toote akut/akusid ise hõlpsasti asendada.

Η μπαταρία[-ες] στο προϊόν αυτό δεν μπορούν να αντικατασταθούν εύκολα από τους ίδιους τους χρήστες

La/les batterie(s présente(s) dans ce produit ne peuvent être facilement remplacée(s) par les utilisateurs eux-mêmes. Korisnik ne može lako zamijeniti Bateriju sam u ovom proizvodu.

Korisiik ne nioże tako zamijeniu bateriju sam u ovom proizvodu.

La batteria/le batterie in questo prodotto non può/possono essere facilmente sostituita/e dall'utente.
Lietotāji paši nevar nomainīt šā ražojuma akumulatoru(-us).

Šio gaminio baterijos [bateriju] pats vartotojas negali lengvai pakeisti.

A termék akkumulatorat/akkumulatorat/a a felhasználó nem tudja egysdül egyszerűen kicserélni.

Il-batterija/batteriji f'dan il-prodott ma tistax/jistgħux tiġi/jiġu sostitwita/i mill-utenti stess. Batteriet [ene] i dette produktet kan ikke lett erstattes av brukerne selv.

De batterij(en) in dit product is (zijn) door de gebruiker niet gemakkelijk vervangbaar.

Użytkownik nie może sam w łatwy sposób wymienić baterii w tym produkcie. A ou as baterias deste produto não podem ser facilmente substituídas pelos próprios utilizadores.

Bateria (bateriile) din acest produs nu poate (pot) fi ușor înlocuită (înlocuite) de utilizatorii înșiși.

Batériu(-ie) v tomto výrobku nemôže vymieňať používateľ. Baterij/baterije v tem izdelku uporabniki sami ne morejo zlahka zamenjati.

Tämän tuotteen akku [akut] ei[vät] ole helposti käyttäjän vaihdettavissa.

Det är inte enkelt för kunden att själv byta ut batteriet/batterierna. Bu üründeki batarya(lar) kullanıcılar tarafından kolaylıkla değiştirilemez.