

Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lenovo	Logo
Company name *	Lenovo	
Contact information *	Lenovo Global Environmental Affairs	
	Alvin L Carter	-
	1009 Think Place	lenovo
	Building 2 / 5J3	
	Morrisville, North Carolina 27560	
	alcarter@lenovo.com	
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment	t.html
Additional information		

	The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.							
Type of product *	Notebook PC							
Commercial name *	Lenovo IdeaPad U430 Touch							
Model number *	20270; 80B3							
Issue date *	2015-01-13							
Intended market *	🛛 Global 🔲 Europe 📃 Asia, Pacific & Japan 🔛 Americas 📃 Other							
Additional information								

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Control F	Requireme	nt met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).	I 🔀	

Model number *	20270; 80B3		
Issue date *	2015-01-13	Logo	lenovo

Product	environmental attributes - Legal requirements	Require	ment	met
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)	I, 🔀		
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.	\boxtimes		
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).	\square		
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).	e 🔀		
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.			\square
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)			\square
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm ² /week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:1998.	\square		
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact): http://www.lenovo.com/social_responsibility/us/en/ThinkGreen_products.html#environment	\boxtimes		
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)			
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)	\boxtimes		
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medical or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*	The product complies with legally required safety standards as specified (see legal reference).	\square		
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference)).		
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).	\square		
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	\boxtimes		
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).			
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).			\mathbf{X}
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and hexavalent chromium by weight of these together.			
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	\square		
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montrea Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.	al 🔀		

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Issue dat Product Item P6 P6.1* P7	environ *=manda	2015-01-13 mental attributes - Market requirements - Environmental conscious d	Logo	lena	vo	
Item P6 P6.1*	*=manda	montal attributos - Markot roquiromonts - Environmontal conscious d				
Item P6 P6.1*	*=manda		esian P	Require	mont	mot
P6 P6.1*		tory to fill in. Additional information regarding each item may be found under P14.	esign i	Yes	No	n.a
		nt information				
P7	Informati	on for recyclers/treatment facilities is available (see legal reference).		\boxtimes		
		nbly, recycling				
P7.1*	Parts that	t have to be treated separately are easily separable		\square		
P7.2*		aterials in covers/housing have no surface coating.		\square		
P7.3*		arts >100g consist of one material or of easily separable materials.		\square		
P7.4*		arts >25g have material codes according to ISO 11469 referring ISO 1043.		\boxtimes		
P7.5	Plastic pa	arts are free from metal inlays or have inlays that can be removed with commonly a	vailable tools.	\boxtimes		
P7.6*	Labels a	e easily separable. (This requirement does not apply to safety/regulatory labels).		\square		
	Product					
P7.7*	Upgradin	g can be done e.g. with processor, memory, cards or drives		\square		
P7.8*	Upgradin	g can be done using commonly available tools		\boxtimes		
P7.9.	Spare pa	rts are available after end of production for: 5 years				
P7.10	Service i	s available after end of production for: 5 years				
		and substance requirements				
P7.11*		cover/housing material type:				
P7.12		ype: PC+ABS-FR(40) Material type: Materia	l type:			
		cable insulation materials of power cables are PVC free.		<u> </u>		╞
P7.13		cable insulation materials of signal cables are PVC free				ᄂ
P7.14		housing plastic parts >25g are free from chlorine and bromine.	1010 0 01 (0			느
P7.15	Note B2)	d circuit boards (without components) >25g are halogen free. as defined in IEC6	1249-2-21. (See			
P7.16	Marking:	tarded plastic parts >25g in covers / housings are marked according ISO 1043-4: <i>FR(40)</i>				
P7.17		l specifications of flame retardants in printed circuit boards >25g (without componer additive) , TBBPA (reactive) , Other; chemical name: , CAS #:	nts):			
	ISO 1043	l specifications of flame retardants in printed circuit boards (without components) >2 -4: <i>Brominated Epoxy Resin See P14</i>	25g according			
P7.18	concentr	etarded plastic parts >25g contain the following flame retardant substances ations above 0.1%:	/preparations in			
	Provide a complete 1. Chemi 2. Chemi	t: No legal limits exist, this is a market requirement. a list of all used flame retardants including MSDS for each flame retardant. The l chemical name, CAS number and supplier. cal name: , CAS #: , Supplier: cal name: , CAS #: , Supplier:	list must contain	I		
	Alt. 2	cal name: , CAS #: , Supplier: I specifications of flame retardants in plastic parts >25g according ISO 1043-4:				
P7.19		arts >25g are free from flame retardant substances/ preparations above 0.1% classi 6, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)	ified as R45,	\square		
P7.20		lastic parts' weight >25g, recycled material content is 0.5%.				
P7.21		lastic parts' weight >25g, biobased material content is 0% .		<u></u>		
P7.22	<u> </u>	rces are free from mercury				
P8	Batteries					
P8.1* P8.2		hemical composition: <i>Lithium Ion/Lithium Manganese Dioxide</i> meet the requirements of the following voluntary program/s: US RBRC				

Annex B of ECMA-370 4th edition, June 2009

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

rroduct environmental attributes - Market requirements (continued) Requirement me Requirement me Requirement me Requirement me Requirement Requirement Requirement Requirement Requirement Requireme	Model number *	2027	0; 80B3						
em Yes No n.a. 9 Energy consumption	Issue date *	2015-01-	-13				Logo	lenov	0
em Yes No n.a. 9 Energy consumption	Product environ	mental at	tributes - Market	requirements (co	ontinued)			Requirem	ont mot
9 Energy consumption 1 For the product the following power levels or energy consumptions are reported: See P14 The product is shipped w/ WOL Enabled. Image: Consumption are reported. See P14 Reference / Standard for energy modes and the power level at 100 v AC Reference / Standard for energy modes and the power level at 115 v AC Reference / Standard for energy modes and the power level at 100 v AC Reference / Standard for energy modes and the power level at 100 v AC Reference / Standard for energy modes and the power level at 100 v AC Reference / Standard for energy star V5 registration(P _{mod}) Ideg (53) - WOL Enabled 0.42 W 0.42 W 0.44 W Use for Energy Star V5 registration(P _{mod}) ideg (53) - WOL Disabled 0.42 W 0.41 W 0.23 W Use for Energy Star V5 registration(P _{mod}) ideg (53) - WOL Disabled 0.21 W 0.21 W 0.23 W Use for EuP Image: power level at 0.74 W (55) - WOL Disabled 0.27 W 0.104 W Image: power level at 0.071 W 0.104 W Image: power level at 0.14 W Image: power level at 0.071 W 0.104 W External power supply / proced meast form the valuation is provided with the product. Image: power level at 0.14 W Image: powe	Item	incintar at		requirements (et	Jinnacaj				
1 For the product the following power levels or energy consumptions are reported. See P14		consump	tion						
100 VAC 115 VAC 230 VAC and test method * Image: Construction of the second	9.1 For the	product the	e following power lev		mptions are reporte	ed: See P14			
atetagory B die State - WOL Enabled 4.1W 4.1W 4.1 W Use for Energy Star V5 registration(P _{sed}) ilee p(S3) - WOL Enabled 0.42 W 0.42 W 0.4W Use for Energy Star V5 registration(P _{sed}) ilee p(S3) - WOL Disabled 0.21 W 0.21 W 0.23 W Use for Energy Star V5 registration(P _{sed}) iff (S5) - WOL Disabled 0.21 W 0.21 W 0.23 W Use for Eurp Image playsed PS No-load 0.071 W 0.74 W 0.104 W Use for Eurp Image playsed	Energy mode *							rd for energy mod	des
Ide State - WOL Enabled 4.1W 4.1W Use for Energy Star V5 registration(P _{any}) Ideop (S3) - WOL Enabled 0.42 W 0.44W Use for Energy Star V5 registration(P _{any}) Ideop (S3) - WOL Disabled 0.21 W 0.21 W 0.23 W Use for Energy Star V5 registration(P _{any}) If (S5) - WOL Disabled 0.21 W 0.21 W 0.23 W Use for Energy Star V5 registration(P _{any}) If (S5) - WOL Disabled 0.71 W 0.74 W 0.23 W Use for EurP Image plugged in the value Inside power supply / harger plugged in the value 0.71 W 0.74 W 0.104 W Image plugged in the value	Peak (On-max)		65W	65 W	65 W	Full load			
ieep (S3) - WOL Enabled 0.42 W 0.44 W Use for Energy Star V5 registration(P _{swp}) ieep (S3) - WOL Disabled 0.41 W 0.4 W 0.44 W Reference Uff (S5) - WOL Enabled 0.21 W 0.21 W 0.23 W Use for Energy Star V5 registration(P _{swp}) Uff (S5) - WOL Disabled 0.21 W 0.21 W 0.23 W Use for Energy Star V5 registration(P _{swp}) PS No-load 0.071 W 0.74 W 0.104 W Ise for EuP Image Poly (P _{swp}) EXternal power supply / harger plugged in the wall utlet but disconcted from the product.) 0.071 W 0.74 W 0.104 W Image Poly (P _{swp}) Image Poly	Category B								
Heep (S3) - WOL Disabled 0.4 W 0.4 W 0.4 W Reference Iff (S5) - WOL Enabled 0.21 W 0.21 W 0.23 W Use for Energy Star V5 registration(P _{xd}) PS No-load 0.71 W 0.74 W 0.23 W Use for EuP Image: Comparison of the comparison o	Idle State - WOL E	nabled	4.1 W	4.1W	4.1 W	Use for Ene	ergy Star	V5 registration(P _{id}	1e)
http://signature 0.21 W 0.21 W 0.23 W Use for Energy Star V5 registration(P _{end}) http://signature 0.21 W 0.21 W 0.23 W Use for EuP Image: Construction (P _{end}) PS No-load 0.071 W 0.74 W 0.104 W Image: Construction (P _{end}) Image: Construct	Sleep (S3) - WOL I	Enabled	0.42 W	0.42 W	0.44 W	Use for Ene	ergy Star	V5 registration(P _{sk}	eep)
Iff (S5) - WOL Disabled 0.21W 0.21 W 0.23 W Use for EuP PS No-load 0.071 W 0.74 W 0.104 W PS No-load 0.071 W 0.74 W 0.104 W EC ypical Energy Consumption kWh/week kWh/week kWh/week FEC ypical Energy Consumption 12.246 kWh/year 12.246 kWh/year 12.369 kWh/year Errcc = (8760/1000) × (Port × 0.6 + P_streep × Long) Innual Energy Consumption 12.246 kWh/year 12.246 kWh/year 12.369 kWh/year Errcc = (8760/1000) × (Port × 0.6 + P_streep × Long) Innual Energy Consumption 12.246 kWh/year 12.246 kWh/year 12.369 kWh/year Errcc = (8760/1000) × (Port × 0.6 + P_streep × Long) Innual Energy Consumption 12.246 kWh/year 12.246 kWh/year 12.369 kWh/year Errcc = (8760/1000) × (Port × 0.6 + P_streep × Long) Intege Vision 12.246 kWh/year 12.246 kWh/year 12.246 kWh/year Errcc = (8760/1000) × (Port × 0.6 + P_streep × Long) Integer Vision 12.246 kWh/year 12.246 kWh/year 12.369 kWh/year Errcc = (8760/1000) × (Port × 0.6 + P_streep × Long) Integer Vision 12.246 kWh/year 12.246 kWh/year 12.246 kWh/year 12.246 kWh/year Errcc = (8760	Sleep (S3) - WOL I	Disabled	0.4 W	0.4 W	0.4 W	Reference			
PS No-load 0.071 W 0.74 W 0.104 W External power supply / harger plugged in the wall utilet but disconnected from the product.) 0.071 W 0.74 W 0.104 W EC ypical Energy Consumption kWh/week kWh/week kWh/week kWh/week TEC * unnual Energy Consumption 12.246 kWh/year 12.246 kWh/year 12.369 kWh/year Erec = (8760/1000) x (Port x 0.6 + Power x 0.6) Port: Off Mode(55) - WOL Enabled; Poince; Sleep Mode(S3) - WOL Enabled; Poince X 0.3) Port: Off Mode(55) - WOL Enabled; Poince; Sleep Mode(S3) - WOL Enabled; Poince X 0.3) Images per minute Hisplay resolution : 1280*300 Megapixels Images per minute Images per minute Images per minute 9.2* Information about the energy save function is provided with the product. Images per minute Images per minute Images per minute 9.2* Information about the energy save function is provided with the product. Images per terret start of External Power Supplies Eligibility Criteria Version 2 Images per terret searts; Energy Star for External Power Supplies Eligibility Criteria Version 2 Images per terret searts; Energy Start of External Power Supplies Eligibility Criteria Version 2 Images per terret searts; Energy Start of External Power Supplies Eligibility Criteria Version 2 Images per terret searts; Energy Start of External Power Supplies Eligibility Criteria Version 2 Im	Off (S5) - WOL End	abled	0.21 W	0.21 W	0.23 W	Use for Ene	ergy Star	V5 registration(Pof	"
External power supply / harger plugged in the wall utter but disconnected from the product.) Image plugged in the wall utter but disconnected from the product.) EC multiple but disconnected from the product.) Image plugged in the wall utter but disconnected from the product.) Image plugged in the wall utter but disconnected from the product.) EC multiple plugged in the wall utter but disconnected from the product.) Image plugged in the wall utter but disconnected from the product.) Image plugged in the wall utter but disconnected from the plugged	Off (S5) - WOL Dis	abled	0.21W	0.21 W	0.23 W	Use for Eul	>		
ypical Energy Consumption kWh/week kWh/week kWh/week kWh/week TTEC * 12.246 kWh/year 12.246 kWh/year 12.369 kWh/year Ercc = (8760/1000) x (P_{off} x 0.6 + P_{alleep} x 0.1 + P_{ulice} x 0.3) P_off: Off Mode(S5) - WOL Enabled; P_alsep: Sleep Mode(S3) - WOL Enabled; P_{odip: Idle State - WOL Enabled Pisplay resolution : 1280*800 Megapixels Images per minute Port: Off Mode(S5) - WOL Enabled; P_alsep: Sleep Mode(S3) - WOL Enabled; P_odip: Idle State - WOL Enabled Port: Off Mode(S5) - WOL Enabled; P_alsep: Sleep Mode(S3) - WOL Enabled; P_odip: Idle State - WOL Enabled Port: Off Mode(S5) - WOL Enabled; P_alsep: Sleep Mode(S3) - WOL Enabled; P_odip: Idle State - WOL Enabled Port: Specify: Images per minute Images per minute Port: Information about the energy save function is provided with the product. Images per minute 9.2* Information about the energy requirements of the following voluntary program/s: ENERGY STAR® version: Version 5.0 dated July 1, 2009 Product category: A Others specify: Energy Star for External Power Supplies Eligibility Criteria Version 2 Images per minute 10 Emissions Declared A-weighted sound power Sound pressure level L_pAm (dB) P_operator position is provided with the product is not operating in the position is position is provided is ound power Images per since is andi	charger plugged in	the wall	0.071 W	0.74 W	0.104 W				
Impact Service 0.1 + P _{late} x 0.3) Port: Off Mode(S5) - WOL Enabled; P _{attep} : Sleep Mode(S3) - WOL Enabled; P _{atte} : Idle State - WOL Enabled Port: Off Mode(S5) - WOL Enabled; P _{attep} : Sleep Mode(S3) - WOL Enabled; P _{atte} : Idle State - WOL Enabled Pisplay resolution : 1280*800 Megapixels Frint Speed : Images per minute Information about the energy save mode: 25 minutes Images per minute 9.2* Information about the energy requirements of the following voluntary program/s: ENERGY STAR® version: Version 5.0 dated July 1, 2009 Product category: A Others specify: Energy Star for External Power Supplies Eligibility Criteria Version 2 Images per minute 10.1 Mode Mode description Declared A-weighted sound pressure level L _{pAm} (dB) Operator position Declared A-weighted sound pressure level L _{pAm} (dB) Operator positions Idle * HDD: Idle * 3.06 22 Operation * HDD: Operating * 3.4 25.3 Other mode Images per mode Images per mode Images per mode	TEC Typical Energy Con	sumption	kWh/week	kWh/week	kWh/week				
isplay resolution : 1280*800 Megapixels Images per minute irrint Speed Images per minute Images per minute information about the energy save mode: 25 minutes Images per minute Images per minute 9.2* Information about the energy save function is provided with the product. Images per minute Images per minute 9.3* The product meets the energy requirements of the following voluntary program/s: ENERGY STAR® version: Version 5.0 dated July 1, 2009 Product category: A content of the product of the product category: A content of the product of the product of the product category: A content of the product of the product category: A content of the product of the product of the product category: A content of the product of the pro	ETEC * Annual Energy Con	sumption	12.246 kWh/year	12.246 kWh/year	12.369 kWh/year			$x (P_{off} \times 0.6 + P_{slee})$	<i>p</i> x
images per minute Images per minute information about the energy save mode: 25 minutes Images per minute 9.2* Information about the energy requirements of the following voluntary program/s: ENERGY STAR® version: Version 5.0 dated July 1, 2009 Product category: A Others specify: Energy Star for External Power Supplies Eligibility Criteria Version 2 10 Emissions Noise emission – Declared according to ISO 9296 110.1 Mode Mode Mode description Declared A-weighted sound power Declared A-weighted sound pressure level L _p Am (dB) Idle * HDD: Idle * 3.06 Operation * 3.4 25.3 Other mode Measured according to: X ISO7779 ECMA-74 Other (only if not covered by ECMA-74 with L _{pAm} measurement distance m)			Poff: Off Mode(S5) - V	NOL Enabled; P _{sleep} : S	Sleep Mode(S3) - WO	L Enabled; Pidl	e: Idle Sta	te - WOL Enabled	I
lefault time to enter energy save mode: 25 minutes Important in about the energy save function is provided with the product. 9.2* Information about the energy requirements of the following voluntary program/s: ENERGY STAR® version: Version 5.0 dated July 1, 2009 Product category: A Others specify: Energy Star for External Power Supplies Eligibility Criteria Version 2 10 Emissions Noise emission – Declared according to ISO 9296 10.1 Mode Mode Mode description Declared sound power Declared A-weighted sound power Idle * HDD: Idle * HDD: Idle * 3.06 22 Operation Other mode Idle Measured according to: ISO7779 ECMA-74 Other (only if not covered by ECMA-74 with LpAm measurement distance m)	Display resolution	: 1280*80	0 Megapixels						
befault time to enter energy save mode: 25 minutes	Print Speed	:	Images per minu	ite					
9.3* The product meets the energy requirements of the following voluntary program/s: ENERGY STAR® version: Version 5.0 dated July 1, 2009 Product category: A Other specify: Energy Star for External Power Supplies Eligibility Criteria Version 2 10 Emissions Noise emission – Declared according to ISO 9296 110.1 Mode description Declared A-weighted sound power Declared A-weighted sound power Ievel L _{WAd} (B) Operator position Desktop ion Operator position Idle * HDD: Idle Operation * 3.4 Operation ISO7779 ECMA-74 Other (only if not covered by ECMA-74 with L _{pAm} measurement distance m)	Default time to ente	r energy sa	ave mode: 25 minute:	S					
ENERGY STAR® version: Version 5.0 dated July 1, 2009 Product category: A Others specify: Energy Star for External Power Supplies Eligibility Criteria Version 2 10 Emissions Noise emission – Declared according to ISO 9296 10.1 Mode Mode Mode description Declared A-weighted sound power Declared A-weighted sound pressure level L_{pAm} (dB) Desktop in the standard	P9.2* Informa	tion about f	the energy save fund	tion is provided with	the product.				
Noise emission – Declared according to ISO 9296 '10.1 Mode Mode description Declared A-weighted sound power level L _{WAd} (B) Declared A-weighted sound pressure level L _{pAm} (dB) Idle * HDD: Idle * 3.06 22 Operation * HDD: Operating * 3.4 25.3 Other mode ISO7779 ECMA-74 Measured according to: ISO7779 ECMA-74	ENERG Others	BY STAR® specify: <mark>En</mark>	version: Version 5.0) dated July 1, 2009	Product category:	Α			
Mode Mode description Declared A-weighted sound power level L_{WAd} (B) Declared A-weighted sound pressure level L_{pAm} (dB) Idle * HDD: Idle * 3.06 22 Operation * HDD: Operating * 3.4 25.3 Other mode ISO7779 ECMA-74 Other (only if not covered by ECMA-74 with LpAm measurement distance m)			Declared according	to ISO 9296					
Idle * HDD: Idle * 3.06 22			9		A-weighted sound power	sound p Operator posi Desi	oressure I ition 🔀 ktop 🔀	level $L_{p Am}$ (dB) Bystander position	
Operation * HDD: Operating * 3.4 25.3 Other mode						or Desk :		operator attend	
Other mode									[]
Measured according to: ISO7779 ECMA-74 Other (only if not covered by ECMA-74 with L _{pAm} measurement distance m)			טעה: Operating		3.4		25).0	-
		1			ed by ECMA 74 with	the monor	rement di	istance m)	
	P10.2 The pro	duct mosts					rement d		

Model nu	mber *	20270; 8	0B3								
Issue dat	е *	2015-01-13					Logo	lei	101	VO.	
Product	environ	mental attribute	es - Market r	equirements (continued)			Req	uirer	nent	met
Item								١	′es	No	n.a.
	Chemic	al emissions from	m printing pro	oducts							
P10.3*	Test per	formed according	to ECMA-328	(ISO/IEC 28360)) standard 🔲,	other specify:					\boxtimes
P10.4	Typical	emission rate (prir	nt phase) is (m	g/h):							\boxtimes
			Dzone	Styrene	Benzene	TVOC					
P10.5		al emission require		-	ry program/s	are met for					\boxtimes
			Ozone	Styrene	Benze	ene 🔄	TVOC				
		magnetic emission									
P10.6	Computer display meets the requirement for low frequency electromagnetic fields of the following voluntary program/s: <i>MPR-II</i>								\ge		
P11		nable materials f									
P11.1*	A Safety	/ Data Sheet (SDS	S) is available f	for the ink/toner p	preparation, eve	n if not legally req	uired (see P4	.3).			\boxtimes
P11.2*	Paper o EN1228		onsumer recycl	led fibers can b	e used, provide	ed that it meets t	he requireme	ents of			\square
P11.3*	2-sided	(duplex) printing/c	copying is an in	tegrated product	function.						\boxtimes
P12	Ergono	mics for comput	ing products								
P12.1*	The disp	play meets the erg	gonomic require	ements of ISO 92	241-307 for visu	al display technolo	gies.		X		
P12.2*	The phy	sical input device	meets the requ	uirements of ISO	9995 and ISO	9241-410.			\mathbf{X}		
P13	Packag	ing and docume	ntation								
P13.1*	Product	packaging materi packaging materi packaging materi	ial type(s): Poly	yethylene Cush	ions weight (k						
P13.2*	Product	plastic packaging	is free from P	VC.					X		
P13.3*		media for user an iic 🔀, Paper 🔀,		imentation (tick b	oox):						
P13.4*	For pap		ict documentati	on, please speci	fy contained pe	rcentage of post-co	onsumer recy	/cled			
P14	Additio	nal information (See Note B4)								
	informat knowled	ion contained in the lge available at the d here is approxim	his document. e time of comp	All information pr letion, and suppl	ovided by supp ier shall have n	warranties whethe lier in this docume o obligation to upd hly. See a Lenovo	nt is provided ate such info	d based on rmation. Th	supp ne info	lier's ormati	
P7.17	Produc	t does not contai	in free TBBPA	in printed circu	it boards(with	out components)	>25g.				
P9						ktop, Notebook, e sert appropriate v		atest infor	mati	on:	

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19

Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	Lenovo IdeaPad U430 Touch	Logo
Model Number	20270; 80B3	_
Issue Date	2015-01-13	lenovo
Additional information		

P7.1.1 F	Product environmental attributes	
(d)	year of manufacture: 2013	
(e)	E TEC value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete graphics care disabled and if the system is tested with switchable graphics mode with UMA driving the display:	ds (dGfx) are
	Category (according to ErP Lot 3): A Etec: 12.37	
(f)	E TEC value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete graphics card enabled:	ls (dGfx) are
	Category (according to ErP Lot 3): NA Etec: NA	
(g)	idle state power demand (Watts);	4.1
(h)	sleep mode power demand (Watts);	0.44
(i)	sleep mode with WOL enabled power demand (Watts) (where enabled);	0.4
(j)	off mode power demand (Watts);	0.23
(k)	off mode with WOL enabled power demand (Watts) (where enabled);	0.23
(I)	internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable):	
	10% 20% 50% 100% Average	
(m)	external power supply efficiency (if applicable):	
	Average*: 45W:87.58%,87.60%,88.32%; 65W:89.18%,89.04%,87.37%	
	*internal note: show values for all available external power supplies	
(0)	the minimum number of loading cycles that the batteries can withstand (applies only to notebook computers):	300cycles
(p-1)	the measurement methodology used to determine information mentioned in points (I) – internal PSU efficiency:	
	NA	
(p-2)	the measurement methodology used to determine information mentioned in points (m) – external PSU efficiency:	
	Energy-star requirement	

(p-3) the measu batteries:	irement methodolog		to determine information mentioned in points (o) - loadingcycles	
		IEC	61960 measurement methodology	
			determine information mentioned in maximum, idle, sleep, off mode roduct IT Eco Declaration:	
			Energy-star requirement	
(q) sequence of	of steps for achieving	g a stabl	e condition with respect to power demand::	
			Based on user manual	
(r) description	of how sleep and/or	off mod	e was selected or programmed:	
			Based on user manual	
(s) sequence of off mode:	of events required to	reach th	ne mode where the equipment automatically changes to sleep and/or	
			Based on user manual	
			efore the computer automatically reaches sleep mode, or another pplicable power demand requirements for sleep mode (in minutes):	25
			er inactivity in which the computer automatically reaches a demand requirement than sleep mode (in minutes):	NA
(v) the length	of time before the	display	sleep mode is set to activate after user inactivity (in minutes):	10
(w) information	on the energy-savir	ng poten	tial of power management functionality:	
			Based on user manual	
(x) user inform	nation on how to ena	ble the p	oower management functionality:	
			Based on user manual	
	supply system, — inf		est voltage in V and frequency in Hz, — total harmonic distortion of the and documentation on the instrumentation, set-up and circuits used	
	ar testing.	230V/5	0Hz, Total Harmonic Distortion <2 %	
Addition Notebook Ba		nla	This notebook computer is operated by battery/ies that cannot be accessed	and replaced
Yes (Battery not user	No (Battery user	n/a	by a non-professional user.	
replaceable)	replaceable)		The battery[ies] in this product cannot be easily replace themselves	d by users
Additional informatio	n			

Г