

## Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lenovo	Logo
Company name *	Lenovo	
Contact information *	Lenovo Global Environmental Affairs Alvin L Carter 1009 Think Place Building 2 / 5F1 Morrisville, North Carolina 27560 alcarter@lenovo.com	Lenovo
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environmen	t.html
Additional information	The latest version of this document can be found at http://www.lenovo.com/social_responsibility/us/en/datasheets	notebooks.html

	ased on product specification or test results based obtained from sample testing), that the product ts given in this declaration.
Type of product *	Notebook Computer
Commercial name *	Lenovo IdeaPad 700-17ISK
Model number *	80RV
Issue date *	2015-12-29
Intended market *	🔀 Global 📃 Europe 📃 Asia, Pacific & Japan 📃 Americas 📃 Other
Additional information	

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Control	Requireme	ent met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	$\boxtimes$	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🔀	

<b>BORV</b>	
Issue date * 2015-12-29 Logo	Lenovo

Product	luct environmental attributes - Legal requirements F						
Item		Yes	No	n.a.			
P1	Hazardous substances and preparations						
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)						
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.	$\boxtimes$					
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.						
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).	$\square$					
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).	$\boxtimes$					
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.			$\boxtimes$			
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)			$\square$			
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference). Comment: Legal reference has no maximum concentration values.			$\boxtimes$			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm <sup>2</sup> /week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:1998.						
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact): http://www.lenovo.com/social_responsibility/us/en/materials.html						
P2	Batteries						
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)						
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)						
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medic or data integrity reasons do not have to be "easily removable". (See legal reference)	e 🔀					
P3	Safety, EMC connection to the telephone network and labeling						
P3.1*	The product complies with legally required safety standards as specified (see legal reference).	$\square$					
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).						
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).	s 🔀					
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	$\square$					
P4	Consumable materials						
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).			$\boxtimes$			
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).			X			
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).			$\boxtimes$			
P5	Product packaging						
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium an hexavalent chromium by weight of these together.	id 🔀					
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	$\boxtimes$					
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montre Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.	al 🔀					

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Pre-treatment information       Image: Construction of recyclers/treatment facilities is available (see legal reference).       Image: Construction of the cyclers/treatment facilities is available (see legal reference).         PF1       Image: Construction of the cyclers/treatment facilities is available (see legal reference).       Image: Construction of the cyclers/treatment facilities is available (see legal reference).         P1       Parts that have to be treated separately are easily separable materials.       Image: Construction of the cyclers/treatment facilities is available (see legal reference).       Image: Construction of the cyclers/treatment facilities is available (see legal reference).         P1       Parts that have to be treated separately are easily separable materials.       Image: Construction of the cyclers/treatment facilities is available (see legal reference).       Image: Construction of the cyclers/treatment facilities is available (see legal reference).         P1       Parts the available cyclers and the cyclers of the cyclers o	Model n	umber *	80RV			
tem       *mandatory to fill in Additional information regarding each item may be found under P14.       Yes       No       na         P6       Treatment Information       Image: Strength S	Issue da	nte *	2015-12-29 Logo	Len	ovo	
tem       *mandatory to fill in Additional information regarding each item may be found under P14.       Yes       No       na         P6       Treatment Information       Image: Strength S	Produc	t environ	mental attributes - Market requirements - Environmental conscious design	Require	ment	met
P6       Treatment information         P61       Information for recyclera/treatment facilities is available (see legal reference).       Image: Comparison of the construction of the consthe consthe construction of the construction of the con	Item					n.a.
Product         Product <t< td=""><td>P6</td><td></td><td></td><td></td><td></td><td></td></t<>	P6					
Disa         Disa           P11         Pats that have to be treated separately are easily separable         Image: Control of Contro	P6.1*	Informati	on for recyclers/treatment facilities is available (see legal reference).	$\boxtimes$		
P7.1       Parts that have to be treated separately are easily separable       □         P7.2       Plastic materials in covers/housing have no surface costing.       □         P7.3       Plastic parts >100g consist of one material or of easily separable materials.       □         P7.3       Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.       □         P7.5       Plastic parts >25g have material and that can be removed with commonly available tools.       □         P7.6       Labels are easily separable. (This requirement does not apply to safety/regulatory labels).       □         P7.7       Upgrading can be done e.g. with processor, memory, cards or drives       □         P7.8       Spare parts are available after end of production for: 5 years       □         P7.10       Pograding can be done e.g. with processor, memory, cards or drives       □       □         P7.10       Pograding can be done using commonly available tools       □       □         P7.11       Poduct over/housing plasma type:       □       □         P7.12       Psectric acable insulation materials of power cobles are PVC free.       □       □         P7.14       Picotuc over/housing plasma free from chlorine and bromine.       □       □         P7.14       Picotuc boards (without components) >25g are halogen free, as defined in IEC61249-2-21. (See Note B2)	P7	•				
P1.2'       Plastic materials in covers/housing have no surface coating.       Image: Construct on the material or of easily separable materials.       Image: Construct on the material control of easily separable materials.         P1.4'       Plastic parts 3:26 have material codes according to ISO 11469 referring ISO 1043.       Image: Construct on the material code searcording to ISO 11469 referring ISO 1043.         P7.6'       Labels are easily separable. (This requirement does not apply to safety/regulatory labels).       Image: Construct on the code code on the code on the code on the code o	P7 1*					
P7.3       Plastic parts >100g consist of one material or of easily separable materials.       Image: Constraint of the image: Constraint on the im						-  -
P7.4'       Plastic parts 25g have material codes according to ISO 11469 referring ISO 1043.       Image: Content of the image:			5			-  -
P7.5       Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.       Image: Commonly available tools.         P7.6       Labels are easily separable. (This requirement does not apply to safety/regulatory labels).       Image: Commonly available tools.         P7.7       Upgrading can be done e.g. with processor, memory, cards or drives       Image: Commonly available tools         P7.8       Upgrading can be done e.g. with processor, memory, cards or drives       Image: Commonly available tools         P7.9       Spare parts are available after end of production for: 5 years       Image: Commonly available tools         P7.10       Service is available after end of production for: 5 years       Image: Commonly available tools         P7.11       Product cover/housing material type:       Image: Commonly available tools         P7.11       Product cover/housing material type:       Image: Commonly available tools         P7.12       Electrical cable insulation materials of power cables are PVC free.       Image: Commonly available tools         P7.14       All cover/housing plastic parts >25g are free from choine and bromine.       Image: Commonly available tools         P7.14       All cover/housing blastic parts >25g in covers / housings are marked according ISO 1043-4:       Image: Commonly available tools         P7.17       Alt 1       Chemical apecifications of flame retardants in printed circuit boards (without components):	-				<u> </u>	<u> </u>
P7.6'       Labels are easily separable. (This requirement does not apply to safety/regulatory labels).       □         Product lifetime       □         P7.0'       Upgrading can be done e.g. with processor, memory, cards or drives       □         P7.0'       Upgrading can be done e.g. with processor, memory, cards or drives       □         P7.0'       Upgrading can be done e.g. with processor, memory, cards or drives       □         P7.0'       Upgrading can be done using commonly available tools       ∞         P7.10'       Sparce is available after end of production for: 5 years       ∞         Material and substance requirements       ∞       ∞         P7.11'       Product cover/housing material type:       Material type: PC+ABS-FR(40)       Material type:         P7.13       Electrical cable insulation materials of signal cables are PVC free.       ∞       ○         P7.14       All cover/housing plastic parts >25g are free from chlorine and bromine.       ∞       ○         P7.14       All cover/housing blastic parts >25g are free trom chlorine and bromine.       ∞       ○         P7.15       All rined circuit boards (without components) >25g are halogen free. as defined in IEC61249-2:1. (See Note B2)       ○       ○         P7.16       Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:       ∞       ○						<u> </u>
Product lifetime         P7.7'       Upgrading can be done e.g. with processor, memory, cards or drives         P7.8'       Upgrading can be done using commonly available tools         P7.9'       Upgrading can be done using commonly available tools         P7.9'       Spare parts are available after end of production for: 5 years         Material and substance requirements         P7.11       Product cover/housing material type:         Material type: PC-485-FR400         Material type: C-485-FR400         P7.12       Electrical cable insulation materials of power cables are PVC free.         P7.13       Electrical cable insulation materials of signal cables are PVC free.         P7.14       All cover/housing plastic parts >25g are free from chlorine and bromine.         P7.15       All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2:1. (See Note B2)         P7.16       Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:         Material specifications of flame retardants in printed circuit boards >25g (without components):         TAL 1       Chemical specifications of flame retardants in printed circuit boards (without components):         Chemical appecifications of flame retardants in printed circuit boards (without components):       C         Chemical appecifications of flame retardants in printed circuit boards (without components):       C						<u> </u>
P7.7*       Upgrading can be done e.g. with processor, memory, cards or drives       □         P7.8*       Upgrading can be done using commonly available tools       □         P7.9       Spare parts are available after end of production for: 5 years       □         P7.10       Service is available after end of production for: 5 years       □         P7.110       Product cover/housing material type:       Material type:         P7.12       Electrical cable insulation materials of signal cables are PVC free.       □         P7.13       Electrical cable insulation materials of signal cables are PVC free.       □         P7.14       All cover/housing plastic parts >25g are free from chlorine and bromine.       □         P7.14       All cover/housing plastic parts >25g in covers / housings are marked according ISO 1043-4:       □         Matrixij: FR400       P7.14       IC during the during the processor / housings are marked according ISO 1043-4:       □         P7.14       It. 1       Chemical specifications of flame retardants in printed circuit boards >25g (without components):       □         P7.18       Alt. 2       Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:       □         ISO 1043-4:       Brominated Epoxy Resin See P14       □       □         P7.18       Alt. 1       Comment: No legal li	P7.6*					
P7.8*       Upgrading can be done using commonly available tools       □         P7.9       Spare parts are available after end of production for: 5 years         Material and substance requirements       □         P7.10       Service is available after end of production for: 5 years         Material and substance requirements       □         P7.11       Product cover/housing materials of power cables are PVC free.       ⊠         P7.12       Electrical cable insulation materials of power cables are PVC free       ⊠         P7.13       Electrical cable insulation materials of power cables are PVC free       ⊠         P7.14       All cover/housing plastic parts >25g are free from chlorine and bromine.       ⊠       □         P7.16       Flarm retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:       ⊠       □         P7.17       Alt. 1       Chemical specifications of flame retardants in printed circuit boards >25g (without components):       ⊠       □         P7.17       Alt. 1       Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:       ☑       □         D50 1043-4:       Erominated Epoxy Resin See P14       □       □       □         P7.18       Alt. 1       Flarm eretarded plastic parts >25g contain the following flame retardant. Substances/preparations in concentrat	D7 7					
P7.9.       Spare parts are available after end of production for: 5 years         P7.10       Service is available after end of production for: 5 years         Material and substance requirements         P7.11       Product cover/housing material type: Material type: PC+ABS-FR(40)         P7.11       Product cover/housing materials of power cables are PVC free.         P7.12       Electrical cable insulation materials of signal cables are PVC free         P7.13       All printed circuit boards (without components) >25g are free from chlorine and bromine.         P7.16       Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR(40)         P7.17       Att. 1         Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive)       Image: TBBPA (reactive)         P7.17       Att. 1         Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive)       Image: TBBPA (reactive)         P7.18       Alt. 1       Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:       Image: TBBPA (reactive)         P7.17       Att. 1       Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%:       Image: TBBPA (reactive)         P7.18       Alt. 2       Chemical name: Act/pointrile-But						<u> </u>
P7.10       Service is available after end of production for: 5 years         Material and substance requirements         P7.111       Product cover/housing materials of signal type:         Material type: PC+ABS-FR(40)       Material type:         P7.12       Electrical cable insulation materials of signal cables are PVC free       □         P7.13       All cover/housing plastic parts >25g are free from chlorine and bromine.       □         P7.14       All cover/housing plastic parts >25g in covers / housings are marked according ISO 1043-4:       □         Material specifications of flame retardants in printed circuit boards >25g (without components):       □       □         P7.17       Alt. 1       Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:       □         P7.18       Alt. 2       Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:       □         P7.18       Alt. 1       Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:       □         P7.18       Alt. 1       Chemical name: Kalty active is is a market requirement.	-	Upgradir	ig can be done using commonly available tools	$\square$		
Material and substance requirements         P7.11         P7.12         Electrical cable insulation materials of power cables are PVC free.         P7.13         Electrical cable insulation materials of signal cables are PVC free         P7.14         All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2·21. (See         P7.15         All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2·21. (See         Note B2)         P7.16         P7.17         All. printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2·21. (See         Marking: FR(40)         P7.17         P7.18         Alt. 1         Chemical specifications of flame retardants in printed circuit boards >25g (without components):         TBBPA (additive)         TBBPA (additive)         P7.18         Alt. 2         Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:         Browninated Epoxy Resin See P14         P7.18         P7.18         Alt. 1         Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%:         Comment: No lega		Spare pa	arts are available after end of production for: 5 years	_		
P7.11       Product cover/housing material type: Material type: PC+ABS-FR(40)       Material type: Material type: PC+ABS-FR(40)         P7.12       Electrical cable insulation materials of power cables are PVC free       Image: Cover/housing plastic parts >25g are free from chlorine and bromine.         P7.13       All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2:21. (See       Image: Cover/housing plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR(40)         P7.16       Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR(40)       Image: Cover/housing ISO 1043-4: Marking: FR(40)         P7.17       Alt. 1       Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) Image: TBBPA (reactive) Image: Covers / housings are marked according ISO 1043-4: Marking: FR(40)       Image: Covers / housings are marked according ISO 1043-4: Marking: FR(40)         P7.17       Alt. 1       Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: BISO 1043-4: Brominated Epoxy Resin See P14         P7.18       Alt. 1       Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. Provide a laused flame retardants including MSDS for each flame retardant. The list must contain complete chemical name: Acrylonitrile-Butadiene-Styrene-Copolymer, CAS #: 903-56-9, Supplier: Mitsubishi         1. Chemical name: Acrylonitri	P7.10	Service i	s available after end of production for: 5 years			
Material type:       Material type:       Material type:         P7.12       Electrical cable insulation materials of power cables are PVC free.       X         P7.13       Electrical cable insulation materials of signal cables are PVC free       X         P7.14       All cover/housing plastic parts >25g are free from chlorine and bromine.       X         P7.15       Fletrical cable insulation materials of signal cables are PVC free       X         P7.16       All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See       X         Note B2       P7.16       Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:       X         Matring: <i>RP(40)</i> TBBPA (additive)       TBBPA (reactive)       X       0         P7.17       Alt 1       Chemical specifications of flame retardants in printed circuit boards >25g (without components):       X       I         TBBPA (additive)       TBBPA (reactive)       X       0.0161; Chemical aname: BISPHENOL A DIGLYCIDYL ETHER, CAS #: 40039-93-8         Alt. 2       Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:       Image: Chemical name: Chemical name: Case of the chemical name: BISPHENOL A DIGLYCIDYL ETHER, CAS #: 40039-93-8         Alt. 1       Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations						
P7.12       Electrical cable insulation materials of power cables are PVC free.       Image: Constraint of the insulation materials of signal cables are PVC free         P7.14       Electrical cable insulation materials of signal cables are PVC free       Image: Constraint of the insulation materials of signal cables are PVC free         P7.14       All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See         Note B2)       Image: Pr.16         P7.16       Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:         Marking: FR(40)       Image: Pr.17         P7.17       Alt. 1         Chemical specifications of flame retardants in printed circuit boards >25g (without components):         TBBPA (additive)       TBBPA (reactive)         J. Other; chemical specifications of flame retardants in printed circuit boards (without components) >25g according         ISO 1043-4:       Brominated Epoxy Resin See P14         P7.18       Alt. 2         Chemical pacifications of flame retardants in printed circuit boards (without components) >25g according         ISO 1043-4:       Brominated Epoxy Resin See P14         P7.18       Alt. 1         Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%:         Comment: No legal limits exist, this is a market requirement.         Provi	P7.11*		5 11			
P7.13       Electrical cable insulation materials of signal cables are PVC free       □         P7.14       All cover/housing plastic parts >25g are free from chlorine and bromine.       □         P7.15       All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See       □         P7.16       Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: <i>FR(40)</i> □         P7.17       Alt 1       Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) □, TBBPA (reactive) ☑, Other; chemical name: <i>BISPHENOL A DIGLYCIDYL</i> □         P7.18       Alt 1       Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: <i>Brominated Epoxy Resin See P14</i> □         P7.18       Alt 1       Flame retarded plastic parts >25g contain the following flame retardant. The list must contain concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. Provide a list of all used flame retardants supplier.       □         P7.18       Alt 1       Flame retardant supplier.       1         Chemical name: <i>Rolycarbonate</i> , CAS #: <i>13983-17-0</i> , Supplier: <i>Mitsubishi</i> 2. Chemical name: <i>Talc</i> , CAS #: <i>14807-96-6</i> , Supplier: <i>Sabic</i> 1       Chemical name: <i>Talc</i> , CAS #: <i>13487-96-7</i> , Supplier: <i>Sabic</i> 3. Chemical name: <i>CALCIUM METASILICATE</i> , CAS #: <i>13983-17-0</i> , Supplier: <i>Sabic</i> 2 <td>D7 12</td> <td></td> <td></td> <td></td> <td></td> <td></td>	D7 12					
P7.14       All cover/housing plastic parts >25g are free from chlorine and bromine.       Image: Construct and the construction of the			·		<u> </u>	<u> </u>
P7.15       All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2)         P7.16       Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:         Marking: FR(40)       P7.17         P7.17       Alt. 1         Chemical specifications of flame retardants in printed circuit boards >25g (without components):       Image: Comparison of the circuit boards (without components):         TBBPA (additive)       TBBPA (reactive)       Other; chemical name: BISPHENOL A DIGLYCIDYL ETHER, CAS #: 40039-93-8         Alt. 2       Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:       Image: Comparison of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:         P7.18       Alt. 1       Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%:       Image: Comparison of the retardants including MSDS for each flame retardant. The list must contain complete chemical name: CAS number and supplier.         1. Chemical name: CAS number and supplier.       Image: Sabic       Image: Sabic         2. Chemical name: Natural Wollastonite, CAS #: 13983-17-0, Supplier: Sabic       Image: CAS #: 14807-96-6, Supplier: Sabic         3. Chemical name: Titanium dioxide, CAS #: 13983-17-0, Supplier: Sabic       Image: CAS MULL CAS #: 13983-17-0, Supplier: Sabic         3. Chemical name: CALCLUM METASILICATE, CAS #: 13983-17-	-		-		<u> </u>	<u> </u>
Note B2)         P7.16       Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: <i>FR</i> (40)         P7.17       Att. 1         Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive)					<u> </u>	<u> </u>
Marking: FR(40)       P7.17         Alt. 1       Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive)	P7.15			e 🔀		
Chemical specifications of flame retardants in printed circuit boards >25g (without components):       □         TBBPA (additive)       , TBBPA (reactive)       , Other; chemical name: BISPHENOL A DIGLYCIDYL         ETHER, CAS #: 40039-93-8       □       □         Alt 2       □       □         Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: Brominated Epoxy Resin See P14       □         P7.18       Alt 1       Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%:       □         Comment: No legal limits exist, this is a market requirement.       Provide a list of all used flame retardants including MSDS for each flame retardant. The list must contain complete chemical name: CAS number and suppler.       1         1. Chemical name: CAS unber and suppler.       1. Chemical name: CAS supplier: Supplier: Mitsubishi       2. Chemical name: CAS unber and suppler.         3. Chemical name: Matural Wollastonite, CAS #: 13983-17-0, Supplier: Sabic       5. Chemical name: Tata: CAS #: 14807-96-6, Supplier: Sabic         5. Chemical name: Tata: CAS #: 14807-96-6, Supplier: Sabic       6. Chemical name: CALCIUM METASILICATE, CAS #: 13983-17-0, Supplier: Sabic         6. Chemical name: CALCIUM METASILICATE, CAS #: 13983-17-0, Supplier: Sabic       7. Chemical name: Carbon black, CAS #: 1333-86-4, Supplier: Sabic         7. Chemical name: Carbon black, CAS #: 1333-86-4, Supplier: Sabic       1 <td>P7.16</td> <td>Marking:</td> <td></td> <td></td> <td></td> <td></td>	P7.16	Marking:				
Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: Brominated Epoxy Resin See P14         P7.18       Alt. 1         Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: <ul> <li>Comment: No legal limits exist, this is a market requirement.</li> <li>Provide a list of all used flame retardants including MSDS for each flame retardant. The list must contain complete chemical name, CAS number and supplier.</li> <li>Chemical name: Polycarbonate, CAS #: 25971-63-5, Supplier: Mitsubishi</li> <li>Chemical name: Acrylonitrile-Butadiene-Styrene-Copolymer, CAS #: 9003-56-9, Supplier: Mitsubishi</li> <li>Chemical name: Natural Wollastonite, CAS #: 13983-17-0, Supplier: Sabic</li> <li>Chemical name: Titanium dioxide, CAS #: 13463-67-7, Supplier: Sabic</li> <li>Chemical name: CALCIUM METASILICATE, CAS #: 13983-17-0, Supplier: Sabic</li> <li>Chemical name: Carbon black, CAS #: 1333-86-4, Supplier: Sabic</li> <li>Chemical name: Carbon black, CAS #: 1333-86-4, Supplier: Sabic</li> </ul> P7.19     Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)	P7.17	Chemica TBBPA (	additive) , TBBPA (reactive) , Other; chemical name: <b>BISPHENOL A DIGLYCIDYL</b>			
Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in Concentrations above 0.1%:       Image: Comment: No legal limits exist, this is a market requirement.         Provide a list of all used flame retardants including MSDS for each flame retardant. The list must contain complete chemical name, CAS number and supplier.       1. Chemical name: CAS number and supplier.         1. Chemical name: Polycarbonate, CAS #: 25971-63-5, Supplier: Mitsubishi       2. Chemical name: CAS number and supplier.         3. Chemical name: Natural Wollastonite, CAS #: 13983-17-0, Supplier: Sabic       3. Chemical name: Natural Wollastonite, CAS #: 13983-17-0, Supplier: Sabic         5. Chemical name: Titanium dioxide, CAS #: 13463-67-7, Supplier: Sabic       6. Chemical name: CALCIUM METASILICATE, CAS #: 13983-17-0, Supplier: Sabic         7. Chemical name: CalLCIUM METASILICATE, CAS #: 13983-17-0, Supplier: Sabic       7. Chemical name: Carbon black, CAS #: 1333-86-4, Supplier: Sabic         7. Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:       FR(40)         P7.19       Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)		Chemica ISO 1043				
Provide a list of all used flame retardants including MSDS for each flame retardant. The list must contain complete chemical name, CAS number and supplier.         1. Chemical name: Polycarbonate, CAS #: 25971-63-5, Supplier: Mitsubishi         2. Chemical name: Acrylonitrile-Butadiene-Styrene-Copolymer, CAS #: 9003-56-9, Supplier: Mitsubishi         3. Chemical name: Natural Wollastonite, CAS #: 13983-17-0, Supplier: Sabic         4. Chemical name: Talc, CAS #: 14807-96-6, Supplier: Sabic         5. Chemical name: Titanium dioxide, CAS #: 13983-17-0, Supplier: Sabic         6. Chemical name: CALCIUM METASILICATE, CAS #: 13983-17-0, Supplier: Sabic         7. Chemical name: CALCIUM METASILICATE, CAS #: 13983-17-0, Supplier: Sabic         7. Chemical name: CALCIUM METASILICATE, CAS #: 13983-17-0, Supplier: Sabic         7. Chemical name: CALCIUM METASILICATE, CAS #: 13983-17-0, Supplier: Sabic         7. Chemical name: Carbon black, CAS #: 1333-86-4, Supplier: Sabic         7. Chemical name: Carbon black, CAS #: 1333-86-4, Supplier: Sabic         7. Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:         FR(40)       Image: Pr.19         Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)	P7.18	Flame r concentr	ations above 0.1%:	n 🔀		
<ul> <li>2. Chemical name: Acrylonitrile-Butadiene-Styrene-Copolymer, CAS #: 9003-56-9, Supplier: Mitsubishi</li> <li>3. Chemical name: Natural Wollastonite, CAS #: 13983-17-0, Supplier: Sabic</li> <li>4. Chemical name: Titanium dioxide, CAS #: 13463-67-7, Supplier: Sabic</li> <li>5. Chemical name: Titanium dioxide, CAS #: 13463-67-7, Supplier: Sabic</li> <li>6. Chemical name: CALCIUM METASILICATE, CAS #: 13983-17-0, Supplier: Sabic</li> <li>7. Chemical name: Carbon black, CAS #: 1333-86-4, Supplier: Sabic</li> <li>Alt. 2</li> <li>Chemical specifications of flame retardants in plastic parts &gt;25g according ISO 1043-4: FR(40)</li> <li>P7.19 Plastic parts &gt;25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)</li> </ul>		Provide a complete	a list of all used flame retardants including MSDS for each flame retardant. The list must contait chemical name, CAS number and supplier.	n		
<ul> <li>4. Chemical name: <i>Talc</i>, CAS #: <i>14807-96-6</i>, Supplier: <i>Sabic</i></li> <li>5. Chemical name: <i>Titanium dioxide</i>, CAS #: <i>13463-67-7</i>, Supplier: <i>Sabic</i></li> <li>6. Chemical name: <i>CALCIUM METASILICATE</i>, CAS #: <i>13983-17-0</i>, Supplier: <i>Sabic</i></li> <li>7. Chemical name: <i>Carbon black</i>, CAS #: <i>1333-86-4</i>, Supplier: <i>Sabic</i></li> <li>Alt. 2 Chemical specifications of flame retardants in plastic parts &gt;25g according ISO 1043-4: <i>FR(40)</i></li> <li>P7.19 Plastic parts &gt;25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)</li> </ul>		2. Chem <i>Mitsubi</i>	ical name: <i>Acrylonitrile-Butadiene-Styrene-Copolymer</i> , CAS #: <i>9003-56-9</i> , Supplier: shi			
<ul> <li>7. Chemical name: <i>Carbon black</i>, CAS #: <i>1333-86-4</i>, Supplier: <i>Sabic</i></li> <li>Alt. 2 Chemical specifications of flame retardants in plastic parts &gt;25g according ISO 1043-4: <i>FR(40)</i></li> <li>P7.19 Plastic parts &gt;25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)</li> </ul>		4. Chem	ical name: <i>Talc</i> , CAS #: <i>14807-96-6</i> , Supplier: <i>Sabic</i>			
Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:         FR(40)         P7.19       Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)						
R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)		Chemica	I specifications of flame retardants in plastic parts >25g according ISO 1043-4:	$\square$		
P7.20 Of total plastic parts' weight >25g, recycled material content is 0%.	P7.19					
	P7.20	Of total p	plastic parts' weight >25g, recycled material content is 0%.			

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

P7.22	Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg	$\square$	
P8	Batteries		
P8.1*	Battery chemical composition: Lithium Ion/Lithium Manganese Dioxide	$\boxtimes$	
P8.2	Batteries meet the requirements of the following voluntary program/s: US RBRC	$\boxtimes$	

Issue date * 2015-1	12-29			Logo Lenovo	).
Product environmental attr	ibutes - Market	requirements (	continued)	Requireme	nt met
Item				Yes No	o n.a.
P9 Energy consumption					
9.1 For the product the f	81				
	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference / Standard for energy modes and test method *	st
Peak (On-max)	90 W	90 W	90 W	Full load	$\boxtimes$
Category I2			•		
Short Idle State - WOL Enabled	d 11.184 W	<b>11.376</b> W	<b>11.496</b> W	Use for ENERGY STAR V6 registration(Pidle)	
Long Idle State - WOL Enabled	<b>7.824</b> W	8.304 W	8.016 W	Use for ENERGY STAR V6 registration(P <sub>idle</sub> )	
Sleep (S3) - WOL Enabled	0.504 W	0.492 W	0.564 W	Reference	
Off (S5) - WOL Enabled	0.288 W	0.288 W	0.36 W	Use for EuP	
EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.)	0.098 W	0.084 W	0.144 W		
PTEC * Typical Energy Consumption	W	W	W		
TEC * Typical Energy Consumption	0.7388 kWh/week	0.7559 kWh/week	07644 kWh/week	= <i>E<sub>TEC</sub></i> /52	
ETEC * Annual Energy Consumption	<b>38.42</b> kWh/year	<mark>39.31</mark> kWh/year	<b>39.75</b> kWh/year	$E_{TEC} = (8760/1000) \times (P_{off} \times 0.25 + P_{sleep} \times 0.35) + P_{long_ldle} \times 0.10 + P_{short_ldle} \times 0.30)$	5
		5) - WOL Enabled; I	P <sub>sleep</sub> : Sleep Mode(	(S3) - WOL Enabled; P <sub>idle</sub> : Idle State - WOL Enabled	
Display resolution* : 2.074 Mega	apixels				
Print Speed * : Imag	ges per minute				
Default time to enter energy save	e mode: 30 minute	S			
			th the product.		

Product environmental attr	ibutes - Market	requirements (	continued)	Requirement	met
Item				Yes No	n.a.
P9 Energy consumption	on				
9.1 For the product the f	ollowing power leve	els or energy cons	umptions are re	ported: See P14	
Energy mode *	Power level at <b>100</b> V AC	Power level at 115 V AC	Power level at 230 V AC	Reference / Standard for energy modes and test method *	
Peak (On-max)	90 W	90 W	90 W	Full load	$\square$
Category I3		1	1		
Short Idle State - WOL Enabled	d 11.952 W	11.88 W	<b>12.756</b> W	Use for ENERGY STAR V6 registration(Pidle)	
Long Idle State - WOL Enabled	<b>8.448</b> W	8.604 W	8.916 W	Use for ENERGY STAR V6 registration(Pidle)	
Sleep (S3) - WOL Enabled	0.516 W	0.516 W	0.588 W	Reference	
Off (S5) - WOL Enabled	0.276 W	0.276 W	0.336 W	Use for EuP	
EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.)	0.098 W	0.084 W	0.144 W		
PTEC * Typical Energy Consumption	W	W	W		

TEC * Typical Energy Consumption	<b>0.788</b> kWh/week	<b>0.7873</b> kWh/week	<b>0.8436</b> kWh/week	=E <sub>TEO</sub> /52			
ETEC * Annual Energy Consumption41.0 kWh/year40.94 kWh/year43.87 kWh/year $E_{TEC} = (8760/1000) \times (P_{off} \times 0.25 + P_{sleep} \times 0.35 + P_{long_ldle} \times 0.10 + P_{short_ldle} \times 0.30)$ $P_{off}$ : Off Mode(S5) - WOL Enabled; $P_{sleep}$ : Sleep Mode(S3) - WOL Enabled; $P_{idle}$ : Idle State - WOL Enabled							
	Poff: Off Mode(	S5) - WOL Enabled	l; P <sub>sleep</sub> : Sleep Mode	(S3) - WOL Enabled; P <sub>idle</sub> : Idle State - WOL Enabled			
Display resolution* : 2.074 Meg	apixels						
Print Speed * : Ima	ges per minute				$\square$		
Default time to enter energy sav	e mode: 30 minut	es					
P9.2* Information about th	e energy save fur	nction is provided	with the product.				
	ENERGY STAR® version: Version 6.1 dated Oct, 2014       Tier:       Product category: 13       Image: Content of the specify: 13         Others specify:       Image: Content of the specify: 13       Image: Content of the specify: 13       Image: Content of the specify: 13						
Noise emission – D	Declared according	a to ISO 9296					
	ode description		Declared A-weighter sound power $L_{WAd}$	b sound pressure level $L_{pAm}$ (dB)			
Idle *	HDD:Idle		* 2.7	4.3			
Operation *	HDD: Operating		* 17	31			
Other mode							
P10.2 The product meets t	Other	(only if not co	,	with L <sub>pAm</sub> measurement distance m)			

Model number *	80RV		
Issue date *	2015-12-29	Logo	Lenovo

Product	environmental attributes - Market requirements (continued)	Require	ment m	let
Item		Yes	No n	n.a.
	Chemical emissions from printing products			
P10.3*	Test performed according to ECMA-328 (ISO/IEC 28360) standard 🔲, other specify:			$\boxtimes$
P10.4	Typical emission rate (print phase) is (mg/h):			$\mathbf{X}$
	Dust Ozone Styrene Benzene TVOC			
P10.5	Chemical emission requirements of the following voluntary program/s are met for :			X
	Dust Ozone Styrene Benzene TVOC			
	Electromagnetic emissions			
P10.6	Computer display meets the requirement for low frequency electromagnetic fields of the following voluntary program/s: <i>MPR-II(3 pin AC adapter only)</i>	$\boxtimes$		
P11	Consumable materials for printing products			
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).			$\boxtimes$
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements EN12281.	of 🗌		$\boxtimes$
P11.3*	2-sided (duplex) printing/copying is an integrated product function.			$\mathbf{X}$
P12	Ergonomics for computing products			
P12.1*	The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.			$\boxtimes$
P12.2*	The physical input device meets the requirements of ISO 9995 and ISO 9241-410.	<u> </u>		
P13	Packaging and documentation			
P13.1*				
P13.1	Product packaging material type(s): weight (kg): Product packaging material type(s): weight (kg):			
P13.2*	Product packaging material type(s): weight (kg): Product plastic packaging is free from PVC.			_
				_
P13.3*	Specify media for user and product documentation (tick box):		L	
	Electronic 🔀, Paper 🔀, Other 📃			
P13.4*	For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber: %		[	
P				

P14	Additional information (See Note B4)
	NOTE: Supplier makes no representations, guarantees, assurances or warranties whether express or implied, regarding the information contained in this document. All information provided by supplier in this document is provided based on supplier's knowledge available at the time of completion, and supplier shall have no obligation to update such information. The information provided here is approximate and provided for informational purposes only. See a Lenovo Account Representative for more information.
P9	See Energy Star Qualified Notebooks & Tablet Computers for the latest information: http://www.energystar.gov/index.cfm?fuseaction=find_a_product.showProductGroup&pgw_code=CO

## Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

## Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

## Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	Lenovo ideapad 700-17ISK	Logo
Model Number	80RV	
Issue Date	2015-12-29	Lenovo
Additional information		

P7.1.1	Product environmental attributes							
(d)	year of manufacture:	2015						
(e)	<b>E TEC value</b> (kWh) per ErP Lot 3 Category and capability adjustments applied when <b>all discrete graphics cards (dGfx) are disabled</b> and if the system is tested with switchable graphics mode with UMA driving the display:							
	Category (according to ErP Lot 3): NA	Etec: NA						
(f)	E TEC value (kWh) per ErP Lot 3 Category and cap enabled:	bability adjustments applied when all discrete graphics cards (dGfx) are						
	Category (according to ErP Lot 3): B	itec: 24.99						
(g)	idle state power demand (Watts);	8.42						
h)	sleep mode power demand (Watts);	0.70						
i)	sleep mode with WOL enabled power demand (Wat	ts) (where enabled); 0.70						
i)	off mode power demand (Watts);	0.43						
k)	off mode with WOL enabled power demand (Watts)	(where enabled); 0.43						
I)	internal power supply efficiency at 10 %, 20 %, 50 %	and 100 % of rated output power (if applicable):						

	10%	20%	50%	100%	Average	9		
(m)	external p	ower supp	oly efficience	y (if app	licable):			
	Average*:	90W:88.	52%,88.49	%, <mark>88.5</mark> 7	%			
					l power supplies			
(0)	the minim	um numbe	er of Ioadin	g cycles	that the batte	ries can withstand (applies only to notebook computers):	300 cycles	
(p-1)			methodolo	gy used	to determin	e information mentioned in points (I) - internal PSU		
	efficiency:					ΝΑ		
(p-2)			methodolog	gy used	to determine	e information mentioned in points (m) - external PSU		
	efficiency:			En	ergy-star req	uirement by EPA 2.0		
(p-3)		urement	methodolog	gy used	I to determine	e information mentioned in points (o) - loadingcycles		
	batteries:			En	ergy-star req	uirement by EPA 2.0		
(p-4)	the measurement methodology used to determine information mentioned in maximum, idle, sleep, off mode power as defined in Point P9.1 in the Product IT Eco Declaration:							
			IEC 62	623 / IE	C EN50564:20	011 measurement methodology		
(q)	sequence	of steps f	or achievin	g a stab	le condition wi	ith respect to power demand::		
	IEC 62623 / IEC EN50564:2011 measurement methodology							
(r)	descriptio	n of how s	leep and/o	r off moo	de was selecte	ed or programmed:		
					Based on	user manual		
(s)	sequence off mode:	of events	required to	reach t	he mode wher	re the equipment automatically changes to sleep and/or		
					Based on	user manual		
(t)						nputer automatically reaches sleep mode, or another er demand requirements for sleep mode (in minutes):	30	
(u)						in which the computer automatically reaches a irement than sleep mode (in minutes):	NA	
(v)	the length	n of time I	before the	display	sleep mode i	is set to activate after user inactivity (in minutes):	10	
(w)	informatio	n on the e	energy-savi	ng poter	ntial of power r	nanagement functionality:		
					refer to	user manual		
(x)	user inform	mation on	how to ena	ble the	power manage	ement functionality:		
					refer to	user manual		
(z)		city supply	y system, -			NV and frequency in Hz, — total harmonic distortion of umentation on the instrumentation, set-up and circuits		
				230V/5	50Hz, Total Ha	armonic Distortion <2 %		
Addition	Notebook E	Battery Inf	ormation:					
Yes		No		n/a		bk computer is operated by battery/ies that cannot be accesse fessional user.	ed and replaced	
(Battery replaceab	not user	(Battery replaces				ry[ies] in this product cannot be easily replace	ed bv users	
Toplaceab	,	1001000			themselve		,	
					1			
Additiona	l informatio	on		1	<u> </u>			

Annex B of ECMA-370 4 <sup>th</sup> edition, June 2009	Annex	Bo	f ECMA-370	4 <sup>th</sup>	edition,	June	2009
--	-------	----	------------	-----------------	----------	------	------