

Product environmental attributes - THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable).

Additional information regarding each item may be found under P14.

Brand *	Lenovo Logo			
Company name *	Lenovo			
Contact information *	Lenovo Global Environmental Affairs Alvin L Carter 1009 Think Place Building 2 (EE)	lenovo.		
	Building 2 / 5F1 Morrisville, North Carolina 27560 alcarter@lenovo.com			
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment.html			
Additional information	The latest version of this document can be found at http://www.lenovo.com/social_responsibility/us/en/datasheets_t	notebooks.html		

	The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.				
Type of product *	All-in-One Desktop PC				
Commercial name *	Lenovo C360				
Model number *	10147; F0AB				
Issue date *	14/05/2014				
Intended market *	Global Europe Asia, Pacific & Japan Americas Other				
Additional information					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Quality Control		
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🔀	

Model number *	Lenovo C360	MT: 10147; F0AB		
Issue date *	14/05/2014		Logo	lenovo.

Product	environmental attributes - Legal requirements	Require	ment	met
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)			
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.	\boxtimes		
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),		П	
	hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum			
P1.4*	concentration values. Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated		$\overline{}$	
	terphenyl (PCT) in preparations (see legal reference).		ш	
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).			
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference).			
	Comment: Legal reference has no maximum concentration values.			
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)		Ш	
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference).			
	Comment: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm²/week (see legal reference).		Ш	Ш
P1.10*	Comment: Max limit in legal reference when tested according to EN1811:1998. REACH Article 33 information about substances in articles is available at (add URL or mail contact):			
P1.10	http://www.lenovo.com/social_responsibility/us/en/materials.html		Ш	Ш
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is			
P2.2*	provided in user manual. (See legal reference) Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or			
P2.3*	accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference) Batteries and accumulators are easily removable by either users or service providers (as dependent on the			
F2.3	design of the product). Exception: Batteries that are permanently installed for safety, performance, medical or data integrity reasons do not have to be "easily removable". (See legal reference)	Ш	Ш	Ш
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*	The product complies with legally required safety standards as specified (see legal reference).		П	
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).		Ħ	Ħ
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).			
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	\square		П
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).			
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).			\boxtimes
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and hexavalent chromium by weight of these together.			
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	\boxtimes		
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.			

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number *	Lenovo C360	MT: 10147; F0AB		
Issue date *	14/05/2014		Logo	lenovo

Product	t environmental attributes - Market requirements - Environmental conscious design Re	quire	men	t met
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.
P6	Treatment information			
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).	\boxtimes		
P7	Design Disassembly, recycling			
P7.1*	Parts that have to be treated separately are easily separable	\boxtimes		
P7.2*	Plastic materials in covers/housing have no surface coating.	П	X	$\overline{\Box}$
P7.3*	Plastic parts >100g consist of one material or of easily separable materials.			
P7.4*	Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.			
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.			
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).			
	Product lifetime			
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	\boxtimes		
P7.8*	Upgrading can be done using commonly available tools	\boxtimes		
P7.9.	Spare parts are available after end of production for: 5 years			
P7.10	Service is available after end of production for: 5 years			
	Material and substance requirements			
P7.11*	Product cover/housing material type:			
P7.12	Material type: ABS Material type: Material type:	_		_
	Electrical cable insulation materials of power cables are PVC free.	ᆚ		_ <u></u>
P7.13	Electrical cable insulation materials of signal cables are PVC free	<u>Ц</u>	\boxtimes	_ <u>_</u> _
P7.14	All cover/housing plastic parts >25g are free from chlorine and bromine.	\boxtimes		
P7.15	All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2)			
P7.16	Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking:			
P7.17	Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) , TBBPA (reactive) , Other; chemical name: , CAS #:			
	Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: <i>Brominated Epoxy Resin See P14</i>			
P7.18	Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%:			
	Comment: No legal limits exist, this is a market requirement.			
	1. Chemical name: , CAS #: 2. Chemical name: , CAS #:			
	3. Chemical name: , CAS #:			
	Alt. 2			
	Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:	\square		
P7.19	Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45,			
D7.66	R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)			
P7.20	Of total plastic parts' weight >25g, recycled material content is 75%.			
P7.21 P7.22	Of total plastic parts' weight >25g, biobased material content is 0%. Light sources are free from mercury			
1 1.22	If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg		Ш	Ш
P8	Batteries			
P8.1*	Battery chemical composition:			
P8.2	Batteries meet the requirements of the following voluntary program/s:			$\overline{\Box}$

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *	Lenovo C360	MT: 10147; F0AB		
Issue date *	14/05/2014		Logo	lenovo.

	environmental attributes - Market requirements (continued) Requirement mo						
Item				Yes No	n.a.		
P9 Energy consumption 9.1 For the product the following power levels or energy consumptions are reported: See P14							
Energy mode *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference / Standard for energy modes and test method *	╽╙		
Peak (On-max)	<i>65.234</i> W	<i>65.125</i> W	<i>67.256</i> W	Full load			
Category I1							
Short Idle State - WOL Enable	ed 35.289 W	35.023 W	<i>37.299</i> W	Use for ENERGY STAR V6 registration (Pidle)			
Long Idle State - WOL Enable	ed 28.099 W	28.043 W	30.268 W	Use for ENERGY STAR V6 registration (P _{idle})			
Sleep (S3) - WOL Enabled	1.5723 W	1.5178 W	1.5221 W	Use for ENERGY STAR V6 registration(P _{sleep})			
Sleep (S3) - WOL Disabled	1.4968 W	1.5002 W	1.4639 W	Reference			
Off (S5) - WOL Enabled	1.2991 W	1.2213 W	1.2113 W	Use for ENERGY STAR V6 registration(Poff)	╁═		
Off (S5) - WOL Disabled	1.2875 W	1.2169 W	1.2085 W	Use for EuP	ਜ		
Category I2				<u> </u>			
Short Idle State - WOL Enable	ed W	W	W	Use for ENERGY STAR V6 registration(P _{idle})	П		
Long Idle State - WOL Enable	ed W	W	W	Use for ENERGY STAR V6 registration(P _{idle})	H		
Sleep (S3) - WOL Enabled	W	W	W	Use for ENERGY STAR V6 registration (P _{sleep})	H		
Sleep (S3) - WOL Disabled	W	W	W	Reference	H		
Off (S5) - WOL Enabled	W	W	W	Use for ENERGY STAR V6 registration(Poff)	╁岩		
EPS No-load				Coo ioi ZiiZiioi Civiii to iogica ation(i oii)	卄		
(External power supply / charge plugged in the wall outlet but disconnected from the product.)	0.1862 W	<i>0.1881</i> W	0.2270 W				
PTEC * Typical Energy Consumption	N/A W	N/A W	<i>N/A</i> W				
TEC * Typical Energy Consumption	Cat I1:105.41 kWh/week	Cat I1: 104.81 kWh/week	Cat I1:112.56 kWh/week				
ETEC * Annual Energy Consumption	Cat I1:105.41 kWh/year	Cat I1: 104.81 kWh/year	Cat I1:112.56 kWh/year	$E_{TEC} = (8760/1000) \times (P_{off} \times 0.45 + P_{sleep} \times 0.05 + P_{shortIdle} \times 0.35 + P_{LongIdle} \times 0.15)$			
Displacement them. 400000		5) - WOL Enabled;	P _{sleep} : Sleep Mode	e(S3) - WOL Enabled; P _{idle} : Idle State - WOL Enabled	 		
Display resolution* : 1600*9	<u> </u>				Ш		
Print Speed * : N/A	Images per minute						
Default time to enter energy sav		utes					
	ne energy save func		<u>'</u>		Ш		
	the energy requirem version: Version 6.0		ng voluntary prododuct category:	gram/s:			
P10 Emissions							
	Declared according	to ISO 9296		5 1 14 111			
P10.1 Mode N	lode description		Declared A-weighted				
			sound power	er Protonder neeltiene	4		
			level L_{WAd}				
				or Desk side (only if product is not operator attended)			
Idle *	Idle		* 3.7 Bel(A)	32 dB(A)	1 🗖		
	CPU stress loading	80%	* 4.4 Bel(A)	39 dB(A)	1 🗂		
Other mode	Other mode]		
Measured according to: ECMA-74							
D10 0 The meadwat mass to	Other (only if not covered by ECMA-74 with L _{pAm} measurement distance m) P10.2 The product meets the acoustic noise requirements of the following voluntary program/s:						
P10.2 The product meets	the acoustic noise re	equirements of the	e ioliowing volunt	ary program/s:	\boxtimes		

Model number *	Lenovo C360	MT: 10147; F0AB		
Issue date *	14/05/2014		Logo	lenovo.

Product	environmental attributes - Market requirements (continued)	Requirer	ment	met
Item	• • • • • • • • • • • • • • • • • • • •	Yes	No	n.a.
	Chemical emissions from printing products			
P10.3*	Test performed according to ECMA-328 (ISO/IEC 28360) standard , other specify:			\boxtimes
P10.4	Typical emission rate (print phase) is (mg/h):			\boxtimes
	Dust Ozone Styrene Benzene TVOC			
P10.5	Chemical emission requirements of the following voluntary program/s are met for :			\boxtimes
	Dust Ozone Styrene Benzene TVOC			
	Electromagnetic emissions			
P10.6	Computer display meets the requirement for low frequency electromagnetic fields of the following voluntary program/s:			\boxtimes
P11	Consumable materials for printing products			
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).			\boxtimes
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of EN12281.	f		\boxtimes
P11.3*	2-sided (duplex) printing/copying is an integrated product function.			\boxtimes
P12	Ergonomics for computing products			
P12.1*	The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.	\boxtimes		
P12.2*	The physical input device meets the requirements of ISO 9995 and ISO 9241-410.	\boxtimes		
P13	Packaging and documentation			
P13.1*	Product packaging material type(s): paper weight (kg): 0.87			
	Product packaging material type(s): PE weight (kg): 0.28			
Dia at	Product packaging material type(s): HDPE weight (kg): 0.002			_
P13.2*	Product plastic packaging is free from PVC.		\boxtimes	Ш
P13.3*	Specify media for user and product documentation (tick box):			
	Electronic , Paper , Other			
P13.4*	For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber: 0%			
P14	Additional information (See Note B4)			
	NOTE: Supplier makes no representations, guarantees, assurances or warranties whether express or implied,			
	information contained in this document. All information provided by supplier in this document is provided base knowledge available at the time of completion, and supplier shall have no obligation to update such information			ion
	provided here is approximate and provided for informational purposes only. See a Lenovo Account Represent			1011
	information.	alive for it	norc	
P9	See Energy Star Qualified Notebooks & Tablet Computers for the latest information:			
	http://www.energystar.gov/index.cfm?fuseaction=find_a_product.showProductGroup&pgw_code=CO			

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19

Lenovo ErP Lot3 Information Sheet

- PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	C360	Logo
Model Number	1047/F0AB	_
Issue Date	14/05/2014	lenovo.
Additional information	N/A	

(d)	please	of manufacturing- see product name plate			
(e)	E TEC value (kWh) and capability adjustments applied when all discrete graphics cards (dGfx) are disabled and if the system is tested with switchable graphics mode with UMA driving the display: Cat. B 131				
(f)	E TEC value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete graphics cards (dGfx) are enabled: Cat. B 177				
(g)	idle state power demand (Watts);	30.27			
(h)	sleep mode power demand (Watts);	1.46			
(i)	sleep mode with WOL enabled power demand (Watts) (where enabled);	1.52			
(j)	off mode power demand (Watts);	1.21			
(k)	off mode with WOL enabled power demand (Watts) (where enabled);	1.21			
(I)	internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable): 10% 80.77% 20% 87.00% 50% 89.90% 100% 90.59% Average 87.07%				
(m)	external power supply efficiency (if applicable): 10% N/A 20% N/A 50% N/A 100% N/A Average N/A; or Level: N/A				
(o)	the minimum number of loading cycles that the batteries can withstand (applies only to notebook computers):	N/A			
(f)	test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: Test Voltage: 230V-50HZ Test Equipment: Digital Power Meter: Chroma 66202 Measurement Test fixture: Chroma A662003 AC Source: Gwinstek ASP-9102				
(p-1)	the measurement methodology used to determine information mentioned in points (I) – internal PSU efficiency: Test Equipment: AC Source CHROMA: 6430/643000000908				

	Electronic Load CHROMA: 63030/6300006368	
	Power Meter CHROMA: 66202/662022003033	
	Test Setup:	
	☐ Connect the EUT to suitably calibrated AC source, power meter and electronic load.	
	☐ Warm up at least 30 minutes at 100% of nameplate current output.	
	☐ The EUT shall be tested at 100%, 75%, 50%, 25% of nameplate output current and no load	
	condition.	
	☐ Measure the relative parameters required from test record.	
	☐ The input test voltage shall be used 230V/50HZ.	
	☐ Ambient temperature: 23 +/-5 ℃.	
	No-Load mode: Not connection to a product or any other load.	
	Test procedure following Test Method for Calculating the Energy Efficiency of single-voltage	
	External AC-DC and AC-AC Power Supplies and "IEC 62301"	
(p-2)	the measurement methodology used to determine information mentioned in points (m) - external PSU	
	efficiency:	
(p-3)	the measurement methodology used to determine information mentioned in points (o) – loadingcycles	
(/	batteries:	
, A)	N/A	
(p-4)	the measurement methodology used to determine information mentioned in maximum, idle, sleep, off mode power as defined in Point P9.1 in the Product IT Eco Declaration: Test Condition:	
	long idle Mode: Measure Panel brightness 150cd/m2	
	short idle Mode: Turn off the display: after 10minutes Max: Open Burn In Mode(Driver: Burn In Pro 7.1 Build 1017)	
	Sleep(S3): PC Setting go to Sleep	
	Off(S5): PC Setting to Shut down	
(q)	sequence of steps for achieving a stable condition with respect to power demand:: N/A	
(r)	description of how sleep and/or off mode was selected or programmed:	
	Sleep Mode	
	Step 1. Select Shut down or sign out	
	Step2. Select Sleep Off Mode	
	Step1. Select Shut down or sign out	
	Step2. Select Shut down	
(s)	sequence of events required to reach the mode where the equipment automatically changes to sleep and/or	
	off mode:	
	Sleep Mode Step 1. Select control panel	
	Step2. Select Power Options	
	Step3. Select Choose when to turn off the display	
	Step4. Setting Turn off the display Off Mode	
	Step1. Select Shut down or sign out	
	Step2. Select Shut down	
(t)	the duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes):	25 minutes
(u)	the length of time after a period of user inactivity in which the computer automatically reaches a	
	power mode that has a lower power demand requirement than sleep mode (in minutes):	25 minutes
(v)	the length of time before the display sleep mode is set to activate after user inactivity (in minutes):	10 minutes
(w)	information on the energy-saving potential of power management functionality:	
(**)	Press F1 Button to BIOS Setting:	
	Step1. Select Enhanced Power Saving Mode(ErP)	
(x)	user information on how to enable the power management functionality:	
	Press F1 Button to BIOS Setting: Step1. Select Automatic Power on	
	Step2. Select Wake on LAN	
(z)	test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the	
	electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing:	
	Test Voltage: 230V-50HZ	
	Test Equipment:	
	Digital Power Meter: Chroma 66202 Measurement Test fixture : Chroma A662003	
	AC Source: Gwinstek ASP-9102	
	Notebook Battery Information:	

Yes	No	n/a	This notebook computer is operated by battery/ies that cannot be accessed and replaced by a non-professional user.
			The battery[ies] in this product cannot be easily replaced by users themselves
Additional information			
N/A			