

#### Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

| Brand *                | Lenovo  | Logo    |  |
|------------------------|---|---------|--|
| Company name *         | Lenovo  |         |  |
| Contact information *  | Lenovo Global Environmental Affairs<br>Alvin L Carter<br>1009 Think Place<br>Building 2 / 5J3<br>Morrisville, North Carolina 27560<br>alcarter@lenovo.com | lenovo  |  |
| Internet site *        | http://www.lenovo.com/social_responsibility/us/en/environmen  | nt.html |  |
| Additional information | The latest version of this document can be found at<br>http://www.lenovo.com/social_responsibility/us/en/datasheets_desktops.html                         |         |  |

|                        | The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration. |  |  |  |  |  |
|------------------------|--|--|--|--|--|--|
| Type of product *      | Traditional Desktop  |  |  |  |  |  |
| Commercial name *      | Lenovo H530s   |  |  |  |  |  |
| Model number *         | 90A9; 10131; 90AB; 10132   |  |  |  |  |  |
| Issue date *           | 2013-7-30  |  |  |  |  |  |
| Intended market *      | 🛛 Global 🔲 Europe 📃 Asia, Pacific & Japan 🗌 Americas 🗌 Other   |  |  |  |  |  |
| Additional information | Energy Star Qualified (Model 90A9; 10131)  |  |  |  |  |  |

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

| Quality | Quality Control Re   |             |    |  |
|---------|--|-------------|----|--|
| Item    |  | Yes         | No |  |
| QC1 *   | The company enforces an internal quality control scheme to ensure the correctness of this eco declaration  | $\boxtimes$ |    |  |
| QC2 *   | The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org). | $\boxtimes$ |    |  |

| Model number * | Lenovo H530s |
|----------------|--------------|
| Issue date *   | 2013-7-30    |

## MT: 90A9; 10131; 90AB; 10132

lenovo

| Product | environmental attributes - Legal requirements   | Requirement met |    |             |
|---------|---|-----------------|----|-------------|
| Item    |   | Yes             | No | n.a.        |
| P1      | Hazardous substances and preparations   |                 |    |             |
| P1.1*   | Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)   |                 |    |             |
| P1.2*   | Products do not contain Asbestos (see legal reference).<br>Comment: Legal reference has no maximum concentration value.   | $\boxtimes$     |    |             |
| P1.3*   | Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),  | $\square$       |    |             |
|         | hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-<br>trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum<br>concentration values.  |                 |    |             |
| P1.4*   | Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).   | $\boxtimes$     |    |             |
| P1.5*   | Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).  | $\boxtimes$     |    |             |
| P1.6*   | Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS)<br>Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference).<br>Comment: Legal reference has no maximum concentration values.   | ,               |    |             |
| P1.7*   | Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split<br>aromatic amines. (See legal reference and Note B1)   |                 |    | $\square$   |
| P1.8*   | Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference).   |                 |    | $\square$   |
| P1.9*   | Comment: Legal reference has no maximum concentration values.<br>Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5<br>microgram/cm <sup>2</sup> /week (see legal reference).   | $\square$       |    |             |
|         | Comment: Max limit in legal reference when tested according to EN1811:1998.   |                 |    |             |
| P1.10*  | REACH Article 33 information about substances in articles is available at (add URL or mail contact):<br>http://www.lenovo.com/social_responsibility/us/en/ThinkGreen_products.html#environment  | $\square$       |    |             |
| P2      | Batteries   |                 |    |             |
| P2.1*   | If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference) |                 |    |             |
| P2.2*   | Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)  |                 |    |             |
| P2.3*   | Batteries and accumulators are easily removable by either users or service providers (as dependent on th design of the product). Exception: Batteries that are permanently installed for safety, performance, medic or data integrity reasons do not have to be "easily removable". (See legal reference)   | e 🖂             |    |             |
| P3      | Safety, EMC connection to the telephone network and labeling  |                 |    |             |
| P3.1*   | The product complies with legally required safety standards as specified (see legal reference).   | $\square$       |    |             |
| P3.2*   | The product complies with legally required standards for electromagnetic compatibility (see legal<br>reference).  | $\square$       |    |             |
| P3.3*   | If product is intended for connection to a public telecom network or contains a radio transmitter, it complie<br>with legally required standards for radio and telecommunication devices (see legal reference).   | s 🔀             |    |             |
| P3.4*   | The product is labeled to show conformance with applicable legal requirements (see legal reference).  | $\boxtimes$     |    |             |
| P4      | Consumable materials  |                 |    |             |
| P4.1*   | If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).   |                 |    | $\square$   |
| P4.2*   | If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).  |                 |    | $\boxtimes$ |
| P4.3*   | If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).  |                 |    |             |
| P5      | Product packaging   |                 |    |             |
| P5.1*   | Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium ar hexavalent chromium by weight of these together.  | nd 🖂            |    |             |
| P5.2*   | Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).   |                 |    |             |
| P5.3*   | The product packaging material is free from ozone depleting substances as specified in the Montre Protocol (see legal reference).   | al 🔀            |    |             |
|         | Comment: Legal reference has no maximum concentration values.   |                 |    |             |

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

| Issue date *       |            | 2013-7-30 Logo   | lend        | DVO         | D.  |
|--------------------|------------|--|-------------|-------------|-----|
|                    |            |  |             |             |     |
|                    |            | mental attributes - Market requirements - Environmental conscious design   | Require     |             |     |
| tem                |            | atory to fill in. Additional information regarding each item may be found under P14.   | Yes         | No          | n.a |
| <b>P6</b><br>P6.1* |            | nt information<br>on for recyclers/treatment facilities is available (see legal reference).  |             |             |     |
| •0.1<br>•7         |            | on for recyclers/treatment rachities is available (see regarrelerence).  |             |             |     |
| ~/                 | Design     | mbly, recycling  |             |             |     |
| P7.1*              |            | t have to be treated separately are easily separable   |             |             |     |
| P7.2*              |            | naterials in covers/housing have no surface coating.   |             |             |     |
| P7.3*              |            | arts >100g consist of one material or of easily separable materials.   |             |             |     |
| P7.4*              |            | arts >25g have material codes according to ISO 11469 referring ISO 1043.   |             | H           |     |
| P7.5               |            | arts are free from metal inlays or have inlays that can be removed with commonly available tools.  |             | ⊢⊢          |     |
| P7.6*              |            | re easily separable. (This requirement does not apply to safety/regulatory labels).  |             | ⊢⊢          |     |
| 7.0                | Product    |  |             |             |     |
| P7.7*              |            | ig can be done e.g. with processor, memory, cards or drives  |             |             |     |
| P7.8*              |            | g can be done using commonly available tools   |             | H           |     |
| P7.9.              |            | arts are available after end of production for: <b>5</b> years   |             |             |     |
| P7.10              |            | · · · · · ·  |             |             | +   |
| 7.10               |            | s available after end of production for: 5 years and substance requirements  |             |             |     |
| P7.11*             |            | cover/housing material type:   |             |             | _   |
| ,                  |            | type: >PC+ABS-FR(40)< Material type: Material type:  |             |             |     |
| P7.12              |            | I cable insulation materials of power cables are PVC free.   |             | $\boxtimes$ |     |
| P7.13              |            | I cable insulation materials of signal cables are PVC free   |             |             |     |
| P7.14              |            | /housing plastic parts >25g are free from chlorine and bromine.  |             |             |     |
| P7.15              |            | d circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (S   | ee 🗌        |             | ┢   |
| 7.10               | Note B2)   |  |             |             |     |
| P7.16              | /          | tarded plastic parts >25g in covers / housings are marked according ISO 1043-4:  |             |             |     |
|                    | Marking:   | >PC+ABS-FR(40)<  |             | -           |     |
| P7.17              | Alt. 1     |  |             |             |     |
|                    |            | I specifications of flame retardants in printed circuit boards >25g (without components):  | $\boxtimes$ |             |     |
|                    | TBBPA (    | additive) 🔲, TBBPA (reactive) 🔀, Other; chemical name:, CAS #: 26265-08-7  |             |             |     |
|                    | Alt. 2     |  |             |             |     |
|                    |            | I specifications of flame retardants in printed circuit boards (without components) >25g according   |             |             | Г   |
|                    |            | 3-4: FR(16)  |             |             |     |
| P7.18              | Alt. 1     |  |             |             |     |
|                    |            | etarded plastic parts >25g contain the following flame retardant substances/preparations   | in 🗌        | $\boxtimes$ |     |
|                    |            | ations above 0.1%:   |             |             |     |
|                    |            | nt: No legal limits exist, this is a market requirement.<br>a list of all used flame retardants including MSDS for each flame retardant. The list must conta | ain         |             |     |
|                    |            | e chemical name, CAS number and supplier.  | 1111        |             |     |
|                    | •          | ical name: , CAS #: , Supplier:  |             |             |     |
|                    | 2. Chem    | ical name: , CAS #: , Supplier:  |             |             |     |
|                    |            | ical name: , CAS #: , Supplier:  |             |             |     |
|                    | Alt. 2     | Les siliertiens of flows estandants in also the nexts of Express align 100 dotted.   |             |             | L   |
|                    | Chemica    | I specifications of flame retardants in plastic parts >25g according ISO 1043-4:   |             |             |     |
| P7.19              | Plastic n  | arts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45,   |             |             |     |
| -                  |            | 6, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)   |             |             | L   |
| P7.20              | Of total p | plastic parts' weight >25g, recycled material content is 5%.   |             |             |     |
| P7.21              |            | plastic parts' weight >25g, biobased material content is 0%.   |             |             |     |
| 97.22              | Light sou  | irces are free from mercury  | $\boxtimes$ |             |     |
| 28                 | Batteries  | S  |             |             |     |
| P8.1*              | Battery c  | hemical composition: Lithium manganese dioxide coin battery  |             |             |     |
| P8.2               | Pattorios  | meet the requirements of the following voluntary program/s:  |             | -           |     |

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

| Model number * Len          | ovo H530s                                      | /              | MT: 90A9;         | 10131; 90AB; 10132   |     |
|-----------------------------|--|----------------|-------------------|--|-----|
| Issue date * 2013-7-        | 30   |                |                   | Logo <b>Ienovo</b>   |     |
| Product environmental a     | ttributoo Morkotu                              | roquiromonto   | (continued)       | Requirement  | mo  |
| Item                        |  | requirements   | (continued)       | Yes No   | n.a |
| P9 Energy consum            | otion  |                |                   |  |     |
|                             | ne following power leve<br>ipped w/ WOL Enable |                | sumptions are rep |  |     |
| Energy mode *               | Power level at                                 |                | at Power level    | at Reference / Standard for energy modes                       | ┢   |
|                             | 100 V AC                                       | 115 V AC       | 230 V AC          | and test method *  |     |
|                             | W(50Hz/60Hz)                                   | W              | W                 |  |     |
| Category 0                  |  |                |                   |  |     |
| Short Idle State - WOL Enal | oled W   | W              | W                 | Use for ENERGY STAR V6 registration (P <sub>idle</sub> )       |     |
| Long Idle State - WOL Enal  | oled W   | W              | W                 | Use for ENERGY STAR V6 registration (P <sub>idle</sub> )       |     |
| Sleep (S3) - WOL Enabled    | W  | W              | W                 | Use for ENERGY STAR V6 registration(P <sub>sleep</sub> )       |     |
| Sleep (S3) - WOL Disabled   | W  | W              | W                 | Reference  |     |
| Off (S5) - WOL Enabled      | W  | W              | W                 | Use for ENERGY STAR V6 registration(Port)                      |     |
| Off (S5) - WOL Disabled     | W  | W              | W                 | Use for EuP  |     |
| Category 11                 |  |                |                   |  |     |
| Short Idle State - WOL Enal | bled 25.31 W                                   | 25.09 W        | 25.31 W           | Use for Energy Star V6.0 registration(P <sub>ShortIdle</sub> ) |     |
| Long Idle State - WOL Enal  |  | 24.90 W        | 25.20 W           | Use for Energy Star V6.0 registration(P <sub>Longldle</sub> )  |     |
| Sleep (S3) - WOL Enabled    | 1.13 W   | 1.13 W         | 1.13 W            | Use for Energy Star V6.0 registration (P <sub>sleep</sub> )    |     |
| Sleep (S3) - WOL Disabled   | 1.13 W   | 1.13 W         | 1.13 W            | Reference  |     |
| Off (S5) - WOL Enabled      | 0.37 W   | 0.37 W         | 0.37 W            | Use for Energy Star V6.0 registration (P <sub>off</sub> )      |     |
| Off (S5) - WOL Disabled     | <b>0.27</b> W                                  | 0.27 W         | <b>0.27</b> W     | Use for EuP  |     |
| Category 12                 |  |                |                   |  |     |
| Short Idle State - WOL Enal | bled 25.12 W                                   | 25.54 W        | <b>25.61</b> W    | Use for Energy Star V6.0 registration(P <sub>ShortIdle</sub> ) |     |
| Long Idle State - WOL Enal  | oled 25.10 W                                   | 25.29 W        | 25.09 W           | Use for Energy Star V6.0 registration(P <sub>Longldle</sub> )  |     |
| Sleep (S3) - WOL Enabled    | 1.14 W   | 1.14 W         | 1.28 W            | Use for Energy Star V6.0 registration (P <sub>sleep</sub> )    |     |
| Sleep (S3) - WOL Disabled   | 1.14 W   | 1.14 W         | 1.28 W            | Reference  |     |
| Off (S5) - WOL Enabled      | 0.38 W   | 0.40 W         | 0.53 W            | Use for Energy Star V6.0 registration (Poff)                   |     |
| Off (S5) - WOL Disabled     | 0.27 W   | 0.27 W         | 0.27 W            | Use for EuP  |     |
| Category 13                 |  |                |                   |  |     |
| Short Idle State - WOL Enal | bled 24.45 W                                   | 23.69 W        | 25.34 W           | Use for Energy Star V6.0 registration(P <sub>ShortIdle</sub> ) |     |
| Long Idle State - WOL Enal  | oled 23.89 W                                   | 23.05 W        | 25.25 W           | Use for Energy Star V6.0 registration(P <sub>Longldle</sub> )  |     |
| Sleep (S3) - WOL Enabled    | 1.13 W   | 1.14 W         | 1.41 W            | Use for Energy Star V6.0 registration (P <sub>sleep</sub> )    |     |
| Sleep (S3) - WOL Disabled   | 1.13 W   | 1.14 W         | 1.41 W            | Reference  |     |
| Off (S5) - WOL Enabled      | 0.37 W   | 0.39 W         | 0.66 W            | Use for Energy Star V6.0 registration (P <sub>off</sub> )      |     |
| Off (S5) - WOL Disabled     | <b>0.27</b> W                                  | 0.27 W         | 0.27 W            | Use for EuP  |     |
| Category D1                 |  |                | •                 |  | 1   |
| Short Idle State - WOL Enal | bled 33.06 W                                   | 32.33 W        | <b>32.26</b> W    | Use for Energy Star V6.0 registration(P <sub>ShortIdle</sub> ) |     |
| Long Idle State - WOL Enal  | oled 32.74 W                                   | <b>32.15</b> W | 31.54 W           | Use for Energy Star V6.0 registration(P <sub>Longldle</sub> )  | 1   |
| Sleep (S3) - WOL Enabled    | 1.37 W   | <b>1.26</b> W  | 1.83 W            | Use for Energy Star V6.0 registration (P <sub>sleep</sub> )    |     |
| Sleep (S3) - WOL Disabled   | 1.37 W   | 1.26 W         | 1.83 W            | Reference  |     |
| Off (S5) - WOL Enabled      | <i>0.85</i> W                                  | 0.86 W         | 1.03 W            | Use for Energy Star V6.0 registration (Poff)                   |     |
| Off (S5) - WOL Disabled     | 0.27 W   | 0.27 W         | 0.27 W            | Use for EuP  |     |
| Category D2                 |  |                |                   |  | F   |
| Short Idle State - WOL Enal | bled 28.95 W                                   | <b>29.08</b> W | 31.41 W           | Use for Energy Star V6.0 registration(P <sub>ShortIdle</sub> ) |     |
| Long Idle State - WOL Enal  | oled 28.81 W                                   | 28.54 W        | 31.01 W           | Use for Energy Star V6.0 registration(P <sub>Longldle</sub> )  |     |
| Sleep (S3) - WOL Enabled    | <b>1.24</b> W                                  | 1.26 W         | 1.43 W            | Use for Energy Star V6.0 registration (P <sub>sleep</sub> )    |     |
| Sleep (S3) - WOL Disabled   | <b>1.24</b> W                                  | 1.26 W         | 1.43 W            | Reference  |     |
| Off (S5) - WOL Enabled      | 0.85 W   | 0.86 W         | 1.03 W            | Use for Energy Star V6.0 registration (Poff)                   |     |
| Off (S5) - WOL Disabled     | 0.27 W   | 0.27 W         | 0.27 W            | Use for EuP  |     |

| plugged i                           | load<br>I power supply / charge<br>In the wall outlet but<br>cted from the product.) |   | W   | W  |   |
|-------------------------------------|--|---|---|--|---|
| TEC<br>Typical E                    | nergy Consumption  | kWh/week  | kWh/week  | kWh/week   |   |
| ETEC *<br>Annual Energy Consumption |  | Cat I1: 112.67;<br>Cat I2: 112.00;<br>Cat I3: 108.31;<br>CatD1:148.33;<br>CatD2:130.51;<br>kWh/year | Cat 11: 111.60;<br>Cat 12: 113.61;<br>Cat 13: 104.96;<br>CatD1:145.31;<br>CatD2:130.60;<br>kWh/year | Cat I1:112.88;<br>Cat I2:114.14;<br>Cat I3:114.09;<br>CatD1:145.52;<br>CatD2:141.74;<br>kWh/year | ETEC = (8760/1000) x (Poff x 0.45 + Psleep x<br>0.05 + Pshortidle x 0.35 + PLongidle x 0.15)  |
| Display re                          | esolution : Megapixel  |   |   | sieep. Coop mooo(  |   |
|                                     |  |   |   |  |   |
| Print Spe                           |  | Images per minute   | •   |  |   |
|                                     | me to enter energy sav   |   |   |  |   |
| P9.2*                               | Information about the  | e energy save functi  | on is provided w  | vith the product.  |   |
| P9.3*                               |  | the energy requirement<br>ersion: 6.0 Product   |   |  | gram/s:   |
| P10                                 | Emissions  |   |   |  |   |
|                                     |  | Declared according to   | o ISO 9296  | Declared   |   |
| P10.1                               | Mode   | Mode description  | e description   |  | Declared A-weighted sound pressure level $L_{p {\rm Am}}$ (dB)  |
|                                     |  |   |   | sound power<br>level   | Operator position Bystander positions   |
|                                     |  |   |   | $L_{WAd}$ (B)  | Desktop 🔀<br>or Desk side 🗌 (only if product is not<br>operator attended)   |
|                                     | Idle   | * System: Idle  |   | * 4. 1   |   |
|                                     | CPU Loading  | * Intel PTU tool  |   | * 4. 1   | Acoustical Noise Emission Values (unbit)(d)           Machine         Product Value           Type         INVad (reb)         LpAm (dB)  |
|                                     | Operating(HDD)   |   |   |  | Ide         Oper         Id |
|                                     | CD accessing   |   |   |  | 90A9 D1 PSU: 240W 4.1 4.1 50 30 25 25<br>90AB VGA: HD8570   |
|                                     | Measured according   | g to: 🛛 ISO7779 🗌<br>Other  | ECMA-74<br>(only if not cov   | vered by ECMA-74   | t with L <sub>pAm</sub> measurement distance m)   |
| P10.2                               |  |   |   | ne following volunt  |   |

| Model nu     | mber *              | Lenovo H530s 🛛 🕺 🗛   | MT: 90A9; 10131; 90AB; 10   | )132   |            |             |
|--------------|---------------------|--|---|--|------------|-------------|
| Issue date * |                     | 2013-7-30  | Logo  |  | ovo        | ).          |
| Product      | environ             | nental attributes - Market requirements  | (continued)   | Requ   | iremen     | t me        |
| ltem         |                     | •  | · · · · ·   | Ýe   |            |             |
|              | Chemic              | al emissions from printing products  |   |  |            |             |
| P10.3*       | Test per            | formed according to ECMA-328 (ISO/IEC 28360  | 0) standard 🔀, other specify:   | $\succ$  |            |             |
| P10.4        |                     | emission rate (print phase) is (mg/h):   | ·/·····   |  |            | 一一一         |
|              |                     | Dust Ozone Styrene I   | Benzene TVOC  |  |            |             |
| P10.5        |                     | al emission requirements of the following volunta  |   |  |            |             |
|              | Electro             | magnetic emissions   |   |  |            |             |
| P10.6        |                     | er display meets the requirement for low frequer   | ncy electromagnetic fields of the following volunt  | ary  |            | $\boxtimes$ |
| P11          | Consun              | nable materials for printing products  |   |  |            |             |
| P11.1*       | A Safety            | / Data Sheet (SDS) is available for the ink/toner  | preparation, even if not legally required (see P4   | .3).   |            | $\boxtimes$ |
| P11.2*       | Paper c<br>EN1228   | ontaining post-consumer recycled fibers can b  | be used, provided that it meets the requireme   | nts of   |            | $\square$   |
| P11.3*       | 2-sided             | (duplex) printing/copying is an integrated produc  | t function.   |  |            | $\square$   |
| P12          | Ergono              | mics for computing products  |   |  |            |             |
| P12.1*       | The disp            | play meets the ergonomic requirements of ISO 9   | 241-307 for visual display technologies.  |  |            | $\boxtimes$ |
| P12.2*       | The phy             | sical input device meets the requirements of ISC   | D 9995 and ISO 9241-410.  |  |            |             |
| P13          | Packag              | ing and documentation  |   |  |            |             |
| P13.1*       | Product             | packaging material type(s): EPE  | weight (kg): 0. 215   |  |            |             |
|              | Product             | packaging material type(s): Carton   | weight (kg):1.3   |  |            |             |
|              | Product             | packaging material type(s): BOX  | weight (kg): 0. 09  |  |            |             |
|              | Product             | packaging material type(s): Laminatio Bag  | weight (kg): 0. 042   |  |            |             |
|              | Product             | packaging material type(s): PE film  | weight (kg): 0. 025   |  |            |             |
|              | Product             | packaging material type(s): PAD-Tray cover   | weight (kg): 0. 842   |  |            |             |
| P13.2*       | Product             | plastic packaging is free from PVC.  |   |  |            |             |
| P13.3*       | Specify             | media for user and product documentation (tick   | box):   |  |            | 一一一         |
|              |                     | ic 🔀, Paper 🔀, Other 🗌   |   |  |            |             |
| P13.4*       |                     | er user and product documentation, please spec   | ify contained percentage of post-consumer recy  | cled   |            |             |
|              |                     | (Japan only 70%)   | · · · · ·   |  |            |             |
| P14          |                     | nal information (See Note B4)  |   |  |            |             |
|              | informat<br>knowled | Supplier makes no representations, guarantees<br>ion contained in this document. All information p<br>ge available at the time of completion, and supp<br>d here is approximate and provided for information<br>ion. | provided by supplier in this document is provided<br>plier shall have no obligation to update such info | based on string to the second se | supplier's | s<br>ation  |

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

### Legal references Europe Annex B

| Reference  | Declaration item             |
|--|------------------------------|
| 2002/95/EC (ROHS Directive)  | P1.1, P4.1                   |
| REACH, Annex XVII  | P1.6, P1.8, P4.2             |
| REACH, Annex XVII  | P1.4                         |
| REACH, Annex XVII  | P1.2                         |
| REACH, Annex XVII  | P1.7                         |
| REACH, Annex XVII  | P1.9                         |
| Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000  | P1.3                         |
| Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002 | P1.5                         |
| 2006/66/EC (Battery and accumulators Directive)  | P2.1, P2.2, P2,3, P3.4, P8.1 |
| 2006/95/EC (Low Voltage Directive)   | P3.1, 3.4                    |
| 2004/108/EEC (New EMC Directive)   | P3.2, 3.4                    |
| 1999/5/EC (R&TTE Directive)  | P3.3, 3.4                    |
| "REACH" Regulation (1907/2006), annex VII  | P1.10                        |
| (EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)                       | P4.3                         |
| REACH article 31, annex II   | P4.3                         |
| 2004/12/EC (Directive on packaging and packaging waste)  | P5.1                         |
| (97/129/EC) (Commission Decision on Identification<br>System for Packaging Materials               | P5.2                         |
| 2037/2000/EC Regulation on Substances that Deplete the Ozone Layer                                 | P5.3                         |
| 2002/96/EC (WEEE directive)  | P3.4, P6.1                   |
| (EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)                       | P7.19                        |

# Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

#### Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

| Commercial name        | Lenovo H530s  | Logo    |  |
|------------------------|---|---------|--|
| Model Number           | 90A9; 10131; 90AB; 10132  | lenovo  |  |
| Issue Date             | 2014-06-03  | Ienovo. |  |
| Additional information | Only 90A9; 10131; is Erp Lot3 Qualified, which is equipped with ES PSU. |         |  |

| P7.1.1 | Product environmental attrib   | utes  |   |                            |  |  |  |
|--------|--|---|---|----------------------------|--|--|--|
| (a)    | Year of manufacture:   |   |   |                            |  |  |  |
| (d)    | rear of manufacture:   |   |   | Availible on product label |  |  |  |
| (e)    | E TEC value (kWh) and capab<br>are disabled and if the system<br>display:  | N/A   |   |                            |  |  |  |
| (f)    | <b>E TEC value</b> (kWh) and capab<br><b>are enabled:</b><br>Cat. B <i>122.36</i><br>Cat. C <i>121.85</i><br>Cat. D <i>122.43</i>      | ility adjustments applied when <b>a</b>   | II discrete graphics cards (dGfx)   |                            |  |  |  |
| (g)    | idle state power demand (Watt  | s);   |   | 33.77                      |  |  |  |
| (h)    | sleep mode power demand (W   | atts);  |   | 1.23                       |  |  |  |
| (i)    | sleep mode with WOL enabled  | power demand (Watts) (where   | enabled);   | 1.23                       |  |  |  |
| (j)    | off mode power demand (Watt  | s);   |   | 0.74                       |  |  |  |
| (k)    | off mode with WOL enabled po   | 0.74  |   |                            |  |  |  |
| (I)    | Internal power supply efficiency   | Internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable): |   |                            |  |  |  |
|        | 10% 78.61% 20% 84.02%  | 50% 86.51% 100% 83.02%  |   |                            |  |  |  |
| (m)    | External power supply efficience   | cy (if applicable):   |   | N/A                        |  |  |  |
|        | 10% 20% 50<br>or Level:  | % 100% Avera  | age ;   |                            |  |  |  |
| (0)    | The minimum number of loadir computers):   | N/A   |   |                            |  |  |  |
| (f)    | the electricity supply system, –<br>used for electrical testing:<br>Test voltage in V and frequenc<br>Total harmonic distortion of the | - information and documentation<br>y in Hz 230V/50Hz<br>e electricity supply system $\leq 2\%$        | equency in Hz, — total harmonic diston<br>n on the instrumentation, set-up and c<br>and circuits used for electrical testing<br>Make and Model **<br>NF;EC1000S; SN:9152124 | rtion of<br>ircuits        |  |  |  |
|        | Digital Watch  | Full range  | CASIO; HS-70W; SN:208Q08R   |                            |  |  |  |

|   |  | Power Meter                            | 0~600V;0~20A                     | YOKOGAWA;WT210;SN:91M94456                           |                           |  |
|---|--|--|----------------------------------|--|---------------------------|--|
|   |  |  |                                  | 0<br>tooto: 608 H1 SN:1024805602                     |                           |  |
|   |  | Hygrothermograph<br>Thermal anemometer | 15~35℃/15~90%<br>0~20m/s,-20~70℃ | testo; 608-H1,SN:1034895602<br>Testo:425:SN:02591883 |                           |  |
|   |  | Light Measuring                        | 1°;1-300cd/ m <sup>2</sup>       | Konica Minolta:LS-110:                               |                           |  |
| (p-1)   | The  | <u> </u>                               |                                  | mation mentioned in points (I) - internal            | PSU                       |  |
| . ,   | efficiency: 80 PLUS® Program   |  |                                  |  |                           |  |
|   | 001 2000 1 10g.um  |  |                                  |  |                           |  |
| (p-2)   | The measurement methodology used to determine information mentioned in points (m) – external PSU efficiency:   |  |                                  |  |                           |  |
|   |  |  |                                  |  |                           |  |
| (p-3)   | The measurement methodology used to determine information mentioned in points (o) – loadingcycles<br>batteries:  |  |                                  |  |                           |  |
|   | N/A  |  |                                  |  |                           |  |
| (p-4) The measurement methodology used to determine information mentioned in maximum, idle, sleep, off mode |  |  |                                  |  |                           |  |
| (p-4)   | power as defined in Point P9.1 in the Product IT Eco Declaration:  |  |                                  |  |                           |  |
| IEC 62301   |  |  |                                  |  |                           |  |
|   |  |  |                                  |  |                           |  |
| (q)   | a) Sequence of steps for achieving a stable condition with respect to power demand::   |  |                                  |  |                           |  |
| Power on -> Wait 5 minutes -> Stable condition  |  |  |                                  |  |                           |  |
| (r) Description of how sleep and/or off mode was selected or programmed:                                    |  |  |                                  |  |                           |  |
| Begin menu -> Power -> Select sleep or off mode   |  |  |                                  |  |                           |  |
| (s)   | (s) Sequence of events required to reach the mode where the equipment automatically changes to sleep and/or<br>off mode:   |  |                                  |  |                           |  |
| Control Panel->Power Options-> Change Settings-> Restore default settings for this plan                     |  |  |                                  |  |                           |  |
|   |  |  |                                  |  |                           |  |
| (t)   | The duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes): 30 minutes |  |                                  |  |                           |  |
| (u)   | (u) The length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes): 45 minutes                   |  |                                  |  |                           |  |
| (v)   | The length of time before the display sleep mode is set to activate after user inactivity (in minutes): 15 minutes   |  |                                  |  |                           |  |
| (w)   | w) Information on the energy-saving potential of power management functionality:   |  |                                  |  |                           |  |
| N/A   |  |  |                                  |  |                           |  |
|   |  |  |                                  |  |                           |  |
| (x) User information on how to enable the power management functionality:                                   |  |  |                                  |  |                           |  |
| Refer to User Guide   |  |  |                                  |  |                           |  |
|   |  | ok Battery Information:                |                                  |  |                           |  |
| Yes   | No   | n/a This notebook user.                | computer is operated by batt     | ery/ies that cannot be accessed and replace          | ced by a non-professional |  |
|   |  |  | lies) in this product of         | annot be easily replaced by users                    | s themselves              |  |
|   |  |  |                                  |  | , (1011301463             |  |
|   |  |  |                                  |  |                           |  |
| Additional information  |  |  |                                  |  |                           |  |
|   |  |  |                                  |  |                           |  |
|   |  |  |                                  |  |                           |  |
| L   |  |  |                                  |  |                           |  |