

Ecma/TC38-TG3/2015/026 (Rev. 1 – 15 April 2015)

Annex B2 - Product environmental attributes Notebooks and Tablets

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

| Brand * | Lenovo | Logo | | |
|---|--|--------|--|--|
| Company name * | Lenovo | | | |
| Contact information * e-mail address | Lenovo Global Environmental Affairs Alvin L Carter alcarter@lenovo.com | Lenovo | | |
| Internet site * | http://www.lenovo.com/social_responsibility/us/en/environment | html | | |
| Additional information | The latest version of this document can be found at: http://www.lenovo.com/ecodeclaration | | | |

| The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration. | | | | | | |
|--|--|--|--|--|--|--|
| Type of product * | Type of product * NB | | | | | |
| Commercial name * | Lenovo V330-14ISK, Lenovo V330-14IKB, Lenovo V330-14ARR, 昭阳 E43-80 | | | | | |
| Model number * | 81AY,81B0,81CJ, 81B1 | | | | | |
| Issue date * | 2017/8/17 | | | | | |
| Intended market * | 🛛 Global 🔲 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other | | | | | |
| Additional information | | | | | | |

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products

| Model nu | mber * | 81AY, 81B0, 81CJ, 81B1 | Logo | Long | | |
|-----------|-----------------------|---|-----------------|-------------|-----|-----------|
| Issue dat | e * | 2017/8/17 | | Lend | | Оти |
| Product | environ | mental attributes - Legal requirements | | Require | men | t met |
| Item | | | | Yes | No | n.a. |
| P1 | Hazardo | ous substances and preparations | | | | |
| P1.1* | Products | s do comply with current European RoHS Directive. (See legal reference and NOTE | B1) | \boxtimes | | |
| P1.2* | | s do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value. | | \square | | |
| P1.3* | hydrobro trichloro | s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), pmofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachle ethane, methyl bromide (see legal reference). Comment: Legal reference has no ma ration values. | | | | |
| P1.4* | terpheny | s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlo /l (PCT) in preparations (see legal reference). | | \boxtimes | | |
| P1.5* | | s do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carb ntaining at least 48% per mass of chlorine in the SCCP (see legal reference). | on atoms in th | e 🔀 | | |
| P1.6* | (see leg | th direct and prolonged skin contact do not release nickel in concentrations above 0, al reference). nt: Max limit in legal reference when tested according to EN1811:2011-5. | 5 μg/cm²/weeł | (🖂 | | |
| P1.7* | | Article 33 information about substances in articles is available at (add URL or mail c | contact): | \square | | |
| P2 | Batterie | | | | | |
| P2.1* | If the pro symbol. | oduct contains a battery or an accumulator, the battery/accumulator is labeled with the Information on proper disposal is provided in user manual. (See legal reference) | ne disposal | \boxtimes | | |
| P2.2* | Batteries referenc | s or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmi e) | ium. (See lega | I 🛛 | | |
| P2.3* | Batteries | s and accumulators are readily removable. (See legal reference) | | \boxtimes | | |
| P3 | Conform | nity verification & Eco design (ErP) | | | | |
| P3.1* | The proc | duct is CE-marked to show conformance with applicable legal requirements (see legal laration of Conformity can be requested at (add link or e-mail address): | al reference). | \boxtimes | | |
| P3.2* | The proc | duct complies with the Eco design requirements for energy-related products, al reference). | | \boxtimes | | |
| | , U | d information is; X given in item P15 or added to this document, available at (add URL): | | | | \square |
| P5 | Product | packaging | | | | |
| P5.1* | Packagi | ng and packaging components do not contain more than 0,01% lead, mercury ent chromium by weight of these together. | , cadmium an | d 🔀 | | |
| P5.2* | The pac | kaging materials are marked with abbreviations and numbers indicating the nature o e legal reference). | f the material(| s) 🔀 | | |
| P5.3* | The pro Protocol | duct packaging material is free from ozone depleting substances as specified i (see legal reference). nt: Legal reference has no maximum concentration values. | in the Montrea | al 🔀 | | |
| P6 | Treatme | nt information | | | | |
| P6.1* | Informati | on for recyclers/treatment facilities is available (see legal reference). | | \boxtimes | | |

Annex B1 of ECMA-370 5th edition (Lenovo) 2015-04-08

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

| Model number * | | 81AY, 81B0, 81CJ,81B1 | Logo | | | |
|----------------|------------------------------------|---|-------------------------------|------------------------|------|------------------------|
| Issue dat | :e * | 2017/8/17 | | Len | ovc | D _{EM} |
| Product | | mental attributes - Market requirements (See General NOTE GN onmental conscious design | | Require | mont | met |
| Item | | tory to fill in. Additional information regarding each item may be found under P14. | | Yes | No | n.a. |
| P7 | Design | mbly, recycling | | | 110 | |
| P7.1* | | t have to be treated separately are easily separable | | \square | | |
| P7.2* | Plastic m | aterials in covers/housing have no surface coating. | | | | |
| P7.3* | Plastic p | arts > 100 g consist of one material or of easily separable materials. | | | Ē | Ē |
| P7.4* | Plastic p | | | Ē | | |
| P7.5 | Plastic p | arts are free from metal inlays or have inlays that can be removed with commonly a | available tools. | | | |
| P7.6* | Labels a | re easily separable. (This requirement does not apply to safety/regulatory labels). | | $\overline{\boxtimes}$ | | |
| | Product | lifetime | | | | |
| P7.7* | Upgradir | ng can be done e.g. with processor, memory, cards or drives | | \boxtimes | | |
| P7.8* | Upgradir | ig can be done using commonly available tools | | \boxtimes | | |
| P7.9 | Spare pa | arts are available after end of production for: 5 years | | | | |
| P7.10 | Service i | s available after end of production for: 5 years | | | | |
| | | and substance requirements | | | | |
| P7.11* | | cover/housing material type (e.g. plastics, metal, aluminum): | | | | |
| P7.12 | | type: PC+ABS Material type: Metal Materia n materials of external electrical cables are PVC free. | al type: <mark>Aluminu</mark> | <u>m</u> | | |
| P7.12 | | n materials of external electrical cables are PVC free. | | <u> </u> | | <u> </u> |
| P7.13 P7.14 | | | romine and 0 10/ | | | <u> </u> |
| 17.14 | weight (' polyvinyl | plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) b 1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) og more than 25% post-consumer recycled content. | e retardants, and | I – | | |
| P7.15 | Printed | circuit boards, PCBs (without components) are low halogen: all 🔀 PCBs > as defined in IEC 61249-2-21. (See 1NOTE B2) | 25 g 🗌 are low | v 🖂 | | |
| P7.16 | Flame re Marking: | tarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: (FR40) | | \boxtimes | | |
| P7.17 | | nemical specifications of flame retardants in printed circuit boards > 25 g (without c PA (additive), TBBPA (reactive) (See NOTE B3), Other: <i>DOPO</i> , CAS #: 3594 | | \boxtimes | | |
| | | nemical specifications of flame retardants in printed circuit boards (without compon g ISO 1043-4: FR(40) | ents) > 25 g | \boxtimes | | |
| P7.18 | concentr 1. Chem | ame retarded plastic parts > 25 g contain the following flame retardant substance ations above 0,1%: ical name: , CAS #: (See NOTE B4) ical name: , CAS #: " | es/preparations ir | | | |
| | 3. Chem | ical name: , CAS #: " nemical specifications of flame retardants in plastic parts > 25 g according ISO 104 | 3-4: | | | |
| P7.19 | | parts > 25 g, flame retardant substances/preparations above 0,1% are used which | | <u> </u> | Π | |
| | assigned | the following Risk phrases; and Hazard statements: | | | | |
| P7.20* | | rce(s) for these classifications is/are found at (add URL(s)): , (S sumer recycled plastic material content is used in the product (See Note B6): | See note B5) | \square | | |
| | lf YES; a a) Of t a pe or | t least one of the two alternatives below shall be answered; otal plastic parts' weight > 25 g, the postconsumer recycled plastic material conten ercentage of total plastic by weight) is 0.02% . | t (calculated as | | | |

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

| Model number * 814 | AY, 81B0, 81CJ,81B1 | | | Logo | | |
|-------------------------------------|--|---|-------------------------------------|------------------|-----------------|-------------|
| Issue date * 201 | 7/8/17 | | | | Lenovo | |
| Product environment | tal attributes - Market r | equirements (conti | nued) | | Requiremen | t met |
| Item | | | | | Yes No | n.a. |
| Material and | substance requirements | (continued) | | | | |
| | stic material content is used | | OTE B7): | | | \boxtimes |
| If YES; at lea | st one of the two alternative | es below shall be answ | ered; | | | |
| | plastic parts' weight > 25 g plastic by weight) is | , the biobased plastic 6. | material content (calcul | ated as a percen | tage | |
| | ght of the biobased plastic | material is g. | | | | |
| | are free from mercury, i.e. used specify: Number of lar | | um mercury content per | r lamp: mg | | \boxtimes |
| P8 Batteries | | | · · · | | | |
| • | ical composition: Lithium-i | on Polymer | | | | |
| | umption (See NOTE B8) | | | | | |
| P9.1 For the produ Energy mode * | ict the following power leve Power level at | Is or energy consumption Power level at | ons are reported: Power level at | Reference/Stan | dard for energy | |
| | 100 V AC | 115 V AC | 230 V AC | modes and test | | |
| Peak (On-max) | 65 W | 65 W | 65 W | Full load | | |
| Category NBI2 | | | | | | |
| Short Idle State - WOL Enabled | 6.690 W | 6.807 W | 7.628 W | Reference | | |
| Long Idle State - WOL Enabled | 4.618 W | 4.312 W | 4.321 W | Reference | | |
| Sleep (S3) - WOL Enable | ed 0.728 W | 0.724 W | 0.769 W | Reference | | |
| Sleep (S3) - WOL Disab | led 0.679 W | 0.685 W | 0.714 W | Reference | | |
| Off (S5) - WOL Enabled | 0.386 W | 0.389 W | 0.437 W | Reference | | |
| Off (S5) - WOL Disabled | 0.390 W | 0.391 W | 0.436 W | Reference | | |
| | W | W | W | Reference | | |
| Category NBI1 | | | | | | |
| Short Idle State - WOL Enabled | W | W | W | Reference | | |
| Long Idle State - WOL Enabled | W | W | W | Reference | | |
| Sleep (S3) - WOL Enabl | ed W | W | W | Reference | | |
| Sleep (S3) - WOL Disab | led W | W | W | Reference | | |
| Off (S5) - WOL Enabled | W | W | W | Reference | | |
| Off (S5) - WOL Disabled | W | W | W | Reference | | |
| | W | W | W | Reference | | |
| Category | | | | | | |
| Short Idle State - WOL Enabled | W | W | W | Reference | | |
| Long Idle State - WOL Enabled | W | W | W | Reference | | |
| Sleep (S3) - WOL Enabl | ed W | W | W | Reference | | |

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see <u>http://www.ecma-international.org/publications/standards/Ecma-370.htm</u>

| Sleep (S3 | 3) - WOL Disabled | W | W | W | Reference |
|------------------------|--|--------------------------------|-----------------------------------|-----------------------|---|
| Off (S5) - | WOL Enabled | W | W | W | Reference |
| Off (S5) - | WOL Disabled | W | W | W | Reference |
| | | W | W | W | Reference |
| EPS No-le | oad | 0.070 W | 0.072 W | 0.119 W | |
| | er supply / charger plugged in th disconnected from the product.) | e | | | |
| PTEC * Typical Ei | nergy Consumption | W | W | W | |
| ETEC * Annual Er | nergy Consumption | 24.704 kWh/year | 24.738 kWh/year | 27.146 kWh/year | |
| External F | Power Supply Efficie | ency Level (Internation | al Efficiency Marking F | Protocol) * : V | |
| Display re megapixe | esolution * : 1920*1 els | 080 | | | |
| . . | | ave mode: 10 minutes | 3 | | |
| P9.2* | Information abou | t the energy save func | tion is provided with th | e product. | |
| P9.3 | Energy efficiency | class (monitors only): | 12 | | |
| P10 | Emissions | | | | |
| | Noise emission | - Declared according | to ISO 9296 (See NOT | ГЕ В9) | |
| P10.1 | Mode | Mode description | | Statistical upper lin | nit A-weighted sound power level, <i>L_{WA,c}</i> (B) |
| | Idle | * Idle | | * 2.8 | |
| | Operation | * CPU Operating | | * 4.4 | |
| | Other mode | | | | |
| | Measured accord | ling to: 🔀 ISO 7779 [Other | ECMA-74 (only if not covered b | by ECMA-74) | |

| Model nu | umber * | 81AY, 81B0, 81 | ICJ,81B1 | | | L | ogo | | | |
|----------|--|--------------------------------------|--|--|--|--|----------------|-------------|-----------|-------------|
| Issue da | te * | 2017/8/17 | | | | | | Lenc | VO | тм |
| Product | environ | mental attribut | es - Market require | ments (cor | ntinued) | | | Require | ment | met |
| Item | | | | | | | | Yes | No | n.a. |
| | Electro | magnetic emissi | ons | | | | | | | |
| P10.4 | program | ı(s): | the requirement for low | / frequency el | lectromagnetic field | is of the follow | ving voluntary | / | | \boxtimes |
| P12 | | mics for comput | | | | | | | | |
| P12.1* | The disp | play meets the erg | gonomic requirements | of ISO 9241- | 307 for visual displa | ay technologi | es. | | | \boxtimes |
| P12.2* | The physical input device meets the requirements of ISO 9995 and ISO 9241-410. | | | | | | | | | |
| P13 | Packag | ing and docume | ntation | | | | | | | |
| P13.1* | Product Product | packaging mater packaging mater | ial type(s): paper | weight (kg weight (kg weight (kg | j): 0.09 | | | | | |
| P13.2* | Product | plastic primary pa | ackaging is free from P | VC. | | | | \boxtimes | | |
| P13.3* | For product primary corrugated fiberboard packaging, specify the contained percentage of minimum post- | | | | | | | | | |
| P13.4* | | media for user ar ronic, 🔀 Paper, | nd product documentat | ion (tick box): | | | | | | |
| P13.5 | Ùser an | | s item if paper docume entation on paper medi | | | | | | | |
| | Totally o | hlorine-free | | | | | | | | |
| | | al chlorine-free | | | | | | H | | |
| | | ed chlorine-free | | | | | | H | | |
| P14 | Volunta | ry programs | | | | | | | | |
| P14.1 | The pro | duct meets the re | quirements of the follo | wing voluntar | y program(s): | | | | | |
| | ENERG Eco-labo Eco-labo | | Criteria version: 6 Criteria version: Criteria version: | .1 | Date: 2017/9/22 Date: Date: | Product ca Product ca Product ca | • • | | | |
| P15 | | nal information | | | | | <u> </u> | | | |
| P9 | | | specific configuratio | on may vary; | description of the | e tested prod | luct configur | ation: | | |
| | | | | | | | U | | | |
| | | | | | | | | | | |
| - | | | | | | | | | | |

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B2

| Reference | Declaration item |
|--|------------------------|
| Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications. | P1.1 |
| Regulation (EC) 1907/2006(REACH, Annex XVII | P1.2, P1.4, P1.6, P1.7 |
| Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances) | P1.3, P5.3 |
| Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002 | P1.5 |
| Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator. | P2.1, P2.2, P2,3, P8.1 |
| Directive 2006/95/EC (Low Voltage Directive) | P3.1 |
| Directive 2004/108/EC (EMC Directive) | P3.1 |
| Directive 1999/5/EC (R&TTE Directive) | P3.1 |
| Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions | P3.1, P3.2 |
| Regulation (EC) No 1272/2008 (CLP Regulation) | P7.19 |
| Directive 2004/12/EC (Packaging Directive) | P5.1 |
| Decision 97/129/EC (Secondary packaging legislation) | P5.2 |
| Directive 2012/19/EU (WEEE directive) | P6.1 |

Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

| Commercial name | Lenovo V330-14ISK, Lenovo V330-14IKB, Lenovo V330-14ARR, 昭阳 E43-80 | Logo |
|------------------------|---|--------|
| Model Number | 81AY, 81B0, 81CJ,81B1 | |
| Issue Date | 2017/8/17 | Lenovo |
| Additional information | | |

| (d) | year of manufacture: | | | | 2017 | | |
|--|---|--|--|--|--|--|--|
| (e) | Etec value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete graphics cards (dGfx) are disabled and if the system is tested with switchable graphics mode with UMA driving the display. | | | | | | |
| f) | Etec value (kWh) per ErP Lot 3 Catego enable | ory and capability adju | stments applied when a | all discrete graphics of | cards (dGfx) are | | |
| | | Category A (according to ErP Lot 3) | Category B (according to ErP Lot 3) | Category C (according to ErP Lot 3) | Category D (according to ErP Lot 3) | | |
| | Memory over base [GB] | 20 | 20 | | | | |
| lents sting | Additional internal storage | Yes (Yes / No) | Yes (Yes / No) | (Yes / No) | (Yes / No) | | |
| capability adjustments applied during testing | Discrete television tuner | No (Yes / No) | No (Yes / No) | (Yes / No) | (Yes / No) | | |
| | Discrete Audio Card | No (Yes / No) | No (Yes / No) | (Yes / No) | (Yes / No) | | |
| capa app | Discrete graphics Card(s) [number / #] | No #: (Yes / No) | Yes #: 1 (Yes / No) | #: (Yes / No) | #: (Yes / No) | | |
| | Category of discrete graphics Card(s) | | G1 | | | | |
| sults | Etec Value (kWh) - dGfx disabled all discrete graphics cards (dGfx) are disabled/ UMA is active for switchable graphics/ product has no graphics cards (dGfx) | 15.36 | 14.94 | | | | |
| Test results | Etec Value (kWh) - dGfx enabled all discrete graphics cards (dGfx) are enabled | | | | | | |
| (g) | Idle state power demand (Watts); | I | | | A: 4.66 B: 4.52 | | |
| (h) | Sleep mode power demand (Watts); | | | | A: 0.79 B: 0.77 | | |
| (i) | Sleep mode with WOL enabled power | demand (Watts) (where | e enabled); | | | | |
| (j) | Off mode power demand (Watts); | | | | A: 0.46 B: 0.46 | | |
| k) | Off mode with WOL enabled power der | mand (Watts) (where e | nabled); | | <i>D</i> . 0.40 | | |
| (1) | Internal power supply efficiency at 10 % | %, 20 %, 50 % and 100 | % of rated output pow | er (if applicable): | | | |
| | 10% 20% 50% | 100% Ave | rage | | | | |
| m) | external power supply efficiency (if app | licable)*: | | | | | |
| | Average active efficiency: 45W:81.449 | %,87.60%,88.51%,88.5 | 53%,65W:89.04%,89.18 | 8% | | | |
| (0) | *internal note: show values for all available external Minimum number of loading cycles that | | stand (applies only to n | otebook computers): | 300CYCLES | | |
| (p-1) | Measurement methodology used to de | tormino information | ntioned in points (1) | atomol DCLL officiar and | | | |

| (p-2) | Measurement methodology used to determine information mentioned in points (m) – external PSU efficiency: EPA "Test Method for Calculating the Energy Efficiency of Single-voltage External AC-DC and AC-AC Power Supplies" dated August 11, 2004 | | | | | | |
|---|--|---|-------------------------------------|-----|--|--|--|
| (p-3) | Measurement methodology used to determine information mentioned in points (o) – loading cycles batteries: IEC 61960 measurement methodology | | | | | | |
| (p-4) | Measurement methodology used to determine information mentioned in maximum, idle, sleep, off mode power as defined in Point P9.1 in the Product IT Eco Declaration: IEC 62623/ IEC EN50564:2011 measurement methodology | | | | | | |
| (q) | Sequence of steps for | r achieving a stable condition with respect to power IEC 62623/ IEC EN50564:2011 measurement n | | | | | |
| (r) | Description of how sl | eep and/or off mode was selected or programmed: Energy-star requirement | | | | | |
| (s) | Sequence of events off mode: | equired to reach the mode where the equipment au | tomatically changes to sleep and/or | | | | |
| | on mode. | Energy-star requirement | | | | | |
| (t) | | e condition before the computer automatically re not exceed the applicable power demand requirement | | 30 | | | |
| (u) | Length of time after | a period of user inactivity in which the compute ver power demand requirement than sleep mode (in | r automatically reaches a power | NA | | | |
| (v) | Length of time befo | re the display sleep mode is set to activate after | user inactivity (in minutes): | 10 | | | |
| (w) | Information on the er | ergy-saving potential of power management function Based on user manual | nality: | | | | |
| (x) | user information on h | ow to enable the power management functionality: | | | | | |
| | | Based on user manual | | | | | |
| (Z) | | easurements: — test voltage in V and frequency in lem, — information and documentation on the instruction of the instruction | mentation, set-up and circuits used | | | | |
| Addition | Notebook Battery | Information: | | | | | |
| 710011011 | | Battery[ies] not user replaceable | Battery[ies] user replaceable | n/a | | | |
| | | The battery[ies] in this product cannot be easily replaced by users themselves. ¹⁾ | | | | | |
| Internal/b | uilt-in Battery | | | | | | |
| External/o | detachable Battery | | | | | | |
| Bios Back | kup Battery | | | | | | |
| Other: | | | | | | | |
| Additiona | l information | | | | | | |
| | | | | | | | |
| 1) | | | | | | | |
| The battery[ies Akymynaropna Las baterias d Výměnu bateri Brugeren kan Der Akku/die A Kasutajad ei s H μπαταρία[-ε· La/les batterie Korisnik ne mα La batteria/le b Lietotāji paši n Šio gaminio ba A termék akku II-batterija/batt Batteriet [ene] De batterij(en) Užytkownik nie A ou as bateria Bateria (bateri Bateriu(-ie) v t Batterij/batterije | Tra[μτε] δατερικη[μ] в този i e este producto no pueden ie/baterií v tomto výrobku by ikke uden videre udskifte ba kkus dieses Produkts kann aa selle toote akut/akusid is g στο προϊόν αυτό δεν μπο (s présente(s) dans ce prod bže lako zamijeniti Bateriju s poatterie in questo prodotto n evar nomainīt šā ražojuma aterijos [bateriju] pats vartot mulátorát/akkumulátorait a eriji fdan il-prodott ma tista: i dette produktet kan ikke le in dit product is (zijn) door e može sam w łatwy sposób as deste produto não poder ile) din acest produs nu poa omto výrobku nemôže vymi v tem izdelku uporabniki sa n akku [akut] ei[vät] ole helj | ουύν να αντικατασταθούν εύκολα από τους ίδιους τους χρήστες uit ne peuvent être facilement remplacée(s) par les utilisateurs e am u ovom proizvodu. on può/possono essere facilmente sostituita/e dall'utente. akumulatoru(-us). ojas negali lengvai pakeisti. felhasználó nem tudja egyedül egyszerűen kicserélni. (/jistgħux tiġi/jiġu sostitwita/i mill-utenti stess. tt erstattes av brukerne selv. fe gebruiker niet gemakkeljik vervangbaar. wymienić baterii w tym produkcie. s ser facilmente substituídas pelos próprios utilizadores. te (pot) fi uşor înlocuită (înlocuite) de utilizatorii înşişi. eñať používateľ. mi ne morejo zlahka zamenjati. osoti käyttäjän vaihdettavissa. | werden. | | | | |
| Det ar inte enk | telt för kunden att själv byta | ut patteriet/batterierna. | | | | | |