

Ecma/TC38-TG3/2015/026 (Rev. 1 - 15 April 2015)

Annex B2 - Product environmental attributes **Notebooks and Tablets**

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lenovo	Logo
Company name *	Lenovo	
Contact information * e-mail address		
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment	.html
Additional information	The latest version of this document can be found at: http://www.lenovo.com/ecodeclaration	

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.					
Type of product *	NB				
Commercial name *	Lenovo ideapad 720S-14, Lenovo XiaoXin Air Pro				
Model number *	80XC, 80XD				
Issue date *	2017/4/6				
Intended market *	🔀 Global 📃 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other				
Additional information					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template: P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products

Model nu	mber *	80XC, 80XD	Logo			
Issue dat	e *	2017/4/6		Lend		D
Product	environ	mental attributes - Legal requirements		Require	ment	tmet
Item				Yes	No	n.a.
P1	Hazardo	ous substances and preparations				
P1.1*		${\mathfrak s}$ do comply with current European RoHS Directive. (See legal reference and NOTE	B1)	\boxtimes		
P1.2*		s do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value.		\square		
P1.3*	hydrobro trichloro	s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), pmofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachl ethane, methyl bromide (see legal reference). Comment: Legal reference has no ma ration values.				
P1.4*	terpheny	s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychl /I (PCT) in preparations (see legal reference).		\square		
P1.5*		s do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carb ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).	on atoms in the	e 🛛		
P1.6*	(see lega	th direct and prolonged skin contact do not release nickel in concentrations above 0, al reference). nt: Max limit in legal reference when tested according to EN1811:2011-5.	5 μg/cm²/week			
P1.7*		Article 33 information about substances in articles is available at (add URL or mail o	contact):	\square		
P2	Batterie	S				
P2.1*		oduct contains a battery or an accumulator, the battery/accumulator is labeled with th Information on proper disposal is provided in user manual. (See legal reference)	ne disposal	\square		
P2.2*	Batteries referenc	s or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadm e)	ium. (See lega			
P2.3*	Batteries	s and accumulators are readily removable. (See legal reference)		\square		
P3	Conform	nity verification & Eco design (ErP)				
P3.1*	The proc	duct is CE-marked to show conformance with applicable legal requirements (see leg	al reference).	\boxtimes		
		laration of Conformity can be requested at (add link or e-mail address):				
P3.2*	•	duct complies with the Eco design requirements for energy-related products, al reference).		\square		
	-	d information is; given in item P15 or added to this document,				
		available at (add URL):				
P5	Product	packaging				
P5.1*	Packagi hexavale	ng and packaging components do not contain more than 0,01% lead, mercury ent chromium by weight of these together.	, cadmium an	d 🔀		
P5.2*	The pac	kaging materials are marked with abbreviations and numbers indicating the nature one legal reference).	f the material(s	s) 🔀		
P5.3*	The pro Protocol	duct packaging material is free from ozone depleting substances as specified (see legal reference). nt: Legal reference has no maximum concentration values.	in the Montrea	al 🔀		
P6		nt information				
P6.1*	Informati	on for recyclers/treatment facilities is available (see legal reference).		\square		

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model number *		80XC, 80XD	Logo				
Issue dat	te *	2017/4/6		Len	_enovo.		
Product		mental attributes - Market requirements (See General NOTE GN onmental conscious design	below)	Require	ment	met	
Item		tory to fill in. Additional information regarding each item may be found under P14.		Yes	No	n.a.	
P7	Design	mbly, recycling					
P7.1*		It have to be treated separately are easily separable		\square			
P7.2*	Plastic m	naterials in covers/housing have no surface coating.					
P7.3*		arts > 100 g consist of one material or of easily separable materials.		<u> </u>			
P7.4*	Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.						
P7.5		arts are free from metal inlays or have inlays that can be removed with commonly a	available tools.		Ħ	Ħ	
P7.6*		re easily separable. (This requirement does not apply to safety/regulatory labels).			Ħ	Ħ	
	Product						
P7.7*		ig can be done e.g. with processor, memory, cards or drives			\square		
P7.8*	Upgradir	ng can be done using commonly available tools			Ē		
P7.9		arts are available after end of production for: 5 years					
P7.10	Service i	s available after end of production for: 5 years				Ħ	
	Material	and substance requirements					
P7.11*		cover/housing material type (e.g. plastics, metal, aluminum):					
			al type: <mark>Alumin</mark>	um			
P7.12		n materials of external electrical cables are PVC free.				\square	
P7.13		n materials of internal electrical cables are PVC free.			\boxtimes		
P7.14	weight (' polyvinyl	plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) b 1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) ng more than 25% post-consumer recycled content.	e retardants, ar	nd			
P7.15	Printed c	circuit boards, PCBs (without components) are low halogen: all ⊠PCBs > 25 g ⊠ ad in IEC 61249-2-21. (See 1NOTE B2)	are low haloge	en 🔀			
P7.16	Marking:	tarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: > <i>PC+ABS-TD15</i> <		\boxtimes			
P7.17		nemical specifications of flame retardants in printed circuit boards > 25 g (without co PA (additive), TBBPA (reactive) (See NOTE B3), Other: <i>D0P0</i> ,, CAS #: 35948					
		nemical specifications of flame retardants in printed circuit boards (without compone g ISO 1043-4: <i>FR(40)</i>	ents) > 25 g	\square			
P7.18	concentr 1. Chemi 2. Chemi	ame retarded plastic parts > 25 g contain the following flame retardant substance ations above 0,1%: ical name: , CAS #: (See NOTE B4) ical name: , CAS #: " ical name: , CAS #: "	es/preparations	in			
	<u>Alt. 2: </u> Cł	nemical specifications of flame retardants in plastic parts > 25 g according ISO 104	3-4:				
P7.19	•	parts > 25 g, flame retardant substances/preparations above 0,1% are used which the following Risk phrases; and Hazard statements:	n have been				
	The source(s) for these classifications is/are found at (add URL(s)): , (See note B5)						
P7.20*		sumer recycled plastic material content is used in the product (See Note B6):	,	\boxtimes			
	a) Oft ape or	It least one of the two alternatives below shall be answered; otal plastic parts' weight > 25 g, the postconsumer recycled plastic material conten ercentage of total plastic by weight) is <i>0.1</i> %.	nt (calculated as				

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Material and substance requirements (continued) Image: Continued Control Intervent Int	Model numb	er * 80	XC, 80	XD			Logo		
Item Yes No No P7.21 Biobased plastic material content is used in the product (See NOTE B7): □ □ 0 0 P7.22 Light sources are free from mercury, is less than 0,1 mg/lamp. mercury content per lamp: mg 0	Issue date *	20	17/4/6					Lenovo	н
Item Yes No. n. P7.21 Biobased plastic material contents (continued)	Product en	vironmer	ntal att	ributes - Market r	equirements (cont	tinued)		Requirement	met
Material and substance requirements (continued) Image: Content is used in the product (See NOTE B7): Image: Content is used in the product (See NOTE B7): P7.22 Light sources are from mercury, is less han 0,1 mpRamp. Image: Content is used in the product (See NOTE B7): Image: Content is used in the product (See NOTE B7): P8 Batteries Image: Content is used in the product (See NOTE B8): Image: Content is used in the product is content is used in the product (See NOTE B8): P8 For the product the following power levels or energy consumptions are reported: Former level at Content is used in the product is					equirements (com	indea			n.a.
P7.21 Biobased plaste material content is used in the product (See NOTE B7): P7.22 Light sources are free from mercury, leaves hand,		latorial and	d subs	tance requirements	(continued)			100 110	
P7.22 Light sources are free from mercury. Le less than 0.1 mg/lamp: and maximum mercury content per lamp: mg P8 Batteries operated composition: P9 Energy consumption (See NOTE B8) P9.1 Teatter chemical composition: P9 Energy consumption (See NOTE B8) P9.1 To the product the following power levels or energy consumptions are reported: Energy mode's and test method in the power level at Power level at 200 V AC Power level at 200 V AC Power level at 150 V AC 65 W 65 W 65 W 65 W 70 C 1150 V AC 7150 V AC						NOTE B7):			
P8 Batteries P91 Energy comment composition: Performance in the following power level as or energy consumptions are reported: P1 For the product the following power level as a formation of the product level at 100 V AC Power level at 230 V AC Reference/Standard for energy modes and lest method." Peak (On-max) 65 W 65 W 65 W 65 W 7 W Reference/Standard for energy modes and lest method." Peak (On-max) 65 W 65 W 65 W 65 W 7 W Reference Short file State - WOL 2.768 W 2.762 W 2.915 W Reference Short file State - WOL 2.788 W 2.762 W 0.543 W Reference Steep (S3) - WOL Enabled 0.462 W 0.4763 W 0.543 W Reference Off (S5) - WOL Enabled 0.199 W 0.203 W 0.2667 W Reference Off (S5) - WOL Enabled 0.199 W 0.203 W 0.2667 W Reference Category NBI2 233 W 2.329 W 2.454 W Reference Short file State - WOL 2.33 W 2.329 W 2.454 W Reference Steep (S3) - WOL Enabled 0.4258 W 0.435 W 0	P7.22* L	ight source	s are fr	ee from mercury, i.e.	less than 0,1 mg/lam	0.	or lowp: ma		
P8.1* Battery chemical composition: P P9 Energy consumption (See NOTE B) P0.1 For the product the following power levels or energy consumptions are reported: Reference/Standard for energy mode* Peak (0n-max) 65 W 65 W 65 W Reference/Standard for energy mode* Category NBI1 S05 W 65 W 65 W Reference/Standard for energy mode* Long Idle State - WOL 4.701 W 5.05 W 5.182 W Reference Long Idle State - WOL 2.768 W 2.762 W 2.915 W Reference Steep (S3) - WOL Enabled 0.462 W 0.4763 W 0.543 W Reference Steep (S3) - WOL Enabled 0.462 W 0.4763 W 0.2567 W Reference Off (S5) - WOL Enabled 0.199 W 0.203 W 0.2567 W Reference Category NBI2 Energies Energies Energies Energies Short Idle State - WOL 2.33 W 2.329 W 2.454 W Reference Steep (S3) - WOL Enabled 0.4258 W 0.435 W 0.529 W Reference Steep (S3) - WOL Enabled 0.4258 W 0.435 W 0.529 W Refere			useu s	specity. Number of lai	nps. anu maxii		er lamp. mg		
P9 Energy consumption (5ee NOTE B8) Reference/Standard for energy P9.1 For the product the following power levels or energy consumptions are reported: Reference/Standard for energy modes and test method.* Peak (0n-max) 65 W 65 W 65 W Full foad Category NBI1 50 W 65 W 50 W Full foad Short fide State - WOL 4.701 W 5.05 W 2.915 W Reference Short fide State - WOL 2.768 W 2.762 W 2.915 W Reference Steep (33) - WOL Enabled 0.462 W 0.4763 W 0.543 W Reference Off (55) - WOL Disabled 0.462 W 0.4763 W 0.2567 W Reference Off (55) - WOL Disabled 0.499 W 0.203 W 0.2567 W Reference Off (55) - WOL Disabled 0.199 W 0.203 W 0.2567 W Reference Short fide State - WOL 2.33 W 2.329 W 2.454 W Reference Steep (53) - WOL Disabled 0.4258 W 0.435 W 0.529 W Reference Steep (53) - WOL Enabled 0.4258 W 0.435 W 0.529 W Reference Off (55) - WOL Enabled 0.2			nical co	omposition:					\square
P9.1 For the product the following power levels or energy consumptions are reported: Reference: Energy mode* Power level at 100 V AC Power level at 230 V AC Reference: Refere				•					
Energy mode* Power level at 100 V AC Power level at 230 V AC Power level AC					ls or energy consumption	tions are reported:			
Category NB1 File File File File Short Idle State - WOL Enabled 4.701 W 5.05 W 5.182 W Reference Long Idle State - WOL Enabled 2.768 W 2.762 W 2.915 W Reference Sleep (S3) - WOL Enabled 0.462 W 0.4763 W 0.543 W Reference Sleep (S3) - WOL Enabled 0.462 W 0.4763 W 0.543 W Reference Off (S5) - WOL Enabled 0.199 W 0.203 W 0.2567 W Reference Off (S5) - WOL Enabled 0.199 W 0.203 W 0.2567 W Reference Category NB12 C C C C Short Idle State - WOL Enabled 4.28W 4.309W 4.833W Reference Long Idle State - WOL Enabled 2.33 W 2.329 W 2.454 W Reference Sileep (S3) - WOL Enabled 0.4258 W 0.435 W 0.529 W Reference Sileep (S3) - WOL Enabled 0.211 W 0.219 W 0.308 W Reference Off (S5) - WOL Enabled 0.211 W 0.219 W 0.308 W Reference Sileep (S3) - WOL Disabled 0.6228 W 0.435				Power level at	Power level at	Power level at			
Short Idle State - WOL Enabled 4.701 W 5.05 W 5.182 W Reference Long Idle State - WOL Enabled 2.768 W 2.762 W 2.915 W Reference Sileep (S3) - WOL Enabled 0.462 W 0.4763 W 0.543 W Reference Sileep (S3) - WOL Enabled 0.462 W 0.4763 W 0.543 W Reference Off (S5) - WOL Disabled 0.462 W 0.4763 W 0.543 W Reference Off (S5) - WOL Disabled 0.199 W 0.203 W 0.2567 W Reference Category NBI2 Image: Comparison of the state of the st	Peak (On-ma	ax)		65 W	65 W	65 W	Full load		
Enabled Normality Normality Normality Long Idle State - WOL 2.768 W 2.762 W 2.915 W Reference Sleep (S3) - WOL Enabled 0.462 W 0.4763 W 0.543 W Reference Sleep (S3) - WOL Disabled 0.462 W 0.4763 W 0.543 W Reference Off (S5) - WOL Disabled 0.199 W 0.203 W 0.2567 W Reference Off (S5) - WOL Disabled 0.199 W 0.203 W 0.2567 W Reference Category NB12 Short Idle State - WOL 4.28W 4.309W 4.833W Reference Short Idle State - WOL 2.33 W 2.329 W 2.454 W Reference Sleep (S3) - WOL Enabled 0.4258 W 0.435 W 0.529 W Reference Sleep (S3) - WOL Enabled 0.4258 W 0.435 W 0.529 W Reference Off (S5) - WOL Disabled 0.211 W 0.219 W 0.308 W Reference Off (S5) - WOL Disabled 0.211 W 0.219 W 0.308 W Reference Off (S5) - WOL Disabled 0.527 W 0.529 W Reference EPS No-load 0.5287 W 0.529 W Reference<	Category	NBI1							
Enabled Out Add State Reference Sleep (S3) - WOL Enabled 0.462 W 0.4763 W 0.543 W Reference Off (S5) - WOL Enabled 0.199 W 0.203 W 0.2567 W Reference Off (S5) - WOL Disabled 0.199 W 0.203 W 0.2567 W Reference Off (S5) - WOL Disabled 0.199 W 0.203 W 0.2567 W Reference Category NBI2 Image: Comparison of the state of the		tate - WOL		4.701 W	5.05 W	5.182 W	Reference		
Step (S) WOL Disabled 0.462 W 0.4763 W 0.543 W Reference Off (S) WOL Disabled 0.199 W 0.203 W 0.2567 W Reference Off (S) WOL Disabled 0.199 W 0.203 W 0.2567 W Reference Category NBI2 Image: Constraint of the state - WOL enabled 4.28W 4.309W 4.833W Reference Short Idle State - WOL enabled 0.4258 W 4.309W 4.833W Reference Sleep (S) - WOL Enabled 0.4258 W 0.435 W 0.529 W Reference Sleep (S) - WOL Disabled 0.4258 W 0.435 W 0.529 W Reference Off (S) - WOL Disabled 0.211 W 0.219 W 0.308 W Reference Off (S) - WOL Disabled 0.211 W 0.219 W 0.308 W Reference EPS No-load 0.05287 W 0.052 W 0.149 W Image: Consumption Image: Consumption TETC * W W W W Image: Consumption Image: Consumption Image: Consumption Image: Consumption Image: Consumption		ate - WOL		2.768 W	2.762 W	2.915 W	Reference		
Off (S5) - WOL Enabled 0.199 W 0.203 W 0.2567 W Reference Off (S5) - WOL Disabled 0.199 W 0.203 W 0.2567 W Reference Category NBI2	Sleep (S3) - I	WOL Enab	led	0.462 W	0.4763 W	0.543 W	Reference		
Off (S5) - WOL Disabled 0.199 W 0.203 W 0.2567 W Reference Category NBI2 Image: Construction of the state of the	Sleep (S3) - I	WOL Disat	oled	0.462 W	0.4763 W	0.543 W	Reference		
Category NBI2 Allow Allow Reference Short Idle State - WOL Enabled 4.28W 4.309W 4.833W Reference Long Idle State - WOL Enabled 2.33 W 2.329 W 2.454 W Reference Sileep (S3) - WOL Disabled 0.4258 W 0.435 W 0.529 W Reference Off (S5) - WOL Disabled 0.4258 W 0.435 W 0.529 W Reference Off (S5) - WOL Disabled 0.211 W 0.219 W 0.308 W Reference Off (S5) - WOL Disabled 0.211 W 0.219 W 0.308 W Reference PTEC * W W W W PTEC * Annual Energy Consumption 15.075 kWh/year 15.178 kWh/year 17.147 kWh/year C External Power Supply Efficiency Level (International Efficiency Marking Protocol) * V E C C Display resolution *: 1920*1080 megapixels C C C C P9.2* Information about the energy save function is provided with the product. C C C P9.3 Energy efficiency class (monitors only): C C C C P10.1	Off (S5) - WC	OL Enabled	1	0.199 W	0.203 W	0.2567 W	Reference		
Short Idle State - WOL Enabled 4.28W 4.309W 4.833W Reference Long Idle State - WOL Enabled 2.33 W 2.329 W 2.454 W Reference Sleep (S3) - WOL Enabled 0.4258 W 0.435 W 0.529 W Reference Off (S5) - WOL Enabled 0.4258 W 0.435 W 0.529 W Reference Off (S5) - WOL Enabled 0.211 W 0.219 W 0.308 W Reference Off (S5) - WOL Disabled 0.211 W 0.219 W 0.308 W Reference Off (S5) - WOL Disabled 0.211 W 0.219 W 0.308 W Reference EPS No-load 0.05287 W 0.052 W 0.149 W	Off (S5) - WC	OL Disable	d	0.199 W	0.203 W	0.2567 W	Reference		
Enabled 2.33 W 2.329 W 2.454 W Reference Sleep (S3) - WOL Enabled 0.4258 W 0.435 W 0.529 W Reference Off (S5) - WOL Enabled 0.4258 W 0.435 W 0.529 W Reference Off (S5) - WOL Enabled 0.211 W 0.219 W 0.308 W Reference Off (S5) - WOL Disabled 0.211 W 0.219 W 0.308 W Reference Off (S5) - WOL Disabled 0.211 W 0.219 W 0.308 W Reference Off (S5) - WOL Disabled 0.211 W 0.219 W 0.308 W Reference Off (S5) - WOL Disabled 0.211 W 0.219 W 0.308 W Reference EPS No-load 0.05287 W 0.052 W 0.149 W	Category	NBI2							
Enabled 0.4258 W 0.435 W 0.529 W Reference Sleep (S3) - WOL Enabled 0.4258 W 0.435 W 0.529 W Reference Off (S5) - WOL Enabled 0.211 W 0.219 W 0.308 W Reference Off (S5) - WOL Disabled 0.211 W 0.219 W 0.308 W Reference Off (S5) - WOL Disabled 0.211 W 0.219 W 0.308 W Reference EPS No-load 0.05287 W 0.052 W 0.149 W P PTEC * W W W W [] Typical Energy Consumption 15.057 kWh/year 17.147 kWh/year [] [] External Power Supply Efficiency Level (International Efficiency Marking Protocol) * : V [] [] Display resolution * : 1920*1080 megapixels [] [] [] Default time to enter energy save function is provided with the product. [] [] P9.2 * Information about the energy save function is provided with the product. [] [] P9.2 * Information according to ISO 9296 (See NOTE B9) [] [] [] P10 Emission Declared according to ISO 9296 (See NOTE B9) <td></td> <td>tate - WOL</td> <td></td> <td>4.28W</td> <td>4.309W</td> <td>4.833W</td> <td>Reference</td> <td></td> <td></td>		tate - WOL		4.28 W	4.309W	4.833W	Reference		
Sleep (S3) - WOL Disabled 0.4258 W 0.435 W 0.529 W Reference Off (S5) - WOL Enabled 0.211 W 0.219 W 0.308 W Reference Off (S5) - WOL Disabled 0.211 W 0.219 W 0.308 W Reference EPS No-load 0.05287 W 0.052 W 0.149 W EPS No-load 0.05287 W PTEC * W W W W W C PTEC * W W W C C Annual Energy Consumption 15.057 kWh/year 15.178 kWh/year 17.147 kWh/year C External Power Supply Efficiency Level (International Efficiency Marking Protocol) * : V C C C Display resolution * : 1920*1080 megapixels C C C C Default time to enter energy save mode: 30 minutes C C C C P9.2* Information about the energy save function is provided with the product. C C C C P9.3 Energy efficiency class (monitors only): V C C C C		ate - WOL		2.33 W	2.329 W	2.454 W	Reference		
Off (S5) - WOL Enabled 0.211 W 0.219 W 0.308 W Reference Off (S5) - WOL Disabled 0.211 W 0.219 W 0.308 W Reference EPS No-load 0.05287 W 0.052 W 0.149 W PTEC* Typical Energy Consumption W W W C ETEC * 15.057 kWh/year 15.178 kWh/year 17.147 kWh/year C Annual Energy Consumption 15.057 kWh/year 15.178 kWh/year 17.147 kWh/year C External Power Supply Efficiency Level (International Efficiency Marking Protocol) * : V C C C Display resolution * : 1920*1080 megapixels C C C C Default time to enter energy save mode: 30 minutes C C C C P9.2* Information about the energy save function is provided with the product. C C C P9.3 Energy efficiency class (monitors only): V C C C P10 Emissions Statistical upper limit A-weighted sound power level, LwAc (B) C C C P10.1 Mode description Statistical upper limit A-weighted sound power level, LwAc (B) </td <td>Sleep (S3) - I</td> <td>WOL Enab</td> <td>led</td> <td>0.4258 W</td> <td>0.435 W</td> <td>0.529 W</td> <td>Reference</td> <td></td> <td></td>	Sleep (S3) - I	WOL Enab	led	0.4258 W	0.435 W	0.529 W	Reference		
Off (S5) - WOL Disabled 0.211 W 0.219 W 0.308 W Reference EPS No-load 0.05287 W 0.052 W 0.149 W Image: Construction of the second se	Sleep (S3) - I	WOL Disat	oled	0.4258 W	0.435 W	0.529 W	Reference		
EPS No-load 0.05287 W 0.052 W 0.149 W PTEC* W W W Typical Energy Consumption 15.057 kWh/year 15.178 kWh/year 17.147 kWh/year ETEC* 15.057 kWh/year 15.178 kWh/year 17.147 kWh/year Annual Energy Consumption 15.057 kWh/year 17.147 kWh/year [] External Power Supply Efficiency Level (International Efficiency Marking Protocol)*: V [] [] Display resolution*: 1920*1080 megapixels [] [] Default time to enter energy save mode: 30 minutes [] [] P9.2* Information about the energy save function is provided with the product. [] [] P9.3 Energy efficiency class (monitors only): [] [] [] P10 Emissions [] [] [] [] P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, L _{WAc} (B) [] [] [] [] [] [] [] [] [] [] [] [] [] [] [] [] [] [] []	Off (S5) - WC	OL Enabled	1	0.211 W	0.219 W	0.308 W	Reference		
PTEC * W W W W Typical Energy Consumption 15.057 kWh/year 15.178 kWh/year 17.147 kWh/year [] ETEC * 15.057 kWh/year 15.178 kWh/year 17.147 kWh/year [] Annual Energy Consumption External Power Supply Efficiency Level (International Efficiency Marking Protocol) * : V [] Display resolution * : 1920*1080 megapixels [] [] Default time to enter energy save mode: 30 minutes [] P9.2 * Information about the energy save function is provided with the product. [] P9.3 Energy efficiency class (monitors only): [] P10 Emissions [] P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, L _{WA,c} (B) Idle * + HDD:Idle * 2.6 [] Operation * + HDD:Idle * 4.1 [] Other mode * HDD: Operating [] [] Measured according to: [] ISO 7779 [] ECMA-74 [] []	Off (S5) - WC	OL Disable	d	0.211 W	0.219 W	0.308 W	Reference		
Typical Energy Consumption 15.057 kWh/year 15.178 kWh/year 17.147 kWh/year ETEC * 15.057 kWh/year 15.178 kWh/year 17.147 kWh/year Annual Energy Consumption 15.057 kWh/year 17.147 kWh/year External Power Supply Efficiency Level (International Efficiency Marking Protocol) * : V									
ETEC * 15.057 kWh/year 15.178 kWh/year 17.147 kWh/year Annual Energy Consumption 15.057 kWh/year 17.147 kWh/year External Power Supply Efficiency Level (International Efficiency Marking Protocol) * : V Image: Consumption Display resolution * : 1920*1080 megapixels Image: Consumption Image: Consumption Default time to enter energy save mode: 30 minutes Image: Consumption Image: Consumption P9.2* Information about the energy save function is provided with the product. Image: Consumption Image: Consumption P9.3 Energy efficiency class (monitors only): Image: Consumption Image: Consumption Image: Consumption P10 Emissions Image: Consumption Image: Consumption Image: Consumption Image: Consumption Image: Consumption P10.1 Mode Mode description Image: Consumption]	W	W	W			
External Power Supply Efficiency Level (International Efficiency Marking Protocol)*: V Display resolution * : 1920*1080 megapixels	ETEC *			15.057 kWh/year	15.178 kWh/year	17.147 kWh/year			
Display resolution * : 1920*1080 megapixels				y lovel (Internationa	 Efficiency Marking P	rotocol) * : V			
Default time to enter energy save mode: 30 minutes				•					╞
P9.2* Information about the energy save function is provided with the product. P9.3 Energy efficiency class (monitors only): P10 Emissions Noise emission – Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode Mode description Idle * HDD:Idle Operation * 4.1 Other mode * HDD: Operating Measured according to: ISO 7779 ECMA-74	. ,			.					╞
P9.3 Energy efficiency class (monitors only): P10 Emissions Noise emission – Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode description Idle * HDD:Idle * 2.6 Operation * HDD:Idle * 4.1 Other mode * HDD: Operating Measured according to: ISO 7779 ECMA-74			0,		on is provided with the	a product			<u> </u>
P10 Emissions Noise emission – Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, L _{WA,c} (B) Idle * HDD:Idle * 2.6 Operation * HDD:Idle * 4.1 Other mode * HDD: Operating Measured according to: ISO 7779 ECMA-74									
Noise emission – Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, L _{WA,c} (B) Idle * HDD:Idle * 2.6 Operation * HDD:Idle * 4.1 Other mode * HDD: Operating Measured according to: ISO 7779 ECMA-74			ency cl	ass (monitors only):					
P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, L _{WA,c} (B) Idle * HDD:Idle * 2.6 Operation * HDD:Idle * 4.1 Other mode * HDD: Operating Measured according to: ISO 7779 ECMA-74			sion	Declared according to	150 9296 (See NOT	E B0)			
Idle * HDD:Idle * 2.6 Operation * HDD:Idle * 4.1 Other mode * HDD: Operating Measured according to: ISO 7779					0 100 9290 (SEE NOT		it A-weighted soun	d power level / wa - (I	B)
Operation * HDD:Idle * 4.1 Other mode * HDD: Operating Measured according to: ISO 7779			*					a portor lovor, LWA,c (I	<u></u>
Other mode * HDD: Operating Measured according to: ISO 7779			*						╞
Measured according to: 🔀 ISO 7779 📃 ECMA-74		-	*			7.7			
					ECMA-74	I			
Other (only if not covered by ECMA-74)	IV			0 ther	-	y ECMA-74)			

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available;

see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see <u>http://www.ecma-international.org/publications/standards/Ecma-370.htm</u>

Model nu		80XC, 80XD			Logo		Leno	VO	
ssue da	te *	2017/4/6					Leno		X
Product	t environ	mental attribu	tes - Market requireme	nts (continued)			Require	ment	me
Item							Yes	No	n.a
	Electro	magnetic emiss	ions						
P10.4	program	n(s):	the requirement for low free	quency electromagneti	c fields of the following	voluntary			
P12		mics for compu							
P12.1*	The dis	play meets the e	gonomic requirements of IS	O 9241-307 for visual	display technologies.				
P12.2*	The phy	sical input devic	e meets the requirements of	f ISO 9995 and ISO 92	41-410.			\boxtimes	
P13	Packag	ing and docum	entation						
P13.1*	Product	packaging mate	rial type(s): EPE w	veight (kg): 0.871 veight (kg): 0.068 veight (kg): 0.017					
P13.2*	Product	plastic primary p	backaging is free from PVC.				\times		
P13.3*		duct primary con er recovered fibe	rugated fiberboard packag er content: 80 %	ing, specify the conta	ined percentage of mi	nimum po	ost-		
P13.4*		media for user a tronic, XPaper,	nd product documentation (tick box):					
P13.5	Ùser an		nis item if paper documentat ientation on paper media is						
	Totally of	chlorine-free							
	Elemen	tal chlorine-free							
	Process	ed chlorine-free					H		
P14	Volunta	ary programs							
P14.1			equirements of the following	voluntary program(s):					
	ENERG Eco-lab Eco-lab		Criteria version: Criteria version: Criteria version:	Date: Date: Date:	Product catego Product catego Product catego	ry:			
P15		-	(See NOTE B10)			,			
P9			f specific configuration m	ay vary; description	of the tested product	configura	ation:		
					•	•			
-									

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B2

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1
Regulation (EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7
Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)	P1.3, P5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) No 1272/2008 (CLP Regulation)	P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1

Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	Lenovo YOGA 720S-14IKB, Lenovo XiaoXin Air Pro	Logo
Model Number	80XC, 80XD	
Issue Date	2017/4/6	Lenovo
Additional information		

P7.1.1 Product environmental attributes							
(d)	year of manufacture:				2017		
(e)	Etec value (kWh) per ErP Lot 3 Catego disabled and if the system is tested with				cards (dGfx) are		
(f)	Etec value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete graphics cards (dGfx) are enable						
		Category A (according to ErP Lot 3)	Category B (according to ErP Lot 3)	Category C (according to ErP Lot 3)	Category D (according to ErP Lot 3)		
	Memory over base [GB]		4				
ients sting	Additional internal storage	(Yes / No)	Yes (Yes / No)	(Yes / No)	(Yes / No)		
capability adjustments applied during testing	Discrete television tuner	(Yes / No)	No (Yes / No)	(Yes / No)	(Yes / No)		
ability a	Discrete Audio Card	(Yes / No)	No (Yes / No)	(Yes / No)	(Yes / No)		
capo app	Discrete graphics Card(s) [number / #]	#: (Yes / No)	Yes #: 1 (Yes / No)	#: (Yes / No)	#: (Yes / No)		
	Category of discrete graphics Card(s)		G3				
esults	Etec Value (kWh) - dGfx disabled all discrete graphics cards (dGfx) are disabled/ UMA is active for switchable graphics/ product has no graphics cards (dGfx)		8.53				
Test results	Etec Value (kWh) - dGfx enabled all discrete graphics cards (dGfx) are enabled						
(g)	Idle state power demand (Watts);				1.516		
(h)	Sleep mode power demand (Watts);				0.487		
(i)	Sleep mode with WOL enabled power de	emand (Watts) (where	e enabled);		0.487		
(j)	Off mode power demand (Watts);				0.266		
(k)	Off mode with WOL enabled power dem	and (Watts) (where er	nabled);		0.266		
(I)	Internal power supply efficiency at 10 %,	20 %, 50 % and 100	% of rated output pow	er (if applicable):			
	10% 20% 50%	100% Aver	age				
(m)	external power supply efficiency (if applied	cable)*:					
	Average active efficiency: 65W : 89.23%,89.31%,88.93% *internal note: show values for all available external power supplies						
(o)	Minimum number of loading cycles that t		stand (applies only to r	otebook computers):	300		
(p-1)	Measurement methodology used to dete	rmine information me NA	ntioned in points (I) – i	nternal PSU efficiency:	:		
(p-2)	p-2) Measurement methodology used to determine information mentioned in points (m) – external PSU efficiency: EPA "Test Method for Calculating the Energy Efficiency of Single-voltage External AC-DC and AC-AC Power Supplies" dated August 11, 2004						

(p-3)	Measurement metho	dology used to determine information mentioned in p IEC 61960 measurement methodolo						
(p-4)		dology used to determine information mentioned in r Point P9.1 in the Product IT Eco Declaration:						
		IEC 62623/ IEC EN50564:2011 measurement n	nethodology					
(q)	Sequence of steps for	or achieving a stable condition with respect to power	demand::					
		IEC 62623/ IEC EN50564:2011 measurement methodology						
(r)	Description of how s	eep and/or off mode was selected or programmed:						
		Energy-star requirement						
(s)	Sequence of events off mode:	Sequence of events required to reach the mode where the equipment automatically changes to sleep and/or off mode:						
		Energy-star requirement						
(t)		te condition before the computer automatically re s not exceed the applicable power demand requirement		30				
(u)	Length of time after	r a period of user inactivity in which the compute ver power demand requirement than sleep mode (in	r automatically reaches a power	NA				
(v)		ore the display sleep mode is set to activate after		10				
(w)		nergy-saving potential of power management function						
		Based on user manual	·					
(x)	user information on I	now to enable the power management functionality:						
		Based on user manual						
(z)		neasurements: — test voltage in V and frequency in tem, — information and documentation on the instru						
		230V/50Hz, Total Harmonic Distortion	<2 %					
Additio	on Notebook Battery	Information:						
		Battery[ies] not user replaceable	Battery[ies] user replaceable	n/a				
		The battery[ies] in this product cannot be easily replaced by users themselves. ¹⁾						
Internal	/built-in Battery							
Externa	l/detachable Battery		\boxtimes					
Bios Ba	ackup Battery							
Other:								
Addition	nal information			•				
1)								
Акумулатор	оната[ите] батерия[и] в този	easily replaced by users themselves. продукт не може да се замени[ят] лесно от самите потребите	ели.					
		ser sustituidas fácilmente por los propios usuarios. y neměli provádět sami uživatelé.						
		atteriet/batterierne i dette produkt.						
Der Akku/di	e Akkus dieses Produkts kanı	h/können nicht ohne weiteres vom Benutzer selbst ausgetauscht	werden.					
	ei saa selle toote akut/akusid is [-εc] στο ποοϊόν αυτό δεν μπο	se hölpsasti asendada. ορούν να αντικατασταθούν εύκολα από τους ίδιους τους χρήστες						
La/les batte	rie(s présente(s) dans ce proc	uit ne peuvent être facilement remplacée(s) par les utilisateurs e	eux-mêmes.					
	može lako zamijeniti Bateriju	sam u ovom proizvodu. non può/possono essere facilmente sostituita/e dall'utente.						
Lietotāji paš	ši nevar nomainīt šā ražojuma	akumulatoru(-us).						
Šio gaminio	baterijos [baterijų] pats vartol							
		reinasznalo nem tudja egyedul egyszeruen kicsereini. x/jistgħux tiģi/jiģu sostitwita/i mill-utenti stess.						
Batteriet [en	ne] i dette produktet kan ikke l	ett erstattes av brukerne selv.						
		de gebruiker niet gemakkelijk vervangbaar. o wymienić baterii w tym produkcie.						
A ou as bate	erias deste produto não poder	n ser facilmente substituídas pelos próprios utilizadores.						
	eriile) din acest produs nu poa	ate (pot) fi ușor înlocuită (înlocuite) de utilizatorii înșiși.						

Batériu(-ie) v tomto výrobku nemôže vymieňať používateľ. Batériu(-ie) v tomto výrobku nemôže vymieňať používateľ. Baterij/baterije v tem izdelku uporabniki sami ne morejo zlahka zamenjati. Tämän tuotteen akku [akut] ei[vät] ole helposti käyttäjän vaihdettavissa. Det är inte enkelt för kunden att själv byta ut batteriet/batterierna. Bu üründeki batarya(lar) kullanıcılar tarafından kolaylıkla değiştirilemez.