



ECMA/TC38-TG3/2015/026 (Rev. 1 – 15 April 2015)

Annex B2 - Product environmental attributes Notebooks and Tablets

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

| Brand * | Lenovo | Logo |
|--------------------------------------|--|---------|
| Company name * | Lenovo | _ |
| Contact information * e-mail address | Lenovo Global Environmental Affairs Alvin L Carter alcarter@lenovo.com | Lenovo. |
| Internet site * | http://www.lenovo.com/social_responsibility/us/en/environment | .html |
| Additional information | The latest version of this document can be found at: | |
| | http://www.lenovo.com/ecodeclaration | |

| The company declares (| The company declares (based on product specification or test results based obtained from sample testing), that the product | | | | |
|--------------------------|--|--|--|--|--|
| conforms to the statemer | nts given in this declaration. | | | | |
| Type of product * | NB | | | | |
| Commercial name * | Lenovo YOGA 730-15 | | | | |
| Model number * | 81CU | | | | |
| Issue date * | 2017/11/20 | | | | |
| Intended market * | Global Europe Asia, Pacific & Japan Americas Other | | | | |
| Additional information | | | | | |

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products

| Model nu | mber * | 81CU | Logo | Lond | | |
|-----------|--|---|------------------|-------------|------|-------------|
| Issue dat | e * | 2017/11/20 | | Lend | JVC |) ,, |
| Product | environ | mental attributes - Legal requirements | | Require | ment | met |
| Item | | | | Yes | No | n.a. |
| P1 | | ous substances and preparations | | | | |
| P1.1* | Products | s do comply with current European RoHS Directive. (See legal reference and NOTE | EB1) | \boxtimes | | |
| P1.2* | | s do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value. | | | | |
| P1.3* | Products hydrobro trichloroo concentr | s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), omofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrach ethane, methyl bromide (see legal reference). Comment: Legal reference has no mation values. | naximum | | | |
| P1.4* | terpheny | s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polych vl (PCT) in preparations (see legal reference). | | | | |
| P1.5* | | s do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carb ntaining at least 48% per mass of chlorine in the SCCP (see legal reference). | oon atoms in the | | | |
| P1.6* | (see lega | th direct and prolonged skin contact do not release nickel in concentrations above 0 al reference). nt: Max limit in legal reference when tested according to EN1811:2011-5. | l,5 μg/cm²/week | | | |
| P1.7* | REACH | Article 33 information about substances in articles is available at (add URL or mail own.lenovo.com/social_responsibility/us/en/environment.html | contact): | \boxtimes | | |
| P2 | Batterie | s | | | | |
| P2.1* | | oduct contains a battery or an accumulator, the battery/accumulator is labeled with t Information on proper disposal is provided in user manual. (See legal reference) | he disposal | | | |
| P2.2* | Batteries referenc | s or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadme) | nium. (See legal | | | |
| P2.3* | Batteries | s and accumulators are readily removable. (See legal reference) | | \square | | |
| P3 | Conform | nity verification & Eco design (ErP) | | _ | | |
| P3.1* | The prod | duct is CE-marked to show conformance with applicable legal requirements (see leg | gal reference). | \square | П | П |
| | The Dec | laration of Conformity can be requested at (add link or e-mail address): | | | | |
| P3.2* | | duct complies with the Eco design requirements for energy-related products, al reference). | | | | |
| | Required | d information is; given in item P15 or added to this document, | | | | |
| | | available at (add URL): | | | | |
| | http://v | www.lenovo.com/social_responsibility/us/en/datasheets_notebooks/ | | | | |
| P5 | Product | packaging | | | | |
| P5.1* | | ng and packaging components do not contain more than 0,01% lead, mercury ent chromium by weight of these together. | , cadmium and | d 🔀 | | |

The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s)

The product packaging material is free from ozone depleting substances as specified in the Montreal Protocol (see legal reference).

Comment: Legal reference has no maximum concentration values.

Information for recyclers/treatment facilities is available (see legal reference).

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

P5.2*

P5.3*

P6 P6.1*

used (see legal reference).

Treatment information

| Model number * | 81CU | Logo | Lonovo | _ |
|----------------|------------|------|-----------|---|
| Issue date * | 2017/11/20 | | LEI IOVO" | |

| Product | environmental attributes - Market requirements (See General NOTE GN below) | | | |
|---------|--|-------------|------|------|
| | · | Require | ment | met |
| Item | *=mandatory to fill in. Additional information regarding each item may be found under P14. | Yes | No | n.a. |
| P7 | Design, Disassembly, recycling | | | |
| P7.1* | Parts that have to be treated separately are easily separable | \boxtimes | | |
| P7.2* | Plastic materials in covers/housing have no surface coating. | \boxtimes | | |
| P7.3* | Plastic parts > 100 g consist of one material or of easily separable materials. | \boxtimes | | |
| P7.4* | Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. | \boxtimes | | |
| P7.5 | Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. | \boxtimes | | |
| P7.6* | Labels are easily separable. (This requirement does not apply to safety/regulatory labels). | \boxtimes | | |
| | Product lifetime | | | |
| P7.7* | Upgrading can be done e.g. with processor, memory, cards or drives | | | |
| P7.8* | Upgrading can be done using commonly available tools | \boxtimes | | |
| P7.9 | Spare parts are available after end of production for: 5 years | | | |
| P7.10 | Service is available after end of production for: 5 years | | | |
| | Material and substance requirements | | | |
| P7.11* | Product cover/housing material type (e.g. plastics, metal, aluminum): | | | |
| | Material type: <i>plastics</i> Material type: <i>aluminum</i> Material type: | | | |
| P7.12 | Insulation materials of external electrical cables are PVC free. | \boxtimes | | |
| P7.13 | Insulation materials of internal electrical cables are PVC free. | \boxtimes | | |
| P7.14 | External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% | | | |
| | weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polygipul chloride or 0.3% weight (2000 ppm) chlorine in parts | | | |
| | polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. | , | | |
| P7.15 | Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low | v | X | |
| | halogen as defined in IEC 61249-2-21. (See 1NOTE B2) | | | |
| P7.16 | Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: | \boxtimes | | |
| D7 47 | Marking: >PC+ABS-FR(40)< | | | |
| P7.17 | Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other: D0P0, CAS #: 35948-25-5 | | | |
| | _ , _ , _ , _ | ш | ш | ш |
| | Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g | | | |
| | according ISO 1043-4: FR(40) | | Ш | |
| P7.18 | Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in | ۱ 🗖 | | |
| | concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) | | Ш | Ш |
| | 2. Chemical name: , CAS #: (See NOTE B4) | | | |
| | 3. Chemical name: , CAS #: " | | | |
| | Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: <i>FR(40)</i> | | | |
| P7.19 | In plastic parts > 25 g, flame retardant substances/preparations above 0.1% are used which have been | | Ħ | |
| | assigned the following Risk phrases; and Hazard statements: | ш | ш | |
| | The source(s) for these classifications is/are found at (add URL(s)): (See note B5) | | | |
| P7.20* | Postconsumer recycled plastic material content is used in the product (See Note B6): | \square | | |
| | | <u>~_3</u> | | |
| | If YES; at least one of the two alternatives below shall be answered; | | | |
| | a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 0.8%. | | | |
| | or | | | |
| | b) The weight of recycled material is g. | | | |

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

| Model number * | 81CU | Logo | Lanava |
|----------------|------------|------|-----------|
| Issue date * | 2017/11/20 | | Lei IOVO. |

| Product environmental at | tributes - Market re | equirements (conti | nued) | Requirement met |
|-----------------------------------|---|--|----------------------------------|--|
| Item | | | | Yes No n.a. |
| Material and subs | stance requirements | (continued) | | |
| | | in the product (See No | OTE B7): | |
| a) Of total plasti | c parts' weight > 25 g | | ered; material content (calcu | lated as a percentage |
| of total plastic or | by weight) is % | o. | | |
| , , | the biobased plastic name in the biobased plastic name in the biobased plastic name in the biobased in the biobased plastic name in | naterial is g. less than 0,1 mg/lamp. | | lacksquare |
| | specify: Number of lan | | um mercury content pe | r lamp: mg |
| | | Polymor | | |
| Dattery critimical c | omposition: Li-ion F tion (See NOTE B8) | orymer | | |
| | | s or energy consumption | one are reported: | |
| Energy mode * | Power level at | Power level at | Power level at | Reference/Standard for energy |
| | 100 V AC | 115 V AC | 230 V AC | modes and test method * |
| Peak (On-max) | 90 W | 90 W | 90 W | Full load |
| Category NBI2 | | | | |
| Short Idle State - WOL Enabled | 8.81 W | 10.08 W | 9.647 W | Use for ENERGY STAR V6 registration (P _{idle}) |
| Long Idle State - WOL Enabled | 2.601 W | 0.569 W | 2.602 W | Use for ENERGY STAR V6 registration (P _{idle}) |
| Sleep (S3) - WOL Enabled | 0.568 W | 0.569 W | 0.631 W | Use for ENERGY STAR V6 registration(P _{sleep}) |
| Sleep (S3) - WOL Disabled | 0.568 W | 0.569 W | 0.631 W | Reference |
| Off (S5) - WOL Enabled | 0.305 W | 0.311 W | 0.367 W | Use for ENERGY STAR V6 registration(P _{off}) |
| Off (S5) - WOL Disabled | 0.305 W | 0.311 W | 0.367 W | Use for ErP |
| | W | W | W | Reference |
| | | | | |
| Category | | | | |
| Short Idle State - WOL Enabled | W | W | W | Reference |
| Long Idle State - WOL Enabled | W | W | W | Reference |
| Sleep (S3) - WOL Enabled | W | W | W | Reference |
| Sleep (S3) - WOL Disabled | W | W | W | Reference |
| Off (S5) - WOL Enabled | W | W | W | Reference |
| Off (S5) - WOL Disabled | W | W | W | Reference |
| | W | W | W | Reference |
| | | | | |
| Category | | | | |
| Short Idle State - WOL Enabled | W | W | W | Reference |
| Long Idle State - WOL Enabled | W | W | W | Reference |

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

| Sleep (S3 | B) - WOL Enabled | W | W | W | Reference |
|-------------------|--|-------------------------|---|-----------------------|---|
| Sleep (S3 | B) - WOL Disabled | W | W | W | Reference |
| Off (S5) - | WOL Enabled | W | W | W | Reference |
| Off (S5) - | WOL Disabled | W | W | W | Reference |
| | | W | W | W | Reference |
| EPS No-lo | | W | W | W | |
| wall outlet but d | r supply / charger plugged in the lisconnected from the product.) | | | | |
| PTEC * | | W | W | W | |
| ETEC * | nergy Consumption | 27.841 kWh/year | 31.139 kWh/year | 30.37 kWh/year | $E_{TEC} = (8760/1000) \times (P_{off} \times 0.25)$ |
| | nergy Consumption | 27.047 KWII/yeai | 31.139 KWII/yeai | 30.37 KWII/yeai | + P _{sleep} x 0.35 + P _{long_Idle} x 0.10+ P _{short Idle} x 0.30) |
| | | Poff: Off Mode(S5) - W | /OL Enabled; Psleep: Slee | p Mode(S3) - WOL Enal | bled; Pidle: Idle State - WOL Enabled |
| External F | Power Supply Efficier | ncy Level (Internationa | al Efficiency Marking P | rotocol) * : VI | |
| Display re | esolution * : 3840*21 | 60 megapixels | | | |
| Default tin | ne to enter energy sa | ive mode: minutes | | | |
| P9.2* | Information about | the energy save funct | tion is provided with the | e product. | |
| P9.3 | Energy efficiency | class (monitors only): | <u> </u> | • | |
| P10 | Emissions | , ,, | | | |
| - | Noise emission - | Declared according t | to ISO 9296 (See NOT | E B9) | |
| P10.1 | | Node description | | | mit A-weighted sound power level, LwA,c (B) |
| | Idle * | Idle | | * 2.7 | |
| | | CPU Operating | | * 4.3 | |
| | Other mode | Declared A-weighted sou | nd pressure level (dB) $L_{p m A}$ | m 19 (operator posi | tion desktop – idle) |
| | Other mode | Declared A-weighted sou | nd pressure level (dB) $L_{p	extsf{A}}$ | .m 34.7 (operator po | sition desktop – operating) |
| | Measured according | ng to: X ISO 7779 Other | ECMA-74 (only if not covered b | y ECMA-74) | |

| Model nu | ımber * | 81CU | | | | Logo | Long | \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\ | |
|----------|----------------------|--|--|------------------------------|---|---|-------------------------------|--|-------------|
| Issue da | te * | Error! Referen | ice source not fo | ound. | | | Lenc | , V O | TM |
| Product | t environr | nental attributes | - Market requirem | nents (con | ntinued) | | Require | ment | met |
| Item | | | | | | | Yes | No | n.a. |
| | | magnetic emission | | | | | | | |
| P10.4 | program | (s): | • | frequency el | ectromagnetic field | ds of the following volunta | ry 🔲 | | |
| P12 | Ergono | mics for computing | products | | | | | | |
| P12.1* | The disp | lay meets the ergon | omic requirements of | f ISO 9241-3 | 307 for visual displ | ay technologies. | | | \boxtimes |
| P12.2* | The phys | sical input device me | eets the requirements | s of ISO 999 | 5 and ISO 9241-4 | 10. | \boxtimes | | |
| P13 | Packagi | ng and documenta | tion | | | | | | |
| P13.1* | Product | packaging material t packaging material t packaging material t | type(s): EPE | weight (kg weight (kg | | | | | |
| P13.2* | Product | plastic primary pack | aging is free from PV | C. | | | | | \Box |
| P13.3* | | duct primary corrugater recovered fiber co | | aging, spec | cify the contained | percentage of minimum | post- | | |
| P13.4* | | media for user and pronic, Paper, | oroduct documentation | n (tick box): | | | | | |
| P13.5 | Ùser and | | em if paper documen ation on paper media | | | | | | |
| | Element | hlorine-free al chlorine-free | | | | | | | |
| | Process | ed chlorine-free | | | | | | | |
| P14 | | ry programs | | | | | | | |
| P14.1 | The prod | duct meets the requi | rements of the followi | ing voluntar | y program(s): | | | | |
| | Eco-labe | el: | Criteria version: <i>6.1</i> Criteria version: Criteria version: | 1 | Date: 2018.1.5 Date: Date: | Product category: NBI : Product category: Product category: | 2 | | |
| P15 | | nal information (Se | | | | | | | |
| P9 | | | | | | e tested product configu | | | |
| | informati knowled | ion contained in this ge available at the ti I here is approximate | document. All information of completion, and | ation provid d supplier s | ed by supplier in the hall have no obligate | es whether express or implies document is provided lition to update such inform a Lenovo Account Representation | pased on supposation. The inf | olier's format | ion |
| P9 | See Ene | ergy Star Qualified N | otebooks & Tablet Co dex.cfm?fuseaction=f | | | | | | |
| | | <u> </u> | | | | <u> </u> | | | |
| | | | | | | | | | |

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B2

| Reference | Declaration item |
|---|------------------------|
| Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications. | P1.1 |
| Regulation (EC) 1907/2006(REACH, Annex XVII | P1.2, P1.4, P1.6, P1.7 |
| Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances) | P1.3, P5.3 |
| Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002 | P1.5 |
| Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator. | P2.1, P2.2, P2,3, P8.1 |
| Directive 2006/95/EC (Low Voltage Directive) | P3.1 |
| Directive 2004/108/EC (EMC Directive) | P3.1 |
| Directive 1999/5/EC (R&TTE Directive) | P3.1 |
| Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions | P3.1, P3.2 |
| Regulation (EC) No 1272/2008 (CLP Regulation) | P7.19 |
| Directive 2004/12/EC (Packaging Directive) | P5.1 |
| Decision 97/129/EC (Secondary packaging legislation) | P5.2 |
| Directive 2012/19/EU (WEEE directive) | P6.1 |

Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

| Commercial name | Lenovo YOGA 730-15 | Logo | |
|------------------------|--------------------|------|----------|
| Model Number | 81CU | | Lenovo |
| Issue Date | 2017/11/20 | | reliovo. |
| Additional information | | | |

| d) | Year of manufacture: | | | | |
|--|--|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|
| e) | Etec value (kWh) per ErP Lot 3 Catego disabled and if the system is tested with | | | | cards (dGfx) are |
| f) | Etec value (kWh) per ErP Lot 3 Catego enable | ry and capability adju | stments applied when a | III discrete graphics o | cards (dGfx) are |
| | | Category A (according to ErP Lot 3) | Category B (according to ErP Lot 3) | Category C (according to ErP Lot 3) | Category D (according to ErP Lot 3) |
| | Memory over base [GB] | 16 | 16 | | |
| ents sting | Additional internal storage | No (Yes / No) | No (Yes / No) | (Yes / No) | (Yes / No) |
| capability adjustments applied during testing | Discrete television tuner | No (Yes / No) | No (Yes / No) | (Yes / No) | (Yes / No) |
| ability a | Discrete Audio Card | No (Yes / No) | No (Yes / No) | (Yes / No) | (Yes / No) |
| cap | Discrete graphics Card(s) [number / #] | No #: (Yes / No) | Yes #: 1 (Yes / No) | #: (Yes / No) | #: (Yes / No) |
| | Category of discrete graphics Card(s) | No | G5 | | |
| sults | Etec Value (kWh) - dGfx disabled all discrete graphics cards (dGfx) are disabled/ UMA is active for switchable graphics/ product has no graphics cards (dGfx) | 7.73 | | | |
| Test results | Etec Value (kWh) - dGfx enabled all discrete graphics cards (dGfx) are enabled | | 10.37 | | |
| g) | Idle state power demand (Watts); | | | | A: 2.17 B: 2.91 |
| h) | Sleep mode power demand (Watts); | | | | A: 0.53 B: 0.71 |
| i) | Sleep mode with WOL enabled power d | emand (Watts) (wher | e enabled); | | A: 0.53 |
|) | Off mode power demand (Watts); | | | | B: 0.71 A: 0.28 B: 0.40 |
| ς) | Off mode with WOL enabled power dem | and (Watts) (where e | nabled); | | A: 0.28 B: 0.40 |
| l) | Internal power supply efficiency at 10 % | , 20 %, 50 % and 100 | % of rated output pow | er (if applicable): | |
| | 10% 20% 50% | 100% Ave | rage | | |
| m) | external power supply efficiency (if appli | cable)*: | | | |
| | Average active efficiency: 89.04%, 88. | .86%,89.92%,88.5 | 7%,89.18%,89.18% | | |
| o) | *internal note: show values for all available external p Minimum number of loading cycles that | | stand (applies only to n | otebook computers): | 300 |
| p-1) | Measurement methodology used to dete | ermine information me | entioned in points (I) – ir | nternal PSU efficiency: | : |

| (p-2) | | dology used to determine information mentioned in program Requirements for Single Voltage Externa Eligibility Criteria (Version 2.0) | | |
|---|--|---|-------------------------------------|-------|
| (p-3) | Measurement methodology used to determine information mentioned in points (o) – loading cycles batteries: ≥ 70% of Cmin | | | |
| (p-4) | Measurement methodology used to determine information mentioned in maximum, idle, sleep, off mode power as defined in Point P9.1 in the Product IT Eco Declaration: IEC 62623 | | | |
| (q) | Sequence of steps for achieving a stable condition with respect to power demand:: *Power on -> Wait 5 minutes -> Stable condition* | | | |
| (r) | Description of how sleep and/or off mode was selected or programmed: **Begin menu -> Power -> Select sleep or off mode** | | | |
| (s) | Sequence of events off mode: | required to reach the mode where the equipment au | tomatically changes to sleep and/or | |
| (t) | | te condition before the computer automatically renot exceed the applicable power demand requirement | | 30min |
| (u) Length of time after a period of user inactivity in which the computer automatically reaches a p mode that has a lower power demand requirement than sleep mode (in minutes): | | | er automatically reaches a power | NA |
| (v) | Length of time before the display sleep mode is set to activate after user inactivity (in minutes): | | 10min | |
| (w) | Information on the er | nergy-saving potential of power management function Refer to User Guide | nality: | |
| (x) | User information on I | now to enable the power management functionality: *Refer to User Guide* | | |
| (z) | | measurements: — test voltage in V and frequency in system, — information and documentation on the in sting: 230V50HZ-2%-Edition 2.0, 2011-01, Section | strumentation, set-up and circuits | |
| Addition | nal Notebook Batter | | | |
| | | Battery[ies] <u>not</u> user replaceable The battery[ies] in this product cannot be easily replaced by users themselves. 1) | Battery[ies] user replaceable | n/a |
| Internal/built-in Battery | | | | |
| External/detachable Battery | | | | |
| Bios Backup Battery | | | | |
| Other: | | | | |
| Addition | al information | | | |
| | | | | |
| Akymynatoru Las baterías Výměnu bate Výměnu bate Brugeren kar Der Akku/die Kasutajad ei H μπαταρία[- La/les batteria/le Lailes batteria/le Lietotāji paši Šio gaminio l A termék akk Il-batterija/ba Batteriat [ene De batterij(ene Użytkownik r A ou as bate Bateria (bate Bateriu(-ie) v Baterij/ba | ната[ите] батерия[и] в този de este producto no pueden erie/baterií v tomto výrobku by n ikke uden videre udskifte bæ Akkus dieses Produkts kanr saa selle toote akut/akusid is ec] στο προϊόν αυτό δεν μπο ie(s présente(s) dans ce procupze lako zamijeniti Bateriju sæ batterie in questo prodotto revar nomainīt šā ražojuma baterijos [bateriju] pats vartot kumulátorát/akkumulátorait a titeriji f'dan il-prodott ma tista e] i dette produktet kan ikke len) in dit product is (zijn) door nie može sam w łatwy sposóť rias deste produto não poder trille) din acest produs nu poze tomto výrobku nemôže vymi je v tem izdelku uporabniki sien akku [akut] ejívátj ole helnkelt för kunden att själv byta | pούν να αντικατασταθούν εύκολα από τους ίδιους τους χρήστες uit ne peuvent être facilement remplacée(s) par les utilisateurs e sam u ovom proizvodu. on può/possono essere facilmente sostituita/e dall'utente. akumulatoru(-us). ojas negali lengvai pakeisti. felhasználó nem tudja egyedül egyszerűen kicserélni. k/jistghux tiģi/jiģu sostitwita/i mill-utenti stess. stt erstattes av brukerne selv. de gebruiker niet gemakkelijk vervangbaar. o wymienić baterii w tym produkcie. n ser facilmente substituídas pelos próprios utilizadores. tte (pot) fi uşor înlocuită (înlocuite) de utilizatorii înşişi. eñat' používatel'. ami ne morejo zlahka zamenjati. posti käyttäjän vaihdettavissa. | werden. | |