

ECMA/TC38-TG3/2015/026 (Rev. 1 – 15 April 2015)

### Annex B2 - Product environmental attributes Desktop/All-in-One Computers

The declaration may be published only when all rows and/or fields marked with \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

| Brand *                | Lenovo  | Logo  |         |  |  |  |
|------------------------|---|-------|---------|--|--|--|
| Company name *         | Lenovo  |       |         |  |  |  |
| Contact information *  | Lenovo Global Environmental Affairs                           |       | Lenovo  |  |  |  |
| e-mail address         | Alvin L Carter  |       | LEIIOVO |  |  |  |
|                        | alcarter@lenovo.com   |       |         |  |  |  |
| Internet site *        | http://www.lenovo.com/social_responsibility/us/en/environment | .html |         |  |  |  |
| Additional information | The latest version of this document can be found at:          |       |         |  |  |  |
|                        | http://www.lenovo.com/ecodeclaration                          |       |         |  |  |  |

| The company declares (based on product specification or test results based obtained from sample testing), that the product |  |  |  |  |  |  |
|--|--|--|--|--|--|--|
| conforms to the statement  | conforms to the statements given in this declaration.        |  |  |  |  |  |
| Type of product *  | Desktop  |  |  |  |  |  |
| Commercial name *  | ThinkCentre M75t Tower 2nd Gen                               |  |  |  |  |  |
| Model number *   | 11KB,11KC,11KD,11KE,11RB,11RC,11RD,11RE                      |  |  |  |  |  |
| Issue date *   | 2020-8-4   |  |  |  |  |  |
| Intended market *  | 🔀 Global 📃 Europe 📃 Asia, Pacific & Japan 📃 Americas 📃 Other |  |  |  |  |  |
| Additional information   |  |  |  |  |  |  |

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

#### About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template: P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products.

| Model n      | umber *   | 11KB,11KC,11KD,                       | 11KE,11RB,11RC,11RD,11RE   |                          | Logo                        |             |    |       |
|--------------|---|---------------------------------------|--|--------------------------|-----------------------------|-------------|----|-------|
| Issue date * |   | 2020-8-4                              |  |                          | 1                           | Lenovo.     |    |       |
|              | t enviror   | mental attributes                     | - Legal requirements   |                          | ·                           | Require     |    | t met |
| Item         |   |                                       |  |                          |                             | Yes         | No | n.a.  |
| P1           |   | ous substances and                    |  |                          |                             |             |    |       |
| P1.1*        |   |                                       | ent European RoHS Directive. (See leg  | al reference and NOT     | E B1)                       |             |    |       |
| P1.2*        | Comme   | nt: Legal reference ha                | estos (see legal reference).<br>as no maximum concentration value.   |                          |                             |             |    |       |
| P1.3*        | hydrobr<br>trichloro  | omofluorocarbons (Hl                  | ne Depleting Substances: Chlorofluoroc<br>BFC), hydrochlorofluorcarbons (HCFC),<br>de (see legal reference). Comment: Le | , Halons, carbontetrach  |                             |             |    |       |
| P1.4*        | Products do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated terphenyl (PCT) in preparations (see legal reference).   |                                       |  |                          |                             |             |    |       |
| P1.5*        | Products do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).          |                                       |  |                          |                             |             |    |       |
| P1.6*        | (see leg  | al reference).                        | ed skin contact do not release nickel in o<br>eference when tested according to EN1                                      |                          | J,5 μg/cm²/we               | ek 🔀        |    |       |
| P1.7*        | REACH Article 33 information about substances in articles is available at (add URL or mail contact):<br>https://static.lenovo.com/ww/docs/sustainability/ww-disclosure-Lenovo-REACH-SVHC-Disclosure.pdf |                                       |  |                          |                             |             |    |       |
| P2           | Batterie  |                                       |  |                          |                             |             |    |       |
| P2.1*        |   |                                       | ery or an accumulator, the battery/accur<br>r disposal is provided in user manual. (\$                                   |                          | the disposal                | $\boxtimes$ |    |       |
| P2.2*        | Batterie  |                                       | not contain more than 0,0005% of merc  | cury or 0,002% of cadr   | nium. (See le               | gal 🔀       |    |       |
| P2.3*        | Batterie  | s and accumulators a                  | re readily removable. (See legal referer   | ice)                     |                             | $\square$   |    |       |
| P3           | Confor  | mity verification & E                 | co design (ErP)  |                          |                             |             |    |       |
| P3.1*        | The pro   | duct is CE-marked to                  | show conformance with applicable lega<br>y can be requested at: https://www.leno   | I requirements (see le   | gal reference<br>nce/eu-doc | e). 🔀       |    |       |
| P3.2*        |   | duct complies with the al reference). | e Eco design requirements for energy-re  | elated products,         |                             | $\boxtimes$ |    |       |
|              | • •   | d information is;                     | given in item P15 or added to this available at: https://www.lenovo.c  |                          | laas deslarati              |             |    |       |
| P5           | Droduc  | t packaging                           |  | om/us/en/compliance/     |                             |             |    |       |
| P5.1*        |   |                                       | omponents do not contain more than   | 0.01% lead moreu         | av cadmium                  | and 🔽       | _  |       |
| 13.1         | Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium and $\sum$ hexavalent chromium by weight of these together.  |                                       |  |                          |                             |             |    |       |
| P5.2*        | The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s) used (see legal reference).  |                                       |  |                          |                             | al(s) 🔀     |    |       |
| P5.3*        | (see leg  | al reference).                        | ial is free from ozone depleting substand<br>as no maximum concentration values.   | es as specified in the l | Montreal Prot               | ocol 🔀      |    |       |
|              |   |                                       |  |                          |                             |             |    |       |
| P6           | Ireatme   | ent information                       |  |                          |                             |             |    |       |

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

| Model number * |   | 11KB,11KC,11KD,11KE,11RB,11RC,11RD,11RE Logo   |          |             |             |             |  |  |
|----------------|---|--|----------|-------------|-------------|-------------|--|--|
| Issue da       | te *  | 2020-8-4   |          | 211         | ονα         |             |  |  |
| Product        | t environ   | mental attributes - Market requirements (See General NOTE GN below)  |          |             |             |             |  |  |
|                |   | onmental conscious design  | Rec      | uire        | ment        | met         |  |  |
| Item           |   | tory to fill in. Additional information regarding each item may be found under P14.  |          | Yes         | No          | n.a.        |  |  |
| P7.1*          |   | Disassembly, recycling   |          |             |             |             |  |  |
| P7.1           |   | It have to be treated separately are easily separable  |          |             | <u> </u>    | <u> </u>    |  |  |
| P7.2<br>P7.3*  |   | naterials in covers/housing have no surface coating.   |          |             | <u> </u>    | <u> </u>    |  |  |
| -              | Plastic parts > 100 g consist of one material or of easily separable materials.       Image: Constant of the second |  |          |             |             |             |  |  |
| P7.4*          |   |  |          | <u> </u>    | <u> </u>    |             |  |  |
| P7.5           | Plastic p   | JOIS.  |          | <u> </u>    | <u> </u>    |             |  |  |
| P7.6*          |   | re easily separable. (This requirement does not apply to safety/regulatory labels).  |          |             |             |             |  |  |
| P7.7*          | Product   | Infetime<br>ng can be done e.g. with processor, memory, cards or drives  |          |             |             |             |  |  |
| P7.8*          |   | ng can be done using commonly available tools  |          |             | <u> </u>    | <u> </u>    |  |  |
| P7.9           |   | arts are available after end of production for: 5 years  |          | $\boxtimes$ |             | <u> </u>    |  |  |
|                |   |  |          |             |             | <u> </u>    |  |  |
| P7.10          |   | s available after end of production for: 5 years   |          |             |             |             |  |  |
| P7.11*         |   | and substance requirements<br>cover/housing material type (e.g. plastics, metal, aluminum):  |          |             |             |             |  |  |
| 1 7.11         |   | type: ABS Material type (e.g. plastics, metal, authintum).   |          |             |             |             |  |  |
| P7.12          |   | n materials of external electrical cables are PVC free.  |          |             | $\square$   |             |  |  |
| P7.13          | Insulatio   | n materials of internal electrical cables are PVC free.  |          | Ħ           |             | Ħ           |  |  |
| P7.14          | External  | plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine an   | nd 0,1%  |             |             | Ħ           |  |  |
|                | weight (´<br>polyvinyl  | 1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardan<br>chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts cor<br>in 25% post-consumer recycled content.  | nts, and |             |             |             |  |  |
| P7.15          | Printed c   | ircuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen: all PCBs > 25 g are low halogen in IEC 61249-2-21. (See 1NOTE B2)   | nalogen  |             | $\boxtimes$ |             |  |  |
| P7.16          | Marking:  |  |          |             | $\boxtimes$ |             |  |  |
| P7.17          |   | nemical specifications of flame retardants in printed circuit boards > 25 g (without components<br>PA (additive), TBBPA (reactive) (See NOTE B3), Other: , CAS #:  | s):      | $\boxtimes$ |             |             |  |  |
|                |   | nemical specifications of flame retardants in printed circuit boards (without components) > 25 g ISO 1043-4:   | g        |             |             | $\boxtimes$ |  |  |
| P7.18          | concentr<br>1. Chemi<br>2. Chemi  | ame retarded plastic parts > 25 g contain the following flame retardant substances/prepara<br>ations above 0,1%:<br>ical name: , CAS #: (See NOTE B4)<br>ical name: , CAS #: "<br>ical name: , CAS #: "  | tions in |             |             |             |  |  |
|                | <u>Alt. 2: </u> Ch  | nemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:   |          |             |             |             |  |  |
| P7.19          | assigned  | : parts > 25 g, flame retardant substances/preparations above 0,1% are used which have bee<br>I the following Risk phrases; and Hazard statements:   | ∍n       |             |             |             |  |  |
|                |   | rce(s) for these classifications is/are found at (add URL(s)): , (See note B   | 5)       |             |             |             |  |  |
| P7.20*         | lfYES;a<br>a) Oft<br>ape<br>or  | sumer recycled plastic material content is used in the product (See Note B6):<br>t least one of the two alternatives below shall be answered;<br>otal plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculate<br>ercentage of total plastic by weight) is <b>47.2%</b> .<br>e weight of recycled material is <b>188.6</b> g. | ed as    |             |             |             |  |  |

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

| Model number *   | 11KB,11KC,11KD,11KE,11RB,11RC,11RD,11RE | Logo | Lenovo    |  |  |  |
|--|---|------|-----------|--|--|--|
| Issue date *   | 2020-8-4                                |      | Lei Iovo. |  |  |  |
| Product environmental attributes - Market requirements (continued) Requirement met |   |      |           |  |  |  |

Item

Ver

| es | No | n.a. |
|----|----|------|

|                       | Material and sub    | stance requirements        | (continued)                       |                             |   |
|-----------------------|---------------------|----------------------------|-----------------------------------|-----------------------------|---|
| P7.21*                |                     |                            | d in the product (See N           | NOTE B7):                   |   |
| P7.22*                |                     | f                          |                                   | -                           |   |
| P7.22"                |                     | specify: Number of la      | . less than 0,1 mg/lam            | o.<br>num mercury content p | er lamp: mg   |
| P8                    | Batteries           |                            | and maxim                         |                             | en ampi my  |
| P8.1*                 | Battery chemical of | composition: Lithium       | Manganese Dioxide                 |                             |   |
| P9                    | Energy consump      | tion (See NOTE B8)         |                                   |                             |   |
| P9.1                  |                     |                            | els or energy consumption         |                             |   |
| Energy mo             |                     | Power level at<br>100 V AC | Power level at<br><b>115</b> V AC | Power level at<br>230 V AC  | Reference/Standard for energy<br>modes and test method *    |
| Peak (On-             | -max)               | W                          | W                                 | W                           | Full load   |
| Catego                | r <u>y  1</u>       |                            |                                   |                             |   |
| Short Idle<br>Enabled | e State - WOL       | 17.4 W                     | 18.4 W                            | 18.2 W                      | Use for ENERGY STAR V8<br>registration (P <sub>idle</sub> ) |
| Long Idle<br>Enabled  | State - WOL         | 17.0 W                     | 17.4 W                            | 16.9 W                      | Use for ENERGY STAR V8<br>registration (P <sub>idle</sub> ) |
| Sleep (S3             | ) - WOL Enabled     | 2.3 W                      | 2.3 W                             | 2.3 W                       | Use for ENERGY STAR V8<br>registration(P <sub>sleep</sub> ) |
| Off (S5) -            | WOL Enabled         | 0.6 W                      | 0.6 W                             | 0.6 W                       | Use for ENERGY STAR V8<br>registration(Poff)                |
| Off (S5) -            | WOL Disabled        | W                          | W                                 | 0.62 W                      | Use for ErP lot3  |
| Catego                | ry <u>12</u>        |                            |                                   |                             |   |
| Short Idle<br>Enabled | e State - WOL       | 15.5 W                     | 15.5 W                            | 16.1 W                      | Use for ENERGY STAR V8<br>registration (P <sub>idle</sub> ) |
| Long Idle<br>Enabled  | State - WOL         | 13.7 W                     | 14.8 W                            | 15.6 W                      | Use for ENERGY STAR V8<br>registration (P <sub>idle</sub> ) |
| Sleep (S3             | ) - WOL Enabled     | 2.3 W                      | 2.3 W                             | 2.3 W                       | Use for ENERGY STAR V8<br>registration(P <sub>sleep</sub> ) |
| Off (S5) -            | WOL Enabled         | 0.7 W                      | 0.7 W                             | 0.7 W                       | Use for ENERGY STAR V8<br>registration(Poff)                |
| Off (S5) -            | WOL Disabled        | W                          | W                                 | 0.66 W                      | Use for ErP lot3  |
| Catego                | r <u>y D1</u>       |                            |                                   |                             |   |
| Enabled               | e State - WOL       | 26.6 W                     | 25.6 W                            | 26.3 W                      | Use for ENERGY STAR V8<br>registration (P <sub>idle</sub> ) |
| Long Idle<br>Enabled  | State - WOL         | 25.5 W                     | 25.3 W                            | 25.2 W                      | Use for ENERGY STAR V8<br>registration (P <sub>idle</sub> ) |
| Sleep (S3             | ) - WOL Enabled     | 2.2 W                      | 2.2 W                             | 2.2 W                       | Use for ENERGY STAR V8<br>registration(P <sub>sleep</sub> ) |
| Off (S5) -            | WOL Enabled         | 0.6 W                      | 0.6 W                             | 0.6 W                       | Use for ENERGY STAR V8<br>registration(Poff)                |
| Off (S5) -            | WOL Disabled        | W                          | W                                 | 0.63 W                      | Use for ErP lot3  |

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B9 A Guidance document on Acoustic Noise is available; see <u>http://www.ecma-international.org/publications/standards/Ecma-370.htm</u>

| Catego  | ry D2                |   |   |   |   |  |  |
|---|----------------------|---|---|---|---|--|--|
| Short Idle<br>Enabled   | e State - WOL        | 24.1 W  | <b>24.0</b> W   | 23.6 W  | Use for ENERGY STAR V8<br>registration (P <sub>idle</sub> )   |  |  |
| Long Idle<br>Enabled  | e State - WOL        | 23.7 W  | 21.8 W  | 21.5 W  | Use for ENERGY STAR V8<br>registration (P <sub>idle</sub> )   |  |  |
| Sleep (S3   | 3) - WOL Enabled     | 2.4 W   | 2.4 W   | <b>2.4</b> W  | Use for ENERGY STAR V8<br>registration(P <sub>sleep</sub> )   |  |  |
| Off (S5) -  | WOL Enabled          | 0.7 W   | 0.7 W   | 0.7 W   | Use for ENERGY STAR V8<br>registration(Port)  |  |  |
| Off (S5) -  | WOL Disabled         | W   | W   | 0.76 W  | Use for ErP lot3  |  |  |
| EPS No-load<br>(External power supply / charger plugged in the<br>wall outlet but disconnected from the product.) |                      | W   | W   | W   |   |  |  |
| PTEC *  | nergy Consumption    | W   | W   | W   |   |  |  |
| ETEC *<br>Annual Energy Consumption   |                      | <b>70.3</b> kWh/year<br><b>63.0</b> kWh/year<br><b>101.9</b> kWh/year<br><b>94.4</b> kWh/year | 73.4 kWh/year<br>63.8 kWh/year<br>99.0 kWh/year<br>92.3 kWh/year                | 72.4 kWh/year<br>66.2 kWh/year<br>100.7 kWh/year<br>91.2 kWh/year | $E_{TEC} = (8760/1000) \times (P_{off} \times 0.45)$<br>+ $P_{sleep} \times 0.05 + P_{long_{ldle}} \times 0.15 + P_{short_{ldle}} \times 0.35)$ |  |  |
| External  | Dowor Supply Efficie | Poff: Off Mode  | ( <mark>S5) - WOL Enabled; P<sub>slee</sub><br/>al Efficiency Marking Pr</mark> | <i>p</i> : Sleep Mode(S3) - WO                                    | L Enabled; P <sub>idle</sub> : Idle State - WOL Enabled   |  |  |
|   |                      | negapixels  |   |   |   |  |  |
|   |                      | ave mode: 25 minutes  |   |   |   |  |  |
| P9.2*   |                      |   | ion is provided with the  | product   |   |  |  |
| P9.3  |                      | class (monitors only):  |   | product.  |   |  |  |
| P10   | Emissions            |   |   |   |   |  |  |
|   |                      | - Declared according t  | o ISO 9296 (See NOTE  | E B9)   |   |  |  |
| P10.1   | Mode                 | Mode description  | Ŷ   | Statistical upper lin   | nit A-weighted sound power level, <i>L<sub>WA,c</sub></i> (B)   |  |  |
|   | Idle                 | * HDD:Idle  |   | * 3.6   |   |  |  |
|   | Operation            | * HDD: Operating  |   | * 3.7   |   |  |  |
|   | Other mode           | Declared A-weighted sour  | nd pressure level (dB) $L_{pAr}$  | m 19.5 (operator position desktop – idle)                         |   |  |  |
|   |                      |   | nd pressure level (dB) $L_{pAr}$  |   |   |  |  |
|   | Measured accord      | ing to: 🔀 ISO 7779 🚺<br>Other   | ECMA-74<br>(only if not covered by  | / ECMA-74)  |   |  |  |

| Model nu | mber *              | 11KB,11KC,11k  | (D,11KE,11RB,11RC,  | 11RD,11RE                              |                                 |                                       | Logo                            |                          |                       |            |
|----------|---------------------|--|---|--|---------------------------------|---------------------------------------|---------------------------------|--------------------------|-----------------------|------------|
| ssue dat | te *                | 2020-8-4   |   |  |                                 | Lei                                   | _enovo                          |                          |                       |            |
| Product  | environ             | nental attribute   | es - Market require   | ments (con                             | tinued)                         |                                       |                                 |                          | uireme                | nt me      |
| Item     |                     |  |   |  |                                 |                                       |                                 | Y                        | es No                 | o n.a      |
|          |                     | magnetic emission  |   |  |                                 |                                       |                                 |                          |                       |            |
| P10.4    | program             | (s):   | he requirement for low  | v frequency el                         | ectromagnetic                   | c fields of the fol                   | lowing volunt                   | ary                      |                       |            |
| P12      |                     | mics for comput  |   |  |                                 |                                       |                                 |                          |                       |            |
| P12.1*   | The disp            | play meets the erg   | onomic requirements   | of ISO 9241-3                          | 307 for visual                  | display technolo                      | gies.                           |                          |                       |            |
| P12.2*   | The phy             | sical input device   | meets the requiremer  | nts of ISO 999                         | 5 and ISO 92                    | 41-410.                               |                                 |                          | $\triangleleft$       |            |
| P13      | Packag              | ing and docume   | ntation   |  |                                 |                                       |                                 |                          |                       |            |
| P13.1*   | Product<br>Product  | packaging materi<br>packaging materi<br>packaging materi       | al type(s): <i>LDPE</i><br>al type(s):  | weight (kg<br>weight (kg<br>weight (kg | ): <b>0.316</b>                 |                                       |                                 |                          |                       |            |
| P13.2*   | Product             | plastic primary pa   | ckaging is free from F  | PVC.                                   |                                 |                                       |                                 |                          | $\triangleleft$       |            |
| P13.3*   | consum              | er recovered fiber   |   |  | -                               | ned percentage                        | of minimun                      | 1 post-                  |                       |            |
| P13.4*   |                     | media for user an<br>ronic, XPaper,                            | d product documentat Other  | ion (tick box):                        |                                 |                                       |                                 |                          |                       |            |
| P13.5    | Úser an             |  | s item if paper docume<br>ntation on paper med  |  |                                 |                                       |                                 |                          |                       | ]          |
|          | Totally o           | hlorine-free   |   |  |                                 |                                       |                                 | D                        | 2                     |            |
|          |                     | al chlorine-free   |   |  |                                 |                                       |                                 | ľ                        | า้                    |            |
|          | Process             | ed chlorine-free   |   |  |                                 |                                       |                                 | F                        | =                     |            |
| P14      |                     | ry programs  |   |  |                                 |                                       |                                 | L                        |                       |            |
| P14.1    |                     |  | quirements of the follo   | wing voluntar                          | y program(s):                   |                                       |                                 |                          |                       |            |
|          |                     | Y STAR®  | Criteria version: 8   | 8.0                                    | Date:                           |                                       | category: De                    |                          |                       |            |
|          | Eco-labe            |  | Criteria version: 8   | 3.0                                    | Date:                           |                                       | category: De                    | sktop                    |                       |            |
|          | Eco-lab             |  | Criteria version:   |  | Date:                           | Product                               | category:                       |                          |                       |            |
| P15      |                     | nal information (  |   |  |                                 |                                       |                                 |                          |                       |            |
| P9       |                     |  | specific configuration  |  |                                 |                                       |                                 |                          |                       |            |
|          | informat<br>knowled | ion contained in the ge available at the<br>l here is approxim | o representations, gua<br>his document. All infor<br>e time of completion, a<br>ate and provided for in | mation provid<br>and supplier s        | ed by supplie<br>hall have no c | r in this docume<br>bligation to upda | nt is provided<br>ate such info | l based on a rmation. Th | supplier'<br>e inform | s<br>ation |
| P9       |                     |  | Notebooks & Tablet<br>/index.cfm?fuseactior   |  |                                 |                                       | _code=CO                        |                          |                       |            |

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

## Legal references Europe Annex B2

| Reference   | Declaration item       |
|---|------------------------|
| Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.  | P1.1                   |
| Regulation (EC) 1907/2006(REACH, Annex XVII   | P1.2, P1.4, P1.6, P1.7 |
| Regulation (EC) 2037/2000, 2038/2000, 2039/2000<br>(Marketing and use of Ozone layer depleting<br>substances)   | P1.3, P5.3             |
| Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002  | P1.5                   |
| Directive 2013/56/EC (Battery and accumulators<br>Directive) *<br>* These provisions shall not apply where, for safety,<br>performance, medical or data integrity reasons, continuity of<br>power supply is necessary and requires a permanent<br>connection between the appliance and the battery or<br>accumulator.               | P2.1, P2.2, P2,3, P8.1 |
| Directive 2006/95/EC (Low Voltage Directive)  | P3.1                   |
| Directive 2004/108/EC (EMC Directive)   | P3.1                   |
| Directive 1999/5/EC (R&TTE Directive)   | P3.1                   |
| Regulation (EC) 801/2013 amending Regulation (EC)<br>No 1275/2008 with regard to ecodesign requirements<br>for standby, off mode electric power consumption of<br>electrical and electronic household and office<br>equipment, and amending Regulation (EC) No<br>642/2009 with regard to ecodesign requirements for<br>televisions | P3.1, P3.2             |
| Regulation (EC) No 1272/2008 (CLP Regulation)   | P7.19                  |
| Directive 2004/12/EC (Packaging Directive)  | P5.1                   |
| Decision 97/129/EC (Secondary packaging legislation)  | P5.2                   |
| Directive 2012/19/EU (WEEE directive)   | P6.1                   |

# Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

#### Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

| Commercial name        | ThinkCentre M75t Tower 2nd Gen          | Logo |        |
|------------------------|---|------|--------|
| Model Number           | 11KB,11KC,11KD,11KE,11RB,11RC,11RD,11RE | _    |        |
| Issue Date             | 2020-8-4                                |      | Lenovo |
| Additional information | Energy Star, EPEAT, TCO                 |      |        |

| P7.1.1   | Product environmental attributes   |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|--|
| (d)  | year of manufacture:   |  |  |  | 2020                                   |  |  |  |
| (e)  | Etec value (kWh) per ErP Lot 3 Categor<br>disabled and if the system is tested with  |  |  |  | cards (dGfx) are                       |  |  |  |
| (f)  | Etec value (kWh) per ErP Lot 3 Categor<br>enable   | y and capability adjust                | ments applied when <b>a</b>            | Il discrete graphics o                 | cards (dGfx) are                       |  |  |  |
|  |  | Category A<br>(according to ErP Lot 3) | Category B<br>(according to ErP Lot 3) | Category C<br>(according to ErP Lot 3) | Category D<br>(according to ErP Lot 3) |  |  |  |
|  | Memory over base [GB]  |  | 126                                    |  | 124                                    |  |  |  |
| ients<br>sting                                   | Additional internal storage  | (Yes / No)                             | Yes<br>(Yes / No)                      | (Yes / No)                             | Yes<br>(Yes / No)                      |  |  |  |
| capability adjustments<br>applied during testing | Discrete television tuner  | (Yes / No)                             | <mark>No</mark><br>(Yes / No)          | (Yes / No)                             | No<br>(Yes / No)                       |  |  |  |
| ability a  | Discrete Audio Card  | (Yes / No)                             | <mark>No</mark><br>(Yes / No)          | (Yes / No)                             | No<br>(Yes / No)                       |  |  |  |
| cap<br>app                                       | Discrete graphics Card(s) [number / #]   | #:<br>(Yes / No)                       | Yes #: 1<br>(Yes / No)                 | #:<br>(Yes / No)                       | Yes #: 1<br>(Yes / No)                 |  |  |  |
|  | Category of discrete graphics Card(s)  |  | G5                                     |  | G5                                     |  |  |  |
| esults   | Etec Value (kWh) - dGfx disabled<br>all discrete graphics cards (dGfx) are disabled/<br>UMA is active for switchable graphics/<br>product has no graphics cards (dGfx) |  | 67.75                                  |  | 59.05                                  |  |  |  |
| Test results                                     | Etec Value (kWh) - dGfx enabled<br>all discrete graphics cards (dGfx) are enabled  |  | 96.29                                  |  | 98.54                                  |  |  |  |
| (g)  | Idle state power demand (Watts);   |  |  |  | 26.33<br>26.77                         |  |  |  |
| (h)  | Sleep mode power demand (Watts);   |  |  |  | 2.21<br>2.52                           |  |  |  |
| (i)  | Sleep mode with WOL enabled power de   | emand (Watts) (where                   | enabled);                              |  | 2.26                                   |  |  |  |
| (j)  | Off mode power demand (Watts);   |  |  |  | <u>2.46</u><br>0.63                    |  |  |  |
| (k)  | Off mode with WOL enabled power dem  | and (Watts) (where en                  | abled):                                |  | <u> </u>                               |  |  |  |
| . ,  |  |  |  | <i></i>                                | 0.76                                   |  |  |  |
| (I)  | Internal power supply efficiency at 10 %,  |  |  | ,                                      |  |  |  |  |
| ()   | PCK012 10% 83.83% 20% 85.34% 50% 87.16% 100% 84.63% Average 85.71%   |  |  |  |  |  |  |  |
| (m)  | External power supply efficiency (if appli   | cable)":                               |  |  |  |  |  |  |
|  | Average active efficiency:<br>*internal note: show values for all available external po  | awar supplies                          |  |  |  |  |  |  |
| (0)  | Minimum number of loading cycles that t  |  | and (applies only to n                 | otebook computers):                    | NA                                     |  |  |  |
| (p-1)  | I) Measurement methodology used to determine information mentioned in points (I) – internal PSU efficiency:<br>80 PLUS® Program  |  |  |  |  |  |  |  |

| (p-2)  | Measurement methodology used to determine information mentioned in points (m) – external PSU efficiency:<br>NA  |                 |   |                               |     |  |
|--|---|-----------------|---|-------------------------------|-----|--|
| (p-3)  | Measurement methodology used to determine information mentioned in points (o) – loading cycles batteries:<br>NA   |                 |   |                               |     |  |
|  | Measurement methodology used to determine information mentioned in maximum, idle, sleep, off mode power as defined in Point P9.1 in the Product IT Eco Declaration:   |                 |   |                               |     |  |
| IEC 62623 Ed. 1.0, 2012-10   |   |                 |   |                               |     |  |
| (q)  | Sequence of steps for achieving a stable condition with respect to power demand::   |                 |   |                               |     |  |
|  | Based on Energy Star Computer V7.1I/Power on->Wait 5 minutes->Stable condition(long idle)   |                 |   |                               |     |  |
| (r) Description of how sleep and/or off mode was selected or programmed:   |   |                 |   |                               |     |  |
| Start menu -> Power -> Select sleep or off mode  |   |                 |   |                               |     |  |
|  | Sequence of events required to reach the mode where the equipment automatically changes to sleep and/or off mode:   |                 |   |                               |     |  |
|  | Control Panel->Power Options-> Change Settings-> Restore default settings for this plan   |                 |   |                               |     |  |
|  | Duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes): 25  |                 |   |                               |     |  |
| (u)  | Length of time after a period of user inactivity in which the computer automatically reaches a power<br>mode that has a lower power demand requirement than sleep mode (in minutes):  |                 |   |                               |     |  |
| (v)  | Length of time before the display sleep mode is set to activate after user inactivity (in minutes): 10  |                 |   |                               |     |  |
| (w)  | Information on the energy-saving potential of power management functionality:   |                 |   |                               |     |  |
| NA   |   |                 |   |                               |     |  |
| (x)  | User information on how to enable the power management functionality:   |                 |   |                               |     |  |
| Refer to User Guide  |   |                 |   |                               |     |  |
|  | Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of<br>the electricity supply system, — information and documentation on the instrumentation, set-up and circuits<br>used for electrical testing: |                 |   |                               |     |  |
| Test voltage in V and frequency in Hz: 230V/50Hz<br>Total harmonic distortion of the electricity supply system: ≤2%                  |   |                 |   |                               |     |  |
|  | Instrument  |                 | Range Used or *****   | Make and Model**              |     |  |
|  | AC Power S  |                 | 1~300VAC;1~550Hz; 1000VA  | NF; EC1000S                   |     |  |
|  | Power Meter   |                 | 1~500V;0~20A  | YOKOGAWA; WT310               |     |  |
|  | Digital W   | atch            | Full Range  | CASIO; HS-70W                 |     |  |
|  | Ambient M   | lonitor         | -10~60℃; 0~100&RH   | Testo; 622                    |     |  |
|  | Anemom  | eter            | 0~20m/s   | Testo; 425                    |     |  |
|  |   |                 |   |                               |     |  |
| Additional Notebook Battery Information:         Battery[ies] not user replaceable         Battery[ies] user replaceable         n/a |   |                 |   |                               |     |  |
|  |   | The battery[ies | s] in this product cannot be easily ers themselves. <sup>1)</sup> | batterylies] user replaceable | n/a |  |
| Internal/built-in Battery  |   |                 |   |                               |     |  |
| External/de  | etachable Battery   |                 |   |                               |     |  |
| Bios Backup Battery  |   |                 |   |                               |     |  |
| Other:   |   |                 |   |                               |     |  |
| Additional information   |   |                 |   |                               |     |  |
|  |   |                 |   |                               |     |  |
| )  |   |                 |   |                               |     |  |

Annex B1 of ECMA-370 5<sup>th</sup> edition (Lenovo) 2015-04-08

The battery[ies] in this product cannot be easily replaced by users themselves. Акумулаторната[ите] батерия[и] в този продукт не може да се замени[ят] лесно от самите потребители. Las baterías de este producto no pueden ser sustituidas fácilmente por los propios usuarios. Výměnu baterie/baterií v tomto výrobku by neměli provádět sami uživatelé. Brugeren kan ikke uden videre udskifte batteriet/batterierne i dette produkt. Der Akku/die Akkus dieses Produkts kann/können nicht ohne weiteres vom Benutzer selbst ausgetauscht werden. Kosutraind ni saa selle toote akut/akusid ise hölnsasti asendarla.

H μπαταρία[-ες] στο προϊόν αυτό δεν μπορούν να αντικατασταθούν εύκολα από τους ίδιους τους χρήστες La/les batterie(s présente(s) dans ce produit ne peuvent être facilement remplacée(s) par les utilisateurs eux-mêmes. Korisnik ne može lako zamijeniti Bateriju sam u ovom proizvodu. La batteria/le batterie in questo prodotto non può/possono essere facilmente sostituita/e dall'utente. Lietotāji paši nevar nomainīt šā ražojuma akumulatoru(-us). Šio gaminio baterijos [bateriju] pats vartotojas negali lengvai pakeisti. A termék akkumulátorát/akkumulátorait a felhasználó nem tudja egyedül egyszerűen kicserélni. II-batterija/batteriji f dan il-prodott ma tistax/jistgħux tiġ/jíġu sostitiwita/i mill-utenti stess. Batteriet lenel i dette produktet kan ikke lett erstattes av brukerne selv

Batteria (bateria) i tan il-product ma tistax/jistgnux tig/jigt sostitivita/ mil-utenti stess. Batteriet [ene] i dette produktet kan ikke lett erstattes av brukerne selv. De batterij(en) in dit product is (zijn) door de gebruiker niet gemakkelijk vervangbaar. Użytkownik nie może sam w łatwy sposób wymienić baterii w tym produkcie. A ou as baterias deste produto não podem ser facilmente substituídas pelos próprios utilizadores. Bateria (bateriile) din acest produs nu poate (pot) fi uşor înlocuită (înlocuite) de utilizatorii înșiși. Bateriu(-ie) v tomto výrobku nemôže vymieňať používateľ. Paterii/hetorii o y tomto výrobku nemozie vomieňať používateľ.

Baterij/Setrije v tem izdelku uporabniki sami ne morejo zlahka zamenjati. Tämän tuotteen akku [akut] ei[vät] ole helposti käyttäjän vaihdettavissa. Det är inte enkelt för kunden att själv byta ut batteriet/batterierna.

Bu üründeki batarya(lar) kullanıcılar tarafından kolaylıkla değiştirilemez.