

Annex B2 - Product environmental attributes Computers and computer monitors

The declaration may be published only when all rows and/or fields marked with * are filled-in (N/A for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lenovo	Logo	
Company name *	Lenovo		
Contact information *	Lenovo Environmental Social and Governance		Lenovo
e-mail address	environment@lenovo.com		
Internet site *	https://www.lenovo.com/us/en/sustainability-resources/		
Additional information	The latest version of this document can be found at:		
	http://www.lenovo.com/ecodeclaration		

	(based on product specification or test results based obtained from sample testing), that the product ents given in this declaration.
Type of product *	Notebook Computer
Commercial name *	ThinkPad L14 Gen 4
Model number *	21H1,21H2
Issue date *	2023-04-11
Intended market *	🔀 Global 📃 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other
Additional information	

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 – P4.3 Consumable materials

- P9.1 TEC and Print speed
- P10.2 P10.3 Chemical emissions from printing products
- P11.1 P11.3 Consumable materials for printing products.

Model nu	umber *	21H1,21H2	Logo		
Issue da	te *	2023-04-11		eno	VO,
	t environi	nental attributes - Legal requirements		Requirer	
Item				Yes	No N/A
P1		ous substances and preparations			
P1.1*		s comply with current European RoHS Directive. (See legal reference and NO	IEB1)	\bowtie	
P1.2*		s do not contain Asbestos (See legal reference) nt: Legal reference has no maximum concentration value.		\square	
P1.3*	hydrobr trichloro	s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), pmofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbonte ethane, methyl bromide (See legal reference). Comment: Legal reference has ration values		1-	
P1.4*		s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% p /l (PCT) in preparations (See legal reference)	olychlorinated	\boxtimes	
P1.5*	chain co	s do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 ntaining at least 48% per mass of chlorine in the SCCP (See legal reference)			
P1.6*	(See leg	th direct and prolonged skin contact do not release nickel in concentrations about a reference) nt: Max limit in legal reference when tested according to EN1811:2011-5	ove 0,5 µg/cm²/v	week	
P1.7*	REACH	Article 33 information about substances in articles is available at (add URL or www.lenovo.com/us/en/Lenovo-REACH-SVHCDisclosure	mail contact):	\boxtimes	
P2	Batterie	S			
P2.1*		oduct contains a battery or an accumulator, the battery/accumulator is labeled Information on proper disposal is provided in user manual. (See legal referenc			
P2.2*	Batterie referenc	s or accumulators do not contain more than 0,0005% of mercury or 0,002% of e)	cadmium. (See	legal 🔀	
P2.3*	Batterie	s and accumulators are readily removable. (See legal reference)		\boxtimes	
P2.4*	Docume	ntation includes the number of cycles the (secondary) battery can withstand. (See legal refere	nce) 🔀	
P2.5*		ternal batteries of a notebook computer cannot be "accessed and replaced by e related text is present and legible on the external packaging (See legal refer		nal 🔀	
P3		nity verification & Eco design (ErP)	/	·	
P3.1*	The Dec https://	duct is CE-marked to show conformance with applicable legal requirements (se daration of Conformity can be requested at (add link or e-mail address): www.lenovo.com/us/en/compliance/uk-doc for EU www.lenovo.com/us/en/compliance/uk-doc for UK	ee legal referend	≿e). ⊠	
P3.2*	The pro	duct complies with the applicable Eco design requirements for energy-related p al reference)	products,	\boxtimes	
	Require	d information is; available at (add URL): <u>http://www.lenovo.com/ed</u>	codeclaration	\boxtimes	
P5	Produc	t packaging			
P5.1*	Packagi hexaval	ng and packaging components do not contain more than 0,01% lead, mercury, ent chromium by weight of these together		\boxtimes	
P5.2*		kaging materials are marked with abbreviations and numbers indicating the na	ature of the mate	rial(s) 🔀	
P5.3*	The pro Protoco Comme	duct packaging material is free from ozone depleting substances as specified in (See legal reference) nt: Legal reference has no maximum concentration values	n the Montreal		
P6		nt information			
P6.1*	Informat	ion for recyclers/treatment facilities is available (<u>https://lenovo.com/recycling</u>	2).	\boxtimes	

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model n	umber *	21H1,21H2 Logo			
lssue da	te *	2023-04-11	ler	0	VC
Produc	- Enviro	mental attributes - Market requirements (See General NOTE GN below) onmental conscious design	Require	ment	met
Item		tory to fill in. Additional information regarding each item may be found under P14.	Yes	No	N/A
P7	Design	and the second the se			
P7.1*	Parts tha	mbly, recycling It have to be treated separately are easily separable			
P7.2*		naterials in covers/housing have no surface coating			- 🕂
P7.3*		arts > 100 g consist of one material or of easily separable materials		<u> </u>	
P7.4*	-	arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4		<u> </u>	<u> </u>
	-			<u> </u>	<u> </u>
P7.5	-	arts are free from metal inlays or have inlays that can be removed with commonly available tools		<u> </u>	<u> </u>
P7.6*		re easily separable (This requirement does not apply to safety/regulatory labels)			
D7 7*	Product				
P7.7*		ng can be done e.g. with processor, memory, cards or drives		<u> </u>	<u> </u>
P7.8*		ng can be done using commonly available tools	\square		
P7.9		arts are available after end of production for: 5 years			
P7.10		s available after end of production for: 5 years			
	Material	and substance requirements			
P7.11*		cover/housing material type (e.g. plastics, metal, aluminum): type: PC/ABS Material type: PC/CF Material type: AI			
P7.12		n materials of external electrical cables are PVC free		\square	
P7.13	Insulatio	n materials of internal electrical cables are PVC free			H
P7.14	External weight (1 polyvinyl	plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% (000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts g more than 25% post-consumer recycled content			
P7.15		ircuit boards, PCBs (without components) are low halogen as defined in IEC 61249-2-21. (See 2): Only PCBs > 25g 🔀 or All PCBs 🗌	\boxtimes		
P7.16	Flame re Marking:	tarded plastic parts > 25 g in covers / housings are marked according to ISO 1043-4: FR(40)	\boxtimes		
P7.17		nemical specifications of flame retardants in printed circuit boards > 25 g (without components): additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: <i>DOPO-HQ</i> , CAS #: 0-1			
	accordin	nemical specifications of flame retardants in printed circuit boards (without components) > 25 g g to ISO 1043-4:			
P7.18	Alt. 1: Fla concentr 1. Chem	ame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in ations above 0,1%: ical name: , CAS #: (See NOTE B4) ical name: , CAS #: "			
	3. Chem <u>Alt. 2: </u> Cł	ical name: , CAS #: " nemical specifications of flame retardants in plastic parts > 25 g according to ISO 1043-4: FR(40)			
P7.19	In plastic assigned	parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been I the following Risk phrases; and Hazard statements: ce(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5)			

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see <u>http://www.ecma-international.org/publications/standards/Ecma-370.htm</u>.

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

Model number *	21H1,21H2				Logo			
Issue date *	2023-04-11					en	\mathbf{O}	VO.
Product environ	mental attributes - Ma	rket requirem	ents (continue	ed)		Requir	emei	nt met
Item				,		Yes	No	N/A
	al and substance require	ments (continue	ed)					
	nsumer recycled plastic ma				36):			
a) Of	at least one of the two alte total plastic parts' weight : rcentage of total plastic by	> 25 g, the postc	onsumer recycle		l content (calculated as a			
	e weight of recycled mater							
	ed plastic material content at least one of the two alte							
a) Of	total plastic parts' weight :	> 25 g, the bioba			ulated as a percentage of		\boxtimes	
	tal plastic by weight) is ne weight of the biobased p	%. or	g					
	ources are free from mercu							
	ury is used specify: Numbe			mercury content				
-	ict includes an integral disp	play, the total me	rcury content in	the integrated dis	splay: 0.0 mg			
	chemical composition: Lit	hium ion						
-	consumption (See NOT							
	product the following power		gy consumptions	are reported:				
Energy mode *		Power level at	Power level at	Power level at	Reference/Standard for	energy		
		100 V AC	115 V AC	230 V AC	modes and test method			
Peak (On-Max)		100 W	100 W	100 W	Full Load			
Device Category 1								
Short Idle State –	WOL Enabled (P _{short_idle})	5.328 W	5.208 W	5.436 W	ENERGY STAR Compu	iters V8.	0	
Long Idle State – I	WOL Enabled (Plong_idle)	0.804 W	0.792 W	0.804 W	ENERGY STAR Compu	iters V8.	0	
Sleep (S3) – WOL	Disabled (P _{Sleep})	0.804 W	0.792 W	0.804 W	ENERGY STAR Compu	iters V8.	0	
Off Mode (S5) – W	OL Disabled (P _{off})	0.276 W	0.276 W	0.300 W	ENERGY STAR Compu	iters V8.	0	
Device Category 2	2							
Short Idle State –	WOL Enabled (Pshort_idle)	6.948 W	7.008 W	6.996 W	ENERGY STAR Compu	iters V8.	0	
Long Idle State – I	WOL Enabled (Plong_idle)	1.356 W	1.344 W	1.356 W	ENERGY STAR Compu	iters V8.	0	
Sleep (S3) – WOL	Disabled (P _{Sleep})	1.356 W	1.344 W	1.356 W	ENERGY STAR Compu	iters V8.	0	
Off Mode (S5) – W	OL Disabled (Poff)	0.336 W	0.408 W	0.384 W	ENERGY STAR Compu	iters V8.	0	
Device Category 1	Typical Configuration							
Short Idle State –	WOL Enabled (P _{short_idle})	W	W	W	ENERGY STAR Compu	iters V8.	0	
Long Idle State – I	WOL Enabled (Plong idle)	W	W	W	ENERGY STAR Compu	iters V8.	0	
Sleep (S3) – WOL		W	W	W	ENERGY STAR Compu	iters V8.	0	
Off Mode (S5) – W	1	W	W	W	ENERGY STAR Compu			
PTEC * Typical Energy Cor		W	W	W				
ETEC * Annual Energy Con	sumption	15.79/ 21.89 kWh/year	15.48/ 22.13 kWh/year	16.08/ 22.1 kWh/year	Mode Weighting Full Capability			
External Power Sup	oply Efficiency Level (Interr		-	-	International Efficiency Protocol (IEMP) for Ex Power Supplies		g	
Display resolution *	: 2.074 megapixels				1920*1080			
Default time to ente	er energy save mode: 5 min	nutes			ENERGY STAR Compu	Iters V8	0	
	tion about the energy save		ided with the pro	duct				
	efficiency class (monitors	•						
Lielgy	children of the second se	onny).						\boxtimes

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available;

see http://www.ecma-international.org/publications/standards/Ecma-370.htm.

Model number *	21H1,21H2	Logo	
Issue date *	2023-04-11		Lenovo

	t environmenta	attributes - Market requirements (contin	uea) R	equire		
Item				Yes	No	N/A
P10	Emissions		80)			
D40.4		n – Declared according to ISO 9296 (See NOTE				
P10.1	Mode	Mode description	Statistical upper limit A-weighted sound power $L_{WA,c}$ (B)	er level,		
	Idle	* Idle Mode	* 2.6			
	Operation	* Operating (CPU)	* 3.3			Π
	Other Mode	Declared A-weighted sound pressure level (dB)	NA (operator position desktop – idle)			
	Other mode	Declared A-weighted sound pressure level (dB)	NA (operator position desktop – operating-HD NA (operator position desktop – operating-CP			
	Measured acco	rding to: ISO 7779 ECMA-74	ECMA-74)			
	Electromagne					
P10.4	Computer disp	ay meets the requirement for low frequency elect ?R-II(3 pin AC adapter only)	romagnetic fields of the following voluntary			
P12	Ergonomics for	or computing products				
P12.1*	The display me	ets the ergonomic requirements of ISO 9241-307	for visual display technologies	\boxtimes		
P12.2*	The physical in	put device meets the requirements of ISO 9995 a	nd ISO 9241-410		Π	
P13	Packaging an	documentation		<u>K</u>		
P13.1*	Product package Product package	jing material type(s): Carboard weight (kg): 0 jing material type(s): Carboard weight (kg): 0 jing material type(s): Paper weight (kg): 0 jing material type(s): Paper weight (kg): 0	.050 .1512			
P13.2*	Product plastic	primary packaging is free from PVC		\boxtimes		
P13.3*	For product pri	mary corrugated fiberboard packaging, specify th vered fiber content: 60 %	e contained percentage of minimum post-			
P13.4*	Specify media	or user and product documentation (tick box): Paper 🔀, Other 🗌				
P13.5		mplete this item if paper documentation used) ict documentation on paper media is chlorine-free pecify:	:			
	Totally chlorine	-free				
	Elemental chlo					
	Processed chlo					
P14	Voluntary pro					
P14.1	The product me	eets the requirements of the following voluntary p	rogram(s):			
	ENERGY STA Eco-label: <i>EPE</i>		ate: 2023-02-02 Product category: 1,2 ate: 2023-04-17 Product category: Notebook			
	Eco-label: TCC		ate: 2023-04-30 Product category: Notebook			
P15		ormation (See NOTE B10)				
<u>P9</u>		mption of computer products; description of t				
P7.7 P7.8	In further expl Processor	anation of Upgradability (P7.7/P7.8), the follow Not Upgradeable	ving components can be upgraded:			
	Memory	Upgradeable using cor	nmon tools			
	Cards	Not Upgradeable				
	Drives/Storag		nmon tools			
	the information supplier's known information. T	er makes no representations, guarantees, ass n contained in this document. All information wledge available at the time of completion, ar he information provided here is approximate esentative for more information.	provided by supplier in this document is pro d supplier shall have no obligation to updat	ovided e such	based	lon

NOTE B9 A Guidance document on Acoustic Noise is available;

see http://www.ecma-international.org/publications/standards/Ecma-370.htm.

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B2

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive)* * Specific exemptions apply for certain products and applications.	P1.1, P3.1
Regulation (EC) 1907/2006 (REACH Regulation), annex XVII	P1.2, P1.4, P1.6, P1.7
Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)	P1.3, P5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2006/66/EC (Battery and accumulators Directive), as amended.* * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2.3, P8.1
Directive 2014/35/EU (Low Voltage Directive)	P3.1
Directive 2014/30/EU (EMC Directive)	P3.1
Directive 2014/53/EU (RE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Commission Regulation (EC) No 278/2009 of 6 April 2009 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for no-load condition electric power demand and average active efficiency of external power supplies	P3.1, P3.2, P9.1
COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers	P2.4, P2.5, P3.1, P3.2, P7.23, P9.1
Regulation (EC) No 1272/2008 (CLP Regulation)	P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1
Implementing Regulation (EU) 2019/290 establishing the format for registration and reporting of producers of electrical and electronic equipment to the register.	
Commission Implementing Regulation 2017/699 establishing a common methodology for the calculation of the weight of electrical and electronic equipment (EEE) placed on the national market in each Member State and a common methodology for the calculation of the quantity of waste electrical and electronic equipment (WEEE) generated by weight in each Member State.	

Lenovo ErP Lot26 Information Sheet - Network Equipment -

As required by_

- Commission Regulation (EC) No 1275/2008 of 17 December 2008 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for standby and off-mode electric power consumption of electrical and electronic household equipment (ErP Lot 6)
- Commission Regulation (EU) No 801/2013 of 22 August 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for (ErP Lot 26).

Products scope of this sheet:

Notebook/Tablet Computer < 6 W Idle

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	ThinkPad L14 Gen 4	Logo
Model Number	21H1,21H2	
Product Type	Notebook Computer with Idle Power < 6 W	Lenovo
Issue Date	2023-04-011	
Additional information		

	2023
Network Standby Classification	LoNA Equipment
Off Mode Power (Watts)	0.3 Watts
Standby Mode	Watts Mode Not Applicable
	minutes Default Delay Time
Description of how to enable Network Standby Mode	Network Standby Mode is enabled at Shipment
Description of how to manually enter Network Standby Mode	1) Press the Power Button once; 2) Click on the Power Button and choose Sleep
Default Delay time to Network Standby Mode	10 minutes
Reactivation Function from Network Standby Mode	Open Notebook, Press Keyboard or power button, activate USB

		Wired Ethernet	Wireless Ethernet	USB-A	USB-C	HDMI	BlueTooth	Other: Smart-card slot
	Present in Product							
	Activated at Shipment						\boxtimes	
	Active in Network Standby Mode							
	Location of Network Port	Left	N/A	Left	Left	Left	N/A	Left
	Network Port Maximum Performance	1.0 GB/s	0.1 GB/s	GB/s	s GB/s	GB/s	GB/s	GB/s
	Network Protocol	802.3	Wi-Fi 6; 802.11ax	USB 3.2 Gen 1	2 Thunderb olt™ 4		BT5.2	4G
	Network Standby Mode Power	1.3 Watts	1.3 Watts	Watts	Watts	Watts	Watts	Watts
	Network Standby Power – All Connections		I	1	1.3 Watts			
4)	Test parameters for r	measurements,				he User Manua		
)	Test parameters for r ambient temperatur			2	4.8 degrees Cels			
)		re	łz		4.8 degrees Cels 30 V / 50 Hz			
)	ambient temperatur	re d frequency in ⊦		2	-			
•)	ambient temperatur test voltage in V an	re d frequency in ⊦		2. iem 2.	30 V / 50 Hz .00% Equipment			Calibration
ł)	ambient temperatur test voltage in V an	re d frequency in H prtion of the elec cumentation on t	tricity supply syst	2. iem 2. on, set-	30 V / 50 Hz .00% Equipment AC Source Power Analyzer	iius	al Last (Date	Calibration
)	ambient temperatur test voltage in V an total harmonic disto	re d frequency in H prtion of the elec cumentation on t	tricity supply syst	2. tem 2. on, set-	30 V / 50 Hz .00% Equipment AC Source Power Analyzer Timer Thermometer	Make/Mode	al Last (Date	Calibration
	ambient temperatur test voltage in V an total harmonic disto information and doo up and circuits used	re d frequency in H ortion of the elec cumentation on f d for electrical te	tricity supply syst	2. tem 2. on, set-	30 V / 50 Hz .00% Equipment AC Source Power Analyzer Timer	Make/Mode	al Last (Date	Calibration
	ambient temperatur test voltage in V an total harmonic disto information and doo up and circuits used External power supp	re d frequency in H prtion of the elec cumentation on t d for electrical te ly efficiency (if a	tricity supply syst the instrumentation sting pplicable)*:	2. tem 2. on, set-	30 V / 50 Hz .00% Equipment AC Source Power Analyzer Timer Thermometer Hygrometer	Make/Mode YOKOGAV WT210	el Last (Date	
	ambient temperatur test voltage in V an total harmonic disto information and doo up and circuits used	re d frequency in H prtion of the elec cumentation on f d for electrical te ly efficiency (if a Output	tricity supply syst	tem 2.	30 V / 50 Hz .00% Equipment AC Source Power Analyzer Timer Thermometer Hygrometer Average Active	Make/Mode YOKOGAV WT210	el Last (Date VA-	ad
	ambient temperatur test voltage in V an total harmonic disto information and doo up and circuits used External power supp	re d frequency in H prtion of the elec cumentation on t d for electrical te ly efficiency (if a	tricity supply syst the instrumentation sting pplicable)*:	2. tem 2. on, set-	30 V / 50 Hz .00% Equipment AC Source Power Analyzer Timer Thermometer Hygrometer	Make/Mode YOKOGAV WT210	el Last (Date VA-	nd r
	ambient temperatur test voltage in V an total harmonic disto information and doo up and circuits used External power supp Model	re d frequency in H portion of the elec cumentation on f d for electrical te ly efficiency (if a Output Voltage 20 V 20 V	tricity supply syst the instrumentation sting pplicable)*: Output Current 5 A 5 A	2. tem 2. on, set-	30 V / 50 Hz .00% Equipment AC Source Power Analyzer Timer Thermometer Hygrometer Average Active Efficiency 90% 89%	Make/Mode YOKOGAV WT210	el Last (Date VA-	ıd r
	ambient temperatur test voltage in V an total harmonic disto information and doo up and circuits used External power supp Model Delta Chicony Liteon	re d frequency in F prtion of the elec cumentation on f d for electrical te ly efficiency (if a Output Voltage 20 V 20 V 20 V	tricity supply syst the instrumentation sting pplicable)*: Output Current 5 A 5 A 5 A	2. tem 2. on, set-	30 V / 50 Hz .00% Equipment AC Source Power Analyzer Timer Thermometer Hygrometer Average Active Efficiency 90% 89% 89%	Make/Mode YOKOGAV WT210	VA-	id r V
	ambient temperatur test voltage in V an total harmonic disto information and doo up and circuits used External power supp Model Delta Chicony	re d frequency in H prtion of the elec cumentation on t d for electrical te ly efficiency (if a Output Voltage 20 V 20 V 20 V 20 V	tricity supply syst the instrumentation sting pplicable)*: Output Current 5 A 5 A 5 A 5 A	2. tem 2. on, set-	30 V / 50 Hz .00% Equipment AC Source Power Analyzer Timer Thermometer Hygrometer Average Active Efficiency 90% 89%	Make/Mode YOKOGAV WT210	VA-	ad r V V
	ambient temperatur test voltage in V an total harmonic disto information and doo up and circuits used External power supp Model Delta Chicony Liteon	re d frequency in H prtion of the elec cumentation on the d for electrical te ly efficiency (if a Output Voltage 20 V 20 V 20 V 20 V 20 V 20 V 20 V 20 V	tricity supply syst the instrumentation sting pplicable)*: Output Current 5 A 5 A 5 A	2. tem 2. on, set-	30 V / 50 Hz .00% Equipment AC Source Power Analyzer Timer Thermometer Hygrometer Average Active Efficiency 90% 89% 89%	Make/Mode YOKOGAV WT210	VA-	ad r V
4) 5) 6)	ambient temperatur test voltage in V an total harmonic disto information and doo up and circuits used External power supp Model Delta Chicony Liteon Acbel	re d frequency in F prion of the elec cumentation on f d for electrical te ly efficiency (if a Output Voltage 20 V 20 V	tricity supply syst the instrumentation (sting) pplicable)*: Output Current 5 A 5 A 5 A 5 A 5 A 5 A 4 5 A 5 A 5 A 5 A 5 A 5 A 5 A 5 A 5 A 5 A	2 tem 2 on, set-	30 V / 50 Hz .00% Equipment AC Source Power Analyzer Timer Thermometer Hygrometer Average Active Efficiency 90% 89% 90% ed in points (5) –	Make/Mode YOKOGAV WT210	VA-	ad r V V