

Annex B2 - Product environmental attributes Computers and computer monitors

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

| Brand * | Lenovo | Logo | |
|------------------------|--|------|---------|
| Company name * | Lenovo | | |
| Contact information * | Lenovo Global Environmental Affairs | | Lenovo |
| e-mail address | Alvin L Carter | | LEIIUVU |
| | alcarter@Jenovo.com | | |
| Internet site * | https://www.lenovo.com/us/en/sustainability-resources/ | | |
| Additional information | The latest version of this document can be found at: | | |
| | http://www.lenovo.com/ecodeclaration | | |

| | based on product specification or test results based obtained from sample testing), that the product nts given in this declaration. |
|------------------------|--|
| Type of product * | Notebook Computer |
| Commercial name * | ThinkPad X1 Carbon Gen 11 |
| Model number * | 21HM,21HN |
| Issue date * | 2023-03-06 |
| Intended market * | 🛛 Global 🗌 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other |
| Additional information | |

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products.

| Model n | umber * | 21HM,21HN | | | | | Logo | | | _ | |
|-----------|------------------------------------|---|---|--|---------------------------------|----------------|--------------|-------------|-------------|-------|------------------------|
| lssue da | ite * | 2023-03-06 | | | | | | Le | nc | | O _{TM} |
| Produc | tenvironn | nental attributes | - Logal roquir | romonte | | | | P | equire | mont | mot |
| Item | | ientai attributes | - Legai lequii | ements | | | | n | Yes | No | n.a. |
| P1 | Hazardo | ous substances and | d preparations | | | | | | 100 | 110 | n.u. |
| P1.1* | | do comply with cur | | RoHS Directive | . (See legal re | ference and N | NOTE B1) | | \square | | |
| P1.2* | | do not contain Asb | • | | . (| | | | | ⊢⊢ | |
| 1 1.2 | | nt: Legal reference h | | | value. | | | | | | |
| P1.3* | Products hydrobro trichloroe | do not contain Ozc mofluorocarbons (H ethane, methyl brom ation values. | ne Depleting Su IBFC), hydrochlo | bstances: Chlo profluorcarbons | orofluorocarbo s (HCFC), Hal | ons, carbonte | | | | | |
| P1.4* | Products | do not contain mor (I (PCT) in preparation | | | d biphenyl (PC | B), 0,005% p | olychlorinat | ed | \boxtimes | | |
| P1.5* | Products | do not contain mor ntaining at least 48% | e than 0,1% sho | ort chain chloro | | | 3 carbon at | oms in the | \boxtimes | | |
| P1.6* | (see lega | h direct and prolong al reference). nt: Max limit in legal | | | | | ove 0,5 μg/ | cm²/week | | | |
| P1.7* | REACH | Article 33 informatic | n about substan | ices in articles | | | mail contac | xt): | | | |
| P2 | Batterie | S | | | | | | | | | |
| P2.1* | | oduct contains a batt Information on prop | | | | | | posal | \boxtimes | | |
| P2.2* | Batteries referenc | or accumulators do e) | o not contain mo | re than 0,0005 | % of mercury | or 0,002% of | cadmium. (| See legal | \boxtimes | | |
| P2.3* | Batteries | and accumulators | are readily remo | vable. (See leg | gal reference) | | | | \times | | |
| P2.4* | Docume | ntation includes the | number of cycle | s the (seconda | ary) battery ca | n withstand. (| See legal re | eference) | \boxtimes | | |
| P2.5* | | ternal batteries of a e related text is pres | | | | | | ssional | | | |
| P3 | | nity verification & I | | | | | | | | | |
| P3.1* | The Dec <u>https://v</u> | luct is CE-marked to laration of Conformi <u>www.lenovo.com/u</u> www.lenovo.com/u | ty can be reques <u>s/en/complianc</u> | sted at (add lini <u>e/eu-doc</u> for E | k or e-mail ado EU ; | | ee legal ref | erence). | | | |
| P3.2* | The proc | luct complies with that reference). | | | | ergy-related p | products, | | \boxtimes | | |
| | Required | d information is; | = - | em P15 or add at (add URL): | | | codeclarati | ion | \boxtimes | | |
| P5 | Product | packaging | | | | | | | | | |
| P5.1* | hexavale | ng and packaging co ent chromium by we | ight of these tog | ether. | | | | | \boxtimes | | |
| P5.2* | | kaging materials are e legal reference). | marked with ab | breviations and | d numbers ind | icating the na | ture of the | material(s) | \boxtimes | | |
| P5.3* | Protocol Commer | luct packaging mate (see legal reference ht: Legal reference h | e). | • | 0 | as specified i | n the Montr | eal | | | |
| P6.1* | | nt information | | | | | | | | | |
| | lun for sumo oti | on for recyclers/trea | tment facilities is | a availahla (htt | tns://lenovo.c | om/recyclind | 7) | | | - I I | |

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

| Model n | | 21HM,21HN Logo | | | |
|----------|--------------------------------|--|-------------|-----------|----------|
| lssue da | te * | 2023-03-06 | Ler | 10 | VC |
| Produc | - Enviro | mental attributes - Market requirements (See General NOTE GN below) onmental conscious design | Require | ement | met |
| ltem | | tory to fill in. Additional information regarding each item may be found under P14. | Yes | No | n.a. |
| P7 | Design | | | | |
| P7.1* | | mbly, recycling It have to be treated separately are easily separable | | | |
| P7.2* | | | | | <u> </u> |
| P7.2 | | naterials in covers/housing have no surface coating. | <u> </u> | | |
| | | arts > 100 g consist of one material or of easily separable materials. | | <u> </u> | |
| P7.4* | | arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. | | | |
| P7.5 | • | arts are free from metal inlays or have inlays that can be removed with commonly available tools. | | | |
| P7.6* | | re easily separable. (This requirement does not apply to safety/regulatory labels). | \square | | |
| | Product | | | | |
| P7.7* | | ng can be done e.g. with processor, memory, cards or drives | | | |
| P7.8* | | g can be done using commonly available tools | \square | | |
| P7.9 | Spare pa | arts are available after end of production for: 5 years | | | |
| P7.10 | Service i | s available after end of production for: 5 years | | | |
| | | and substance requirements | | | |
| P7.11* | | cover/housing material type (e.g. plastics, metal, aluminum): type: CF Material type: Mg Material type: AL Material type: PC/AB | s | | |
| P7.12 | Insulatio | n materials of external electrical cables are PVC free. | | \square | |
| P7.13 | Insulatio | n materials of internal electrical cables are PVC free. | | Ē | Ē |
| P7.14 | weight (1 polyvinyl | plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% 1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts g more than 25% post-consumer recycled content. | 6 | | |
| P7.15 | Printed of | ircuit boards, PCBs (without components) are low halogen: all ☐ PCBs > 25 g | \boxtimes | | |
| P7.16 | | tarded plastic parts > 25 g in covers / housings are marked according to ISO 1043-4: | \boxtimes | | |
| P7.17 | TBBPA (| nemical specifications of flame retardants in printed circuit boards > 25 g (without components): additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: of A diphosphate, CAS #: 181028-79-5 | | | |
| | accordin | nemical specifications of flame retardants in printed circuit boards (without components) > 25 g g ISO 1043-4: | | | |
| P7.18 | concentr 1. Chem 2. Chem | ame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in ations above 0,1%: ical name: , CAS #: (See NOTE B4) ical name: , CAS #: " | | | |
| | | ical name: , CAS #: " nemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: <i>FR(40)</i> | | | |
| P7.19 | In plastic assigned | parts > 25 g according ISO 1043-4.FR(40) parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been it he following Risk phrases; and Hazard statements: cre(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5) | | | |

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

| modernu | mber * | 21HM,21 | HN | | | Logo | | | |
|------------------------------------|---|--------------------------------|---|-----------------------------------|---|---|-----------|-------------|-----------|
| lssue dat | e * | 2023-03-(| 06 | | | | Ler | 0 | VO |
| Product | environ | nental att | tributes - Market | requirements (cont | tinued) | | Requi | remer | nt met |
| Item | | | | | | | Yes | No | n.a. |
| | | | tance requirements | | | | | | |
| P7.20* | If YES; a | at least one | of the two alternativ | es below shall be answ | product (See NOTE B6 vered; cycled plastic material (| | | | |
| | or per | centage of | total plastic by weight | ht) is 20.14% . | Sycieu plastic material | content (calculated as | a | | |
| P7.21* | | | | ed in the product (See I | NOTE B7): | | | \boxtimes | |
| | a) Of tota or | total plastic al plastic by | parts' weight > 25 g | | wered; material content (calcul | ated as a percentage | of | | |
| P7.22* | Light so | urces are fr | ee from mercury, i.e | e. less than 0,1 mg/lam | р. | | \square | | |
| P7.23* | | | specify: Number of la an integral display, t | he total mercury conter | mum mercury content p nt in the integrated disp | per lamp: mg plav: 0.0 mg | | \boxtimes | |
| P8 | Batterie | | 5 1 77 | , | 5 1 | <u> </u> | | | |
| P8.1* | | | omposition: <i>Lithium</i> | ion | | | | | |
| P9 | Energy | consumnt | ion (See NOTE B8) | | | | | | <u> </u> |
| P9.1 | For the | product the | following power leve | els or energy consump | tions are reported: | | | | |
| Energy m | ode * | | Power level at 100 V AC | Power level at 115 V AC | Power level at 230 V AC | Reference/Standar modes and test me | | IY | |
| Peak (On | -Max) | | 65 W | 65 W | 65 W | Full Load | | | |
| Device Ca | ategory 2 | | | | | | | | |
| Short Idle Enabled (| e State – V (P _{short_idle}) | VOL | 4.96 W | 5.19 W | 4.96 W | ENERGY STAR C | omputers | V8.0 | |
| Long Idle Enabled (| | VOL | 0.61 W | 0.70 W | 0.93 W | ENERGY STAR C | omputers | V8.0 | |
| Sleep (S3 (P _{Sleep}) | - | | 0.61 W | 0.70 W | 0.93 W | ENERGY STAR C | omputers | V8.0 | |
| Off Mode Disabled | | DL | 0.44 W | 0.44 W | 0.50 W | ENERGY STAR C | omputers | V8.0 | |
| PTEC * Typical Er | nergy Con | sumption | W | W | W | | | | \square |
| ETEC * Annual Er | nergy Cons | sumption | 14.5 kWh/year | 15.42 kWh/year | 16.0 kWh/year | $E_{TEC} = (8760/1000) \\ P_{sleep} \times 0.05 + P_{long} \\ P_{short_Idle} \times 0.35)$ | | | |
| External F | Power Sup | ply Efficien | cy Level (Internation | al Efficiency Marking P | Protocol) * : VI | International Effic Protocol (IEMP) fo Power Supplies | | | |
| | colution * | : 9.216 me | gapixels | | | 3840*2400 | | | |
| Display re | Solution | | | | | | | | |
| | | | ve mode: 5 minutes | | | ENERGY STAR CO | omputers | V8.0 | |
| | ne to enter | energy sa | | tion is provided with the | e product. | ENERGY STAR CO | omputers | V8.0 | |

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available;

see http://www.ecma-international.org/publications/standards/Ecma-370.htm.

| Model number * | 21HM,21HN | Logo | |
|----------------|------------|------|--------|
| Issue date * | 2023-03-06 | | Lenovo |

| | environmenta | I attributes - Market requirements (cont | inueu) i | Require | | me |
|--------|---|---|--|-------------|----|-----|
| tem | | | | Yes | No | n.a |
| P10 | Emissions | | | | | |
| | | n – Declared according to ISO 9296 (See NOTI | | | | |
| P10.1 | Mode | Mode description | Statistical upper limit A-weighted sound pow $L_{WA,c}$ (B) | /er level, | | |
| | Idle | * Idle Mode | * 2.6 | | | 7 |
| | Operation | * Operating (CPU) | * 3.6 | | [| |
| | Other Mode | Declared A-weighted sound pressure level (dB) | 19 (operator position desktop – idle) | | | |
| | Other mode | Declared A-weighted sound pressure level (dB) | 19 (operator position desktop – operating-CP | טי) | | |
| | Measured acco | ording to: ISO 7779 ECMA-74 | by ECMA-74) | | | |
| | Electromagne | | | | | |
| P10.4 | Computer displ | ay meets the requirement for low frequency ele PR-II(3 pin AC adapter only) | ctromagnetic fields of the following voluntary | \square | | |
| P12 | | or computing products | | | | |
| P12.1* | The display me | ets the ergonomic requirements of ISO 9241-30 | 07 for visual display technologies. | \boxtimes | | |
| P12.2* | The physical in | put device meets the requirements of ISO 9995 | and ISO 9241-410. | \boxtimes | | |
| P13 | Packaging and | d documentation | | | | |
| | Product package Product package Product package | ging material type(s): Cardboard weight (kg): ging material type(s): Paper weight (kg): weight (kg): weight (kg): weight (kg): weight (kg): weight (kg): weight (kg): weight (kg): weight (kg): | 0.130 0.012 | | | |
| P13.2* | Product plastic | primary packaging is free from PVC. | | \boxtimes | | |
| P13.3* | consumer reco | mary corrugated fiberboard packaging, specify t vered fiber content: 80 % | he contained percentage of minimum post- | | | |
| P13.4* | | for user and product documentation (tick box): Paper 🔀, Other 🗌 | | | | |
| P13.5 | | omplete this item if paper documentation used) act documentation on paper media is chlorine-fre specify: | 66 : | | | |
| | Totally chlorine | -free | | \square | | |
| | Elemental chlo | | | × | | |
| | Processed chlo | prine-free | | | | |
| P14 | Voluntary pro | grams | | | | |
| P14.1 | • | eets the requirements of the following voluntary | | | | |
| | ENERGY STAI Eco-label: <i>EPE</i> | | Date: 2023/01/03 Product category: 2 Date: 2023/03/10 Product category: Noteboo | k | | |
| | Eco-label: TCC | | Date: 2023/01/09 Product category: Noteboo | k | | |
| | | | | | | |
| P15 | Additional info | ormation (See NOTE B10) | | | | |

NOTE B9 A Guidance document on Acoustic Noise is available;

see http://www.ecma-international.org/publications/standards/Ecma-370.htm.

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B2

| Reference | Declaration item |
|---|-------------------------------------|
| Directive 2011/65/EU (RoHS Directive)* * Specific exemptions apply for certain products and applications. | P1.1, P3.1 |
| Regulation (EC) 1907/2006 (REACH Regulation), annex XVII | P1.2, P1.4, P1.6, P1.7 |
| Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances) | P1.3, P5.3 |
| Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002 | P1.5 |
| Directive 2006/66/EC (Battery and accumulators Directive), as amended.* * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator. | P2.1, P2.2, P2,3, P8.1 |
| Directive 2014/35/EU (Low Voltage Directive) | P3.1 |
| Directive 2014/30/EU (EMC Directive) | P3.1 |
| Directive 2014/53/EU (RE Directive) | P3.1 |
| Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions | P3.1, P3.2 |
| Commission Regulation (EC) No 278/2009 of 6 April 2009 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for no-load condition electric power demand and average active efficiency of external power supplies | P3.1, P3.2, P9.1 |
| COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers | P2.4, P2.5, P3.1, P3.2, P7.23, P9.1 |
| Regulation (EC) No 1272/2008 (CLP Regulation) | P7.19 |
| Directive 2004/12/EC (Packaging Directive) | P5.1 |
| Decision 97/129/EC (Secondary packaging legislation) | P5.2 |
| Directive 2012/19/EU (WEEE directive) | P6.1 |
| Implementing Regulation (EU) 2019/290 establishing the format for registration and reporting of producers of electrical and electronic equipment to the register. | |
| Commission Implementing Regulation 2017/699 establishing a common methodology for the calculation of the weight of electrical and electronic equipment (EEE) placed on the national market in each Member State and a common methodology for the calculation of the quantity of waste electrical and electronic equipment (WEEE) generated by weight in each Member State. | |

Lenovo ErP Lot26 Information Sheet - Network Equipment -

As required by_

- Commission Regulation (EC) No 1275/2008 of 17 December 2008 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for standby and off-mode electric power consumption of electrical and electronic household equipment (ErP Lot 6)
- Commission Regulation (EU) No 801/2013 of 22 August 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for (ErP Lot 26).

Products scope of this sheet:

Notebook/Tablet Computer < 6 W Idle

This document is only valid in connection with the IT Eco Declaration of the specific Product.

| Commercial name | ThinkPad X1 Carbon Gen 11 | Logo |
|------------------------|---|--------|
| Model Number | 21HM,21HN | |
| Product Type | Notebook Computer with Idle Power < 6 W | Lenovo |
| Issue Date | 2023-03-06 | |
| Additional information | | |

P7.1.1 Product environmental attributes

|) | year of manufacture: | 2023 |
|----|---|---|
| 2) | Network Standby Classification | LoNA Equipment |
| | Off Mode Power (Watts) | 0.48 Watts |
| | Standby Mode | Watts Mode Not Applicable |
| | | minutes Default Delay Time |
| | Description of how to enable Network Standby Mode | Network Standby Mode is enabled at Shipment |
| | Description of how to manually enter Network Standby Mode | 1) Press the Power Button once |
| | | 2) Click on the Power Button and choose Sleep |
| | Default Delay time to Network Standby Mode | 7.5 minutes |
| | Reactivation Function from Network Standby Mode | Open Notebook, Press Keyboard or power button, activate USB |

| Network Port | Wired Ethernet | Wireless Ethernet | USB-A | USB-C | HDMI | BlueTooth | Other: Nano SIM | | | |
|--|---|---|---|---|---|---|--|--|--|--|
| Present in Product | | | | | | | | | | |
| Activated at Shipment | | | | | | | | | | |
| Active in Network | | | | | | | | | | |
| Standby Mode | | | | | | | | | | |
| Network Port | N/A | N/A | Left and Righ | Left | Left | N/A | Right | | | |
| Network Port Maximum Performance | GB/s | 0.15 GB/s | GB/s | GB/s | GB/s | GB/s | GB/s | | | |
| Network Protocol | | Wi-Fi 6; 802.11ax | USB 3.2 Gen 1 | Thunderbol t 4 | | BT5.2 | 4G | | | |
| Network Standby Mode Power | Watts | 0.76Watts | Watts | Watts | Watts | Watts | Watts | | | |
| Network | | | | | | | | | | |
| Standby Power – All | | | | 0 7004 11 | | | | | | |
| | 0.76Watts | | | | | | | | | |
| Activo | 0.7000alls | | | | | | | | | |
| Active Connections Additional Informa | | nd disconnecti | ng from wirolog | | luded in the | | | | | |
| Connections Additional Informa Instructions on c | onnecting to ar | | ng from wireles | | cluded in the | User Manual | | | | |
| Connections Additional Informa Instructions on c | onnecting to an | | | ss networks is in | | User Manual | | | | |
| Connections Additional Informa Instructions on c | onnecting to an | | | ss networks is inc 25.3 degree Celsi | | User Manual | | | | |
| Connections Additional Informa Instructions on c | onnecting to an or measurement rature, | S, | | ss networks is in | | User Manual | | | | |
| Connections Additional Informa Instructions on c Test parameters fo ambient temper | onnecting to an or measurement rature, ' and frequency | s, in Hz, | | ss networks is inc 25.3 degree Celsi | | User Manual | | | | |
| Connections Additional Informa Instructions on c Test parameters fo ambient temper test voltage in V total harmonic o information and set-up and circu | onnecting to an or measurement rature, and frequency distortion of the documentatio its used for elec | s, in Hz, e electricity sup n on the instru ctrical testing | ply system, mentation, | ss networks is ind 25.3 degree Celsi 230 V / 50 Hz | us | | Irce: ALLPOWE | | | |
| Connections Additional Informa Instructions on c Test parameters fo ambient temper test voltage in V total harmonic o information and | onnecting to an or measurement rature, and frequency distortion of the documentatio its used for ele- pply efficiency (i Output | in Hz, e electricity sup n on the instru ctrical testing f applicable)*: Output | ply system, mentation, | ss networks is ind 25.3 degree Celsi 230 ∨ / 50 Hz 0.36% Power Meter: HIT APF-500W Average Active | us ESTER HIOK | 1 3332; AC Sou | Load | | | |
| Connections Additional Informa Instructions on c Test parameters for ambient temper test voltage in V total harmonic of information and set-up and circu External power su | onnecting to an or measurement rature, ' and frequency distortion of the I documentatio hits used for ele- pply efficiency (i | in Hz, e electricity sup n on the instru ctrical testing f applicable)*: Output | ply system, | ss networks is ind 25.3 degree Celsi 230 V / 50 Hz 0.36% Power Meter: HIT APF-500W | us ESTER HIOK | 1 3332; AC Sou bad No I | | | | |
| Connections Additional Informa Instructions on c Test parameters for ambient temper test voltage in V total harmonic of information and set-up and circu External power su Model Delta Chicony | onnecting to an or measurement rature, rature, rand frequency distortion of the l documentatio its used for ele- pply efficiency (it Output Voltage 20 V | s, e electricity sup n on the instru ctrical testing f applicable)*: Output Current 2.25 A 2.25 A | ply system, mentation, Power 45 W 45 W | 25.3 degree Celsi 23.0 V / 50 Hz 0.36% Power Meter: HIT APF-500W Average Active Efficiency 90% 89% | US ESTER HIOK 10% Lo Efficier 88% 88% | 1 3332; AC Sou bad No I icy Po 0.0 0.0 | Load wer 7 W 5 W | | | |
| Connections Additional Informa Instructions on c Test parameters for ambient temper test voltage in V total harmonic of information and set-up and circu External power su Model Delta Chicony Liteon | onnecting to an or measurement rature, rature, rand frequency distortion of the l documentatio its used for ele- pply efficiency (it Output Voltage 20 V 20 V | in Hz, e electricity sup n on the instruc ctrical testing f applicable)*: Output Current 2.25 A 2.25 A 2.25 A | Dutput Power 45 W 45 W | ss networks is inc 25.3 degree Celsi 230 V / 50 Hz 0.36% Power Meter: HIT APF-500W Average Active Efficiency 90% 89% 90% | US ESTER HIOK 10% LC Efficier 88% 88% | 1 3332; AC Sou bad No I incy Po 0.0 0.0 0.0 | Load wer 7 W 5 W 7 W | | | |
| Connections Additional Informa Instructions on c Test parameters for ambient temper test voltage in V total harmonic of information and set-up and circu External power su Model Delta Chicony Liteon Acbel Delta | onnecting to an or measurement: rature, rand frequency distortion of the documentation its used for eler pply efficiency (in Output Voltage 20 V 20 V 20 V 20 V 20 V | in Hz, e electricity sup n on the instruc ctrical testing f applicable)*: Output Current 2.25 A 2.25 A 2.25 A 3.25 A | Dutput Power 45 W 45 W | ss networks is inc 25.3 degree Celsi 230 V / 50 Hz 0.36% Power Meter: HIT APF-500W Average Active Efficiency 90% 89% 90% 81% 92% | us ESTER HIOK Efficier 88% 88% 88% 88% 81% 91% | 1 3332; AC Sou bad No I icy Po 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 | Load 7 W 7 W 7 W 7 W 6 W 6 W | | | |
| Connections Additional Informa Instructions on c Test parameters for ambient temper test voltage in V total harmonic of information and set-up and circu External power su Model Delta Chicony Liteon Acbel Delta Chicony | onnecting to an or measurement rature, rand frequency distortion of the documentatio its used for ele- pply efficiency (it Voltage 20 V 20 V 20 V 20 V 20 V 20 V | s, e electricity sup n on the instruc ctrical testing f applicable)*: Output Current 2.25 A 2.25 A 2.25 A 3.25 A 3.25 A | Dutput Power 45 W 45 W 45 W 45 W 45 W 65 W 65 W | ss networks is inc 25.3 degree Celsi 230 ∨ / 50 Hz 0.36% Power Meter: HIT APF-500W Average Active Efficiency 90% 89% 90% 81% 92% 91% | us ESTER HIOK Efficier 88% 88% 88% 88% 88% 89% | 1 3332; AC Sou had No I icy Po 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0. | Load 7 W 5 W 7 W 6 W 6 W 7 W | | | |
| Connections Additional Informa Instructions on c Test parameters for ambient temper test voltage in V total harmonic of information and set-up and circu External power su Model Delta Chicony Liteon Acbel Delta | onnecting to an or measurement: rature, rand frequency distortion of the documentation its used for eler pply efficiency (in Output Voltage 20 V 20 V 20 V 20 V 20 V | in Hz, e electricity sup n on the instruc ctrical testing f applicable)*: Output Current 2.25 A 2.25 A 2.25 A 3.25 A | Dutput Power 45 W 45 W | ss networks is inc 25.3 degree Celsi 230 V / 50 Hz 0.36% Power Meter: HIT APF-500W Average Active Efficiency 90% 89% 90% 81% 92% | us ESTER HIOK Efficier 88% 88% 88% 88% 81% 91% | Vad No I ncy Po 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0. | Load 7 W 5 W 7 W 6 W 6 W | | | |
| Connections Additional Informa Instructions on c Test parameters for ambient temper test voltage in V total harmonic c information and set-up and circu External power su Model Delta Chicony Liteon Acbel Delta Chicony | onnecting to an or measurement rature, distortion of the distortion of the documentatio its used for ele- pply efficiency (in Output Voltage 20 V 20 V 20 V 20 V 20 V 20 V 20 V 20 V | in Hz, e electricity sup n on the instruc- ctrical testing f applicable)*: 0utput Current 2.25 A 2.25 A 2.25 A 3.25 A 3.25 A 3.25 A | Dutput Power 45 W 45 W 45 W 65 W 65 W 65 W | 25.3 degree Celsi 230 ∨ / 50 Hz 0.36% Power Meter: HIT APF-500W Average Active Efficiency 90% 89% 90% 81% 92% 91% 90% | US ESTER HIOK Efficier 88% 88% 88% 81% 91% 99% | Vad No I ncy Po 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0. | Load wer 7 W 5 W 7 W 6 W 6 W 7 W 8 W | | | |
| Connections Additional Informa Instructions on c Test parameters for ambient temper test voltage in V total harmonic of information and set-up and circu External power su Model Delta Chicony Liteon Acbel Delta Chicony Liteon Acbel | onnecting to an or measurement rature, 7 and frequency distortion of the distortion of the documentatio its used for elec- pply efficiency (in Voltage 20 V 20 V 20 V 20 V 20 V 20 V 20 V 20 V | s, e electricity sup n on the instruc- ctrical testing f applicable)*: Output Current 2.25 A 2.25 A 2.25 A 3.25 A 3.25 A 3.25 A 3.25 A 3.25 A | Dutput Power 45 W 45 W 45 W 65 W 65 W 65 W 65 W | 25.3 degree Celsi 230 V / 50 Hz 0.36% Power Meter: HIT APF-500W Average Active Efficiency 90% 89% 90% 81% 92% 91% 90% 82% | US ESTER HIOK Efficier 88% 88% 88% 81% 91% 99% 81% | Vad No I ncy Po 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0. | Load wer 7 W 5 W 7 W 6 W 6 W 7 W 8 W | | | |