

Annex B2 - Product environmental attributes Servers/Data Storage Products

The declaration may be published only when all rows and/or fields marked with * are filled-in (N/A for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lenovo	Logo
Company name *	Lenovo	
Contact information *	Lenovo Global Environmental Affairs	Lenovo
e-mail address	Alvin L Carter	LEIIOVO
	alcarter@lenovo.com	
Internet site *	https://www.lenovo.com/us/en/sustainability-resources/	
Additional information		

	The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.					
Type of product *	Type of product * SERVER					
Commercial name *	al name * Lenovo ThinkSystem SR630 V3					
Model number *	number * 7D72, 7D73, 7D74					
Issue date *	Issue date * 2023-01-10					
Intended market * 🛛 🔀 Global 🔲 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other						
Additional information	https://lenovopress.lenovo.com/lp1600-thinksystem-sr630-v3-server					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products.

Model n	umber *	7D72, 7D73, 7D74 Logo	000		
Issue date *		2023-01-10	-enc	enovo	
Produc	t environ	mental attributes - Legal requirements F	Require	ment	met
Item		- ·	Yes	No	N/A
P1	Hazardo	ous substances and preparations			
P1.1*	Product	s do comply with current European RoHS Directive. (See legal reference and NOTE B1)	\boxtimes		
P1.2*	Products Comme	\square			
P1.3*	Products hydrobro trichloro	s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), omofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- ethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum ration values.			
P1.4*	terpheny	s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated yl (PCT) in preparations (see legal reference).	\square		
P1.5*	chain co	s do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the ontaining at least 48% per mass of chlorine in the SCCP (see legal reference).	\square		
P1.6*	(see leg	th direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm²/week al reference). nt: Max limit in legal reference when tested according to EN1811:2011-5.			
P1.7*	REACH	Article 33 information about substances in articles is available at (add URL or mail contact): www.lenovo.com/us/en/Lenovo-REACH-SVHC-Disclosure	\square		
P2	Batterie				
P2.1*	If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal symbol. Information on proper disposal is provided in user manual. (See legal reference)				
P2.2*	Batterie: referenc	s or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal ee)	\square		
P2.3*	Batterie	s and accumulators are readily removable. (See legal reference)	\square		
P2.4*	Docume	entation includes the number of cycles the (secondary) battery can withstand. (See legal reference)		Π	
P2.5*		ternal batteries of a notebook computer cannot be "accessed and replaced by a nonprofessional e related text is present and legible on the external packaging (see legal reference)			
P3		nity verification & Eco design (ErP)			
P3.1*	The Dec https://	duct is CE-marked to show conformance with applicable legal requirements (see legal reference). claration of Conformity can be requested at: <u>www.lenovo.com/us/en/compliance/eu-doc</u> for EU; <u>www.lenovo.com/us/en/compliance/uk-doc</u> for UK			
P3.2*		duct complies with the Eco design requirements for energy-related products,			
1 0.2	(see leg	a reference). d information is;			
	•	available at: https://www.lenovo.com/us/en/compliance/eco-			
P5	declara Product	t packaging			
P5.1*	Packagi	ng and packaging components do not contain more than 0,01% lead, mercury, cadmium and ent chromium by weight of these together.			
P5.2*	The pac	kaging materials are marked with abbreviations and numbers indicating the nature of the material(s) be legal reference).	\square		
P5.3*	The prov (see leg Comme	\boxtimes			
P6		ent information			
		ion for recyclers/treatment facilities is available (see legal reference).			_

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model nu	ımber *	7D72, 7D73, 7D74	Logo				
Issue dat	te *	2023-01-10		Lene		TH	
Product	environ	mental attributes - Market requirements (See General NOTE GN	below)				
		onmental conscious design		Require			
Item		tory to fill in. Additional information regarding each item may be found under P14.		Yes	No	N/A	
P7.1*		Disassembly, recycling at have to be treated separately are easily separable				_	
					<u> </u>		
P7.2*	Plastic materials in covers/housing have no surface coating.						
P7.3*							
P7.4*		arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.					
P7.5	•	arts are free from metal inlays or have inlays that can be removed with commonly a	available tools.	\square			
P7.6*		re easily separable. (This requirement does not apply to safety/regulatory labels).		\square			
		lifetime					
P7.7*		ng can be done e.g. with processor, memory, cards or drives					
P7.8*	Upgradir	ng can be done using commonly available tools					
P7.9	Spare pa	arts are available after end of production for: years					
P7.10	Service i	is available after end of production for: years					
		and substance requirements					
P7.11*		cover/housing material type (e.g. plastics, metal, aluminum):					
P7.12			al type:				
		n materials of external electrical cables are PVC free.		<u> </u>			
P7.13		n materials of internal electrical cables are PVC free.				<u>Ц</u>	
P7.14	weight (polyvinyl	plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) b 1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame I chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine i an 25% post-consumer recycled content.	e retardants, a	nd 🗖			
P7.15		circuit boards, PCBs (without components) are low halogen: all \square PCBs > 25 g \square ed in IEC 61249-2-21. (See ⁵ NOTE B2)	are low halog	en 🗌			
P7.16		etarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:					
P7.17		hemical specifications of flame retardants in printed circuit boards > 25 g (without c	omponents):]	
	TBBPA ((additive), TBBPA (reactive) (See NOTE B3), Other: chemical name:	, CAS #:				
		hemical specifications of flame retardants in printed circuit boards (without compone g ISO 1043-4:	ents) > 25 g				
P7.18	<u>Alt. 1: </u> FI	ame retarded plastic parts > 25 g contain the following flame retardant substance	s/preparations	in			
	1. Chem 2. Chem	rations above 0,1%: ical name: , CAS #: (See NOTE B4) ical name: , CAS #: " ical name: , CAS #: "					
	<u>Alt. 2: </u> Cl	hemical specifications of flame retardants in plastic parts > 25 g according ISO 104	3-4:				
P7.19	•	c parts > 25 g, flame retardant substances/preparations above 0,1% are used which d the following Risk phrases; and Hazard statements:	have been				
	•		See note B5)				
P7.20*		sumer recycled plastic material content is used in the product (See Note B6):			\boxtimes		
	a) Oft apo or	at least one of the two alternatives below shall be answered; total plastic parts' weight > 25 g, the postconsumer recycled plastic material conten ercentage of total plastic by weight) is %.	t (calculated as	5			

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see <u>http://www.ecma-international.org/publications/standards/Ecma-370.htm</u>.

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model number *	lodel number * 7D72, 7D73, 7D74		Lenovo
Issue date *	2023-01-10		LEHOVO
Product environm	nental attributes - Market requirements (continued)		Requirement met

Item

	Material and	substance requirements	(continued)							
P7.21*		tic material content is use		OTE B7):						
	-									
	If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of									
total plastic by weight) is %.										
	or									
	b) The weight of the biobased plastic material is g.									
P7.22*		Light sources are free from mercury, i.e. less than 0,1 mg/lamp.								
P7.23*		sed specify: Number of la		um mercury content pe						
	•	udes an integral display, th	le total mercury content	in the integrated displ	ay: mg					
P8	Batteries		New York							
P8.1*		cal composition: Lithium I	wanganese Dioxide							
P9		umption (See NOTE B8)	l							
P9.1		t the following power leve Power level at	Power level at	ons are reported: Power level at	Defense of Standard for anormy					
Energy mo	bde	100 V AC	115 V AC	230 V AC	Reference/Standard for energy modes and test method *					
Peak (On-	max)	W	W W	W	Full load					
			••	••						
Categor			-							
EPS No-lo		W	W	W						
	ower supply /									
	ugged in the wa disconnected fro									
the produc										
PTEC *		W	W	W						
Typical En	ergy Consumpti	on			_					
ETEC *		kWh/year	kWh/year	kWh/year						
	ergy Consumpti									
		iciency Level (Internationa	I Efficiency Marking Pro	otocol) ^ :						
Display res	solution * :	megapixels								
Default tim	ne to enter energ	gy save mode: minu	ites							
P9.2*	Information at	oout the energy save funct	ion is provided with the	product.						
P9.3	Energy efficie	ncy class (monitors only):								
P10	Emissions									
		on – Declared according t	o ISO 9296 (See NOTE							
P10.1	Mode	Mode description			it A-weighted sound power level, <i>L_{WA,c}</i> (B)					
	Idle	* Typical Configuration		* 6.7						
	Operation	* Typical Configuration	(100% TDP)	* 7.7						
ļ	Idle	* GPU Configuration		* 6.7						
	Operation	* GPU Rich Configuration	n (Nvqaul+80%TDP)	* 8.3						
	Idle	* Storage Configuration		* 7.5						
	Operation	* Storage Configuration		* 7.5						
	Measured acc	ording to: 🔀 ISO 7779 🗌	ECMA-74							
		Other	(only if not covered by	ECMA-74)						
		etic emissions								
P10.4		play meets the requiremer	t for low frequency elec	ctromagnetic fields of th	he following voluntary					
	program(s):									

Yes

No

N/A

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

Model nu	ımber *	7D72, 7D73, 7D74					Logo	Lama				
Issue date *		2023-01-10						Leno	vo	THI .		
Product	roduct environmental attributes - Market requirements (continued)							Requirement met				
Item				•				Yes	No	N/A		
P12		mics for computing										
P12.1*	The disp	play meets the ergon	omic requirement	ts of ISO 9241-30	07 for visual o	display technolo	gies.			\boxtimes		
P12.2*	The phy	sical input device me	ets the requirement	ents of ISO 9995	and ISO 924	41-410.				\boxtimes		
P13		ing and documenta										
P13.1*	Product Product	packaging material t packaging material t packaging material t packaging material t	ype(s): Paper - C ype(s): Plastic -	Corrugated sing Solid EPE (solid	le wall weig d Expanded	ght (kg): 0.228 polyethylene) v		8				
P13.2*	Product	plastic primary pack	aging is free from	n PVC.				\boxtimes				
P13.3*		duct primary corruga er recovered fiber co		oackaging, specil	y the contain	ned percentage	e of minimum po	ost-				
P13.4*		media for user and p ronic, XPaper,	roduct documenta Other	tation (tick box):								
P13.5	Ùser and	only complete this it d product documenta lease specify:			ee:							
	,	chlorine-free al chlorine-free										
	Process	ed chlorine-free						П				
P14	Volunta	ry programs										
P14.1	The proc	duct meets the requi	rements of the fol	llowing voluntary	program(s):							
	Eco-labe	el: ENERGY STAR	Eco-label:		Eco-label:	Eco-labe	el:					
	Eco-labe	el:	Eco-label:		Eco-label:	Eco-labe	el:					
P15		nal information (Se	e NOTE B10)									
P 9		consumption of co		s; description o	f the tested j	product config	uration:					
	the info supplie informa Accoun	Supplier makes no rmation contained r's knowledge avail tion. The information t Representative fo	in this documen able at the time on provided here r more informati	nt. All informatio of completion, a re is approximate tion.	n provided k and supplier e and provid	by supplier in t shall have no led for information	his document is obligation to up	s provided odate such	based	d on		
P 9		ergy Star Qualified www.energystar.go										

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B2

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive)* * Specific exemptions apply for certain products and applications.	P1.1, P3.1
Regulation (EC) 1907/2006 (REACH Regulation), annex XVII	P1.2, P1.4, P1.6, P1.7
Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)	P1.3, P5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2006/66/EC (Battery and accumulators Directive), as amended.* * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2014/35/EU (Low Voltage Directive)	P3.1
Directive 2014/30/EU (EMC Directive)	P3.1
Directive 2014/53/EU (RE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Commission Regulation (EC) No 278/2009 of 6 April 2009 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for no-load condition electric power demand and average active efficiency of external power supplies	P3.1, P3.2, P9.1
COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers	P2.4, P2.5, P3.1, P3.2, P7.23, P9.1
Regulation (EC) No 1272/2008 (CLP Regulation)	P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1
Implementing Regulation (EU) 2019/290 establishing the format for registration and reporting of producers of electrical and electronic equipment to the register.	
Commission Implementing Regulation 2017/699 establishing a common methodology for the calculation of the weight of electrical and electronic equipment (EEE) placed on the national market in each Member State and a common methodology for the calculation of the quantity of waste electrical and electronic equipment (WEEE) generated by weight in each Member State.	

Lenovo ErP Lot9 Information Sheet - Servers & Storage Products-

As required by COMMISSION REGULATION (EU) 2019/424 of 15 March 2019 laying down ecodesign requirements for servers and data storage products pursuant to Directive 2009/125/EC of the European Parliament and of the Council and amending Commission Regulation (EU) No 617/2013. (ErP Lot9)

Products scope of this sheet: Servers & storage products

This document is only valid in connection with the IT Eco Declaration of the specific Product.

SERVERS

General information							
Commercial name (3.1 (b))	Commercial name (3.1 (b)) Lenovo ThinkSystem SR630 V3 Logo						
Contact Address (3.1 (b))	7001 Development Dr. Building 7 Morrisville, NC 27560 United States	Lenovo					
Model Number (3.1 (c))	7D72, 7D73, 7D74						
Issue Date	2023-3-28						
Additional information							

Product e	environmental attributes (EU) 2019/424 – Annex II points 3.1 and 3.3							
1.a	Is the product consider to be in scope of ErP Lot 9 🛛 in scope 🗌 out of scope, product is out of scope as:							
1.b (3.1 (a))	Server type Rack Server High Performance Computing (HPC) Tower Server Multi Node Server Blade Server Data Storage product (Please go to "DATA STORAGE PRODUCTS" section							
1.c	Year of manufacture: 2023							
(3.1 (d))								
1.d (3.1 (p))	Product model part of a server product family? No X Yes List of all model configurations that are represented by the model: https://lenovopress.lenovo.com/lp1600-thinksystem-sr630-v3- server							
1.e	Information on the secure data deletion functionality							
(3.1 (n))	 (a) instructions on how to use the functionality: 2 methods are provided to use the functionality. 1) Use a command line tool to do the secure data deletion on the remote target system via boot up a customized 							
	Linux OS on it.							
	Eg: OneCli.exe serase -bmc USERID:PASSWORD@xx.xx.xxsftp root:password@xx.xx.xx.xx:/home -log 5							
	2) Use BoMC to create a full functions bootable media, start the media and choose secure erase from the text menu.(b) techniques used:							
	OS tools under Linux -> Standard Linux Open Source tool							
	(c) supported secure data deletion standard (if any): Secure Erase/block Erase/Crypto Erase, Sanitize							
	OR - Reference to other information: Hdparm: <u>https://en.wikipedia.org/wiki/Hdparm</u>							
	Nvme-format: https://www.mankier.com/1/nvme-format							
	sg_sanitize: https://www.systutorials.com/docs/linux/man/8-sg_sanitize/							
	scrub: https://www.systutorials.com/docs/linux/man/1-scrub/							
	storcli: https://docs.broadcom.com/docs-and-downloads/raid-controllers/raid-controllers-common-iles/StorCLI RefMan revf.pdf							
1.f (3.1 (o))	Blade servers? 🛛 No 🗌 Yes							
	list of recommended combinations with compatible chassis:							
2.a	g Data Indicative weight range at component level, of the (a) Cobalt in the batteries (b) Neodymium in the HDDs							
(3.3 (a))	following critical raw materials:							
	\square between 5 g and 25 g \square between 5 g and 25 g							
	\square above 25 g \square above 25 g							
2.b (3.3 (b))	Instructions on the disassembly operations (a) the type of operation; (b) the type and number of fastening technique(s) to be unlocked; (c) the tool(s) required.							
	OR - Reference to other information: https://pubs.lenovo.com/sr630-v3/hardware_replacement_procedures https://pubs.lenovo.com/sr630-v3/disassemble_for_recycle							

2.c	Firmware						
	Reference to information on last available firmware:						
https://datacentersupport.lenovo.com/products/servers/thinksystem/sr630v3/7d72/downloads/driver-list/							
Additio	nal information						

Server family specific information Family 1

Family r	no. / name	1 - 2 CPU populated fam	ilv		
Model number(s) / Description Standard or low-end performance configuration: (3.1 (c)) Processor (Minimum result of core count * frequency in family): INTEL GOLD 5415+ * 2, 420TB 3.5" HDD * 2, Memory: 16GB * 16, PSU: 1100W * 2, 1GbE RJ45 4-port * 1 High-end performance configuration: Processor (Maximum result of core count * frequency in family): Intel Platinum 8458P * 2 480GB SSD * 2, Memory: 64GB * 16, PSU: 1100W * 2, 1GbE RJ45 4-port * 1					
Additior	nal information	You can refer to <u>https://www.plugloadsolutio</u> along with	ns.com/80PlusPowerSupplies	sDetail.aspx?id=49&type=1	
Produc	t environmental attril	outes (EU) 2019/424 – Annex			
F1.a (3.1 (e))	PSU efficiency at 10 (expressed in % and Standard or low-end	% (if applicable), 20 %, 50 % ar	nd 100 % of rated output power ce): 🗌 Multi-output 🛛 Singl		
	High-end performanc 10% 92.07 20% 95	e configuration(s): . 44 50% 96.23 100% 94.6	Average 95.42		
F1.b (3.1 (f)) F1.c	(rounded to three dee PSU rated power out	put	standard or low-end performa configuration: 0.9955 standard or low-end performa	configuration: 0.9955 Ince high-end performance	
(3.1 (g)) F1.d (3.1 (h))	idle state power (in Watts and rounde	ver product family, all PSUs offered in a server ith the information specified in (e) and (f) d to the first decimal place)	configuration: 1100 standard or low-end performa configuration: 169.2	configuration: 1100 ince high-end performance configuration: 201.0	
F1.e (3.1 (i))		configurati	r low-end performance on:	high-end performance configuration:	
	CPU Performance	2 Sock	xet (10 × PerfCPU W) xet (7 × PerfCPU W)	1 Socket (10 × PerfCPU W) 2 Socket (7 × PerfCPU W)	
ents	Additional PSU	Yes #: 1		Yes #: 1	
stm	HDD SDD	Yes #: 2		No #: 0	
g J	Additional memory	No #: 0 Yes #: 252	PCB	Yes #: 2 Yes #: 1020GB	
es a stinç	Additional buffered DDF			Yes #: 8	
idle power allowances adjustments during testing	Additional I/O devices	$\begin{vmatrix} \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\$	No Allowance 2,0 W/Active Port and < 10 Gb/s: 4,0 W/Active Port s and < 25Gb/s: 15,0 W/Active Port s and < 50Gb/s: 20,0 W/Active Port s 26,0 W/Active Port	none < 1 Gb/s: No Allowance = 1 Gb/s: 2,0 W/Active Port > 1 Gb/s and < 10 Gb/s: 4,0 W/Active Port ≥ 10 Gb/s and < 25Gb/s: 15,0 W/Active Port ≥ 25 Gb/s and < 50Gb/s: 20,0 W/Active Port ≥ 50 Gb/s 26,0 W/Active Port	
F1.f (3.1 (j))	maximum power		standard or low-end performa	nce high-end performance	
F1.g (3.1 (k))	operating condition c (as defined in Table (configuration: 433.6 standard or low-end performa configuration: A1 A2 A3 A4	configuration: 1133.7 Ince high-end performance configuration: □A1 ⊠A2 □A3 □A4	
F1.h		e higher boundary temperature	Exception comments https://lenovopress.lenovo.com 0-thinksystem-sr630-v3-server standard or low-end performa	-thinksystem-sr630-v3-server nce high-end performance	
(3.1 (l)) F1.i (3.1 (m))		ting condition class (in Watts) ency and the performance in rver;	configuration: 221.3 standard or low-end performa configuration: 24.5	configuration: 238.2 Ince high-end performance configuration: 49.2	

Server family specific information Family 2

Family no. / name		1 - 1 CPU populated family			
Model number(s) / Description (3.1 (c))		Standard or low-end performance configuration: Processor (Minimum result of core count * frequency in family): INTEL BRONZE 3408U * 1, Storage: 20TB 3.5" HDD * 2, Memory: 32GB * 8, PSU: 1100W * 2, 1GbE RJ45 4-port * 1 High-end performance configuration: Processor (Maximum result of core count * frequency in family): Intel Platinum 8458P * 1, Storage: 480GB SSD * 2, Memory: 64GB * 8, PSU: 1100W * 2, 1GbE RJ45 4-port * 1			
Additional information		You can refer to <u>https://www.plugloadsolutions.com/80PlusPowerSuppliesDetail.aspx?id=49&type=1</u> along with <u>https://lenovopress.lenovo.com/lp1600-thinksystem-sr630-v3-server</u>			
Produc	ct environmental attril	outes (EU) 2019/424 – Annex			
F1.a (3.1 (e))					
	High-end performanc		-		
F1.b (3.1 (f)) F1.c (3.1 (g))	PSU rated power output		standard or low-end performancehigh-end performanceconfiguration:0.9955standard or low-end performancehigh-end performanceconfiguration:1100configuration:1100		
F1.d (3.1 (h))	idle state power	ver product family, all PSUs offered in a server ith the information specified in (e) and (f) d to the first decimal place)	standard or low-end performa configuration: 106.4	nce high-end performance configuration: 120.6	
F1.e (3.1 (i))		ts for additional idle power allow standard o configurati	r low-end performance	high-end performance configuration:	
ents	CPU Performance	2 Sock	ket (10 × PerfCPU W) ket (7 × PerfCPU W)	1 Socket (10 × PerfCPU W) 2 Socket (7 × PerfCPU W)	
	Additional PSU	No #: 1		Yes #: 1	
stm	HDD	Yes #: 2		No #: 0	
idle power allowances adjustments during testing	SDD	No #: 0		Yes #: 2	
	Additional memory Additional buffered DDF	Yes #: 252 C channel No #: 0	(GB	Yes #: 508GB No #: 0	
	Additional I/O devices	none < 1 Gb/s: = 1 Gb/s: > 1 Gb/s: $\geq 10 \text{ Gb/s}:$ $\geq 25 \text{ Gb/s}:$: No Allowance : 2,0 W/Active Port and < 10 Gb/s: 4,0 W/Active Port s and < 25Gb/s: 15,0 W/Active Port s and < 50Gb/s: 20,0 W/Active Port s 26,0 W/Active Port	none <1 Gb/s: No Allowance ≥ 1 Gb/s: 2,0 W/Active Port >1 Gb/s and < 10 Gb/s: 4,0 W/Active Port ≥ 10 Gb/s and < 25Gb/s: 15,0 W/Active Port ≥ 25 Gb/s and < 50Gb/s: 20,0 W/Active Port ≥ 50 Gb/s 26,0 W/Active Port	
F1.f	maximum power	·	standard or low-end performa	nce high-end performance	
(3.1 (j)) F1.g (3.1 (k))	(in Watts and rounde operating condition c (as defined in Table 6		configuration: 243.8 standard or low-end performa configuration: A1 A2 A3 A4 Exception comments	configuration: A1 A2 A3 A4 Exception comments	
F1.h (3.1 (I)) F1.i	of the declared opera	e higher boundary temperature ating condition class (in Watts) ency and the performance in	https://lenovopress.lenovo.com 0-thinksystem-sr630-v3-server standard or low-end performa configuration: 151.4 standard or low-end performa	-thinksystem-sr630-v3-server nce high-end performance configuration: 153.8	
(3.1 (m))	active state of the se	iver;	configuration: 14.9	configuration: 49	