Date: October 8, 2014

Name of Product: System x3690 (with IMM2 v1.36 or later) X5

VPAT Summary

Criteria	Status	Remarks and Explanations
Section 1194.21 Software Applications and Operating Systems	Not applicable	Not applicable
Section 1194.22 Web-based Internet information & applications	Supports	Refer to Section 1194.22 in VPAT Details section below.
Section 1194.23 Telecommunications Products	Supports	Refer to Section 1194.23 in VPAT Details section below.
Section 1194.24 Video and Multi-media Products	Not applicable	Not applicable
Section 1194.25 Self-Contained, Closed Products	Supports	Refer to Section 1194.25 in VPAT Details section below.
Section 1194.26 Desktop and Portable Computers	Supports	Refer to Section 1194.26 in VPAT Details section below.
Section 1194.31 Functional Performance Criteria	Supports	Refer to Section 1194.31 in VPAT Details section below.
Section 1194.41 Information, Documentation, and Support	Supports	Refer to Section 1194.41 in VPAT Details section below.

VPAT Details

Section 1194.22 Web-based Internet information and applications - Detail

Criteria	Supporting Features	Remarks and Explanations
(a) A text equivalent for every non-text element shall be provided (e.g., via "alt", "longdesc", or in element content).		The following component meets this criterion: - Integrated Management Module I 1.36: - Web Interface - Text alternatives are provided.
(b) Equivalent alternatives for any multimedia presentation shall be synchronized with the presentation.	Not applicable	The following component does not apply to this criterion: - Integrated Management Module: - Web Interface - No multimedia used.
(c) Web pages shall be designed so that all information conveyed with color is also available without color, for example from context or markup.	Supports: Color is used only as an enhancement, and an alternate means to convey information or indicate an action is available to users with visual impairments.	The following component meets this criterion: - Integrated Management Module: - Web Interface - Tests show that color information has alternative text or another means of conveying information.
(d) Documents shall be organized so they are readable without requiring an associated style sheet.	Supports: Web page content is readable without the use of a pre-defined style sheet, allowing low vision users to enable their own style sheets that enhance their viewing preferences.	The following component meets this criterion: - Integrated Management Module: - Web Interface - Tests resulted in readable pages.
(e) Redundant text links shall be provided for each active region of a server-side image map.	Not applicable	The following component does not apply to this criterion: - Integrated Management Module: - Web Interface - There are no image maps.
(f) Client-side image maps shall be provided instead of server-side image maps except where the regions cannot be defined with an available geometric shape.		The following component does not apply to this criterion: - Integrated Management Module: - Web Interface - There are no image maps.
(g) Row and column headers shall be identified for data tables.	Supports: The application is designed to identify	The following component meets this criterion:

Criteria	Supporting Features	Remarks and Explanations
	row and column headers for blind users so the location and context of the table cell are clear and can be communicated by a screen reader.	Integrated Management Module: Web Interface - Tables are properly described with their column headings and the relationships between cells.
(h) Markup shall be used to associate data cells and header cells for data tables that have two or more logical levels of row or column headers.	Supports: Complex tables are designed with additional attributes for blind users so the location and context of the table cell are clear and can be communicated by a screen reader.	The following component meets this criterion: - Integrated Management Module: - Web Interface - Tables are properly described with their column headings and the relationships between cells.
(i) Frames shall be titled with text that facilitates frame identification and navigation.	Supports: Meaningful text titles are used to describe the purpose of frames so blind users can easily navigate to the desired area.	The following component meets this criterion: - Integrated Management Module: - Web Interface - Frames have a correct title.
(j) Pages shall be designed to avoid causing the screen to flicker with a frequency greater than 2 Hz and lower than 55 Hz.	Supports: The use of blinking text, objects or elements has been avoided, reducing risk of seizures for users with photosensitive epilepsy.	The following component meets this criterion: - Integrated Management Module: - Web Interface - The frequency of the flashing content is less than three times in one second period.
(k) A text-only page, with equivalent information or functionality, shall be provided to make a web site comply with the provisions of this part, when compliance cannot be accomplished in any other way. The content of the text-only page shall be updated whenever the primary page changes.	Supports: When necessary, the application has been designed with text-only pages to communicate equivalent information to disabled users.	The following component meets this criterion: - Integrated Management Module: - Web Interface - Text-only pages are provided when accessibility cannot be accomplished any other way. The context help is an example of this.
(I) When pages utilize scripting languages to display content, or to create interface elements, the information provided by the script shall be identified with functional text that can be read by Assistive Technology.	Supports: Alternatives to scripting language are provided, allowing users access to the content via keyboard and assistive technology.	The following component meets this criterion: - Integrated Management Module: - Web Interface - Script content are keyboard accessible.
(m) When a web page requires that an applet, plug- in or other application be present on the client system to interpret page content, the page must provide a link to a plug-in or applet that complies with §1194.21(a) through (l).	Supports: An alternative to inaccessible applets or plug-ins is provided for efficient use by disabled users.	The following component meets this criterion: - Integrated Management Module: - Web Interface - Remote control with 'ActiveX Client in Microsoft Internet Explorer' is fully compliant with accessibility.
(n) When electronic forms are designed to be completed on-line, the form shall allow people using Assistive Technology to access the information, field elements, and functionality required for completion and submission of the form, including all directions and cues.		The following component meets this criterion: - Integrated Management Module: - Web Interface - Form elements are able to be programmatically determined.
(o) A method shall be provided that permits users to skip repetitive navigation links.	Supports: Web pages are designed so that repetitive navigation links can be skipping over, and blind users can navigate to the main content of the page more easily.	The following component meets this criterion: - Integrated Management Module: - Web Interface - Hidden skip to main is provided at heading navigation tree.
(p) When a timed response is required, the user shall be alerted and given sufficient time to indicate more time is required.	Supports: When a timed response is required, an option to request more time to complete the action is provided to the user.	The following component meets this criterion: - Integrated Management Module: - Web Interface - The IMM Web Interface has a timeout for inactivity where once the time expires the user must log into the interface again. To avoid the timeout some navigation through the pages must occur.

Section 1194.23 Telecommunications Products - Detail

Criteria	Supporting Features	Remarks and Explanations
(a) Telecommunications products or systems which provide a function allowing voice communication and which do not themselves provide a TTY functionality shall provide a standard non-acoustic connection point for TTYs. Microphones shall be capable of being turned on and off to allow the user to intermix speech with TTY use.	Not applicable	
(b) Telecommunications products which include	Not applicable	

Criteria	Supporting Features	Remarks and Explanations
voice communication functionality shall support all commonly used cross-manufacturer non proprietary standard TTY signal protocols.		
(c) Voice mail, auto-attendant, and interactive voice response telecommunications systems shall be usable by TTY users with their TTYs.	Not applicable	
(d) Voice mail, messaging, auto-attendant, and interactive voice response telecommunication systems that require a response from a user within a time interval, shall give an alert when the time interval is about to run out, and shall provide sufficient time for the user to indicate more time is required.	Not applicable	
	Not applicable	
(f) For transmitted voice signals, telecommunications products shall provide a gain adjustable up to a minimum of 20 dB. For incremental volume control, at least one intermediate step of 12 dB of gain shall be provided.	Not applicable	
(g) If the telecommunications product allows a user to adjust the receiver volume, a function shall be provided to automatically reset the volume to the default level after every use.	Not applicable	
(h) Where a telecommunications product delivers output by an audio transducer which is normally held up to the ear, a means for effective magnetic wireless coupling to hearing technologies shall be provided.	Not applicable	
(i) Interface to hearing technologies (including hearing aids, cochlear implants, and assistive listening devices) shall be reduced to the lowest possible level that allows a user of hearing technologies to utilize the telecommunications product.	Not applicable	
(j) Products that transmit or conduct information or communication, shall pass through crossmanufacturer, non-proprietary, industry-standard codes, translation protocols, formats or other information necessary to provide the information or communication in usable format. Technologies which use encoding, signal compression, format transformation, or similar techniques shall not remove information needed for access or shall restore it upon delivery.	Not applicable	
(k)(1) Products which have mechanically operated controls or keys shall comply with the following: Controls and Keys shall be tactilely discernible without activating the controls or keys.	Not applicable	The following component does not apply to this criterion: - System x3690 X5: - System - No keyboard provided with system. No other keys on system.
(k)(2) Products which have mechanically operated controls or keys shall comply with the following: Controls and Keys shall be operable with one hand and shall not require tight grasping, pinching, twisting of the wrist. The force required to activate controls and keys shall be 5 lbs. (22.2N) maximum	Supports: Controls and latches can be reached and operated using one hand and require minimal dexterity for ease of use by mobility impaired users.	The following component meets this criterion: - System x3690 X5: - System - Power button and DVD-ROM eject button both accessible and easy to operate.
(k)(3) Products which have mechanically operated controls or keys shall comply with the following: If key repeat is supported, the delay before repeat shall be adjustable to at least 2 seconds. Key repeat rate shall be adjustable to 2 seconds per character.	Supports: An option to change keyboard repeat rate is provided so users can adjust the rate to accommodate their needs.	The following component meets this criterion: - System x3690 X5: - System - Keyboard repeat is OS dependent but supported in Hardware.
(k)(4) Products which have mechanically operated controls or keys shall comply with the following: The status of all locking or toggle controls or keys shall be visually discernible, and discernible either through touch or sound.	Supports: The status of locking and toggle controls or keys can be seen as well as distinguished by touch and/or sound when activated.	The following component meets this criterion: - System x3690 X5: - System - Done with IBM standard keyboard which is not included with system but hardware supports this function.

Section 1194.25 Self-Contained, Closed Products - Detail

Criteria	Supporting Features	Remarks and Explanations
(a) Self contained products shall be usable by	Not applicable	
people with disabilities without requiring an end-user		
to attach Assistive Technology to the product.		
Personal headsets for private listening are not		
Assistive Technology.		
(b) When a timed response is required, the user	Not applicable	
shall be alerted and given sufficient time to indicate		
more time is required.		
(c) Where a product utilizes touchscreens or	Not applicable	
contact-sensitive controls, an input method shall be		
provided that complies with §1194.23 (k) (1) through		
(4).		
(d) When biometric forms of user identification or	Not applicable	
control are used, an alternative form of identification or activation, which does not require the user to		
possess particular biological characteristics, shall		
also be provided.		
(e) When products provide auditory output, the	Not applicable	The following component does not apply to this
audio signal shall be provided at a standard signal	ivot applicable	criterion:
level through an industry standard connector that		ontonon.
will allow for private listening. The product must		- System x3690 X5:
provide the ability to interrupt, pause, and restart the		- System - No audible alerts post-OS.
audio at anytime.		
(f) When products deliver voice output in a public	Not applicable	
area, incremental volume control shall be provided		
with output amplification up to a level of at least 65		
dB. Where the ambient noise level of the		
environment is above 45 dB, a volume gain of at		
least 20 dB above the ambient level shall be user		
selectable. A function shall be provided to		
automatically reset the volume to the default level after every use.		
-	Cupporto	The following compensate meets this exiterior:
(g) Color coding shall not be used as the only means of conveying information, indicating an	Supports: Color is used only as an enhancement,	The following component meets this criterion:
action, prompting a response, or distinguishing a	and an alternate means to convey	- System x3690 X5:
visual element.	information or indicate an action is	- System - Color only used as enhancement for
	available to users with visual	hot swap devices.
	impairments.	
(h) When a product permits a user to adjust color	Not applicable	
and contrast settings, a range of color selections		
capable of producing a variety of contrast levels		
shall be provided.		
(i) Products shall be designed to avoid causing the	Not applicable	
screen to flicker with a frequency greater than 2 Hz		
and lower than 55 Hz.		
(j) (1) Products which are freestanding, non-	Not applicable	
portable, and intended to be used in one location		
and which have operable controls shall comply with		
the following: The position of any operable control		
the following: The position of any operable control shall be determined with respect to a vertical plane,		
the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the		
the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of		
the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the		
the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products		
the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended		
the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls.		
the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls. (j)(2) Products which are freestanding, non-portable,		
the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls. (j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which		
the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls. (j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the		
the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls. (j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches		
the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls. (j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall		
the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls. (j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches		
the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls. (j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum		
the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls. (j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum		
the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls. (j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum above the floor. (j)(3) Products which are freestanding, non-portable, and intended to be used in one location and which		
the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls. (j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum above the floor. (j)(3) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the		
the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls. (j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum		
the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls. (j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum above the floor. (j)(3) Products which are freestanding, non-portable, and intended to be used in one location and which		

Criteria	Supporting Features	Remarks and Explanations
10 inches and not more than 24 inches behind the reference plane, the height shall be 46 inches maximum and 15 inches minimum above the floor.		
(j)(4) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Operable controls shall not be more than 24 inches behind the reference plane.		

Section 1194.26 Desktop and Portable Computers - Detail

Criteria	Supporting Features	Remarks and Explanations
(a) All mechanically operated controls and keys shall comply with §1194.23 (k) (1) through (4).	Supports: See 1194.23(k) 1 through 4.	The following component meets this criterion: - System x3690 X5: - System - Power button and DVD-ROM eject button both accessible and easy to operate.
(b) If a product utilizes touchscreens or touch- operated controls, an input method shall be provided that complies with §1194.23 (k) (1) through (4).	Not applicable	The following component does not apply to this criterion: - System x3690 X5: - System - No touchscreens in system.
(c) When biometric forms of user identification or control are used, an alternative form of identification or activation, which does not require the user to possess particular biological characteristics, shall also be provided.	Not applicable	The following component does not apply to this criterion: - System x3690 X5: - System - No biometrics in system.
(d) Where provided, at least one of each type of expansion slots, ports and connectors shall comply with publicly available industry standards.	Supports: The product design uses industry standard ports so that alternative equipment and assistive technologies can be accommodated.	The following component meets this criterion: - System x3690 X5: - System - USB and serial ports as well as PCI slots available for add-in cards.

Section 1194.31 Functional Performance - Detail

Criteria	Supporting Features	Remarks and Explanations
(a) At least one mode of operation and information retrieval that does not require user vision shall be	Supports:	The following components meet this criterion:
provided, or support for Assistive Technology used by people who are blind or visually impaired shall be	See the following for supporting features:	- System x3690 X5: - System
provided.	- 1194.22 all - 1194.23 k1, k4 - 1194.25 a, b, c, e, f, g - 1194.26 b, d	- Integrated Management Module: - Web Interface
(b) At least one mode of operation and information retrieval that does not require visual acuity greater than 20/70 shall be provided in audio and enlarged	Supports: See the following for supporting	The following components meet this criterion: - System x3690 X5:
print output working together or independently, or support for Assistive Technology used by people what are visually impaired shall be provided.	features: - 1194.22 n - 1194.25 h - 1194.26 d	- System - Integrated Management Module: - Web Interface
(c) At least one mode of operation and information retrieval that does not require user hearing shall be provided, or support for Assistive Technology used by people who are deaf or hard of hearing shall be provided.	Supports: Hardware is designed to alert the software application of system sounds when needed and the software then provides a visual cue so that deaf or hard of hearing users can complete the task. See the following for other supporting	The following components meet this criterion: - System x3690 X5: - System - Integrated Management Module: - Web Interface
	features: - 1194.22 b, m - 1194.23 k4 - 1194.25 e	
(d) Where audio information is important for the use of the product, at least one mode of operation and information retrieval shall be provided in an enhanced auditory fashion, or support for assistive	Supports: See the following for supporting features:	The following component meets this criterion: - System x3690 X5: - System

Criteria	Supporting Features	Remarks and Explanations
hearing devices shall be provided.	- 1194.23 k4 - 1194.25 e	
		The following component does not apply to this criterion:
		- Integrated Management Module: - Web Interface
(e) At least one mode of operation and information retrieval that does not require user speech shall be provided, or support for Assistive Technology used by people with disabilities shall be provided.	Not applicable	This is not a speech product.
(f) At least one mode of operation and information retrieval that does not require fine motor control or	Supports:	The following components meet this criterion:
simultaneous actions and that is operable with limited reach and strength shall be provided.	See the following for supporting features: - 1194.22 I, p	- System x3690 X5: - System
	- 1194.23 k1, k2, k3 - 1194.25 b, j1, j2, j3, j4 - 1194.26 d	- Integrated Management Module: - Web Interface

Section 1194.41 Information, Documentation, and Support - Detail

Criteria	Supporting Features	Remarks and Explanations
	Supports: Product support documentation is provided in at least one accessible format.	The following component meets this criterion: - System x3690 X5: - System - The hardware documentation is in PDF format using a standard template. Minimal or no accessibility testing has been done. If you require an accessible version of the documentation it will be provided to you at no additional cost upon request. If you need an accessible version, send a request to dottieg@us.ibm.com. In the request make sure that you include the publication number and title. Alternative text is not provided for all images, but images are introduced and described in the surrounding text. Headings, sections, lists are used. Bookmarks are provided. The only color in the documentation is related to cautions and warnings, in which case the anchor words accompany the caution or warning icons. The documentation is in PDF format using a standard template. Tables use column and row headings to define relationships between cells. The default language of the reader is used. Bookmarks are provided. Forms are not used in the document. No flashing images are used.
(b) End-users shall have access to a description of the accessibility and compatibility features of products in alternate formats or alternate methods upon request, at no additional charge.	Supports: Documentation includes a description of accessibility and compatibility features that make it easier for people with disabilities to use the product. Those descriptions are available in alternate formats upon request.	The following component meets this criterion: - System x3690 X5: - System - The documentation includes a section on the accessibility features of the product
(c) Support services for products shall accommodate the communication needs of endusers with disabilities.	Supports: In addition to standard IBM help desk and support Web sites, IBM has established a TTY telephone service for use by deaf or hard of hearing customers to access sales and support services.	

This document is for informational purposes only. THE INFORMATION PROVIDED IN THIS DOCUMENT IS PROVIDED "AS IS" WITHOUT WARRANTIES OF ANY KIND, EXPRESSED OR IMPLIED. Supporting features apply to product families as a whole. The information shall not be construed as product specifications for purposes of any warranty of compliance with product specifications in a given contract or order. For information on third party software and applications please contact the software manufacturer. Lenovo may make changes to the information in this document or to the products described in this document at any time without notice.